

2024 **PRODUCT DATA**



TRANSFORMING
HARDSCAPES



THE **ONE** INNOVATOR WITH GAME-CHANGING PRODUCTS

BUILD VERTICALS FASTER

When the plan calls for pillars, a grill island or any vertical feature, the U-Cara Modular System lets you create customizable features in hours – not days!

Simply build the sturdy, aluminum frame in any configuration and choose from a wide selection of fascia panels to clad it with.



Learn more

U-CARA
MODULAR SYSTEM

TABLE OF CONTENTS - OHIO

PAVERS

| | |
|---------------------------|----|
| Artline™ | 4 |
| Beacon Hill™ Flagstone | 5 |
| Beacon Hill™ Smooth | 6 |
| Boulevard™ | 7 |
| Bristol Valley® | 8 |
| Brussels Block® | 9 |
| Camelot™ | 10 |
| Copthorne® | 11 |
| Courtstone® | 12 |
| Eco-Line® | 13 |
| Eco-Optiloc™ | 14 |
| Eco-Priora™ | 15 |
| Eco-Promenade® | 16 |
| Granito™ | 17 |
| Hex™ | 18 |
| Hollandstone™ | 19 |
| Holland Premier™ | 20 |
| Il Campo® | 21 |
| Mattoni™ | 22 |
| Natural Stone - Sandstone | 23 |
| Natural Stone - Limestone | 25 |
| Nordic Cobble™ | 27 |
| Optiloc® | 28 |
| Porcelain | 29 |
| Promenade™ | 31 |
| Promenade EcoTerra™ | 33 |
| Richcliff® | 34 |
| Series™ | 35 |
| Skyline™ | 36 |
| Thornbury™ | 37 |
| Town Hall® | 38 |
| Treo® Premier | 39 |
| Treo® Smooth | 40 |
| Tribeca Cobble™ | 41 |
| Turfstone™ | 42 |
| Umbriano® | 43 |
| Westport™ | 46 |

RETAINING WALLS

| | |
|------------------------------|----|
| Brussels Dimensional System™ | 47 |
| Dimensional Smooth™ | 48 |
| DuraHold® | 49 |
| DuraHold2® | 51 |
| Estate Wall™ | 52 |
| Lineo™ Dimensional Stone | 53 |
| Pisa2™ & Pisa XL | 54 |

| | |
|---------------------------|----|
| Pisa Smooth™ | 55 |
| Rivercrest® Wall | 56 |
| RomanPisa™ | 57 |
| RomanStack™ | 58 |
| SienaEdge™ | 59 |
| SienaStone™ | 60 |
| Split'nStack™ | 61 |
| U-Cara® | 62 |
| U-Cara® Modular System | 67 |
| U-Cara® Wall Mount System | 68 |

COPING, STEPS, PILLAR CAPS

| | |
|---------------------------------|----|
| Architectural Coping | 69 |
| Brussels Fullnose™/DBL Fullnose | 70 |
| Ledgestone™ Coping, Cap & Step | 71 |
| SienaStone Coping | 73 |
| Umbriano Coping | 74 |
| Universal Coping | 75 |

FIRE FEATURES

| | |
|------------------|----|
| Sunset Fire Pit | 76 |
| Unilock Elements | 77 |


ACCESSORIES

| | |
|-------------------------|----|
| Paver Cleaners | 78 |
| Natural Stone Cleaners | 78 |
| Natural Stone Sealers | 78 |
| Sealers | 78 |
| Sands | 79 |
| Adhesive | 81 |
| Edging, Edge Restraints | 82 |
| Drainage | 82 |
| Tools & Accessories | 83 |
| Base Systems | 83 |


PRODUCT & INSTALLATION INFORMATION

| | |
|---------------------------------|----|
| Calculations | 84 |
| Bedding & Base Thickness Charts | 85 |
| Finishes & Color Blends | 86 |
| Important Notes | 87 |
| Quality Commitment | 88 |
| Product Directory | 90 |

APPLICATION INDEX



DESCRIPTION OF EDGE DETAILS





APPLICATIONS



APPEARANCE

Edge Detail - Micro

Surface Texture - Smooth / Brushed (Il Campo®)

Joint Spacing - 3 mm

Void - n/a

TECHNOLOGIES

ENDURACOLOR™


Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERNS



Artline Fixed
Random A



FOSSIL



GRANITE FUSION



GRANITE FUSION
(IL CAMPO)

| | SMOOTH FINISH |
|----------------|---------------|
| Bundle Type | RANDOM |
| Plant Produced | OHIO |
| Thickness (mm) | 70 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 93.25 |
| | Layer | 11.66 |
| | Section | - |
| | Stone | 0.49 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------------|---------|---|
| SAILOR LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 2.06 |
| | Section | - |
| | Bundle | 192.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 364 |
| | Section | - |
| | Bundle | 2,911 |

| COLORS | Reflectance | Stock |
|---------------------------|----------------|-------|
| Fossil | SR n/a SRI n/a | ✓ |
| Granite Fusion | SR n/a SRI n/a | ✓ |
| Granite Fusion (Il Campo) | SR .28 SRI 29 | ✓ |

Random Bundle



UNIT A

125 x 169 x 70mm
4 7/8 x 6 3/4 x 2 3/4"
32 units/Bundle
.23 Sq.Ft./Stone



UNIT B

125 x 262.5 x 70mm
4 7/8 x 10 3/8 x 2 3/4"
32 units/Bundle
.35 Sq.Ft./Stone

Random Bundle



UNIT C

125 x 337.5 x 70mm
4 7/8 x 13 3/8 x 2 3/4"
32 Units/Bundle
.45 Sq.Ft./Stone



UNIT D

125 x 450 x 70mm
4 7/8 x 17 3/4 x 2 3/4"
32 Units/Bundle
.61 Sq.Ft./Stone



UNIT E

187.5 x 225 x 70mm
7 1/2 x 8 7/8 x 2 3/4"
32 Units/Bundle
.45 Sq.Ft./Stone



UNIT F

187.5 x 337.5 x 70mm
7 1/2 x 13 3/8 x 2 3/4"
16 Units/Bundle
.58 Sq.Ft./Stone



UNIT G

187.5 x 450 x 70mm
7 1/2 x 17 3/4 x 2 3/4"
16 Units/Bundle
.91 Sq.Ft./Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Textured
Joint Spacing - 7 mm
Void - n/a

TECHNOLOGIES


ENDURACOLOR™

Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



BeaconHill Fixed
Random A



BeaconHill Fixed
Random B



BeaconHill Multi-
Unit Random C



BIRCH




GRANITE FUSION



RIVER



SIERRA



WALNUT

| Bundle Type | | RANDOM |
|----------------|--|--------|
| Plant Produced | | OHIO |
| Thickness (mm) | | 60 MM |

| | | |
|----------|---------|--------|
| SQFT PER | Bundle | 116.57 |
| | Layer | 11.66 |
| | Section | - |
| | Stone | 1.46 |

| | | |
|------------|----------|-------|
| PER BUNDLE | Layers | 10.00 |
| | Sections | - |




| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------------|---------|-------|
| SAILOR LNFT PER | SqFt | 0.80 |
| | Section | - |
| | Layer | 9.35 |
| | Bundle | 93.50 |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 0.69 |
| | Section | - |
| | Bundle | 80.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 320 |
| | Section | - |
| | Bundle | 3,199 |

| COLORS | Reflectance | Stock |
|----------------|----------------|-------|
| Birch | SR n/a SRI n/a | ✓ |
| Granite Fusion | SR n/a SRI n/a | ✓ |
| River | SR n/a SRI n/a | ✓ |
| Sierra | SR n/a SRI n/a | ✓ |
| Walnut | SR n/a SRI n/a | ✓ |

| | | |
|---------------|--|---|
| Random Bundle |  | LARGE RECTANGLE 380 x 570 x 60mm 15 x 22 1/2 x 2 3/8" 20 Units/Bundle |
| |  | SQUARE 380 x 380 x 60mm 15 x 15 x 2 3/8" 30 Units/Bundle |
| |  | SMALL RECTANGLE 380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 30 Units/Bundle |
| | | |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth
Joint Spacing - 7 mm
Void - n/a

TECHNOLOGIES


ENDURACOLOR™

Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



BeaconHill Fixed
Random A



BeaconHill Multi-
Unit Random C



DARK
CHARCOAL




FOSSIL



GRANITE
FUSION



OPAL



TUSCANY

3 Unit Random Bundle



LARGE RECTANGLE

380 x 570 x 80mm
15 x 22 1/2 x 3 1/8"
16 Units/Bundle



SQUARE

380 x 380 x 80mm
15 x 15 x 3 1/8"
24 Units/Bundle



SMALL RECTANGLE

380 x 190 x 80mm
15 x 7 1/2 x 3 1/8"
24 Units/Bundle

3 Unit Random Bundle



LARGE RECTANGLE

380 x 570 x 60mm
15 x 22 1/2 x 2 3/8"
18 Units/Bundle



SQUARE

380 x 380 x 60mm
15 x 15 x 2 3/8"
27 Units/Bundle



SMALL RECTANGLE

380 x 190 x 60mm
15 x 7 1/2 x 2 3/8"
27 Units/Bundle

Single Units



SMALL RECTANGLE

380 x 190 x 60mm
15 x 7 1/2 x 2 3/8"
135 Units/Bundle
.78 Sq.Ft./Stone



XL UNIT

540 x 900 x 60MM
35 x 21 1/4 x 2 3/8"
20 Units/Bundle
2.00 Sq.Ft./Stone

| | | | XL | SMALL RECTANGLE |
|----------------|--------|--------|--------|--------------------|
| Bundle Type | RANDOM | RANDOM | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO | OHIO | OHIO |
| Thickness (mm) | 80 MM | 60 MM | 60 MM | 60 MM |

| SQFT PER | Bundle | 73.22 | 116.57 | 104.6 | 116.57 |
|----------|---------|-------|--------|-------|--------|
| | Layer | 10.46 | 11.66 | 10.46 | 11.66 |
| | Section | - | - | - | - |
| | Stone | 1.31 | 1.46 | 2.00 | 0.78 |

| PER BUNDLE | Layers | 7.00 | 10.00 | 10.00 | 10.00 |
|------------|----------|------|-------|-------|-------|
| | Sections | - | - | - | - |

| SOLDIER LNFT PER | SqFt | - | - | 0.34 | 0.80 |
|---------------------|---------|---|---|-------|-------|
| | Section | - | - | - | - |
| | Layer | - | - | 3.54 | 9.35 |
| | Bundle | - | - | 35.43 | 93.50 |

| SAILOR LNFT PER | SqFt | 0.85 | 0.80 | 0.56 | 1.60 |
|-----------------|---------|-------|-------|-------|--------|
| | Section | - | - | - | - |
| | Layer | 8.86 | 9.35 | 5.90 | 18.70 |
| | Bundle | 62.00 | 93.50 | 59.05 | 187.01 |

| UNITS PER | SqFt | 0.76 | 0.69 | 0.19 | 1.29 |
|-----------|---------|-------|-------|-------|--------|
| | Section | - | - | - | - |
| | Bundle | 56.00 | 80.00 | 20.00 | 150.00 |

| LBS PER | Layer | 362 | 320 | 292.8 | 320 |
|---------|---------|-------|-------|-------|-------|
| | Section | - | - | - | - |
| | Bundle | 2,548 | 3,199 | - | 3,199 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock |
|----------------|----------------|-------|-------|-------|-------|
| Dark Charcoal | SR n/a SRI n/a | - | - | - | ✓ |
| Fossil | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ |
| Granite Fusion | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ |
| Opal | SR n/a SRI n/a | - | ✓ | ✓ | - |
| Tuscan | SR n/a SRI n/a | - | ✓ | - | - |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| Bundle Type | RANDOM |
|----------------|--------|
| Plant Produced | OHIO |
| Thickness (mm) | 70 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 93.00 |
| | Layer | 11.63 |
| | Section | - |
| | Stone | 1.45 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |


| | | |
|-----------------|---------|-------|
| SAILOR LNFT PER | SqFt | 1.03 |
| | Section | - |
| | Layer | 12.00 |
| | Bundle | 96.04 |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 0.69 |
| | Section | - |
| | Bundle | 64.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 372 |
| | Section | - |
| | Bundle | 2,978 |

| COLORS | Reflectance | Stock |
|----------------|----------------|-------|
| Granite Fusion | SR n/a SRI n/a | ✓ |
| River | SR n/a SRI n/a | ✓ |
| Sierra | SR n/a SRI n/a | ✓ |

LAYING PATTERN




Boulevard Fixed
Random B






GRANITE FUSION



RIVER



SIERRA

| | | | | | | |
|---------------|---|---|---|---|--|---|
| Random Bundle |  | LARGE RECTANGLE 610 X 305 X 70MM 24 X 12 X 2 3/4" 24 Units/Bundle 2.00 SqFt./Stone |  | MEDIUM RECTANGLE 457 X 305 X 70MM 18 X 12 X 2 3/4" 16 Units/Bundle 1.50 Sq.Ft./Stone |  | SQUARE 305 X 305 X 70MM 12 X 12 X 2 3/4" 24 Units/Bundle 1.00 Sq.Ft./Stone |
|---------------|---|---|---|---|--|---|

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Textured
Joint Spacing - 7 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory sealed to provide integral stain resistance


COMFORT STEP

Ultra smooth surface texture


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Bristol Valley Fixed
Random A



Bristol Valley Fixed
Random B



BAVARIAN



FOSSIL



STEEL MOUNTAIN

| | | XL |
|--------------------|---------------|---------------|
| Bundle Type | RANDOM | SINGLE |
| Plant Produced | MARENGO | MARENGO |
| Thickness (mm) | 60 MM | 60 MM |

| | | | |
|-----------------|---------|--------|--------|
| SQFT PER | Bundle | 116.57 | 116.57 |
| | Layer | 11.66 | 11.66 |
| | Section | - | - |
| | Stone | 1.46 | 5.83 |

| | | | |
|-------------------|----------|-------|-------|
| PER BUNDLE | Layers | 10.00 | 10.00 |
| | Sections | - | - |





| | | | |
|-------------------------|---------|---|-------|
| SOLDIER LNFT PER | SqFt | - | 0.32 |
| | Section | - | - |
| | Layer | - | 3.74 |
| | Bundle | - | 37.40 |

| | | | |
|------------------------|---------|-------|-------|
| SAILOR LNFT PER | SqFt | 0.80 | 0.53 |
| | Section | - | - |
| | Layer | 9.35 | 6.23 |
| | Bundle | 93.50 | 62.30 |

| | | | |
|------------------|---------|-------|-------|
| UNITS PER | SqFt | 0.69 | 0.17 |
| | Section | - | - |
| | Bundle | 80.00 | 20.00 |

| | | | |
|----------------|---------|-------|-------|
| LBS PER | Layer | 311 | 321 |
| | Section | - | - |
| | Bundle | 3,113 | 3,210 |

| COLORS | Reflectance | Stock | Stock |
|----------------|----------------|-------|-------|
| Bavarian | SR n/a SRI n/a | ✓ | ✓ |
| Fossil | SR n/a SRI n/a | ✓ | ✓ |
| Steel Mountain | SR n/a SRI n/a | ✓ | ✓ |

| | | | | | | | | | |
|---------------|---|--|---|---|---|--|-------------|---|--|
| Random Bundle |  | LARGE RECTANGLE 380 x 570 x 60mm 15 x 22 1/2 x 2 3/8" 20 Units/Bundle 2.08 Sq.Ft./Stone |  | SQUARE 380 x 380 x 60mm 15 x 15 x 2 3/8" 30 Units/Bundle 1.39 Sq.Ft./Stone |  | SMALL RECTANGLE 380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 30 Units/Bundle .69 Sq.Ft./Stone | Single Unit |  | XL UNIT 950 x 570 x 60mm 37 1/2 x 22 1/2 x 2 3/8" 20 units/Bundle 5.83 Sq.Ft./Stone |
|---------------|---|--|---|---|---|--|-------------|---|--|

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 2 mm
Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | HALF | STANDARD | XL |
|--------------------|---------------|---------------|---------------|
| Bundle Type | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO | OHIO |
| Thickness (mm) | 70 MM | 70 MM | 70 MM |

| | | | | |
|-----------------|---------|-------|-------|-------|
| SQFT PER | Bundle | 88.70 | 88.60 | 76.56 |
| | Layer | 11.09 | 11.08 | 9.57 |
| | Section | 12.67 | 12.66 | 25.52 |
| | Stone | 0.20 | 0.40 | 0.80 |

| | | | | |
|-------------------|----------|------|------|------|
| PER BUNDLE | Layers | 8.00 | 8.00 | 8.00 |
| | Sections | 7.00 | 7.00 | 3.00 |

| | | | | |
|-------------------------|---------|--------|--------|-------|
| SOLDIER LNFT PER | SqFt | 1.72 | 1.44 | 0.86 |
| | Section | 21.84 | 18.27 | 21.84 |
| | Layer | 19.11 | 15.98 | 8.19 |
| | Bundle | 152.86 | 127.87 | 65.51 |


| | | | | |
|------------------------|---------|--------|--------|--------|
| SAILOR LNFT PER | SqFt | 2.87 | 1.73 | 1.43 |
| | Section | 36.33 | 21.84 | 36.54 |
| | Layer | 31.78 | 19.11 | 13.70 |
| | Bundle | 254.28 | 152.86 | 109.61 |

| | | | | |
|------------------|---------|--------|--------|-------|
| UNITS PER | SqFt | 5.05 | 2.53 | 1.25 |
| | Section | 64.00 | 32.00 | 32.00 |
| | Bundle | 448.00 | 224.00 | 96.00 |


| | | | | |
|----------------|---------|-------|-------|-------|
| LBS PER | Layer | 344 | 344 | 316 |
| | Section | 393 | 393 | 843 |
| | Bundle | 2,752 | 2,749 | 2,528 |

| COLORS | Reflectance | Stock | Stock | Stock |
|-----------|----------------|-------|-------|-------|
| Limestone | SR .28 SRI 29 | ✓ | ✓ | ✓ |
| Sandstone | SR .41 SRI 46 | ✓ | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ | ✓ |

LAYING PATTERNS




Brussels Multi-Unit
Random AC



Brussels Multi-Unit
Random AD



LIMESTONE



SANDSTONE



SIERRA

Single Units



HALF
104 x 173 x 70mm
4 x 6 7/8 x 2 3/4"
448 Units/Bundle
.20 Sq.Ft./Stone



STANDARD
173 x 208 x 70mm
6 7/8 x 8 1/4 x 2 3/4"
224 Units/Bundle
.40 Sq.Ft./Stone



XL
208 x 348 x 70mm
8 1/4 x 13 3/4 x 2 3/4"
96 Units/Bundle
.80 Sq.Ft./Stone

Notes: **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
Surface Texture - Smooth
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | SQUARE | RECTANGLE |
|----------------|--------|-----------|
| Bundle Type | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO |
| Thickness (mm) | 60 MM | 60 MM |

| SQFT PER | Bundle | 92.40 | 98.96 |
|----------|---------|-------|-------|
| | Layer | 11.55 | 12.37 |
| | Section | 13.20 | 19.79 |
| | Stone | 0.28 | 0.41 |

| PER BUNDLE | Layers | 8.00 | 8.00 |
|------------|----------|------|------|
| | Sections | 7.00 | 5.00 |

| SOLDIER LNFT PER | SqFt | 1.79 | 1.19 |
|------------------|---------|--------|--------|
| | Section | 23.62 | 23.62 |
| | Layer | 20.67 | 14.76 |
| | Bundle | 165.35 | 118.11 |


| SAILOR LNFT PER | SqFt | 1.79 | 1.79 |
|-----------------|---------|--------|--------|
| | Section | 23.62 | 35.43 |
| | Layer | 20.67 | 22.15 |
| | Bundle | 165.35 | 177.17 |

| UNITS PER | SqFt | 3.64 | 2.43 |
|-----------|---------|--------|--------|
| | Section | 48.00 | 48.00 |
| | Bundle | 336.00 | 240.00 |


| LBS PER | Layer | 325 | 350 |
|---------|---------|-------|-------|
| | Section | 371 | 560 |
| | Bundle | 2,598 | 2,800 |

| COLORS | Reflectance | Stock | Stock |
|---------|----------------|-------|-------|
| Granite | SR .26 SRI 27 | ✓ | ✓ |
| River | SR .32 SRI 34 | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ |

LAYING PATTERNS



Camelot 6x9_HB_A



Camelot 6x9_HB_B



GRANITE



RIVER



SIERRA

Single Units



SQUARE

159.8 x 159.8 x 60mm
6 3/8 x 6 3/8 x 2 3/8"
336 Units/Bundle
.28 Sq.Ft./Stone



RECTANGLE

160 x 240 x 60mm
6 3/8 x 9 1/2 x 2 3/8"
240 Units/Bundle
.41 Sq.Ft./Stone

Notes: Camelot is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured
Joint Spacing - 3 mm

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Realta and Ultima technologies

REALTA™

Cast from European cobblestones

ULTIMA™

Up to 4x stronger than poured-in-place concrete


EASYSOAK™

Factory Sealed to provide integral stain resistance


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Copthorne BW A



Copthorne RB C



ARCTIC GREY



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK



STEEL BLUE

Single Unit



STANDARD

65 x 200 x 60mm
2 5/8 x 7 7/8 x 2 3/8"
600 Units/Bundle
.15 SqFt/Stone

| Bundle Type | | SINGLE |
|----------------|--|--------|
| Plant Produced | | AYR |
| Thickness (mm) | | 60 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 89.20 |
| | Layer | 11.15 |
| | Section | - |
| | Stone | 0.15 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|--------|
| SOLDIER LNFT PER | SqFt | 1.43 |
| | Section | - |
| | Layer | 15.99 |
| | Bundle | 127.95 |

| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 4.41 |
| | Section | - |
| | Layer | 49.21 |
| | Bundle | 393.70 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 6.73 |
| | Section | - |
| | Bundle | 600.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 294 |
| | Section | - |
| | Bundle | 2,349 |

| COLORS | Reflectance | Stock |
|--------------|----------------|-------|
| Arctic Grey | SR n/a SRI n/a | ✓ |
| Basalt | SR n/a SRI n/a | ✓ |
| Burgundy Red | SR n/a SRI n/a | ✓ |
| Burnt Clay | SR n/a SRI n/a | ✓ |
| Old Oak | SR n/a SRI n/a | ✓ |
| Steel Blue | SR n/a SRI n/a | ✓ |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices on Page 80. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Textured

Joint Spacing - 15 mm

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

REALA™

Cast from European cobblestones

ULTIMA™

Up to 4x stronger than poured-in-place concrete

EASYCLEAN™

Factory Sealed to provide integral stain resistance

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

| Bundle Type | | RANDOM |
|----------------|--|--------|
| Plant Produced | | AYR |
| Thickness (mm) | | 60 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 98.30 |
| | Layer | 12.29 |
| | Section | - |
| | Stone | 0.26 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |


| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 2.25 |
| | Section | - |
| | Layer | 27.69 |
| | Bundle | 221.52 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 3.91 |
| | Section | - |
| | Bundle | 384.00 |


| | | |
|---------|---------|-------|
| LBS PER | Layer | 291 |
| | Section | - |
| | Bundle | 2,326 |

| COLORS | Reflectance | Stock |
|--------|----------------|-------|
| Basalt | SR n/a SRI n/a | ✓ |

LAYING PATTERNS



Courtstone Fixed
Random A



BASALT

| | | | | | |
|---------------|---|---|---|---|--|
| Random Bundle |  |  |  |  |  |
| | XL RECTANGLE 215 x 130 x 60mm 8 3/8 x 5 1/8 x 2 3/8" 128 Units/Bundle .30 SqFt/Stone | LARGE RECTANGLE 185 x 130 x 60mm 7 1/4 x 5 1/8 x 2 3/8" 64 Units/Bundle .28 SqFt/Stone | RECTANGLE 165 x 130 x 60mm 6 1/2 x 5 1/8 x 2 3/8" 64 Units/Bundle .23 SqFt/Stone | SMALL RECTANGLE 145 x 130 x 60mm 5 3/4 x 5 1/8 x 2 3/8" 64 Units/Bundle .20 SqFt/Stone | SQUARE 130 x 130 x 60mm 5 1/8 x 5 1/8 x 2 3/8" 64 Units/Bundle .18 SqFt/Stone |

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices on Page 80. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 6.25 mm
Void - 5.80%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936 -Eligible for LEED v4.1 credits

LAYING PATTERN



EcoLine Fixed Random A

| | SMOOTH ENDURA |
|--------------------|---------------|
| Bundle Type | SINGLE |
| Plant Produced | OHIO |
| Thickness (mm) | 100 MM |

| | | |
|-----------------|---------|-------|
| SQFT PER | Bundle | 66.20 |
| | Layer | 11.03 |
| | Section | - |
| | Stone | 0.34 |

| | | |
|-------------------|----------|------|
| PER BUNDLE | Layers | 6.00 |
| | Sections | - |

| | | |
|-------------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|------------------------|---------|---|
| SAILOR LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|------------------|---------|--------|
| UNITS PER | SqFt | 2.90 |
| | Section | - |
| | Bundle | 192.00 |

| | | |
|----------------|---------|-------|
| LBS PER | Layer | 504 |
| | Section | - |
| | Bundle | 3,025 |

| COLORS | Reflectance | Stock |
|-----------------------|----------------|-------|
| All Colors & Finishes | SR n/a SRI n/a | SO |

| Single Units | UNIT A | UNIT B | UNIT C | UNIT D | UNIT E | UNIT F | UNIT G | UNIT H |
|--------------|---|---|---|--|--|--|--|---|
| | 357 x 84 x 100mm 14 x 3 3/8 x 3 7/8" | 317 x 84 x 100mm 12 1/2 x 3 3/8 x 3 7/8" | 277 x 84 x 100mm 10 7/8 x 3 3/8 x 3 7/8" | 237 x 84 x 100mm 9 3/8 x 3 3/8 x 3 7/8" | 357 x 114 x 100mm 14 x 4 1/2 x 3 7/8" | 317 x 114 x 100mm 12 1/2 x 4 1/2 x 3 7/8" | 277 x 114 x 100mm 10 7/8 x 4 1/2 x 3 7/8" | 237 x 114 x 100mm 9 3/8 x 4 1/2 x 3 7/8" |
| | 24 Units/Bundle .32 SqFt/Stone | 24 Units/Bundle .29 SqFt/Stone | 24 Units/Bundle .25 SqFt/Stone | 24 Units/Bundle .21 SqFt/Stone | 24 Units/Bundle .44 SqFt/Stone | 24 Units/Bundle .39 SqFt/Stone | 24 Units/Bundle .34 SqFt/Stone | 24 Units/Bundle .29 SqFt/Stone |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 7 mm
 Void - 7.30%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

| | STANDARD |
|----------------|----------|
| Bundle Type | SINGLE |
| Plant Produced | OHIO |
| Thickness (mm) | 80 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 84.80 |
| | Layer | 10.60 |
| | Section | - |
| | Stone | 0.50 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |


| | | |
|-----------------|---------|---|
| SAILOR LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 1.98 |
| | Section | - |
| | Bundle | 168.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 354 |
| | Section | - |
| | Bundle | 2,831 |

| COLORS | Reflectance | Stock |
|---------|---------------|-------|
| Natural | SR .30 SRI 32 | ✓ |
| River | SR .32 SRI 34 | ✓ |

LAYING PATTERN



Pattern Cluster C



NATURAL



RI VER

Single Unit



STANDARD
 250 x 250 x 80mm
 9 7/8 x 9 7/8 x 3 1/8"
 168 Units/Bundle
 .50 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 7mm
Void - 4.6-7.08%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| Bundle Type | | SINGLE |
|----------------|--|--------|
| Plant Produced | | OHIO |
| Thickness (mm) | | 80 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 75.95 |
| | Layer | 10.85 |
| | Section | 15.19 |
| | Stone | 0.31 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 7.00 |
| | Sections | 5.00 |

| | | |
|------------------|---------|-------|
| SOLDIER LNFT PER | SqFt | 1.27 |
| | Section | 19.29 |
| | Layer | 13.78 |
| | Bundle | 96.46 |


| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 2.25 |
| | Section | 34.17 |
| | Layer | 24.41 |
| | Bundle | 170.87 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 3.23 |
| | Section | 49.00 |
| | Bundle | 245.00 |


| | | |
|---------|---------|-------|
| LBS PER | Layer | 381 |
| | Section | 534 |
| | Bundle | 2,614 |

| COLORS | Reflectance | Stock |
|---------|----------------|-------|
| Natural | SR n/a SRI n/a | SO |
| River | SR n/a SRI n/a | ✓ |


LAYING PATTERNS



EcoPriora 5x10
RB_A



EcoPriora 5x10
HB_E



EcoPriora Multi-Unit
Random C



NATURAL



RIVER

Single Unit



5 x 10
120 x 240 x 80mm
4 3/4" x 9 1/2" x 3 1/8"
245 Units/Bundle
.31 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Smooth / Series™ Exposed
 Joint Spacing - 7 mm
 Void - 10.12%

TECHNOLOGIES

ENDURACOLOR™ (3x12)

Refined surface and long-lasting color

PERMEABLE

Can be installed to allow water to flow through

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

| | 6 x 24 SMOOTH | 3 x 12 PERMEABLE SMOOTH | 3 x 12 PERMEABLE SERIES | 4 x 12 SERIES |
|--------------------|------------------|-------------------------------|-------------------------------|------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | CHICAGO | CHICAGO | CHICAGO |
| Thickness (mm) | 70 MM | 100 MM | 100 MM | 80 MM |

| | | | | | |
|-----------------|---------|-------|-------|-------|-------|
| SQFT PER | Bundle | 93.00 | 63.94 | 63.94 | 93.04 |
| | Layer | 11.63 | 10.66 | 10.66 | 11.63 |
| | Section | - | - | - | - |
| | Stone | 0.97 | 0.24 | 0.24 | 0.32 |

| | | | | | |
|-------------------|----------|------|------|------|------|
| PER BUNDLE | Layers | 8.00 | 6.00 | 6.00 | 8.00 |
| | Sections | - | - | - | - |

| | | | | | |
|-------------------------|---------|-------|-------|-------|-------|
| SOLDIER LNFT PER | SqFt | 0.51 | 1.02 | 1.02 | 1.02 |
| | Section | - | - | - | - |
| | Layer | 5.91 | 10.83 | 10.83 | 11.81 |
| | Bundle | 47.25 | 64.96 | 64.96 | 94.49 |


| | | | | | |
|------------------------|---------|--------|--------|--------|--------|
| SAILOR LNFT PER | SqFt | 2.03 | 4.06 | 4.06 | 3.05 |
| | Section | - | - | - | - |
| | Layer | 23.62 | 43.31 | 43.31 | 35.43 |
| | Bundle | 188.98 | 259.84 | 259.84 | 283.46 |

| | | | | | |
|------------------|---------|-------|--------|--------|--------|
| UNITS PER | SqFt | 1.03 | 4.13 | 4.13 | 3.10 |
| | Section | - | - | - | - |
| | Bundle | 96.00 | 264.00 | 264.00 | 288.00 |


| | | | | | |
|----------------|---------|-------|-------|-------|-------|
| LBS PER | Layer | 372 | 465 | 483 | 426 |
| | Section | - | - | - | - |
| | Bundle | 2,978 | 2,789 | 2,898 | 3,404 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock |
|---------------------|----------------|-----------|-----------|-----------|-------|
| All Finishes/Colors | SR n/a SRI n/a | SO | SO | SO | - |
| Arctic Grey | SR n/a SRI n/a | - | - | - | ✓ |
| Nordic Star | SR n/a SRI n/a | - | - | - | ✓ |


LAYING PATTERNS



EcoPromenade 3x12
RB_A



EcoPromenade 3x12_
DHB_B



EcoPromenade 3x12
HB_C



ARCTIC GREY



NORDIC STAR

| | | | | | | | | |
|--------------|---|---|---|---|---|---|---|---|
| Single Units |  | 6 x 24 SMOOTH 150 x 600 x 70mm 5 7/8 x 6 3/8 x 2 3/4" 96 Units/Bundle .97 Sq.Ft./Stone |  | 3 x 12 SMOOTH 75 x 300 x 100mm 3 x 11 1/2 x 3 7/8" 264 Units/Bundle .24 Sq.Ft./Stone |  | 3 x 12 SERIES 75 x 300 x 100mm 3 x 11 1/2 x 3 7/8" 264 Units/Bundle .24 Sq.Ft./Stone |  | 4 x 12 SERIES 100 x 300 x 80mm 3 7/8 x 11 7/8 x 3 1/8" 288 Units/Bundle .32 Sq.Ft./Stone |
| | | | | | | | | |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Granito/Granito Textured (Random)
Joint Spacing - 7 mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

ARTISTA™

Boldly mottled color finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | | HEX |
|----------------|-----------|-----------|
| Bundle Type | RANDOM | SINGLE |
| Plant Produced | PICKERING | PICKERING |
| Thickness (mm) | 60 MM | 70 MM |

| SQFT PER | Bundle | 94.14 | 73.92 |
|----------|---------|-------|-------|
| | Layer | 10.46 | 9.24 |
| | Section | - | - |
| | Stone | 1.31 | 2.6 |

| PER BUNDLE | Layers | 9.00 | 8.00 |
|------------|----------|------|------|
| | Sections | - | - |

| SOLDIER LNFT PER | SqFt | - | - |
|------------------|---------|---|---|
| | Section | - | - |
| | Layer | - | - |
| | Bundle | - | - |


| SAILOR LNFT PER | SqFt | 0.85 | - |
|-----------------|---------|-------|---|
| | Section | - | - |
| | Layer | 8.86 | - |
| | Bundle | 79.72 | - |

| UNITS PER | SqFt | 0.76 | 0.39 |
|-----------|---------|-------|--------|
| | Section | - | - |
| | Bundle | 72.00 | 192.00 |


| LBS PER | Layer | 287 | 306.24 |
|---------|---------|-------|--------|
| | Section | - | - |
| | Bundle | 2,584 | 2,450 |

| COLORS | Reflectance | Stock | Stock |
|------------------|----------------|-------|-------|
| Notte Random/Hex | SR n/a SRI n/a | ✓ | ✓ |
| Sabia Random/Hex | SR n/a SRI n/a | ✓ | ✓ |
| Scuro Random/Hex | SR n/a SRI n/a | ✓ | ✓ |


LAYING PATTERNS



Pattern Hex_A



Pattern Random_A



Pattern Random_B



NOTTE



SABIA



SCURO

| Random Bundle | | | | Single Unit |
|---------------|---|--|--|---|
| | SMALL RECTANGLE | SQUARE | LARGE RECTANGLE | |
| | 180 x 360 x 60mm 7 x 14 1/4 x 2 3/8" | 360 x 360 x 60mm 14 1/4 x 14 1/4 x 2 3/8" | 360 x 540 x 60mm 14 1/4 x 21 1/4 x 2 3/8" | HEX 200 x 200 x 70mm 7 7/8 x 7 7/8 x 3 1/8" |
| | 27 Units/Bundle .655 Sq.Ft./Stone | 27 Units/Bundle 1.31 Sq.Ft./Stone | 18 Units/Bundle 1.966 Sq.Ft./Stone | 192 Units/Bundle .42 Sq.Ft./Stone |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Random bundle is not suitable for vehicular use. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail Smooth and Granito - Micro
 Edge Detail Umbriano- Zero
 Surface Texture - Smooth / Mottled
 Joint Spacing Smooth - 3 mm
 Joint Spacing Umbriano - 7mm

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYSOAK™ (Umbriano)

Factory Sealed to provide integral stain resistance

COLORFUSION™ (Umbriano)

Subtly mottled color finish

PERMEABLE (Eco-Hex)

Can be installed to allow water to flow through

ARTISTA™ (Granito)

Boldly mottled color finish

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits



MEDIUM GRAY



OPAL



FRENCH GREY



DARK CHARCOAL



SUMMER WHEAT



WINTER MARVEL



MIDNIGHT SKY



NOTTE



SABIA



SCURO

| | HEX SMOOTH ENDURACOLOR | UMBRIANO® PERMEABLE | GRANITO HEX |
|----------------|---------------------------|------------------------|----------------|
| Bundle Type | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | CHICAGO | PICKERING |
| Thickness (mm) | 70 MM | 60 MM | 70 MM |

| | | | | |
|----------|---------|-------|--------|-------|
| SQFT PER | Bundle | 73.92 | 108.31 | 73.92 |
| | Layer | 9.24 | 10.83 | 9.24 |
| | Section | - | - | - |
| | Stone | 0.39 | 0.45 | 0.39 |

| | | | | |
|------------|----------|------|-------|------|
| PER BUNDLE | Layers | 8.00 | 10.00 | 8.00 |
| | Sections | - | - | - |

| | | | | |
|------------------|---------|---|---|---|
| SOLDIER LNFT PER | SqFt | - | - | - |
| | Section | - | - | - |
| | Layer | - | - | - |
| | Bundle | - | - | - |


| | | | | |
|-----------------|---------|---|---|---|
| SAILOR LNFT PER | SqFt | - | - | - |
| | Section | - | - | - |
| | Layer | - | - | - |
| | Bundle | - | - | - |

| | | | | |
|-----------|---------|--------|--------|--------|
| UNITS PER | SqFt | 2.60 | 2.22 | 2.60 |
| | Section | - | - | - |
| | Bundle | 192.00 | 240.00 | 192.00 |

| | | | | |
|---------|---------|-------|-------|-------|
| LBS PER | Layer | 306 | 273 | 306 |
| | Section | - | - | - |
| | Bundle | 2,450 | 2,732 | 2,450 |

| COLORS | Reflectance | Stock | Stock | Stock |
|---------------|----------------|-------|-------|-------|
| Medium Gray | SR n/a SRI n/a | ✓ | | |
| Opal | SR n/a SRI n/a | ✓ | | |
| Dark Charcoal | SR n/a SRI n/a | ✓ | | |
| French Grey | SR .18 SRI 17 | | ✓ | |
| Summer Wheat | SR .42 SRI 48 | | ✓ | |
| Winter Marvel | SR .35 SRI 38 | | ✓ | |
| Midnight Sky | SR n/a SRI n/a | | ✓ | |
| Notte | SR n/a SRI n/a | | | ✓ |
| Sabia | SR n/a SRI n/a | | | ✓ |
| Scuro | SR n/a SRI n/a | | | ✓ |

LAYING PATTERN



Single Unit



HEX
 200 x 200 x 70mm
 7 7/8 x 7 7/8 x 2 3/4"
 192 Units/Bundle
 .39 SqFt/Stone



ECO-HEX UMBRIANO
 200 x 200 x 70mm
 7 7/8 x 7 7/8 x 2 3/4"
 240 Units/Bundle
 .45 SqFt/Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
Surface Texture - Smooth
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



Pattern RB_B



Pattern HB_C



Pattern BW_D



CHARCOAL



RIVER



RUSTIC RED



SIERRA

| Bundle Type | | SINGLE |
|----------------|--|--------|
| Plant Produced | | OHIO |
| Thickness (mm) | | 60 MM |

| | | |
|----------|---------|--------|
| SQFT PER | Bundle | 106.20 |
| | Layer | 11.80 |
| | Section | 17.70 |
| | Stone | 0.22 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 9.00 |
| | Sections | 6.00 |

| | | |
|------------------|---------|--------|
| SOLDIER LNFT PER | SqFt | 1.50 |
| | Section | 26.57 |
| | Layer | 17.72 |
| | Bundle | 159.45 |

| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 3.00 |
| | Section | 53.15 |
| | Layer | 35.43 |
| | Bundle | 318.90 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 4.58 |
| | Section | 81.00 |
| | Bundle | 486.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 319 |
| | Section | 478 |
| | Bundle | 2,868 |

| COLORS | Reflectance | Stock |
|------------|----------------|-------|
| Charcoal | SR .12 SRI 9 | ✓ |
| River | SR .32 SRI 34 | ✓ |
| Rustic Red | SR n/a SRI n/a | ✓ |
| Sierra | SR n/a SRI n/a | ✓ |

Single Unit



STANDARD

100 x 200 x 60mm
3 7/8 x 7 7/8 x 2 3/8"
540 Units/Bundle
.22 Sq.Ft./Stone



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES


ENDURACOLOR™

Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Pattern RB_B



Pattern HB_C



DARK CHARCOAL



FOSSIL



GRANITE FUSION



IVORY



MOCHA BROWN

| Bundle Type | | SINGLE |
|----------------|--|--------|
| Plant Produced | | OHIO |
| Thickness (mm) | | 60 MM |

| | | |
|----------|---------|--------|
| SQFT PER | Bundle | 106.20 |
| | Layer | 11.80 |
| | Section | 17.70 |
| | Stone | 0.22 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 9.00 |
| | Sections | 6.00 |

| | | |
|------------------|---------|--------|
| SOLDIER LNFT PER | SqFt | 1.50 |
| | Section | 26.57 |
| | Layer | 17.72 |
| | Bundle | 159.45 |

| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 3.00 |
| | Section | 53.15 |
| | Layer | 35.43 |
| | Bundle | 318.90 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 4.58 |
| | Section | 81.00 |
| | Bundle | 486.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 307 |
| | Section | 460 |
| | Bundle | 2,759 |

| COLORS | Reflectance | | Stock |
|----------------|-------------|---------|-------|
| Dark Charcoal | SR n/a | SRI n/a | ✓ |
| Fossil | SR n/a | SRI n/a | ✓ |
| Granite Fusion | SR n/a | SRI n/a | ✓ |
| Ivory | SR n/a | SRI n/a | ✓ |
| Mocha Brown | SR n/a | SRI n/a | ✓ |

Single Unit



STANDARD
100 x 200 x 60mm
3 7/8 x 7 7/8 x 2 3/8"
486 units/Bundle
.22 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Il Campo® Brushed
Joint Spacing - 3 mm
Void - n/a


TECHNOLOGIES

ENDURACOLOR™
Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



Pattern 4x8_RB_F




Pattern 4x8_SB_G



Pattern 4x8_HB_H



DARK CHARCOAL



MOCHA BROWN

| Bundle Type | | SINGLE | SINGLE |
|----------------|--|--------|--------|
| Plant Produced | | OHIO | OHIO |
| Thickness (mm) | | 60 MM | 70 MM |

| | | | |
|----------|---------|-------|-------|
| SQFT PER | Bundle | 106.2 | 94.40 |
| | Layer | 11.80 | 11.80 |
| | Section | - | 15.73 |
| | Stone | 0.22 | 0.22 |

| | | | |
|------------|----------|------|------|
| PER BUNDLE | Layers | 9.00 | 8.00 |
| | Sections | - | 6.00 |

| | | | |
|------------------|---------|---|--------|
| SOLDIER LNFT PER | SqFt | - | 1.50 |
| | Section | - | 23.62 |
| | Layer | - | 17.72 |
| | Bundle | - | 141.73 |

| | | | |
|-----------------|---------|---|--------|
| SAILOR LNFT PER | SqFt | - | 3.00 |
| | Section | - | 47.24 |
| | Layer | - | 35.43 |
| | Bundle | - | 283.46 |

| | | | |
|-----------|---------|------|--------|
| UNITS PER | SqFt | 4.58 | 4.58 |
| | Section | - | 72.00 |
| | Bundle | - | 432.00 |

| | | | |
|---------|---------|-------|-------|
| LBS PER | Layer | - | 362 |
| | Section | - | 483 |
| | Bundle | 2,759 | 2,898 |

| COLORS | Reflectance | Stock | Stock |
|---------------|----------------|-------|-------|
| Dark Charcoal | SR n/a SRI n/a | ✓ | - |
| Mocha Brown | SR n/a SRI n/a | - | ✓ |

Single Unit



STANDARD
100 x 200 x 60mm
3 3/8 x 7 7/8 x 2 3/4"
432 Units/Bundle
.22 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid.. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Smooth

Joint Spacing - 4 mm

Void - n/a

TECHNOLOGIES

ENDURACOLOR™


Refined surface and long-lasting color

TECHNICAL INFORMATION


Conforms to ASTM C 936

Eligible for LEED v4.1 credits


LAYING PATTERNS



Pattern RB_A



Pattern HB_C



Pattern DHB_D

| | STANDARD |
|----------------|----------|
| Bundle Type | SINGLE |
| Plant Produced | MARENGO |
| Thickness (mm) | 60 MM |

| | | |
|----------|---------|--------|
| SQFT PER | Bundle | 111.60 |
| | Layer | 11.16 |
| | Section | - |
| | Stone | 0.16 |

| | | |
|------------|----------|-------|
| PER BUNDLE | Layers | 10.00 |
| | Sections | - |

| | | |
|------------------|---------|--------|
| SOLDIER LNFT PER | SqFt | 1.27 |
| | Section | - |
| | Layer | 14.17 |
| | Bundle | 141.73 |

| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 5.08 |
| | Section | - |
| | Layer | 56.69 |
| | Bundle | 566.93 |


| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 6.45 |
| | Section | - |
| | Bundle | 720.00 |

| | | |
|---------|---------|---------|
| LBS PER | Layer | 306 |
| | Section | - |
| | Bundle | 3062.89 |

| COLORS | Reflectance | Stock |
|----------------|----------------|-------|
| Dark Charcoal | SR n/a SRI n/a | ✓ |
| Granite Fusion | SR n/a SRI n/a | ✓ |
| Sable | SR n/a SRI n/a | ✓ |
| Cocoa Brown | SR n/a SRI n/a | ✓ |



DARK CHARCOAL



GRANITE FUSION



SABLE



COCOA BROWN

Single Unit



STANDARD

60 x 240 x 60mm

2 3/8 x 9 1/2 x 2 3/8"

720 Units/Bundle

.16 SqFt/Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. Important: A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.

Natural Stone - Sandstone Slabs



APPLICATIONS




APPEARANCE

Edge Detail - Zero
Surface Texture - Brushed / Riven
Joint Spacing - 0 mm
Void - n/a


TECHNICAL INFORMATION

Visit Unilock.com for more information.

LAYING PATTERNS



NaturalStone
Multi-Unit D



NaturalStone
Multi-Unit E



NaturalStone
Multi-Unit F



AUTUMN HARVEST



GOLDEN SAND



INDIAN COAST



IVORY SAND



STONE CLIFF GREY

| BRUSHED FINISH | 4 PC BUNDLE | 24 x 24 | 24 x 36 |
|----------------|-------------|---------|---------|
| Bundle Type | RANDOM | SINGLE | SINGLE |
| Thickness (mm) | 22 MM | 22 MM | 22 MM |

| SQFT PER | Crate | 174.00 | 160.00 | 180.00 |
|----------|-------|--------|--------|--------|
| | Units | 3.63 | 4.00 | 6.00 |

| UNITS PER | Crate | 48.00 | 40.00 | 30.00 |
|-----------|-------|-------|-------|-------|
| | SqFt | 0.28 | 0.25 | 0.17 |

| LBS PER | Unit | 47 | 46 | 69 |
|---------|--------|-------|-------|-------|
| | Bundle | 2,265 | 1,851 | 2,082 |

| COLORS | Reflectance | Stock | Stock | Stock |
|--------------------------|----------------|-------|-------|-------|
| Autumn Harvest (Riven) | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| Golden Sand (Brushed) | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| Indian Coast (Brushed) | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| Ivory Sand (Brushed) | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| Stone Cliff Grey (Riven) | SR n/a SRI n/a | ✓ | ✓ | ✓ |

| Random Bundle | | | | | Single Units | | |
|---------------|--|--|--|--|--------------|--|--|
| | 12 x 24 | 18 x 24 | 24 x 24 | 24 x 36 | | 24 x 24 | 24 x 36 |
| | 300 x 600 x 22mm 11 3/4 x 23 5/8 x 7/8" | 450 x 600 x 22mm 17 3/4 x 23 5/8 x 7/8" | 600 x 600 x 22mm 23 5/8 x 23 5/8 x 7/8" | 600 x 900 x 22mm 23 5/8 x 35 1/2 x 7/8" | | 600 x 600 x 22mm 23 5/8 x 23 5/8 x 7/8" | 600 x 900 x 22mm 23 5/8 x 35 1/2 x 7/8" |
| | | | Also sold separately in all colors | Also sold separately in all colors | | Also sold separately in all colors | Also sold separately in all colors |

Notes: **SOLD IN FULL CRATES ONLY.** Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurements are nominal. **Product is not intended for vehicular applications.**

Natural Stone - Sandstone Steps, Coping and Pillar Cap



| | | 48 x 12 FULLNOSE COPING | 48 x 12 ROCK FACED COPING | 24 x 24 PILLAR CAP | 28 x 28 PILLAR CAP | 14 x 48 COPING |
|------------------|--------------------|-------------------------------|---------------------------------|-----------------------|-----------------------|-------------------|
| | Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| | Thickness (mm) | 50 MM | 50 MM | 64 MM | 100 MM | 50 MM |
| UNITS PER | Crate | 20.00 | 20.00 | 14.00 | 12.00 | 20.00 |
| | SqFt | - | - | - | - | - |
| LBS PER | Unit | 101 | 106 | 137 | 200 | 127.86 |
| | Bundle | 2,028 | 2,116 | 1,914 | 2,401 | 2,557 |

APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Brushed / Riven

Joint Spacing - 0 mm

Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|--------------------------|----------------|-------|-------|-------|-------|-------|
| Autumn Harvest (Riven) | SR n/a SRI n/a | ✓ | ✓ | ✓ | - | - |
| Golden Sand (Brushed) | SR n/a SRI n/a | ✓ | ✓ | ✓ | - | - |
| Indian Coast (Brushed) | SR n/a SRI n/a | ✓ | ✓ | ✓ | - | - |
| Ivory Sand (Brushed) | SR n/a SRI n/a | ✓ | ✓ | ✓ | - | - |
| Stone Cliff Grey (Riven) | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |


| | 48 x 16 STEP |
|--------------------|-----------------|
| Bundle Type | SINGLE |
| Thickness (mm) | 150 MM |

| | | |
|-----------------|-------|-------|
| FCFT PER | Crate | 32.00 |
|-----------------|-------|-------|

| | | |
|-----------------|-------|-------|
| LNFT PER | Crate | 24.00 |
|-----------------|-------|-------|







| | | |
|------------------|-------|------|
| UNITS PER | Crate | 6.00 |
|------------------|-------|------|

| | | |
|----------------|--------|-------|
| LBS PER | Bundle | 2,526 |
|----------------|--------|-------|



AUTUMN HARVEST GOLDEN SAND INDIAN COAST IVORY SAND STONE CLIFF GREY

| COLORS | Reflectance | Stock |
|--------------------------|----------------|-------|
| Autumn Harvest (Riven) | SR n/a SRI n/a | ✓ |
| Golden Sand (Brushed) | SR n/a SRI n/a | ✓ |
| Indian Coast (Brushed) | SR n/a SRI n/a | ✓ |
| Ivory Sand (Brushed) | SR n/a SRI n/a | ✓ |
| Stone Cliff Grey (Riven) | SR n/a SRI n/a | ✓ |

| | | | | |
|--------------|--|---|---|--|
| Single Units |  | COPING 1,200 x 50 x 350mm 48 x 2 x 14" |  | PILLAR CAP 720 x 720 x 100mm 28 x 28 x 4" |
| |  | 4' FULLNOSE 1,200 x 50 x 300mm 47 1/4 x 2 x 11 7/8" |  | 4' ROCK FACE 1,200 x 50 x 300mm 47 1/4 x 2 x 11 7/8" |
| Single Units |  | PILLAR CAP 600 x 600 x 64mm 23 5/8 x 23 5/8 x 2 5/8" |  | 48 X 16 STEP 1,200 X 150 X 400MM 47 1/4 X 5 7/8 X 15 3/4" |

Notes: Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurements are nominal. **Product is not intended for vehicular applications.**

Natural Stone - Limestone Slabs



APPLICATIONS




APPEARANCE

Edge Detail - Zero
Surface Texture - Riven
Joint Spacing - 0 mm
Void - n/a


TECHNICAL INFORMATION

Visit Unilock.com for more information.


LAYING PATTERNS



NaturalStone
Multi-Unit D



NaturalStone
Multi-Unit E



NaturalStone
Multi-Unit F



BLACK RIVER



WINTER MIST

| BRUSHED FINISH | 4 PC BUNDLE | 24 x 24 | 24 x 36 |
|----------------|-------------|---------|---------|
| Bundle Type | RANDOM | SINGLE | SINGLE |
| Thickness (mm) | 22 MM | 22 MM | 22 MM |

| SQFT PER | Crate | 174.00 | 160.00 | 180.00 |
|----------|-------|--------|--------|--------|
| | Units | 3.63 | 4.00 | 6.00 |

| UNITS PER | Crate | 48.00 | 40.00 | 30.00 |
|-----------|-------|-------|-------|-------|
| | SqFt | 0.28 | 0.25 | 0.17 |

| LBS PER | Unit | 47 | 46 | 69 |
|---------|--------|-------|-------|-------|
| | Bundle | 2,265 | 1,851 | 2,082 |

| COLORS | Reflectance | Stock | Stock | Stock |
|-------------|----------------|-------|-------|-------|
| Black River | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| Winter Mist | SR n/a SRI n/a | ✓ | ✓ | ✓ |

| Random Bundle | | | | | Single Units | | |
|---------------|--|--|---|---|--------------|---|---|
| | 12 x 24 | 18 x 24 | 24 x 24 | 24 x 36 | | 24 X 24 | 24 x 36 |
| | 300 x 600 x 22mm 11 3/4 x 23 5/8 x 7/8" | 450 x 600 x 22mm 17 3/4 x 23 5/8 x 7/8" | 600 x 600 x 22mm 23 5/8 x 23 5/8 x 7/8" Also sold separately in all colors | 600 x 900 x 22mm 23 5/8 x 35 1/2 x 7/8" Also sold separately in all colors | | 600 x 600 x 22mm 23 5/8 x 23 5/8 x 7/8" Also sold separately in all colors | 600 x 900 x 22mm 23 5/8 x 35 1/2 x 7/8" Also sold separately in all colors |

Notes: **SOLD IN FULL CRATES ONLY.** Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurements are nominal. **Product is not intended for vehicular applications.**

Natural Stone - Limestone Steps, Coping and Pillar Cap



APPLICATIONS




APPEARANCE

Edge Detail - Zero
Surface Texture - Riven
Joint Spacing - 0 mm
Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.



BLACK RIVER



WINTER MIST

| | 48 x 12 ROCK FACED COPING | 48 x 12 FULLNOSE COPING | 24 x 24 PILLAR CAP | 28 x 28 PILLAR CAP | 14 x 48 COPING |
|-----------------------|---------------------------------|-------------------------------|-----------------------|-----------------------|-------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Thickness (mm) | 50 MM | 50 MM | 64 MM | 64 MM | 50 MM |

| | | | | | | |
|------------------|-------|-------|-------|-------|-------|-------|
| UNITS PER | Crate | 20.00 | 20.00 | 14.00 | 12.00 | 20.00 |
| | SqFt | - | - | - | - | - |

| | | | | | | |
|----------------|--------|-------|-------|-------|-------|--------|
| LBS PER | Unit | 104 | 159 | 137 | 233.5 | 127.86 |
| | Bundle | 2,072 | 3,175 | 1,914 | 2,802 | 2,557 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|-------------|----------------|-------|-------|-------|-------|-------|
| Black River | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |
| Winter Mist | SR n/a SRI n/a | | | ✓ | | |

| | |
|-----------------------|-------------------------|
| | 48 x 16 STEP |
| Bundle Type | SINGLE |
| Thickness (mm) | 150 MM |

| | | |
|-----------------|-------|-------|
| FCFT PER | Crate | 32.00 |
|-----------------|-------|-------|

| | | |
|-----------------|-------|-------|
| LNFT PER | Crate | 24.00 |
|-----------------|-------|-------|

| | | |
|------------------|-------|------|
| UNITS PER | Crate | 6.00 |
|------------------|-------|------|

| | | |
|----------------|--------|-------|
| LBS PER | Bundle | 2,646 |
|----------------|--------|-------|

| COLORS | Reflectance | Stock |
|-------------|----------------|-------|
| Black River | SR n/a SRI n/a | ✓ |

Single Units



PILLAR CAP
710 x 710 x 64mm
28 x 28 x 2 5/8"



COPING
1,200 x 50 x 350mm
48 x 2 x 14"

Single Units



4' FULLNOSE
1,200 x 50 x 300mm
47 1/4 x 2 x 11 7/8"



4' ROCK FACE
1,200 x 50 x 300mm
47 1/4 x 2 x 11 7/8"



PILLAR CAP
600 x 600 x 64mm
23 5/8 x 23 5/8 x 2 5/8"



48 x 16 STEP
1,200 x 150 x 400mm
47 1/4 x 5 7/8 x 15 3/4"
Black River only

Notes: Natural Stone is available for purchase by Unilock Authorized Dealers only. Unilock offers adjustable and stackable pedestal system; please contact your Territory Manager for pricing and availability. Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. **Important:** Natural Stone is covered under Unilock's Transferable Lifetime Guarantee. All measurements are nominal. **Product is not intended for vehicular applications.**



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Textured

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™


Refined surface and long-lasting color

TECHNICAL INFORMATION


Conforms to ASTM C 936

Eligible for LEED v4.1 credits


LAYING PATTERNS




NordicCobble_A



NordicCobble_Fan




NordicCobble_Circle



DARK CHARCOAL



GRANITE FUSION



OPAL

| | | PREMIER |
|----------------|--|---------|
| Bundle Type | | SINGLE |
| Plant Produced | | CHICAGO |
| Thickness (mm) | | 60 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 98.25 |
| | Layer | 9.82 |
| | Section | - |
| | Stone | 0.09 |

| | | |
|------------|----------|-------|
| PER BUNDLE | Layers | 10.00 |
| | Sections | - |

| | | |
|------------------|---------|--------|
| SOLDIER LNFT PER | SqFt | 3.39 |
| | Section | - |
| | Layer | 33.30 |
| | Bundle | 333.07 |

| | | |
|-----------------|---------|---|
| SAILOR LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 10.99 |
| | Section | - |
| | Bundle | 1,080 |

| | | |
|---------|---------|--------|
| LBS PER | Layer | 230.10 |
| | Section | - |
| | Bundle | 2,301 |

| COLORS | Reflectance | Stock |
|----------------|----------------|-------|
| Dark Charcoal | SR n/a SRI n/a | ✓ |
| Granite Fusion | SR n/a SRI n/a | ✓ |
| Opal | SR n/a SRI n/a | ✓ |

Single Unit



STANDARD

89.9 x 94 x 60mm
3 5/8 x 3 3/4 x 2 3/8"
1,080 units/Bundle
.09 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
Surface Texture - Smooth
Joint Spacing - 8 mm
Void - n/a

TECHNOLOGIES


CLASSIC

Budget-friendly traditional product mix


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Optiloc A



Optiloc B

| Bundle Type | | SINGLE |
|----------------|--|--------|
| Plant Produced | | OHIO |
| Thickness (mm) | | 80 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 77.33 |
| | Layer | 9.67 |
| | Section | - |
| | Stone | 0.54 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------------|---------|---|
| SAILOR LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 1.86 |
| | Section | - |
| | Bundle | 144.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 350 |
| | Section | - |
| | Bundle | 2,801 |

| COLORS | Reflectance | Stock |
|-----------------------|----------------|-------|
| All Colors & Finishes | SR n/a SRI n/a | SO |

Single Unit



STANDARD
100 x 200 x 80mm
3 7/8 x 7 7/8 x 3 1/8"
378 units/Bundle
.22 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.

Porcelain 24x24 - 16x48



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Woodgrain & Stone Finish


Joint Spacing - n/a

Void - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

LAYING PATTERNS



Porcelain 24x24 RB_A



Porcelain 16x48 RB_E

| | 24 x 24 DEL CONCA SQUARE PRESSED EDGE | DEL CONCA SQUARE PRESSED EDGE | 16 x 48 DEL CONCA RECTANGLE PRESSED EDGE |
|--------------------|---|----------------------------------|--|
| Bundle Type | SINGLE | RANDOM | SINGLE |
| Thickness (mm) | 20 MM | 20 MM | 20 MM |

| | | | | |
|-----------------|--------|--------|--------|--------|
| SQFT PER | Pallet | 248.00 | 434.00 | 279.18 |
| | Box | 7.75 | - | 5.17 |
| | Unit | 3.88 | - | 5.17 |

| | | | | |
|-------------------|------|--------|---|--------|
| PER PALLET | Box | 32.00 | - | 54.00 |
| | SqFt | 248.00 | - | 279.18 |
| | Unit | 64.00 | - | 54.00 |

| | | | | |
|------------------|--------|-------|-----|-------|
| UNITS PER | Pallet | 64.00 | 192 | 54.00 |
| | Box | 2.00 | - | 1.00 |

| | | | | |
|----------------|--------|-------|-------|-------|
| LBS PER | Unit | 36 | - | 52 |
| | SqFt | 9 | - | 10 |
| | Box | 72 | - | 52 |
| | Pallet | 2,310 | 4,005 | 2,797 |

| COLORS | Reflectance | Stock | Stock | Stock |
|-----------------------|-------------|-------|-------|-------|
| Chamonix Beige | n/a | ✓ | - | - |
| Chamonix Bianco | n/a | ✓ | - | - |
| Chamonix Dark Grey | n/a | ✓ | - | - |
| Chamonix Grey | n/a | ✓ | - | - |
| Gotham Bianco | n/a | ✓ | - | - |
| Gotham Grey | n/a | ✓ | ✓ | - |
| Gotham Nero | n/a | ✓ | - | - |
| Travestone Beige | n/a | ✓ | ✓ | - |
| Travestone Grey | n/a | ✓ | - | - |
| West 57th Bianco | n/a | ✓ | - | - |
| West 57th Grey | n/a | ✓ | - | - |
| Essential White | n/a | ✓ | - | - |
| Essential Grey | n/a | ✓ | - | - |
| Essential Anthracite | n/a | ✓ | - | - |
| Essential Beige | n/a | ✓ | - | - |
| Nature Dolomite | n/a | ✓ | - | - |
| Nature Carrara | n/a | ✓ | - | - |
| New England White | n/a | ✓ | - | - |
| New England Ivory | n/a | ✓ | - | - |
| New England Cold Grey | n/a | ✓ | - | - |
| Monteverde Beige | n/a | - | - | ✓ |
| Monteverde Grey | n/a | - | - | ✓ |
| Monteverde Noce | n/a | - | - | ✓ |



Notes: **SOLD IN FULL CRATES ONLY.** All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. **Product is not intended for vehicular applications.**



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Woodgrain & Stone Finish

Joint Spacing - n/a


TECHNICAL INFORMATION

Visit Unilock.com for more information.

LAYING PATTERNS



Porcelain 16x32
RB_C



Porcelain 16x32
HB_D



ARBOR BIANCO



QUARTZITE BIANCO



QUARTZITE
DARK GRAY



QUARTZITE GRAY



QUARTZITE SAND



TRAVSTONE BEIGE




TRAVSTONE GRAY



NEW ENGLAND WHITE



NEW ENGLAND IVORY



NEW ENGLAND COLD GRAY

| | | DEL CONCA RECTANGLE PRESSED EDGE (STONE) | DEL CONCA RECTANGLE PRESSED EDGE (WOOD) | 24 x 48 |
|----------------|--------|--|---|---------|
| Bundle Type | | SINGLE | SINGLE | SINGLE |
| Thickness (mm) | | 20 MM | 20 MM | 20 MM |
| SQFT PER | Pallet | 165.36 | 268.71 | 103.4 |
| | Box | 6.89 | 6.89 | 5.17 |
| | Unit | 3.45 | 3.45 | 5.17 |
| PER PALLET | Box | 24.00 | 39.00 | 20.00 |
| | SqFt | 165.36 | 268.71 | 103.4 |
| | Unit | 48.00 | 78.00 | 20.00 |
| UNITS PER | Pallet | 48.00 | 78.00 | 20.00 |
| | Box | 2.00 | 2.00 | 1.00 |
| LBS PER | Unit | 32 | 32 | 49.82 |
| | SqFt | 9 | 9 | 9.63 |
| | Box | 65 | 64 | 49.82 |
| | Pallet | 1,552 | 2,504 | 996.4 |

| COLORS | Reflectance | Stock | Stock | Stock |
|-----------------------|-------------|-------|-------|-------|
| Arbor Bianco (WG) | n/a | - | ✓ | - |
| Quartzite Bianco | n/a | ✓ | - | - |
| Quartzite Dark Grey | n/a | ✓ | - | - |
| Quartzite Grey | n/a | ✓ | - | - |
| Quartzite Sand | n/a | ✓ | - | - |
| Travestone Beige | n/a | ✓ | - | - |
| Travestone Grey | n/a | ✓ | - | - |
| New England White | n/a | ✓ | - | ✓ |
| New England Ivory | n/a | ✓ | - | ✓ |
| New England Cold Grey | n/a | ✓ | - | - |

Single Units



PRESSED EDGE RECTANGLE

400 x 800 x 20mm
15 3/4 x 31 1/2 x 7/8"
3.45 Sq.Ft./Stone



24 x 48

600 x 1200 x 20mm
23 5/8 x 47 1/4 x 7/8"
5.17 Sq.Ft./Stone

Notes: **SOLD IN FULL CRATES ONLY.** All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. **Product is not intended for vehicular applications.**



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth,
Series™ Exposed & Il Campo® Brushed
Joint Spacing - 4 mm
Void - n/a

TECHNOLOGIES


ENDURACOLOR™

Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Promenade 8x24
RB_D



Promenade 8x24
HB_F

| | 4 x 16 SMOOTH | 8 x 24 SMOOTH | 8 x 24 SERIES | 8 x 24 IL CAMPO | 8 x 24 UMBRIANO |
|-----------------------|------------------|------------------|------------------|--------------------|--------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | PICKERING | PICKERING | GEORGETOWN | GEORGETOWN | GEORGETOWN |
| Thickness (mm) | 100 MM | 100 MM | 100 MM | 100 MM | 70 MM |

| | | | | | | |
|-----------------|----------------|-------|-------|-------|-------|-------|
| SQFT PER | Bundle | 51.67 | 51.67 | 51.67 | 51.67 | 82.67 |
| | Layer | 10.33 | 10.33 | 10.33 | 10.33 | 10.33 |
| | Section | - | - | - | - | - |
| | Stone | 0.43 | 1.29 | 1.29 | 1.29 | 1.29 |

| | | | | | | |
|-------------------|-----------------|------|------|------|------|------|
| PER BUNDLE | Layers | 5.00 | 5.00 | 5.00 | 5.00 | 8.00 |
| | Sections | - | - | - | - | - |

| | | | | | | |
|-----------------------------|----------------|-------|-------|-------|-------|-------|
| SOLDIER LNFT PER | SqFt | 0.76 | 0.51 | 0.51 | 0.51 | 0.51 |
| | Section | - | - | - | - | - |
| | Layer | 7.87 | 5.25 | 5.25 | 5.25 | 5.25 |
| | Bundle | 39.37 | 26.25 | 26.25 | 26.25 | 41.99 |

| | | | | | | |
|----------------------------|----------------|--------|-------|-------|-------|-------|
| SAILOR LNFT PER | SqFt | 3.05 | 1.52 | 1.52 | 1.52 | 1.02 |
| | Section | - | - | - | - | - |
| | Layer | 31.50 | 15.75 | 15.75 | 15.75 | 10.50 |
| | Bundle | 157.48 | 78.74 | 78.74 | 78.74 | 83.99 |

| | | | | | | |
|------------------|----------------|--------|-------|-------|-------|-------|
| UNITS PER | SqFt | 2.32 | 0.77 | 0.77 | 0.77 | 0.77 |
| | Section | - | - | - | - | - |
| | Bundle | 120.00 | 40.00 | 40.00 | 40.00 | 64.00 |

| | | | | | | |
|----------------|----------------|-------|-------|-------|-------|-------|
| LBS PER | Layer | 488 | 478 | 478 | 478 | 331 |
| | Section | - | - | - | - | - |
| | Bundle | 2,440 | 2,391 | 2,391 | 2,391 | 2,647 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|-----------------|----------------|-------|-------|-------|-------|-------|
| Black Granite | SR n/a SRI n/a | - | - | ✓ | - | - |
| Dark Charcoal | SR n/a SRI n/a | - | - | - | ✓ | - |
| Granite Fussion | SR n/a SRI n/a | - | - | - | ✓ | - |
| Light Grey | SR n/a SRI n/a | - | - | - | ✓ | - |
| Opal | SR .24 SRI 24 | - | ✓ | - | - | - |
| Steel Grey | SR n/a SRI n/a | ✓ | - | - | - | - |
| French Grey | SR .18 SRI 17 | - | - | - | - | ✓ |
| Midnight Sky | SR .17 SRI 15 | - | - | - | - | ✓ |
| Summer Wheat | SR .42 SRI 48 | - | - | - | - | ✓ |
| Winter Marvel | SR .35 SRI 38 | - | - | - | - | ✓ |

Single Units



**4 x 16
SMOOTH**
100 x 400 x 100mm
3 7/8 x 15 3/4 x 3 7/8"
120 units/Bundle
.43 Sq.Ft./Stone



**8 x 24
SMOOTH**
200 x 600 x 100mm
7 7/8 x 23 5/8 x 3 7/8"
40 Units/Bundle
1.29 Sq.Ft./Stone



**8 x 24 SERIES
EXPOSED**
200 x 600 x 100mm
7 7/8 x 23 5/8 x 3 7/8"
40 units/Bundle
1.29 Sq.Ft./Stone



**8 x 24 IL CAMPO
BRUSHED**
200 x 600 x 100mm
7 7/8 x 23 5/8 x 3 7/8"
40 units/Bundle
1.29 Sq.Ft./Stone

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded

Surface Texture - Smooth, Series™ & Umbriano

Il Campo® Brushed®

Joint Spacing - 4 mm / 7mm (Umbriano

Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™ (Umbriano)

Factory Sealed to provide integral stain resistance

COLORFUSION™ (Umbriano)


Subtly mottled colored finish

TECHNICAL INFORMATION


Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERNS



Promenade 4x12
RB_A



Promenade 4x12
HB_C

| | | SMOOTH | SERIES | IL CAMPO | SMOOTH | UMBRIANO® |
|------------------|----------|-----------|------------|------------|--------|-----------|
| Bundle Type | | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | | PICKERING | GEORGETOWN | GEORGETOWN | OHIO | MARENGO |
| Thickness (mm) | | 100 MM | 100 MM | 100 MM | 80 MM | 80 MM |
| SQFT PER | Bundle | 58.13 | 58.13 | 58.13 | 81.41 | 93.04 |
| | Layer | 11.63 | 11.63 | 11.63 | 11.63 | 11.63 |
| | Section | - | - | - | - | - |
| | Stone | 0.32 | 0.32 | 0.32 | 0.32 | 0.32 |
| PER BUNDLE | Layers | 5.00 | 5.00 | 5.00 | 7.00 | 8.00 |
| | Sections | - | - | - | - | - |
| SOLDIER LNFT PER | SqFt | 1.02 | 1.02 | 1.02 | 1.02 | 1.02 |
| | Section | - | - | - | - | - |
| | Layer | 11.81 | 11.81 | 11.81 | 11.81 | 11.81 |
| | Bundle | 59.06 | 59.06 | 59.06 | 82.68 | 94.49 |
| SAILOR LNFT PER | SqFt | 3.05 | 3.05 | 3.05 | 3.05 | 3.05 |
| | Section | - | - | - | - | - |
| | Layer | 35.43 | 35.43 | 35.43 | 35.43 | 35.43 |
| | Bundle | 177.17 | 177.17 | 177.17 | 248.03 | 283.46 |
| UNITS PER | SqFt | 3.10 | 3.10 | 3.10 | 3.10 | 3.10 |
| | Section | - | - | - | - | - |
| | Bundle | 180.00 | 180.00 | 180.00 | 252.00 | 288.00 |
| LBS PER | Layer | 532 | 532 | 532 | 425 | 426 |
| | Section | - | - | - | - | - |
| | Bundle | 2,659 | 2,659 | 2,659 | 2,978 | 3,404 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|---------------|---------------|-------|-------|-------|-------|-------|
| Black Granite | n/a | - | ✓ | - | - | - |
| Light Grey | n/a | - | - | ✓ | - | - |
| Sandstone | n/a | ✓ | - | - | - | - |
| Opal Blend | n/a | - | - | - | ✓ | - |
| Dark Charcoal | n/a | - | - | - | ✓ | - |
| Medium Grey | n/a | - | - | - | ✓ | - |
| French Grey | SR .17 SRI 15 | - | - | - | - | ✓ |
| Midnight Sky | SR .17 SRI 15 | - | - | - | - | ✓ |
| Winter Marvel | SR .17 SRI 15 | - | - | - | - | ✓ |

| | | | | | | | | | | |
|--------------|---|---|---|--|---|--|--|--|---|--|
| Single Units |  | 4 x 12 SMOOTH 100 x 300 x 80mm 3 7/8 x 11 7/8 x 3 1/8" 252 units/Bundle .32 Sq.Ft./Stone |  | 4 x 12 UMBRIANO® 100 x 300 x 80mm 3 7/8 x 11 7/8 x 3 1/8" 288 units/Bundle .32 Sq.Ft./Stone |  | 4 x 12 SMOOTH 100 x 300 x 100mm 3 7/8 x 11 7/8 x 3 7/8" 180 units/Bundle .32 Sq.Ft./Stone |  | 4 x 12 SERIES 100 x 300 x 100mm 3 7/8 x 11 7/8 x 3 7/8" 180 units/Bundle .32 Sq.Ft./Stone |  | 4 x 12 IL CAMPO BRUSHED 100 x 300 x 100mm 3 7/8 x 11 7/8 x 3 7/8" 180 units/Bundle .32 Sq.Ft./Stone |
|--------------|---|---|---|--|---|--|--|--|---|--|

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Shot Blast
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

ECOTERRA®

Reduced carbon emissions and refined surface protection

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | | |
|--|-----------------------|----------------|
| | | 4 x 12 |
| | Bundle Type | SINGLE |
| | Plant Produced | ONTARIO |
| | Thickness (mm) | 70 MM |

| | | |
|-----------------|---------|-------|
| SQFT PER | Bundle | 93.04 |
| | Layer | 11.63 |
| | Section | 23.26 |
| | Stone | 0.32 |

| | | |
|-------------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | 4.00 |

| | | |
|-------------------------|---------|-------|
| SOLDIER LNFT PER | SqFt | 1.02 |
| | Section | 23.62 |
| | Layer | 11.81 |
| | Bundle | 94.49 |


| | | |
|------------------------|---------|--------|
| SAILOR LNFT PER | SqFt | 3.05 |
| | Section | 70.87 |
| | Layer | 35.43 |
| | Bundle | 283.46 |

| | | |
|------------------|---------|--------|
| UNITS PER | SqFt | 3.10 |
| | Section | 36.00 |
| | Bundle | 288.00 |


| | | |
|----------------|---------|-------|
| LBS PER | Layer | 393 |
| | Section | 785 |
| | Bundle | 3,140 |

| COLORS | Reflectance | Stock |
|------------------|----------------|-------|
| Light Opal Blend | SR n/a SRI n/a | SO |
| Light Steel Gray | SR n/a SRI n/a | SO |

LAYING PATTERNS



4x12 RB_A



4x12 HB_C



LIGHT OPAL BLEND



LIGHT STEEL GRAY

Single Unit



4 x 12
100 x 300 x 70 mm
3 7/8 x 11 7/8 x 2 3/4
288 units/Bundle
.32 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured
Joint Spacing - 10 mm
Void - n/a

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

EASYCLEAN™

Factory Sealed to provide integral stain resistance

REALA™

Cast from natural stone


ULTIMA™

Up to 4x stronger than poured-in-place concrete


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Richcliff Fixed
Random A



Richcliff Fixed
Random B



Richcliff LargeRec
HB_H



DAWN MIST



PEBBLE TAUPE



SMOKE SHALE

| | | LARGE RECTANGLE |
|----------------|--------|-----------------|
| Bundle Type | RANDOM | SINGLE |
| Plant Produced | AYR | AYR |
| Thickness (mm) | 60 MM | 60 MM |

| SQFT PER | Bundle | 90.30 | 82.39 |
|----------|---------|-------|-------|
| | Layer | 11.29 | 10.30 |
| | Section | - | - |
| | Stone | - | 1.72 |

| PER BUNDLE | Layers | 8.00 | 8.00 |
|------------|----------|------|------|
| | Sections | - | - |

| SOLDIER LNFT PER | SqFt | - | 0.58 |
|------------------|---------|---|-------|
| | Section | - | - |
| | Layer | - | 5.94 |
| | Bundle | - | 47.56 |

| SAILOR LNFT PER | SqFt | 1.31 | 1.01 |
|-----------------|---------|--------|-------|
| | Section | - | - |
| | Layer | 14.78 | 10.39 |
| | Bundle | 118.22 | 83.15 |

| UNITS PER | SqFt | 1.77 | 0.58 |
|-----------|---------|--------|-------|
| | Section | - | - |
| | Bundle | 160.00 | 48.00 |

| LBS PER | Layer | 309 | 301 |
|---------|---------|-------|-------|
| | Section | - | - |
| | Bundle | 2,472 | 2,411 |

| COLORS | Reflectance | Stock | Stock |
|--------------|----------------|-------|-------|
| Dawn Mist | SR n/a SRI n/a | ✓ | ✓ |
| Pebble Taupe | SR n/a SRI n/a | ✓ | ✓ |
| Smoke Shale | SR n/a SRI n/a | ✓ | ✓ |

| Random Bundle | RECTANGLE | SQUARE | SMALL RECTANGLE | Single Unit | LARGE RECTANGLE |
|---------------|---|--|--|-------------|--|
| | 226 x 300 x 60mm 8 7/8 x 11 7/8 x 2 3/8" | 226 x 226 x 60mm 8 7/8 x 8 7/8 x 2 3/8" | 150 x 226 x 60mm 5 7/8 x 8 7/8 x 2 3/8" | | 302 x 528 x 60mm 11 7/8 x 20 7/8 x 2 3/8" |
| | 64 Units/Bundle .75 SqFt./Stone | 32 units/Bundle .58 Sq.Ft./Stone | 64 units/Bundle .38 Sq.Ft./Stone | | 48 units/Bundle 1.72 Sq.Ft./Stone |

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer

Surface Texture - Series Exposed

Joint Spacing - n/a

Void - n/a

TECHNOLOGIES

ENDURACOLOR™


Refined surface and long-lasting color

TECHNICAL INFORMATION


Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERNS



Series 4x8_HB_G



Series 4x8_RB_F

| | 4 x 8 | 4 x 12 | 3 x 12 PERMEABLE | 4 x 12 | 8 x 24 |
|--------------------|---------------|---------------|---------------------|---------------|---------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | CHICAGO | CHICAGO | CHICAGO | GEORGETOWN | GEORGETOWN |
| Thickness (mm) | 60 MM | 80 MM | 100 MM | 100 MM | 100 MM |

| | | | | | | |
|-----------------|---------|--------|-------|-------|-------|-------|
| SQFT PER | Bundle | 117.90 | 93.04 | 63.94 | 58.13 | 51.67 |
| | Layer | 11.79 | 11.63 | 10.66 | 11.63 | 10.33 |
| | Section | - | - | - | - | - |
| | Stone | 0.22 | 0.32 | 0.24 | 0.32 | 1.29 |

| | | | | | | |
|-------------------|----------|-------|------|------|------|------|
| PER BUNDLE | Layers | 10.00 | 8.00 | 6.00 | 5.00 | 5.00 |
| | Sections | - | - | - | - | - |


| | | | | | | |
|-------------------------|---------|--------|-------|-------|-------|-------|
| SOLDIER LNFT PER | SqFt | 1.50 | 1.02 | 1.02 | 1.02 | 0.51 |
| | Section | - | - | - | - | - |
| | Layer | 17.72 | 11.81 | 10.83 | 11.81 | 5.25 |
| | Bundle | 177.17 | 94.49 | 64.96 | 59.06 | 26.25 |

| | | | | | | |
|------------------------|---------|--------|--------|--------|--------|-------|
| SAILOR LNFT PER | SqFt | 3.01 | 3.05 | 4.06 | 3.05 | 1.52 |
| | Section | - | - | - | - | - |
| | Layer | 35.43 | 35.43 | 43.31 | 35.43 | 15.75 |
| | Bundle | 354.33 | 283.46 | 259.84 | 177.17 | 78.74 |

| | | | | | | |
|------------------|---------|--------|--------|--------|--------|-------|
| UNITS PER | SqFt | 4.58 | 3.10 | 4.13 | 3.10 | 0.77 |
| | Section | - | - | - | - | - |
| | Bundle | 540.00 | 288.00 | 264.00 | 180.00 | 40.00 |

| | | | | | | |
|----------------|---------|-------|-------|-------|-------|-------|
| LBS PER | Layer | 328 | 426 | 483 | 532 | 478 |
| | Section | - | - | - | - | - |
| | Bundle | 3,283 | 3,404 | 2,898 | 2,659 | 2,391 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|---------------|----------------|-------|-------|-------|-------|-------|
| Onyx Black | SR n/a SRI n/a | ✓ | - | - | - | - |
| Arctic Grey | SR n/a SRI n/a | - | ✓ | ✓ | - | - |
| Nordic Star | SR n/a SRI n/a | - | ✓ | ✓ | - | - |
| Light Grey | SR n/a SRI n/a | - | - | - | ✓ | - |
| Black Granite | SR n/a SRI n/a | - | - | - | - | ✓ |



ONYX BLACK



ARCTIC GREY









NORDIC STAR



LIGHT GREY



BLACK GRANITE

| | | | | | | |
|--------------|--|--|---|--|---|---|
| Single Units |  |  |  |  |  |  |
| | 4 x 8 100 x 200 x 60mm 3 7/8 x 7 7/8 x 2 3/8" 540 Units/Bundle .22 Sq.Ft./Stone | 4 x 12 100 x 300 x 80mm 3 7/8 x 11 7/8 x 3 1/8" 288 units/Bundle .32 Sq.Ft./Stone | 4 x 12 100 x 300 x 100mm 3 7/8 x 11 7/8 x 3 7/8" 180 units/Bundle .32 Sq.Ft./Stone | 3 x 12 PERMEABLE 75 x 300 x 100mm 3 x 11 1/2 x 3 7/8" 264 Units/Bundle .24 Sq.Ft./Stone | 8 x 24 200 x 600 x 100mm 7 7/8 x 23 5/8 x 3 7/8" 40 units/Bundle 1.29 Sq.Ft./Stone | |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 2mm
Void - n/a

TECHNOLOGIES


ENDURACOLOR™

Refined surface and long-lasting color


TECHNICAL INFORMATION

Conforms to ASTM C 1782
Eligible for LEED v4.1 credits

LAYING PATTERNS




Skyline 24x24 SB_A



Skyline 24x24 RB_B



CHAMOIS



SILVER GREY

| | |
|----------------|---------|
| | 24 x 24 |
| Bundle Type | SINGLE |
| Plant Produced | OHIO |
| Thickness (mm) | 50 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 80.00 |
| | Layer | 8.00 |
| | Section | - |
| | Stone | - |

| | | |
|------------|----------|-------|
| PER BUNDLE | Layers | 10.00 |
| | Sections | - |

| | | |
|------------------|---------|-------|
| SOLDIER LNFT PER | SqFt | 0.50 |
| | Section | - |
| | Layer | 4.00 |
| | Bundle | 40.00 |


| | | |
|-----------------|---------|-------|
| SAILOR LNFT PER | SqFt | 0.50 |
| | Section | - |
| | Layer | 4.00 |
| | Bundle | 40.00 |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 0.25 |
| | Section | - |
| | Bundle | 20.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 183 |
| | Section | - |
| | Bundle | 1,756 |

| COLORS | Reflectance | Stock |
|-------------|----------------|-------|
| Chamois | SR n/a SRI n/a | ✓ |
| Silver Grey | SR n/a SRI n/a | ✓ |

Single Unit



24 x 24
606 x 606 x 50mm
23 7/8 x 23 7/8 x 2"
20 units/Bundle
4.00 Sq.Ft./Stone



PEDESTAL SYSTEM

Contact your local Unilock Rep for more information.

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Product is not intended vehicular applications.** Minimum quantities apply. Unilock offers adjustable and stackable pedestal systems; please contact your Territory Manager for pricing and availability. All measurements are nominal.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Textured
Joint Spacing - 11-18 mm
Void - 4.4%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| Bundle Type | RANDOM |
|----------------|--------|
| Plant Produced | OHIO |
| Thickness (mm) | 70 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 88.61 |
| | Layer | 11.08 |
| | Section | - |
| | Stone | 0.92 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |


| | | |
|-----------------|---------|---|
| SAILOR LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 1.08 |
| | Section | - |
| | Bundle | 96.00 |


| | | |
|---------|---------|-------|
| LBS PER | Layer | 330 |
| | Section | - |
| | Bundle | 2,638 |

| COLORS | Reflectance | Stock |
|--------|----------------|-------|
| Fossil | SR n/a SRI n/a | ✓ |
| Sierra | SR n/a SRI n/a | ✓ |


LAYING PATTERNS



Thornbury Fixed
Random A



Thornbury Fixed
Random B






Thornbury Fixed
Random C



FOSSIL



SIERRA

| | | | | | | |
|---------------|---|---|---|---|--|---|
| Random Bundle |  | LARGE RECTANGLE 350 x 420 x 70mm 13 7/8 x 16 5/8 x 2 3/4" 32 Units/Bundle 1.58 SqFt./Stone |  | SQUARE 210 x 350 x 70mm 8 3/8 x 13 7/8 x 2 3/4" 32 units/Bundle .79 Sq.Ft./Stone |  | SMALL RECTANGLE 173 x 210 x 70mm 6 7/8 x 8 3/8 x 2 3/4" 32 units/Bundle .39 Sq.Ft./Stone |
|---------------|---|---|---|---|--|---|

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured
Joint Spacing - 3 mm
Void - n/a

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

EASYSOIL™

Factory Sealed to provide integral stain resistance

REALA™

Cast from historical brick


ULTIMA™

Up to 4x stronger than poured-in-place concrete


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



TownHall 4x10 HB_B



TownHall 4x10 RB_C



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK

| Bundle Type | | SINGLE |
|----------------|--|--------|
| Plant Produced | | AYR |
| Thickness (mm) | | 70 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 88.41 |
| | Layer | 11.05 |
| | Section | - |
| | Stone | 0.28 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|--------|
| SOLDIER LNFT PER | SqFt | 1.19 |
| | Section | - |
| | Layer | 13.12 |
| | Bundle | 104.99 |

| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 2.97 |
| | Section | - |
| | Layer | 32.81 |
| | Bundle | 262.47 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 3.62 |
| | Section | - |
| | Bundle | 320.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 361 |
| | Section | - |
| | Bundle | 2,888 |

| COLORS | Reflectance | Stock |
|--------------|----------------|-------|
| Basalt | SR n/a SRI n/a | ✓ |
| Burgundy Red | SR n/a SRI n/a | ✓ |
| Burnt Clay | SR n/a SRI n/a | ✓ |
| Old Oak | SR n/a SRI n/a | ✓ |

Single Unit



STANDARD
100 x 250 x 70mm
3 7/8 x 9 7/8 x 2 3/4"
320 Units/Bundle
.28 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices on Page 80. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Textured
Joint Spacing - 4mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| TREO PREMIER TEXTURED | |
|-----------------------|--------|
| Bundle Type | RANDOM |
| Plant Produced | OHIO |
| Thickness (mm) | 60 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 98.09 |
| | Layer | 10.90 |
| | Section | - |
| | Stone | 0.45 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 9.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 1.79 |
| | Section | - |
| | Layer | 19.56 |
| | Bundle | 176.06 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 2.20 |
| | Section | - |
| | Bundle | 216.00 |


| | | |
|---------|---------|-------|
| LBS PER | Layer | 285 |
| | Section | - |
| | Bundle | 2,565 |

| COLORS | Reflectance | Stock |
|----------------|----------------|-------|
| Granite Fusion | SR n/a SRI n/a | ✓ |
| River | SR n/a SRI n/a | ✓ |
| Sierra | SR n/a SRI n/a | ✓ |

LAYING PATTERNS



TreoSmooth Fixed
Random_R



TreoSmooth Fixed
Random_S






GRANITE FUSION



RIVER



SIERRA

| | | | | | | |
|---------------|---|--|---|--|---|--|
| Random Bundle |  | LARGE RECTANGLE 225 x 337.5 x 60mm 8 7/8 x 13 3/8 x 2 3/8" 45 units/Bundle .82 Sq.Ft./Stone |  | SQUARE 225 x 225 x 60mm 8 7/8 x 8 7/8 x 2 3/8" 54 units/Bundle .55 Sq.Ft./Stone |  | SMALL RECTANGLE 112.5 x 225 x 60mm 4 1/2 x 8 7/8 x 2 3/8" 117 units/Bundle .27 Sq.Ft./Stone |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Textured
Joint Spacing - 7mm
Void - 5.5 %

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

PERMEABLE

Can be installed to allow water to flow through

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | TREO SMOOTH PERMEABLE |
|----------------|-----------------------|
| Bundle Type | RANDOM |
| Plant Produced | OHIO |
| Thickness (mm) | 60 MM |

| | | |
|----------|---------|--------|
| SQFT PER | Bundle | 108.99 |
| | Layer | 10.90 |
| | Section | - |
| | Stone | 0.52 |

| | | |
|------------|----------|-------|
| PER BUNDLE | Layers | 10.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 1.35 |
| | Section | - |
| | Layer | 14.76 |
| | Bundle | 147.64 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 1.93 |
| | Section | - |
| | Bundle | 210.00 |


| | | |
|---------|---------|-------|
| LBS PER | Layer | 296 |
| | Section | - |
| | Bundle | 2,960 |

| COLORS | Reflectance | Stock |
|----------------|----------------|-------|
| Fossil | SR n/a SRI n/a | ✓ |
| Granite Fusion | SR n/a SRI n/a | ✓ |
| Tuscany | SR n/a SRI n/a | ✓ |


LAYING PATTERNS



TreoSmooth Fixed
Random_R




TreoSmooth Fixed
Random_S






FOSSIL



GRANITE FUSION



TUSCANY

| | | | | | | |
|---------------|---|--|---|--|---|---|
| Random Bundle |  | LARGE RECTANGLE 225 x 337.5 x 60mm 8 7/8 x 13 3/8 x 2 3/8" 60 units/Bundle .82 Sq.Ft./Stone |  | SQUARE 225 x 225 x 60mm 8 7/8 x 8 7/8 x 2 3/8" 70 units/Bundle .55 Sq.Ft./Stone |  | SMALL RECTANGLE 112.5 x 225 x 60mm 4 1/2 x 8 7/8 x 2 3/8" 80 units/Bundle .27 Sq.Ft./Stone |
|---------------|---|--|---|--|---|---|

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro

Surface Texture - Series Exposed Textured

Joint Spacing - 10mm

Void - 5.6%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

| Bundle Type | RANDOM |
|----------------|---------|
| Plant Produced | CHICAGO |
| Thickness (mm) | 70 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 97.53 |
| | Layer | 12.19 |
| | Section | 12.19 |
| | Stone | 0.32 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | 8.00 |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |


| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 2.34 |
| | Section | 28.49 |
| | Layer | 28.49 |
| | Bundle | 227.95 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 3.12 |
| | Section | 38.00 |
| | Bundle | 304.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 398 |
| | Section | 398 |
| | Bundle | 3,186 |

| COLORS | Reflectance | Stock |
|------------------|----------------|-------|
| Cobalt Grey | SR n/a SRI n/a | ✓ |
| Peppered Granite | SR .38 SRI 42 | ✓ |

LAYING PATTERNS



Tribeca Cobble
Fixed Random_A



COBALT GREY



PEPPERED GRANITE

| | | |
|---------------|---|--|
| Random Bundle |  | LARGE RECTANGLE 130 x 305 x 70mm 5 x 12 x 2 ¾" 88 units/Bundle .43 Sq.Ft./Stone |
| |  | RECTANGLE 130 x 230 x 70mm 5 x 9 x 2 ¾" 88 units/Bundle .32 Sq.Ft./Stone |
| |  | SMALL RECTANGLE 130 x 175 x 70mm 5 x 6 7/8 x 2 ¾" 128 units/Bundle .25 Sq.Ft./Stone |
| | | |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices on page 80. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 2mm
Void - 40%

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

PERMEABLE

Can be installed to allow water to flow through

TECHNICAL INFORMATION

Conforms to ASTM C1319
Eligible for LEED v4.1 credits

| | SMOOTH |
|----------------|--------|
| Bundle Type | RANDOM |
| Plant Produced | OHIO |
| Thickness (mm) | 80 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 70.00 |
| | Layer | 10.00 |
| | Section | - |
| | Stone | 2.50 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 7.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |


| | | |
|-----------------|---------|---|
| SAILOR LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 0.40 |
| | Section | - |
| | Bundle | 28.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 249 |
| | Section | - |
| | Bundle | 1,746 |

| COLORS | Reflectance | Stock |
|---------|---------------|-------|
| Natural | SR .30 SRI 32 | ✓ |

LAYING PATTERNS



Turfstone A



NATURAL

Single Unit



LARGE RECTANGLE
400 x 600 x 80mm
15 3/4 x 23 5/8 x 3 1/8"
28 units/Bundle
2.50 Sq.Ft./Stone



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Umbriano Mottled
Joint Spacing - 7mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™



Factory Sealed to provide integral stain resistance

COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | | 4 x 8 | 7 x 14 | 18 x 36 |
|--------------------|---------------|---------------|---------------|---------------|
| Bundle Type | RANDOM | SINGLE | SINGLE | SINGLE |
| Plant Produced | GEORGETOWN | MARENGO | GEORGETOWN | GEORGETOWN |
| Thickness (mm) | 60 MM | 60 MM | 60 MM | 60 MM |

| | | | | | |
|-----------------|---------|-------|--------|-------|------|
| SQFT PER | Bundle | 94.14 | 106.20 | 94.20 | |
| | Layer | 10.46 | 11.80 | 10.46 | 8.71 |
| | Section | - | - | - | - |
| | Stone | 1.31 | 0.22 | 1.43 | 0.23 |

| | | | | | |
|-------------------|----------|------|------|------|---|
| PER BUNDLE | Layers | 9.00 | 9.00 | 9.00 | - |
| | Sections | - | - | - | - |

| | | | | | |
|-------------------------|---------|---|--------|-------|------|
| SOLDIER LNFT PER | SqFt | - | 1.50 | 0.85 | 0.68 |
| | Section | - | - | - | - |
| | Layer | - | 17.72 | 8.85 | 5.90 |
| | Bundle | - | 159.45 | 79.72 | |


| | | | | | |
|------------------------|---------|-------|--------|-------|-------|
| SAILOR LNFT PER | SqFt | 0.85 | 3.00 | 1.69 | 1.35 |
| | Section | - | - | - | - |
| | Layer | 8.86 | 35.43 | 17.71 | 11.81 |
| | Bundle | 79.72 | 318.90 | 159.4 | - |

| | | | | | |
|------------------|---------|-------|--------|--------|------|
| UNITS PER | SqFt | 0.76 | 4.58 | 1.43 | 4.36 |
| | Section | - | - | - | - |
| | Bundle | 72.00 | 486.00 | 135.00 | - |


| | | | | | |
|----------------|---------|-------|-------|---|---|
| LBS PER | Layer | 287 | 322 | - | - |
| | Section | - | - | - | - |
| | Bundle | 2,584 | 2,900 | - | - |

| COLORS | Reflectance | Stock | Stock | Stock | Stock |
|---------------|----------------|-------|-------|-------|-------|
| French Grey | SR .18 SRI 17 | ✓ | - | ✓ | ✓ |
| Grenada White | SR .n/a SRI 52 | ✓ | - | ✓ | ✓ |
| Midnight Sky | SR .17 SRI 15 | - | ✓ | ✓ | ✓ |
| Summer Wheat | SR .42 SRI 48 | ✓ | - | ✓ | ✓ |
| Winter Marvel | SR .35 SRI 2 | ✓ | - | ✓ | ✓ |

LAYING PATTERNS



Umbriano Fixed
Random_A



Umbriano Fixed
Random_B



FRENCH GREY



GRENADA WHITE



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

| | | | | | | | |
|----------------------|--|--|---|---------------------|--|--------------------------------------|--|
| Random Bundle | | | | Single Units | | | |
| | LARGE RECTANGLE | SQUARE | SMALL RECTANGLE | | 4 x 8 | 7 x 14 | 18 x 36 |
| | 350 x 546 x 60mm 13 7/8 x 21 1/2 x 2 3/8" | 360 x 360 x 60mm 14 1/4 x 14 1/4 x 2 3/8" | 180 x 360 x 60mm 7 x 14 1/4 x 2 3/8" | | 100 x 200 x 60mm 3 7/8 x 7 7/8 x 2 3/8" | 180 x 360 x 60mm 7 x 14 x 2 3/8" | 450 x 900 x 60mm 17 3/4 x 35 1/2 x 2 3/8" |
| | 18 Units/Bundle 1.965 Sq.Ft./Stone | 27 Units/Bundle 1.431 Sq.Ft./Stone | 27 Units/Bundle .655 Sq.Ft./Stone | | 486 Units/Bundle .22 Sq.Ft./Stone | 27 Units/Bundle .655 Sq.Ft./Stone | 4.36 Sq.Ft./Stone |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Umbriano Mottled

Joint Spacing - 7mm

Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™



Factory Sealed to provide integral stain resistance

COLORFUSION™


Subtly mottled colored finish

TECHNICAL INFORMATION


Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERNS



Umbriano 24x24
RB_AG



Umbriano 12x24
HB_O

| | 24 x 24 | 12 x 24 | 8 x 24 | 8 x 16 | 16 x 16 |
|--------------------|---------------|---------------|---------------|---------------|---------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | GEORGETOWN | GEORGETOWN | GEORGETOWN | GEORGETOWN | GEORGETOWN |
| Thickness (mm) | 70 MM | 70 MM | 70 MM | 70 MM | 70 MM |

| | | | | | | |
|-----------------|---------|-------|-------|-------|-------|-------|
| SQFT PER | Bundle | 62.00 | 93.00 | 82.67 | 82.67 | 82.67 |
| | Layer | 7.75 | 11.63 | 10.33 | 10.33 | 10.33 |
| | Section | - | - | - | - | - |
| | Stone | 3.88 | 1.94 | 1.29 | 0.86 | 1.72 |

| | | | | | | |
|-------------------|----------|------|------|------|------|------|
| PER BUNDLE | Layers | 8.00 | 8.00 | 8.00 | 8.00 | 8.00 |
| | Sections | - | - | - | - | - |

| | | | | | | |
|-------------------------|---------|-------|-------|-------|-------|-------|
| SOLDIER LNFT PER | SqFt | 0.51 | 0.51 | 0.51 | 0.76 | 0.76 |
| | Section | - | - | - | - | - |
| | Layer | 3.94 | 5.91 | 5.25 | 7.87 | 7.87 |
| | Bundle | 31.50 | 47.24 | 41.99 | 62.99 | 62.99 |

| | | | | | | |
|------------------------|---------|-------|-------|-------|--------|-------|
| SAILOR LNFT PER | SqFt | 0.51 | 1.02 | 1.02 | 1.52 | 0.76 |
| | Section | - | - | - | - | - |
| | Layer | 3.94 | 11.81 | 10.50 | 15.75 | 7.87 |
| | Bundle | 31.50 | 94.49 | 83.99 | 125.98 | 62.99 |

| | | | | | | |
|------------------|---------|-------|-------|-------|-------|-------|
| UNITS PER | SqFt | 0.26 | 0.52 | 0.77 | 1.16 | 0.58 |
| | Section | - | - | - | - | - |
| | Bundle | 16.00 | 48.00 | 64.00 | 96.00 | 48.00 |

| | | | | | | |
|----------------|---------|-------|-------|-------|-------|-------|
| LBS PER | Layer | 258 | 393 | 331 | 343 | 350 |
| | Section | - | - | - | - | - |
| | Bundle | 2,062 | 3,142 | 2,647 | 2,746 | 2,797 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|---------------|---------------|-------|-------|-------|-------|-------|
| French Grey | SR .18 SRI 17 | ✓ | ✓ | ✓ | ✓ | ✓ |
| Midnight Sky | SR .17 SRI 15 | - | - | ✓ | ✓ | - |
| Summer Wheat | SR .42 SRI 48 | ✓ | ✓ | ✓ | ✓ | ✓ |
| Winter Marvel | SR .35 SRI 38 | ✓ | ✓ | ✓ | ✓ | ✓ |



FRENCH GREY



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

| Single Units | 24 x 24 | 12 x 24 | 8 x 24 | 8 x 16 | 16 x 16 |
|--------------|--|--|---|--|--|
| | | | | | |
| | 600 x 600 x 70mm 23 5/8 x 23 5/8 x 2 3/4" 16 Units/Bundle 3.88 Sq.Ft./Stone | 300 x 600 x 70mm 11 7/8 x 23 5/8 x 2 3/4" 48 Units/Bundle 1.94 Sq.Ft./Stone | 200 x 600 x 70mm 7 7/8 x 23 5/8 x 2 3/4" 64 Units/Bundle 1.29 Sq.Ft./Stone | 200 x 400 x 70mm 7 7/8 x 15 3/4 x 2 3/4" 96 Units/Bundle .86 Sq.Ft./Stone | 400 x 400 x 70mm 15 3/4 x 15 3/4 x 2 3/4" 48 Units/Bundle 1.72 Sq.Ft./Stone |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. 24x24" paver is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Umbriano Mottled
Joint Spacing - 7mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance


COLORFUSION™

Subtly mottled colored finish


TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits


LAYING PATTERNS



Umbriano Fixed
Random A



Umbriano Fixed
Random B



Umbriano Multi-Unit
Random G



FRENCH GREY



GRENADA WHITE



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

| | | 7 x 14 | 18 x 36 |
|--------------------|---------------|---------------|---------------|
| Bundle Type | RANDOM | SINGLE | SINGLE |
| Plant Produced | GEORGETOWN | GEORGETOWN | GEORGETOWN |
| Thickness (mm) | 80 MM | 80 MM | 100 MM |

| | | | | |
|-----------------|---------|-------|-------|-------|
| SQFT PER | Bundle | 73.22 | 73.24 | 43.59 |
| | Layer | 10.46 | - | 8.72 |
| | Section | - | - | - |
| | Stone | 1.31 | - | - |

| | | | | |
|-------------------|----------|------|------|------|
| PER BUNDLE | Layers | 7.00 | 7.00 | 5.00 |
| | Sections | - | - | - |





| | | | | |
|-------------------------|---------|---|-------|---|
| SOLDIER LNFT PER | SqFt | - | 62.01 | - |
| | Section | - | 0.59 | - |
| | Layer | - | - | - |
| | Bundle | - | - | - |

| | | | | |
|------------------------|---------|-------|-------|---|
| SAILOR LNFT PER | SqFt | 0.85 | 1.77 | - |
| | Section | - | - | - |
| | Layer | 8.86 | - | - |
| | Bundle | 62.01 | 62.01 | - |

| | | | | |
|------------------|---------|-------|--------|----|
| UNITS PER | SqFt | 0.76 | - | - |
| | Section | - | - | - |
| | Bundle | 56.00 | 105.00 | 10 |

| | | | | |
|----------------|---------|-------|-------|-------|
| LBS PER | Layer | 383 | 383 | 399 |
| | Section | - | - | - |
| | Bundle | 2,680 | 2,680 | 1,994 |

| COLORS | Reflectance | Stock | Stock | Stock |
|---------------|----------------|-------|-------|-------|
| French Grey | SR .18 SRI 17 | ✓ | ✓ | ✓ |
| Grenada White | SR .n/a SRI 52 | ✓ | ✓ | - |
| Midnight Sky | SR .17 SRI 15 | - | ✓ | - |
| Summer Wheat | SR .42 SRI 48 | ✓ | ✓ | ✓ |
| Winter Marvel | SR .35 SRI 38 | ✓ | ✓ | ✓ |

| | | | | | | | | | |
|---------------|---|--|---|---|---|---|-------------|---|---|
| Random Bundle |  | LARGE RECTANGLE 360 x 540 x 80mm 14 x 21 x 2 3/8" 14 Units/Bundle 2.09 Sq.Ft./Stone |  | SQUARE 360 x 360 x 80mm 14 x 14 x 2 3/8" 21 Units/Bundle 1.40 Sq.Ft./Stone |  | SMALL RECTANGLE 180 x 360 x 80mm 7 x 14 1/4 x 2 3/8" 21 Units/Bundle 0.70 Sq.Ft./Stone | Single Unit |  | 18 x 36 450 x 900 x 100mm 18 x 36 x 4" 14 Units/Bundle 4.36 Sq.Ft./Stone |
|---------------|---|--|---|---|---|---|-------------|---|---|

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Textured
Joint Spacing - 3-7mm
Void - n/a

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| Bundle Type | | RANDOM |
|----------------|--|--------|
| Plant Produced | | OHIO |
| Thickness (mm) | | 70 MM |

| | | |
|----------|---------|-------|
| SQFT PER | Bundle | 94.19 |
| | Layer | 11.77 |
| | Section | - |
| | Stone | 0.59 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 8.00 |
| | Sections | - |

| | | |
|------------------|---------|---|
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |


| | | |
|-----------------|---------|--------|
| SAILOR LNFT PER | SqFt | 1.24 |
| | Section | - |
| | Layer | 14.57 |
| | Bundle | 116.56 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 1.70 |
| | Section | - |
| | Bundle | 160.00 |


| | | |
|---------|---------|-------|
| LBS PER | Layer | 361 |
| | Section | - |
| | Bundle | 2,884 |

| COLORS | Reflectance | | Stock |
|---------|-------------|---------|-------|
| Granite | SR n/a | SRI n/a | ✓ |
| River | SR n/a | SRI n/a | ✓ |
| Sierra | SR n/a | SRI n/a | ✓ |

LAYING PATTERNS




Westport Fixed
Random_A



Westport Fixed
Random_B



GRANITE



RIVER



SIERRA

| | | | | | | |
|---------------|--|--|--|---|--|---|
| Random Bundle | | LARGE RECTANGLE 254 x 380 x 70mm 10 x 15 x 2 ¾" 32 units/Bundle XX Sq.Ft./Stone | | SQUARE 254 x 254 x 70mm 10 x 10 x 2 ¾" 56 units/Bundle XX Sq.Ft./Stone | | SMALL RECTANGLE 127 x 254 x 60mm 5 x 10 x 2 ¾" 72 units/Bundle XX Sq.Ft./Stone |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | SMALL TAPERED | STANDARD |
|--------------------|---------------|---------------|
| Bundle Type | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO |
| Thickness (mm) | 100 MM | 100 MM |

| | | | |
|-----------------|--------|-------|-------|
| FCFT PER | Bundle | 36.00 | 36.00 |
| | Layer | 6.00 | 6.00 |
| | Stone | 0.25 | 0.33 |

| | | | |
|-------------------|----------|------|------|
| PER BUNDLE | Layers | 6.00 | 6.00 |
| | Sections | - | 6.00 |

| | | | |
|-----------------|--------|--------|--------|
| LNFT PER | Bundle | 108.00 | 108.00 |
| | Unit | 0.75 | 1.00 |

| | | | |
|------------------|---------|--------|--------|
| UNITS PER | SqFt | 4.00 | 3.00 |
| | Section | - | 18.00 |
| | Bundle | 144.00 | 108.00 |

| | | | |
|----------------|---------|-------|-------|
| LBS PER | Layer | 480 | 530 |
| | Section | - | 530 |
| | Bundle | 2,880 | 3,182 |

| COLORS | Reflectance | Stock | Stock |
|---------------|----------------|-------|-------|
| Dark Charcoal | SR n/a SRI n/a | - | ✓ |
| Limestone | SR n/a SRI n/a | ✓ | ✓ |
| River | SR n/a SRI n/a | ✓ | ✓ |
| Sandstone | SR n/a SRI n/a | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ |

SUNSET FIREPIT KITS

Located on page 76



ROUND



SQUARE



DARK CHARCOAL



LIMESTONE



RIVER



SANDSTONE



SIERRA

Single Units



SMALL TAPERED
229 x 100 x 200mm
9 x 3 7/8 x 7 7/8"
144 units/Bundle
.25 Fc.Ft./Stone



STANDARD
300 x 100 x 200mm
11 7/8 x 3 7/8 x 7 7/8"
108 units/Bundle
.33 Fc.Ft./Stone

Notes: Small tapered units are sold in full bundles only. Maximum height is 24" (under optimum conditions). *Based on 12" deep wall coverage = 21.4 sqft per bundle. Based on an 8" deep wall coverage = 32 sqft per bundle. Ledge stone, Brussels XL or 6" x 12" Fullnose complement as a possible coping unit. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | STANDARD |
|----------------|----------|
| Bundle Type | SINGLE |
| Plant Produced | OHIO |
| Thickness (mm) | 100 MM |

| | | |
|----------|--------|-------|
| FCFT PER | Bundle | 27.00 |
| | Layer | 9.00 |
| | Stone | 0.33 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 3.00 |
| | Sections | 3.00 |

| | | |
|----------|--------|-------|
| LNFT PER | Bundle | 54.00 |
| | Unit | 0.67 |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 3.00 |
| | Section | 27.00 |
| | Bundle | 81.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 784 |
| | Section | 784 |
| | Bundle | 2,353 |

| COLORS | Reflectance | Stock |
|---------------|----------------|-------|
| Dark Charcoal | SR n/a SRI n/a | ✓ |
| Limestone | SR n/a SRI n/a | ✓ |
| Sandstone | SR n/a SRI n/a | ✓ |



DARK CHARCOAL



LIMESTONE



SANDSTONE

Single Unit



STANDARD
300 x 100 x 200mm
11 7/8 x 3 7/8 x 7 7/8"
81 units/Bundle
.33 Fc.Ft./Stone

Notes: Small tapered units are sold in full bundles only. Maximum height is 24" (under optimum conditions). *Based on 12" deep wall coverage = 21.4 sqft per bundle. Based on an 8" deep wall coverage = 32 sqft per bundle. Ledgestone, Brussels XL or 6" x 12" Fullnose complement as a possible coping unit. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

| | STANDARD | HALF COPING | COPING STANDARD | COPING CLOSED-END |
|----------------|----------|-------------|-----------------|-------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | ONTARIO | ONTARIO | ONTARIO | ONTARIO |
| Thickness (mm) | 600 MM | 600 MM | 600 MM | 600 MM |

| | | | | | |
|----------|--------|------|------|------|------|
| FCFT PER | Bundle | 6.02 | 2.95 | 6.02 | 6.02 |
| | Layer | 6.02 | 2.95 | 6.02 | 6.02 |
| | Stone | 6.02 | 2.95 | 6.02 | 6.02 |

| | | | | | |
|------------|----------|------|------|------|------|
| PER BUNDLE | Layers | 1.00 | 1.00 | 1.00 | 1.00 |
| | Sections | - | - | - | - |

| | | | | | |
|----------|--------|------|---|---|---|
| LNFT PER | Bundle | 6.02 | - | - | - |
| | Unit | 6.02 | - | - | - |





| | | | | | |
|-----------|---------|------|------|------|------|
| UNITS PER | SqFt | 0.17 | 0.34 | 0.17 | 0.17 |
| | Section | - | - | - | - |
| | Bundle | 1.00 | 1.00 | 1.00 | 1.00 |

| | | | | | |
|---------|---------|-------|-----|-------|-------|
| LBS PER | Layer | 1,680 | 780 | 1,560 | 1,560 |
| | Section | - | - | - | - |
| | Bundle | 1,680 | 780 | 1,560 | 1,560 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock |
|---------|----------------|-------|-------|-------|-------|
| Natural | SR n/a SRI n/a | SO | SO | SO | SO |



NATURAL

| | | | | |
|--------------|--|--|--|---|
| Single Units |  |  |  |  |
| | STANDARD 1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone | HALF COPING 915 x 300 x 600mm 36 x 11 7/8 x 23 5/8" 1 unit/Bundle 2.95 Fc.Ft./Stone | COPING 1830 x 300 x 600mm 60 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone | CLOSED-END COPING 1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone |

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Smooth

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | TIE-BACK | HALF STANDARD | CORNER 45° | CORNER 90° |
|----------------|----------|---------------|------------|------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | ONTARIO | ONTARIO | ONTARIO | ONTARIO |
| Thickness (mm) | 600 MM | 600 MM | 600 MM | 600 MM |

| FCFT PER | Bundle | 2.00 | 3.00 | 7.04 | 7.04 |
|----------|--------|------|------|------|------|
| | Layer | 2.00 | 3.00 | 7.04 | 7.04 |
| | Stone | 2.00 | 3.00 | 7.04 | 7.04 |

| PER BUNDLE | Layers | 1.00 | 1.00 | 1.00 | 1.00 |
|------------|----------|------|------|------|------|
| | Sections | - | - | - | - |

| LNFT PER | Bundle | - | 3.00 | - | - |
|----------|--------|---|------|---|---|
| | Unit | - | 3.00 | - | - |





| UNITS PER | SqFt | 0.50 | 0.33 | 0.14 | 0.14 |
|-----------|---------|------|------|------|------|
| | Section | - | - | - | - |
| | Bundle | 1.00 | 1.00 | 1.00 | 1.00 |

| LBS PER | Layer | 1,660 | 800 | 1,480 | 1,320 |
|---------|---------|-------|-----|-------|-------|
| | Section | - | - | - | - |
| | Bundle | 1,660 | 800 | 1,480 | 1,320 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock |
|---------|----------------|-------|-------|-------|-------|
| Natural | SR n/a SRI n/a | SO | SO | SO | SO |



NATURAL

| Single Units | | | | |
|--------------|--|---|---|--|
| | TIE-BACK | HALF STANDARD | CORNER 45° | CORNER 90° |
| |  1830 x 300 x 600mm 72 x 12 x 24" 1 unit/Bundle 2.00 Fc.Ft./Stone |  915 x 300 x 600mm 36 x 12 x 24" 1 unit/Bundle 3.00 Fc.Ft./Stone |  1520 x 300 x 600mm 60 x 12 x 24" 1 unit/Bundle 7.04 Fc.Ft./Stone |  1520 x 300 x 600mm 72 x 12 x 24" 1 unit/Bundle 7.04 Fc.Ft./Stone |

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Smooth

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C1372
Eligible for LEED v4.1 credits

| | TIE-BACK | STANDARD | COPING | COPING CLOSED-END |
|-----------------------|----------------|----------------|----------------|----------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | ONTARIO | ONTARIO | ONTARIO | ONTARIO |
| Thickness (mm) | 600 MM | 600 MM | 600 MM | 600 MM |

| | | | | | |
|-----------------|--------|------|------|-------|-------|
| FCFT PER | Bundle | 1.17 | 6.02 | 24.08 | 24.08 |
| | Layer | 1.17 | 6.02 | 6.02 | 6.02 |
| | Stone | 1.17 | 6.02 | 6.02 | 6.02 |

| | | | | | |
|-------------------|----------|------|------|------|------|
| PER BUNDLE | Layers | 1.00 | 1.00 | 4.00 | 4.00 |
| | Sections | - | - | - | - |

| | | | | | |
|-----------------|--------|---|------|---|---|
| LNFT PER | Bundle | - | 6.02 | - | - |
| | Unit | - | 6.02 | - | - |

| | | | | | |
|------------------|---------|------|------|------|------|
| UNITS PER | SqFt | 0.85 | 0.17 | 0.17 | 0.17 |
| | Section | - | - | - | - |
| | Bundle | 1.00 | 1.00 | 4.00 | 4.00 |

| | | | | | |
|----------------|---------|-----|-----|-------|-------|
| LBS PER | Layer | 938 | 938 | 884 | 884 |
| | Section | - | - | - | - |
| | Bundle | 938 | 938 | 3,536 | 3,536 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock |
|---------|----------------|-------|-------|-------|-------|
| Natural | SR n/a SRI n/a | SO | SO | SO | SO |



NATURAL

| Single Units | TIE-BACK | STANDARD | COPING | CLOSED-END COPING |
|--------------|--|--|---|--|
| | | | | |
| | TIE-BACK 1830 x 360 x 300mm 72 x 14 1/4 x 11 7/8" 1 unit/Bundle 1.17 Fc.Ft./Stone | STANDARD 1830 x 360 x 300mm 72 x 14 1/4 x 11 7/8" 1 unit/Bundle 6.02 Fc.Ft./Stone | COPING 1830 x 360 x 300mm 72 x 14 1/4 x 11 7/8" 4 units/Bundle 6.02 Fc.Ft./Stone | CLOSED-END COPING 1830 x 360 x 300mm 72 x 14 1/4 x 11 7/8" 4 units/Bundle 6.02 Fc.Ft./Stone |

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Split

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

| | TAPERED SPLIT CLASSIC ANTIQUED | CORNER SPLIT CLASSIC ANTIQUED |
|----------------|-----------------------------------|----------------------------------|
| Bundle Type | RANDOM | SINGLE |
| Plant Produced | OHIO | OHIO |
| Thickness (mm) | 150 MM | 150 MM |

| | | | |
|----------|--------|-------|-------|
| FCFT PER | Bundle | 24.00 | 16.66 |
| | Layer | 6.00 | 4.17 |
| | Stone | 0.50 | 0.52 |

| | | | |
|------------|----------|------|------|
| PER BUNDLE | Layers | 4.00 | 4.00 |
| | Sections | 4.00 | 4.00 |

| | | | |
|----------|--------|-------|-------|
| LNFT PER | Bundle | 42.56 | 33.28 |
| | Unit | 0.89 | 1.04 |

| | | | |
|-----------|---------|-------|-------|
| UNITS PER | SqFt | 2.00 | 1.92 |
| | Section | 12.00 | 8.00 |
| | Bundle | 48.00 | 32.00 |

| | | | |
|---------|---------|-------|-------|
| LBS PER | Layer | 574 | 444 |
| | Section | 574 | 444 |
| | Bundle | 2,297 | 1,776 |

| COLORS | Reflectance | Stock | Stock |
|---------|----------------|-------|-------|
| Granite | SR n/a SRI n/a | ✓ | ✓ |
| River | SR n/a SRI n/a | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ |







GRANITE



RIVER



SIERRA

| | | | | | |
|---------------|---|--|---|--------------|--|
| Random Bundle |  |  |  | Single Units |  |
| | LARGE TAPERED 375 x 150 x 230mm 14 7/8 x 5 7/8 x 9" 16 units/Bundle | MEDIUM TAPERED 300 x 150 x 230mm 11 7/8 x 5 7/8 x 9" 16 units/Bundle | SMALL TAPERED 228 x 150 x 230mm 9 x 5 7/8 x 9" 16 units/Bundle | | CORNER SPLIT 320 x 150 x 230mm 12 5/8 x 5 7/8 x 9" 32 units/Bundle .52 Sq.Ft./Stone |
| | | | | | |
| | | | | | |

Notes: 6" random wall bundles have convertible large units that can be used for corners or ending seat walls. End caps not sold separately. LedgeStone™, Brussels Block® XL, or Brussels Fullnose™ complement as a possible coping. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Smooth

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | RANDOM CLASSIC | PILLAR CLASSIC |
|--------------------|----------------|----------------|
| Bundle Type | RANDOM | SINGLE |
| Plant Produced | OHIO | OHIO |
| Thickness (mm) | 100 MM | 100 MM |

| | | | |
|-----------------|--------|-------|-------|
| FCFT PER | Bundle | 29.92 | 48.24 |
| | Layer | 9.97 | 16.08 |
| | Stone | 0.50 | 0.67 |

| | | | |
|-------------------|----------|------|------|
| PER BUNDLE | Layers | 3.00 | 3.00 |
| | Sections | - | - |

| | | | |
|-----------------|--------|-------|-------|
| LNFT PER | Bundle | 89.06 | 96.00 |
| | Unit | 1.48 | 1.33 |

| | | | |
|------------------|---------|-------|-------|
| UNITS PER | SqFt | 2.01 | 1.49 |
| | Section | - | - |
| | Bundle | 60.00 | 72.00 |

| | | | |
|----------------|---------|-------|-------|
| LBS PER | Layer | 881 | 936 |
| | Section | - | - |
| | Bundle | 2,642 | 2,808 |

| COLORS | Reflectance | Stock | Stock |
|------------|----------------|-------|-------|
| Granite | SR n/a SRI n/a | ✓ | ✓ |
| Fieldstone | SR n/a SRI n/a | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ |



GRANITE



FIELDSTONE



SIERRA

| | | | | | | | | | | | |
|---------------|---|---|---|---|---|---|--|--|-------------|---|--|
| Random Bundle |  | LARGE RECTANGLE 500 x 100 x 200mm 19 3/4 x 3 7/8 x 7 7/8 15 units/Bundle 55 Fc.Ft./Stone |  | RECTANGLE 400 x 100 x 200mm 15 3/4 x 3 7/8 x 7 7/8 15 units/Bundle 44 Fc.Ft./Stone |  | SMALL RECTANGLE 300 x 100 x 200mm 11 7/8 x 3 7/8 x 7 7/8 15 units/Bundle 33 Fc.Ft./Stone |  | XL RECTANGLE 600 x 100 x 200mm 23 5/8 x 3 7/8 x 7 7/8 15 units/Bundle 66 Fc.Ft./Stone | Single Unit |  | CORNER/PILLAR 400 x 100 x 200mm 15 3/4 x 3 7/8 x 7 7/8 72 units/Bundle .67 Sq.Ft./Stone |
|---------------|---|---|---|---|---|---|--|--|-------------|---|--|

Notes: Sold in full bundles only and is produced and sold on a required, refundable skid. Spacing strips are shipped with random wall bundles to create even spacing between units. Ledgerstone™, Unilock Natural Stone or 6"x12" Fullnose complement as possible coping options. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Split
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | CORNER SPLIT | STANDARD SPLIT | TAPERED SPLIT | 12" COPING SPLIT | XL WALL SPLIT |
|--------------------|-----------------|-------------------|------------------|---------------------|------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO | OHIO | OHIO | OHIO |
| Thickness (mm) | 150 MM | 150 MM | 150 MM | 150 MM | 150 MM |

| | | | | | | |
|---------------------|--------|-------|-------|-------|-------|-------|
| FCFT PER | Bundle | 15.00 | 20.00 | 20.00 | 21.00 | 21.33 |
| | Layer | 5.00 | 6.67 | 6.67 | 3.00 | 5.33 |
| | Stone | 0.83 | 0.33 | 0.33 | 0.25 | 0.67 |

| | | | | | | |
|-----------------------|----------|-------|-------|-------|------|------|
| PER BUNDLE | Layers | 15.00 | 20.00 | 20.00 | 7.00 | 4.00 |
| | Sections | 5.00 | 6.67 | 6.67 | 2.00 | 4.00 |

| | | | | | | |
|---------------------|--------|---|-------|-------|---|-------|
| LNFT PER | Bundle | - | 40.00 | 40.00 | - | 42.67 |
| | Unit | - | 0.67 | 0.67 | - | 1.33 |

| | | | | | | |
|----------------------|---------|-------|-------|-------|-------|-------|
| UNITS PER | SqFt | 1.20 | 3.00 | 3.00 | 4.00 | 1.50 |
| | Section | 6.00 | 30.00 | 30.00 | 42.00 | 8.00 |
| | Bundle | 18.00 | 60.00 | 60.00 | 84.00 | 32.00 |

| | | | | | | |
|--------------------|---------|-----|-------|-------|-------|-------|
| LBS PER | Layer | 314 | 857 | 768 | 388 | 617 |
| | Section | 314 | 1,285 | 1,153 | 1,357 | 617 |
| | Bundle | 943 | 2,570 | 2,305 | 2,714 | 2,467 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|---------|----------------|-------|-------|-------|-------|-------|
| Granite | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |
| River | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |



GRANITE



RIVER



SIERRA

| Single Units | CORNER 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 18 units/Bundle .83 Fc.Ft./Stone | STANDARD 200 x 75 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 60 units/Bundle .33 Fc.Ft./Stone | TAPERED 300 x 75 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 60 units/Bundle .33 Fc.Ft./Stone | XL WALL 400 x 150 x 300mm 15 3/4 x 5 7/8 x 11 7/8" 32 units/Bundle .67 Fc.Ft./Stone | COPING 400 x 150 x 300mm 11 7/8 x 3 x 11 7/8" 84 units/Bundle .25 Fc.Ft./Stone |
|--------------|---|--|---|---|--|
|--------------|---|--|---|---|--|

Notes: XL Wall units are single units and are sold in full bundles only. When purchased by the full bundle, 12" Coping bundle has 14 units of closed-end coping (7 left and 7 right). Closed-end 12" coping not sold separately. Maximum height - 36" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. The set back on Pisa2 wall is 3/4" every course or 1 1/2" every 2 courses. Retaining wall engineering software is also available free of charge at www.unilock.com. Walls greater than 4' in height require professional engineering. Tapered Units allow for a minimum 5' Radius. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Split

CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | CORNER | XL TAPERED | COPING & CLOSED-END / COPING |
|--------------------|---------------|---------------|------------------------------|
| Bundle Type | SINGLE | SINGLE | BUNDLE |
| Plant Produced | OHIO | OHIO | OHIO |
| Thickness (mm) | 150 MM | 150 MM | 75 MM |

| | | | | |
|-----------------|--------|-------|-------|-------|
| FCFT PER | Bundle | 46.52 | 20.67 | 15.50 |
| | Layer | 11.63 | 5.17 | 1.94 |
| | Stone | 0.97 | 0.65 | 0.32 |

| | | | | |
|-------------------|----------|------|------|------|
| PER BUNDLE | Layers | 4.00 | 4.00 | 8.00 |
| | Sections | 3.00 | 4.00 | - |

| | | | | |
|-----------------|--------|---|---|-------|
| LNFT PER | Bundle | - | - | 62.99 |
| | Unit | - | - | 1.31 |

| | | | | |
|------------------|---------|-------|-------|-------|
| UNITS PER | SqFt | 1.03 | 1.55 | 3.10 |
| | Section | 16.00 | 8.00 | - |
| | Bundle | 48.00 | 32.00 | 48.00 |

| | | | | |
|----------------|---------|-------|-------|-------|
| LBS PER | Layer | 629 | 617 | 388 |
| | Section | 839 | 617 | - |
| | Bundle | 2,516 | 2,467 | 3,101 |





| COLORS | Reflectance | Stock | Stock | Stock |
|------------|----------------|-------|-------|-------|
| Fieldstone | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| Granite | SR n/a SRI n/a | ✓ | ✓ | ✓ |



FIELDSTONE



GRANITE

| | | | | | |
|--------------|---|--|---------------|---|--|
| Single Units |  |  | 2 Unit Bundle |  |  |
| | CORNER 400 x 150 x 200mm 15 3/4 x 5 7/8 x 7 7/8" 48 units/Bundle 0.97 Fc.Ft./Stone | XL TAPERED 400 x 150 x 300mm 15 3/4 x 5 7/8 x 11 7/8" 32 units/Bundle 0.65 Fc.Ft./Stone | | COPING 400 x 75 x 300mm 15 3/4 x 3 x 11 7/8" 24 units/Bundle 0.32 Fc.Ft./Stone | CLOSED-END / COPING 400 x 75 x 300mm 15 3/4 x 3 x 11 7/8" 24 units/Bundle 0.32 Fc.Ft./Stone |

Notes: * Special Order - Lead time is required, minimum quantities apply. All Special Order items are sold in full bundles only. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.

Rivercrest® Wall

STONEMARK™



APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Textured

TECHNOLOGIES

REALA™

Cast from natural stone

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

| | WALL | CORNER |
|----------------|--------|--------|
| Bundle Type | RANDOM | RANDOM |
| Plant Produced | AYR | AYR |
| Thickness (mm) | 57 MM | 57 MM |

| FCFT PER | Bundle | 24.30 | 16.21 |
|----------|--------|-------|-------|
| | Layer | 3.0 | 4.0 |
| | Stone | 0.19 | 0.41 |

| PER BUNDLE | Layers | 8.00 | 4.00 |
|------------|----------|------|------|
| | Sections | - | - |

| LNFT PER | Bundle | 130.69 | - |
|----------|--------|--------|---|
| | Unit | 1.02 | - |

| UNITS PER | SqFt | 5.27 | 2.47 |
|-----------|---------|--------|-------|
| | Section | - | - |
| | Bundle | 128.00 | 40.00 |

| LBS PER | Layer | 252 | 293 |
|---------|---------|-------|-------|
| | Section | - | - |
| | Bundle | 2,015 | 1,173 |







| COLORS | Reflectance | Stock | Stock |
|---------------|----------------|-------|-------|
| Buff | SR n/a SRI n/a | ✓ | ✓ |
| Coastal Slate | SR n/a SRI n/a | ✓ | ✓ |



BUFF



COASTAL SLATE

| | | | | |
|---------------|---|---|---|---|
| Corner Bundle |  |  | | |
| | LONG CORNER UNIT 17½ x 9-10 x 2¼" 450 x 230-250 x 57mm | SHORT CORNER UNIT 14½ x 9-10 x 2¼" 375 x 230-250 x 57mm | | |
| Random Bundle |  |  |  |  |
| | STANDARD UNIT 1 8 x 9-10 x 2¼" 200 x 230-250 x 57mm | STANDARD UNIT 2 12 x 9-10 x 2¼" 300 x 230-250 x 57mm | STANDARD UNIT 3 12 x 9-10 x 2¼" 300 x 230-250 x 57mm | STANDARD UNIT 4 17 x 9-10 x 2¼" 425 x 230-250 x 57mm |

Notes: All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Split
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | CORNER SPLIT | STANDARD SPLIT | TAPERED SPLIT |
|--------------------|---------------|----------------|---------------|
| Bundle Type | RANDOM | RANDOM | SINGLE |
| Plant Produced | OHIO | OHIO | OHIO |
| Thickness (mm) | 100 MM | 100 MM | 100 MM |

| | | | | |
|-----------------|--------|-------|-------|-------|
| FCFT PER | Bundle | 20.00 | 19.98 | 19.98 |
| | Layer | 6.67 | 6.66 | 6.66 |
| | Stone | 0.83 | 0.33 | 0.33 |

| | | | | |
|-------------------|----------|------|------|------|
| PER BUNDLE | Layers | 3.00 | 3.00 | 3.00 |
| | Sections | 2.00 | 2.00 | 2.00 |

| | | | | |
|-----------------|--------|---|-------|-------|
| LNFT PER | Bundle | - | 40.00 | 39.99 |
| | Unit | - | 0.67 | 0.67 |

| | | | | |
|------------------|---------|-------|-------|-------|
| UNITS PER | SqFt | 1.20 | 3.00 | 3.00 |
| | Section | 12.00 | 30.00 | 30.00 |
| | Bundle | 24.00 | 60.00 | 60.00 |

| | | | | |
|----------------|---------|-------|-------|-------|
| LBS PER | Layer | 343 | 857 | 750 |
| | Section | 514 | 1,285 | 1,126 |
| | Bundle | 1,028 | 2,570 | 2,251 |

| COLORS | Reflectance | Stock | Stock | Stock |
|---------|----------------|-------|-------|-------|
| Granite | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| River | SR n/a SRI n/a | ✓ | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ | ✓ |






GRANITE



RIVER



SIERRA

| | | | | | | | |
|---------------|---|---|---|---|-------------|---|--|
| Random Bundle |  | CORNER SPLIT 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8 24 units/Bundle .83 Fc.Ft./Stone |  | STANDARD SPLIT 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8 60 units/Bundle .33 Fc.Ft./Stone | Single Unit |  | TAPERED SPLIT 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8 60 units/Bundle .33 Fc.Ft./Stone |
| | | | | | | | |

Notes: Maximum height - 48" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. All measurements are nominal. Corners are sold as double units (one left and one right). Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. Contact your local Unilock representative for details. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Split
Joint Spacing - n/a
Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits



GRANITE



RIVER



SIERRA

Single Unit



COPING TAPERED SPLIT
200 x 100 x 200mm
7 7/8 x 3 7/8 x 7 7/8
144 units/Bundle
.22 Fc.Ft./Stone

| | CORNER SPLIT |
|----------------|--------------|
| Bundle Type | SINGLE |
| Plant Produced | OHIO |
| Thickness (mm) | 100 MM |

| | | |
|----------|--------|-------|
| FCFT PER | Bundle | 31.00 |
| | Layer | 5.17 |
| | Stone | 0.22 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 6.00 |
| | Sections | - |

| | | |
|----------|--------|---|
| LNFT PER | Bundle | - |
| | Unit | - |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 4.65 |
| | Section | - |
| | Bundle | 144.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 393 |
| | Section | - |
| | Bundle | 2,357 |

| COLORS | Reflectance | Stock |
|---------|----------------|-------|
| Granite | SR n/a SRI n/a | ✓ |
| River | SR n/a SRI n/a | ✓ |
| Sierra | SR n/a SRI n/a | ✓ |



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

| | STANDARD SMOOTH | COPING SMOOTH |
|----------------|--------------------|------------------|
| Bundle Type | SINGLE | SINGLE |
| Plant Produced | CHICAGO | CHICAGO |
| Thickness (mm) | 180 MM | 180 MM |

| | | | |
|----------|--------|-------|-------|
| FCFT PER | Bundle | 23.25 | 23.25 |
| | Layer | 7.75 | 7.75 |
| | Stone | 1.94 | 1.94 |

| | | | |
|------------|----------|------|------|
| PER BUNDLE | Layers | 3.00 | 3.00 |
| | Sections | 3.00 | - |

| | | | |
|----------|--------|-------|---|
| LNFT PER | Bundle | 39.37 | - |
| | Unit | 3.28 | - |

| | | | |
|-----------|---------|-------|-------|
| UNITS PER | SqFt | 0.52 | 0.52 |
| | Section | 4.00 | - |
| | Bundle | 12.00 | 12.00 |

| | | | |
|---------|---------|-------|-------|
| LBS PER | Layer | 1,029 | 1,029 |
| | Section | 1,029 | - |
| | Bundle | 3,086 | 3,086 |

| COLORS | Reflectance | Stock | Stock |
|---------|----------------|-------|-------|
| Granite | SR n/a SRI n/a | ✓ | ✓ |



GRANITE

Single Units



STANDARD CORNER
1000 x 180 x 290mm
39 3/8 x 7 x 11 1/2"
12 units/Bundle
1.94 Fc.Ft./Stone



COPING
1000 x 180 x 290mm
39 3/8 x 7 x 11 1/2"
12 units/Bundle
1.94 Fc.Ft./Stone



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Split

CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

| | CORNER SPLIT | STANDARD 333 SPLIT | STANDARD 500 SPLIT | STANDARD 925 SPLIT | COPING SPLIT | COPING C-E SPLIT 48" |
|----------------|--------------|--------------------|--------------------|--------------------|--------------|----------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO | OHIO | OHIO | OHIO | GORMLEY |
| Thickness (mm) | 185 MM | 185 MM | 185 MM | 185 MM | 185 MM | 185 MM |

| | | | | | | | |
|----------|--------|-------|-------|-------|------|-------|-------|
| FCFT PER | Bundle | 17.19 | 18.00 | 12.00 | 6.00 | 12.00 | 14.43 |
| | Layer | 5.73 | 6.00 | 4.00 | 2.00 | 4.00 | 4.81 |
| | Stone | 2.87 | 2.00 | 2.00 | 2.00 | 2.00 | 2.41 |

| | | | | | | | |
|------------|----------|------|------|------|------|------|------|
| PER BUNDLE | Layers | 3.00 | 3.00 | 3.00 | 3.00 | 3.00 | 3.00 |
| | Sections | 3.00 | - | 3.00 | 3.00 | 3.00 | 3.00 |

| | | | | | | | |
|----------|--------|---|---|-------|------|---|---|
| LNFT PER | Bundle | - | - | 19.50 | 9.75 | - | - |
| | Unit | - | - | 3.25 | 3.25 | - | - |

| | | | | | | | |
|-----------|---------|------|------|------|------|------|------|
| UNITS PER | SqFt | 0.35 | 0.50 | 0.50 | 0.50 | 0.50 | 0.42 |
| | Section | 2.00 | - | 2.00 | 1.00 | 2.00 | 2.00 |
| | Bundle | 6.00 | 9.00 | 6.00 | 3.00 | 6.00 | 6.00 |

| | | | | | | | |
|---------|---------|-------|-------|-------|-------|-------|-------|
| LBS PER | Layer | 834 | 864 | 878 | 942 | 954 | 1,140 |
| | Section | 834 | - | 878 | 942 | 954 | 1,140 |
| | Bundle | 2,502 | 2,592 | 2,635 | 2,827 | 2,863 | 3,420 |







| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock | Stock |
|---------|----------------|-------|-------|-------|-------|-------|-------|
| Granite | SR n/a SRI n/a | SO | SO | SO | SO | SO | ✓ |
| Natural | SR n/a SRI n/a | SO | SO | ✓ | SO | ✓ | ✓ |



GRANITE



NATURAL

| | | | | | | |
|--------------|---|--|--|--|--|--|
| Single Units |  |  |  |  |  |  |
| | CORNER SPLIT 90° 925 x 185 x 500mm 36 1/2 x 7 3/8 x 19 3/4" 6 units/Bundle 2.87 Fc.Ft./Stone | STANDARD 333 SPLIT 1000 x 185 x 500mm 39 3/8 x 7 3/8 x 13" 6 units/Bundle 2.00 Fc.Ft./Stone | STANDARD 500 SPLIT 1000 x 185 x 500mm 39 3/8 x 7 3/8 x 19 3/4" 6 units/Bundle 2.00 Fc.Ft./Stone | STANDARD 925 SPLIT 1000 x 185 x 925mm 39 3/8 x 7 3/8 x 36 1/2" 3 units/Bundle 2.00 Fc.Ft./Stone | COPING SPLIT 1000 x 185 x 500mm 39 3/8 x 7 3/8 x 19 3/4" 6 units/Bundle 2.00 Fc.Ft./Stone | COPING C-E SPLIT 48" 1200 x 185 x 500mm 47 1/4 x 7 3/8 x 19 3/4" 6 units/Bundle 2.41 Fc.Ft./Stone |

Notes: * Special Order - Lead time is required, minimum quantities apply. All Special Order items are sold in full bundles only. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Split

Joint Spacing - n/a

Void - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

| TAPERED COPING SPLIT | |
|----------------------|--------|
| Bundle Type | SINGLE |
| Plant Produced | OHIO |
| Thickness (mm) | 100 MM |

| | | |
|----------|--------|-------|
| FCFT PER | Bundle | 32.30 |
| | Layer | 6.46 |
| | Stone | 0.22 |

| | | |
|------------|----------|-------|
| PER BUNDLE | Layers | 5.00 |
| | Sections | 25.00 |

| | | |
|----------|--------|-------|
| LNFT PER | Bundle | 87.50 |
| | Unit | 0.58 |

| | | |
|-----------|---------|--------|
| UNITS PER | SqFt | 4.64 |
| | Section | 6.00 |
| | Bundle | 150.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 522 |
| | Section | 104 |
| | Bundle | 2,611 |

| COLORS | Reflectance | Stock |
|---------|----------------|-------|
| Granite | SR n/a SRI n/a | ✓ |
| River | SR n/a SRI n/a | ✓ |
| Sierra | SR n/a SRI n/a | ✓ |



GRANITE



RIVER



SIERRA

Single Unit



TAPERED COPING SPLIT

200 x 100 x 200mm

7 7/8" x 3 7/8" x 7 7/8"

150 units/Bundle


.22 Fc.Ft./Stone

Notes: Maximum height - 20" (under optimum conditions) including material below grade. Radius - minimum outside radius 29". All measurements are nominal.

U-Cara® Multi-Face Wall System



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth, Standard, Series
Exposed, Umbriano® Mottled & Pitched

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color


COLORFUSION™

Subtly mottled colored finish


TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits




1/2 Running Bond




1/2 Running Bond with Linear Accents



1/2 Running Bond with Random Accents




1/2 Running Bond with Paver Accents



Mixed Bond



1/3 Running Bond



Stacked Bond




Stacked Bond with Accents



Download the U-Cara Multi-Face
Wall Installation Guide.

Pitched Finish



Smooth Finish



Umbriano Finish




Series Finish



3" PANEL

Lavano



Subway



U-Cara® Multi-Face Wall System

| | STANDARD FASCIA SMOOTH | STANDARD CLOSED-END SMOOTH | STANDARD CLOSED-END UMBRIANO | STANDARD FASCIA UMBRIANO | 3" FASCIA PANEL SERIES | STANDARD FASCIA PITCHED | STANDARD CLOSED-END PITCHED |
|--------------------|---------------------------|----------------------------------|------------------------------------|--------------------------------|---------------------------|----------------------------|-----------------------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGE | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO | ONTARIO | ONTARIO | CHICAGO | OHIO | OHIO |
| Thickness (mm) | 150 MM | 150 MM | 150 MM | 150 MM | 71 MM | 150 MM | 150 MM |

| | | | | | | | | |
|-----------------|---------|-------|-------|-------|-------|-------|-------|-------|
| FCFT PER | Bundle | 61.52 | 54.18 | 54.18 | 61.52 | 59.32 | 61.52 | 54.18 |
| | Layer | 10.25 | 9.03 | 9.03 | 10.25 | 9.89 | 10.25 | 9.03 |
| | Section | - | - | - | - | - | - | - |
| | Stone | 0.73 | 1.29 | 1.29 | 0.73 | 0.18 | 0.73 | 1.29 |

| | | | | | | | | |
|-------------------|----------|------|---|------|------|------|---|---|
| PER BUNDLE | Layers | 6.00 | - | 6.00 | 6.00 | 6.00 | - | - |
| | Sections | - | - | - | - | - | - | - |

| | | | | | | | | |
|-----------------|--------|--------|--------|--------|---|---|--------|--------|
| LNFT PER | Bundle | 129.50 | 104.86 | 107.94 | - | - | 129.50 | 104.86 |
| | Unit | 1.54 | 2.50 | 2.57 | - | - | 1.54 | 2.50 |

| | | | | | | | | |
|------------------|---------|-------|-------|-------|-------|--------|-------|-------|
| UNITS PER | SqFt | 1.37 | 0.78 | 0.78 | 1.37 | 5.66 | 1.37 | 0.78 |
| | Section | - | - | - | - | - | - | - |
| | Bundle | 84.00 | 42.00 | 42.00 | 84.00 | 336.00 | 84.00 | 42.00 |

| | | | | | | | | |
|----------------|---------|-------|-------|-------|-------|-------|-------|-------|
| LBS PER | Layer | 275 | 207 | 207 | 252 | 250 | 302 | 236 |
| | Section | - | - | - | - | - | - | - |
| | Bundle | 1,648 | 1,242 | 1,240 | 1,513 | 1,501 | 1,809 | 1,416 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock | Stock | Stock |
|----------------|----------------|-------|-------|-------|-------|-------|-------|-------|
| Granite Fusion | SR n/a SRI n/a | ✓ | ✓ | - | - | - | ✓ | ✓ |
| Dark Charcoal | SR n/a SRI n/a | ✓ | ✓ | - | - | - | - | - |
| Fossil | SR n/a SRI n/a | ✓ | ✓ | - | - | - | ✓ | ✓ |
| Onyx Black | SR n/a SRI n/a | - | - | - | - | ✓ | - | - |
| French Grey | SR n/a SRI n/a | - | - | ✓ | ✓ | - | - | - |
| Midnight Sky | SR n/a SRI n/a | - | - | ✓ | ✓ | - | - | - |
| Summer Wheat | SR n/a SRI n/a | - | - | ✓ | ✓ | - | - | - |
| Winter Marvel | SR n/a SRI n/a | - | - | ✓ | ✓ | - | - | - |

| | | | | |
|--------------|---|--|--|---|
| Single Units |  | 6" STANDARD FASCIA PANEL 5 7/8 x 18 3/8 x 2 3/8" 150 x 466 x 60mm 84 Units/Bundle .73 Sq.Ft./Stone |  | 3" FASCIA PANEL 2 7/8 x 9 x 2 3/8" 71 x 231 x 60mm 336 Units/Bundle .18 Sq.Ft./Stone |
| |  | STANDARD FASCIA HALF PANEL 5 7/8 x 9 1/4 x 2 3/8" 150 x 233 x 60mm 42 Units/Bundle .37 Sq.Ft./Stone |  | CLOSED-END FASCIA PANEL 5 7/8 x 20 7/8 x 2 3/8" 150 x 530 x 60mm 42 Units/Bundle 1.29 Sq.Ft./Stone |


Notes: Sold in full bundles. Produced and sold on a required refundable skids. Sure Track Large Backer Units when used as corners in a pillar application, can achieve 42 FFT/bundle or .757 FFT/unit.

U-Cara® Multi-Face Wall System

NEW DESIGNS COMING SOON



APPLICATIONS



CROSS SECTIONS

All Cross Sections are available on Unilock's Contractor web site under Products:
contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Smooth

TECHNOLOGIES

COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | LAVANO STANDARD | SUBWAY STANDARD |
|----------------|-----------------|-----------------|
| Bundle Type | SINGLE | SINGLE |
| Plant Produced | MICHIGAN | MICHIGAN |
| Thickness (mm) | 150 MM | 150 MM |

| | | | |
|----------|---------|-------|-------|
| FCFT PER | Bundle | 61.52 | 61.52 |
| | Layer | 10.25 | 10.25 |
| | Section | - | - |
| | Stone | 0.73 | 0.73 |


| | | | |
|------------|----------|------|------|
| PER BUNDLE | Layers | 6.00 | 6.00 |
| | Sections | - | - |

| | | | |
|----------|--------|--------|--------|
| LNFT PER | Bundle | 129.50 | 129.50 |
| | Unit | 1.54 | 1.54 |

| | | | |
|-----------|---------|-------|-------|
| UNITS PER | SqFt | 1.37 | 1.37 |
| | Section | - | - |
| | Bundle | 84.00 | 84.00 |

| | | | |
|---------|---------|--------|--------|
| LBS PER | Layer | 252.00 | 252.00 |
| | Section | - | - |
| | Bundle | 1,513 | 1,513 |

| COLORS | Reflectance | Stock | Stock |
|----------------|----------------|-------|-------|
| Granite Fusion | SR n/a SRI n/a | ✓ | - |
| Fossil | SR n/a SRI n/a | ✓ | - |
| Dark Charcoal | SR n/a SRI n/a | - | ✓ |
| Opal | SR n/a SRI n/a | - | ✓ |
| Ivory | SR n/a SRI n/a | - | ✓ |



GRANITE FUSION

FOSSIL



DARK CHARCOAL

OPAL

IVORY


| | | | | |
|--------------|--|---|--|---|
| Single Units | | LAVANO STANDARD FASCIA PANEL 5 7/8 x 18 3/8 x 2 3/8" 150 x 466 x 60mm 84 Units/Bundle .73 Fc.Ft./Stone | | SUBWAY STANDARD FASCIA PANEL 5 7/8 x 18 3/8 x 2 3/8" 150 x 466 x 60mm 84 Units/Bundle .73 Fc.Ft./Stone |
| | | | | |

Notes: Sold in full bundles. Produced and sold on a required refundable skids. Sure Track Large Backer Units when used as corners in a pillar application, can achieve 42 FFT/bundle or .757 FFT/unit.

U-Cara® Multi-Face Wall System



APPLICATIONS



CROSS SECTIONS

All Cross Sections are available on Unilock's Contractor web site under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth,
Standard, Series Exposed,
Umbriano® Mottled & Pitched

TECHNOLOGIES

ENDURACOLOR™

Refined surface
and long-lasting color

COLORFUSION™


Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits


U-CARA RETAINING WALL GEOGRID SECTION



U-CARA® CROSS SECTION

REF: Detail_U-Cara_Garden_Wall

Garden Wall - Max Height 15"




Notes:

This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

U-CARA® CROSS SECTION

REF: Detail_U-Cara_Seal_Wall

Seal Wall - Max Height 21"



Notes:

This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

U-Cara® Multi-Face Wall System

| | LARGE/CORNER/ PILLAR BACKER | STANDARD BACKER | UNIVERSAL BASE CLASSIC |
|--------------------|--------------------------------|-----------------|---------------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO | OHIO |
| Thickness (mm) | 150 MM | 150 MM | 55 MM |

| | | | | |
|-----------------|--------|-------|-------|---|
| FCFT PER | Bundle | 15.82 | 33.91 | - |
| | Layer | 3.96 | 11.30 | - |
| | Stone | 0.28 | 0.32 | - |

| | | | | |
|-------------------|----------|------|------|-------|
| PER BUNDLE | Layers | 4.00 | 3.00 | 10.00 |
| | Sections | - | - | - |

| | | | | |
|-----------------|--------|---|-------|-------|
| LNFT PER | Bundle | - | 69.99 | 70.00 |
| | Unit | - | 0.67 | 1.17 |

| | | | | |
|------------------|---------|-------|--------|-------|
| UNITS PER | SqFt | 3.54 | 3.10 | - |
| | Section | - | - | - |
| | Bundle | 56.00 | 105.00 | 60.00 |

| | | | | |
|----------------|---------|-------|-------|-------|
| LBS PER | Layer | 498 | 773 | 282 |
| | Section | - | - | - |
| | Bundle | 1,992 | 2,320 | 2,816 |

Components




**SURE TRACK
LARGE BACKER**
6 x 7½ x 12"
150 x 190 x 300mm



**SURE TRACK
STANDARD BACKER**
6 x 8 x 6"
150 x 200 x 150mm


Notes: Sold in full pallets only on a refundable, optional skid. All measurements are nominal. Contact Unilock for more information.

| | | | |
|---------------------|---|---|---|
| Smooth Panel |  |  |  |
| | GRANITE FUSION | FOSSIL | DARK CHARCOAL |

| | | |
|----------------------|--|---|
| Pitched Panel |  |  |
| | GRANITE FUSION | FOSSIL |

| | | | | |
|-----------------------|---|---|---|--|
| Umbiano Panels |  |  |  |  |
| | FRENCH GREY | SUMMER WHEAT | WINTER MARVEL | MIDNIGHT SKY |

| | |
|------------------------|---|
| Series 3" Panel |  |
| | ONYX BLACK |

| | | |
|----------------------------------|---|--|
| Recommended Base Unit |  | UNIVERSAL BASE UNIT 14 x 19 x 2 ¼" 355 x 482 x 55mm |
|----------------------------------|---|--|

Extra Components




**SURE TRACK
CORNER INSERT**
L = 2"
50mm

Notes: Sold in full bundles. Produced and sold on a required refundable skids. Sure Track Large Backer Units when used as corners in a pillar application, can achieve 42 FFT/bundle or .757 FFT/unit.

U-Cara® Modular System

The U-Cara Modular System offers a variety of aluminum frames that can be mixed and matched to construct vertical features like grill islands. Speak to your contractor to select a design and a U-Cara fascia panel finish to suit your project.

With the U-Cara Modular System you can build Grill Islands, Bars, Back splashes, Fire Places and Pillars.



| NO. | MODEL | DESCRIPTION |
|----------------|---------------|--|
| UCARA000001 | URS | UCARA 8' RAIL (10/PACK) |
| UCARA000003 | URS | ALIGNMENT BARS 39" (10/PACK) |
| UCARA000007 | UL-OSK | CABINET DEPTH CHANGE KIT |
| RS-UCARA000009 | UL-FIR | U-CARA FIREPLACE |
| RS-UCARA000010 | UL-FIR-M | U-CARA FIREPLACE MANTLE |
| RS-UCARA000015 | UL-HCK-CC | U-CARA HEIGHT CONVERSION CORNER CAB |
| RS-UCARA000016 | UL-FIR-MW | U-CARA FIREPLACE MANTLE WIDE UNIT |
| RS-UCARA000017 | UL-FIR-CH | U-CARA U-CARA FIREPLACE CHIMNEY UNIT |
| RS-UCARA000018 | UL-FIR-CH-MW | U-CARA FIREPLACE CHIMNEY WIDE UNIT |
| RS-UCARA000019 | UL-FIR-RTN | U-CARA FIREPLACE RETURN |
| RS-UCARA000020 | UL-FIR-RTN-OS | U-CARA FIREPLACE RETURN OVERSIZED |
| UCARA001000 | UL-GC | UNIVERSAL GRILL CABINET (fits 36"-42" grill) |
| UCARA002000 | UL-BC | BASE CABINET (fits fire table or fridge) |
| UCARA003000 | UL-CC | CORNER CABINET 27.5" x 27.5" |
| UCARA003001 | UL-CC-OS | CORNER CABINET 27.5" x 36.5" OS |
| UCARA003002 | UL-CC-BP | CORNER CABINET BACK PANEL |
| UCARA004000 | UL-ECK | END CLAD KIT 27.5" |
| UCARA004001 | UL-ECK-OS | END CLAD KIT 36.5" OS |
| UCARA005000 | UL-BS | BACKSPLASH-GRILL/BASE UNIT 64½" |
| UCARA005001 | UL-BS-CC | BACKSPLASH CORNER CABINET |
| UCARA005002 | UL-BS-CC-OS | BACKSPLASH CORNER CABINET OS |
| UCARA006000 | UL-DD | STAINLESS DOUBLE ACCESS DOORS 27" |
| UCARA007000 | UL-PU | PILLAR UNIT (18⅜" x 18⅜") |
| RS-UCARA001002 | UL-GC-36 | UNIVERSAL GRILL CABINET (FITS 36"-42" GRILL) |
| RS-UCARA002001 | UL-BC-36 | BASE CABINET (FITS FIRE TABLE OR FRIDGE) |
| RS-UCARA003004 | UL-CC-OS-36 | CRNR CABINET 27.5X36.5 OS |
| RS-UCARA003005 | UL-CC-36 | CORNER CABINET 27.5X27.5 |
| RS-UCARA004002 | UL-ECK-36 | END CLAD KIT 27.5" |
| RS-UCARA004003 | UL-ECK-OS-36 | END CLAD KIT 36.5" OS |



Download the U-Cara Modular Fireplace Installation Guide.

U-Cara® Wall Mount System



The U-Cara Wall Mount System allows you to put the finishing touches on your project by cladding existing structures like unsightly exposed foundation areas or concrete steps with U-Cara fascia panels.



U-CARA ALIGNMENT BAR:
39" LENGTH - SOLD IN PACKS OF 10 PIECES

U-CARA RAILS:
8' LENGTH - SOLD IN PACKS OF 10 PIECES





APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Exposed
Joint Spacing - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | COPING ENDURACOLOR | PILLAR CAP 28" ENDURACOLOR |
|----------------|-----------------------|-------------------------------|
| Bundle Type | SINGLE | SINGLE |
| Thickness (mm) | 60 MM | 76 MM |

| | | | |
|----------|--------|---|---|
| SQFT PER | Bundle | - | - |
| | Unit | - | - |

| | | | |
|----------|--------|---|---|
| FCFT PER | Bundle | - | - |
| | Layer | - | - |
| | Unit | - | - |

| | | | |
|----------|--------|-------|---|
| LNFT PER | Bundle | 42.00 | - |
| | Unit | 2.00 | - |

| | | | |
|-----------|--------|-------|------|
| UNITS PER | Bundle | 21.00 | 6.00 |
| | SqFt | - | - |

| | | | |
|---------|--------|-------|-------|
| LBS PER | Unit | 68 | 183 |
| | Bundle | 1,428 | 1,098 |

| COLORS | Reflectance | Stock | Stock |
|----------|----------------|-------|-------|
| Buff | SR n/a SRI n/a | ✓ | ✓ |
| Charcoal | SR n/a SRI n/a | ✓ | ✓ |



BUFF



CHARCOAL

Single Units



COPING
609 x 60 x 355mm
24 x 2 3/8 x 14"



PILLAR CAP
711 x 76 x 711mm
28 x 3 x 28"



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Smooth
Joint Spacing - 2mm

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | DOUBLE FULLNOSE | FULLNOSE CLASSIC |
|--------------------|--------------------|---------------------|
| Bundle Type | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO |
| Thickness (mm) | 70 MM | 60 MM |

| | | | |
|-----------------|--------|-------|--------|
| FCFT PER | Bundle | 78.27 | 104.00 |
| | Layer | 19.57 | 10.00 |
| | Stone | 0.49 | 0.49 |

| | | | |
|-------------------|----------|------|------|
| PER BUNDLE | Layers | 4.00 | 4.00 |
| | Sections | 4.00 | 4.00 |

| | | | |
|-----------------|--------|-------|--------|
| LNFT PER | Bundle | 78.27 | 104.00 |
| | Unit | 0.50 | 0.5 |

| | | | |
|------------------|---------|--------|--------|
| UNITS PER | SqFt | 0.5 | 0.5 |
| | Section | 40.00 | 52.00 |
| | Bundle | 160.00 | 208.00 |

| | | | |
|----------------|---------|-------|--------|
| LBS PER | Layer | 594 | 737.75 |
| | Section | 594 | 737.75 |
| | Bundle | 2,376 | 2,951 |

| COLORS | Reflectance | Stock | Stock |
|---------------|----------------|-------|-------|
| Dark Charcoal | SR .12 SRI 9 | ✓ | ✓ |
| Limestone | SR .41 SRI 46 | ✓ | ✓ |
| Sandstone | SR .41 SRI 46 | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ |
| Mocha | SR n/a SRI n/a | ✓ | ✓ |



DARK CHARCOAL



LIMESTONE



SANDSTONE



SIERRA



MOCHA

Single Units



**BRUSSELS FULLNOSE
CLASSIC / TUMBLED**
150 x 300 x 60mm
5 7/8 x 11 7/8 x 2 3/8"
208 units/Bundle



**BRUSSELS DOUBLE FULLNOSE
CLASSIC / TUMBLED**
150 x 300 x 70mm
5 7/8 x 11 7/8 x 2 3/4"
160 units/Bundle



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Textured

TECHNOLOGIES

REALA™

Cast from natural stone

TECHNICAL INFORMATION

Conforms to ASTM C 1776

Eligible for LEED v4.1 credits

| | 24" COPING | 24" CLOSED-END COPING | 24" FULLNOSE COPING | 30" COPING | 30" CLOSED-END COPING |
|--------------------|---------------|-----------------------------|---------------------------|---------------|-----------------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | CHICAGO | CHICAGO | CHICAGO | CHICAGO | CHICAGO |
| Thickness (mm) | 70 MM | 70 MM | 60 MM | 70 MM | 70 MM |

| | | | | | | |
|---------------------|--------|------|------|------|------|------|
| FCFT PER | Bundle | 5.52 | 5.52 | 5.12 | 6.87 | 6.87 |
| | Layer | 1.38 | 1.38 | 0.39 | 1.72 | 1.72 |
| | Stone | 0.46 | 0.46 | 0.39 | 0.57 | 0.57 |

| | | | | | | |
|-----------------------|----------|---|---|---|---|---|
| PER BUNDLE | Layers | - | - | - | - | - |
| | Sections | - | - | - | - | - |

| | | | | | | |
|---------------------|--------|-------|-------|-------|-------|-------|
| LNFT PER | Bundle | 24.00 | 24.00 | 26.00 | 30.00 | 30.00 |
| | Unit | - | - | - | - | - |

| | | | | | | |
|----------------------|---------|-------|-------|-------|-------|-------|
| UNITS PER | SqFt | 2.18 | 2.18 | 2.54 | 1.75 | 1.75 |
| | Section | - | - | - | - | - |
| | Bundle | 12.00 | 12.00 | 13.00 | 12.00 | 12.00 |

| | | | | | | |
|--------------------|---------|-----|-----|-----|-------|-------|
| LBS PER | Layer | - | - | - | - | - |
| | Section | - | - | - | - | - |
| | Bundle | 722 | 796 | 723 | 1,128 | 1,116 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|--------|----------------|-------|-------|-------|-------|-------|
| Buff | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |
| Grey | SR n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |



BUFF



GREY

| Single Units | 24" COPING | 24" CLOSED-END COPING | 24" FULLNOSE COPING | LARGE (30") COPING | LARGE (30") CLOSED-END COPING |
|--------------|---|---|---|---|---|
| | 610 x 305 x 70mm 24 x 12 x 2 3/8" 12 units/Bundle .46 Fc.Ft./Stone | 610 x 305 x 70mm 24 x 12 x 2 3/4" 12 units/Bundle .46 Fc.Ft./Stone | 610 x 305 x 60mm 24 x 12 x 2 3/8" 13 units/Bundle .46 Fc.Ft./Stone | 762 x 343 x 70mm 30 x 13 1/2 x 2 3/4" 12 units/Bundle .57 Fc.Ft./Stone | 762 x 343 x 70mm 30 x 13 1/2 x 2 3/4" 12 units/Bundle .57 Fc.Ft./Stone |

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Coping is rock faced on the front and the back. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured

TECHNOLOGIES

REALA™
Cast from natural stone

TECHNICAL INFORMATION

Conforms to ASTM C 1776
Eligible for LEED v4.1 credits

| | 48" STEP | 24" PILLAR CAP | 29" PILLAR CAP |
|--------------------|---------------|-------------------|-------------------|
| Bundle Type | SINGLE | SINGLE | SINGLE |
| Plant Produced | ONTARIO | CHICAGO | CHICAGO |
| Thickness (mm) | 150 MM | 100 MM | 100 MM |

| | | | | |
|-----------------|--------|------|------|---|
| FCFT PER | Bundle | 5.91 | 3.28 | - |
| | Layer | 1.97 | 0.66 | - |
| | Stone | 1.97 | 0.66 | - |

| | | | | |
|-------------------|----------|------|------|------|
| PER BUNDLE | Layers | 3.00 | 5.00 | 5.00 |
| | Sections | - | - | - |

| | | | | |
|-----------------|--------|-------|-------|---|
| LNFT PER | Bundle | 12.00 | 10.04 | - |
| | Unit | 4.00 | 2.01 | - |

| | | | | |
|------------------|---------|------|------|------|
| UNITS PER | SqFt | 0.51 | 1.52 | - |
| | Section | - | - | - |
| | Bundle | 3.00 | 5.00 | 5.00 |

| | | | | |
|----------------|---------|-------|-----|-------|
| LBS PER | Layer | 574 | 159 | 206 |
| | Section | - | - | - |
| | Bundle | 1,721 | 795 | 1,030 |

| COLORS | Reflectance | Stock | Stock | Stock |
|--------|----------------|-------|-------|-------|
| Buff | SR n/a SRI n/a | * | ✓ | ✓ |
| Grey | SR n/a SRI n/a | * | ✓ | ✓ |

**While Supplies Last*



BUFF



GREY

| | | | | | | |
|--------------|---|--|---|--|---|--|
| Single Units |  | 48" STEP 1220 x 610 x 150mm 48 x 24 x 5 7/8" 3 units/Bundle 1.97 Fc.Ft./Stone |  | 24" PILLAR CAP 610 x 610 x 100mm 24 x 24 x 3 7/8" 5 units/Bundle .66 Fc.Ft./Stone |  | 29" PILLAR CAP 740 x 740 x 100mm 29 1/8 x 29 1/8 x 3 7/8" 5 units/Bundle .66 Fc.Ft./Stone |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Notes: Produced and sold on a required, refundable skid. Coping is rock faced on the front and the back. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Split

CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: contractor.unilock.com

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

| | COPING SPLIT | COPING C-E SPLIT |
|----------------|--------------|------------------|
| Bundle Type | SINGLE | SINGLE |
| Plant Produced | OHIO | ONTARIO |
| Thickness (mm) | 185 MM | 185 MM |

| | | | |
|----------|--------|-------|-------|
| FCFT PER | Bundle | 12.00 | 14.43 |
| | Layer | 4.00 | 4.81 |
| | Stone | 2.00 | 2.41 |

| | | | |
|------------|----------|------|------|
| PER BUNDLE | Layers | 3.00 | 3.00 |
| | Sections | 3.00 | 3.00 |

| | | | |
|----------|--------|---|---|
| LNFT PER | Bundle | - | - |
| | Unit | - | - |

| | | | |
|-----------|---------|------|------|
| UNITS PER | SqFt | 0.50 | 0.42 |
| | Section | 2.00 | 2.00 |
| | Bundle | 6.00 | 6.00 |

| | | | |
|---------|---------|-------|-------|
| LBS PER | Layer | 954 | 1,140 |
| | Section | 954 | 1,140 |
| | Bundle | 2,863 | 3,420 |

| COLORS | Reflectance | Stock | Stock |
|---------|----------------|-------|-------|
| Granite | SR n/a SRI n/a | - | ✓ |
| Natural | SR n/a SRI n/a | ✓ | ✓ |



GRANITE



NATURAL

Single Units




COPING SPLIT
1000 x 185 x 500mm
39 3/8 x 7 3/8 x 19 3/4"
6 units/Bundle
2.00 Fc.Ft./Stone



COPING SPLIT
1200 x 185 x 500mm
47 1/4 x 7 3/8 x 19 3/4"
6 units/Bundle
2.41 Fc.Ft./Stone



APPLICATIONS



APPEARANCE

Edge Detail - Zero
Surface Texture - Umbriano Mottled
Joint Spacing - 7mm
Void - n/a

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance

COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

| | CHAMFERED | BULLNOSE |
|--------------------|---------------|---------------|
| Bundle Type | SINGLE | SINGLE |
| Plant Produced | PICKERING | PICKERING |
| Thickness (mm) | 60 MM | 60 MM |

| | | | |
|-----------------|--------|------|------|
| FCFT PER | Bundle | 9.30 | 9.30 |
| | Layer | - | - |
| | Stone | 0.39 | 0.39 |

| | | | |
|-------------------|----------|------|------|
| PER BUNDLE | Layers | 6.00 | 6.00 |
| | Sections | 2.00 | 2.00 |

| | | | |
|-----------------|--------|-------|-------|
| LNFT PER | Bundle | 47.24 | 47.24 |
| | Unit | 1.97 | 1.97 |

| | | | |
|------------------|---------|-------|-------|
| UNITS PER | SqFt | 12.00 | 12.00 |
| | Section | - | - |
| | Bundle | 24.00 | 24.00 |

| | | | |
|----------------|---------|-------|-------|
| LBS PER | Layer | 252 | 252 |
| | Section | 755 | 755 |
| | Bundle | 1,510 | 1,510 |


| COLORS | Reflectance | Stock | Stock |
|---------------|----------------|-------|-------|
| French Grey | SR n/a SRI n/a | ✓ | ✓ |
| Grenada White | SR n/a SRI 52 | ✓ | ✓ |
| Midnight Sky | SR n/a SRI n/a | ✓ | ✓ |
| Summer Wheat | SR n/a SRI 48 | ✓ | ✓ |
| Winter Marvel | SR n/a SRI 38 | ✓ | ✓ |



FRENCH GREY



GRENADA WHITE



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

Single Units



CHAMFERED
360 x 600 x 60 mm
14 x 24 x 2 3/8"



BULLNOSE
360 x 600 x 60 mm
14 x 24 x 2 3/8"



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Standard / Smooth

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

| | UNIVERSAL COPING SMOOTH ENDURACOLOR |
|----------------|--|
| Bundle Type | SINGLE |
| Plant Produced | OHIO |
| Thickness (mm) | 70 MM |

| | | |
|----------|--------|-------|
| FCFT PER | Bundle | 13.08 |
| | Layer | 2.18 |
| | Stone | 0.36 |

| | | |
|------------|----------|------|
| PER BUNDLE | Layers | 6.00 |
| | Sections | - |

| | | |
|----------|--------|---|
| LNFT PER | Bundle | - |
| | Unit | - |

| | | |
|-----------|---------|-------|
| UNITS PER | SqFt | 2.75 |
| | Section | - |
| | Bundle | 36.00 |

| | | |
|---------|---------|-------|
| LBS PER | Layer | 353 |
| | Section | - |
| | Bundle | 2,118 |

| COLORS | Reflectance | Stock |
|---------------|----------------|-------|
| Dark Charcoal | SR n/a SRI n/a | ✓ |



DARK CHARCOAL

Single Units



UNIVERSAL COPING ENDURACOLOR

482 x 355 x 70mm

19 x 14 x 2 ¾"

36 units/Bundle

.36 Fc.Ft./Stone



APPLICATIONS



APPEARANCE

- Edge Detail - Zero
- Surface Texture - Standard
- Joint Spacing - n/a
- Void % - n/a

TECHNOLOGIES

- CLASSIC™
- Budget-friendly traditional product mix

ANTIQUED™

- Distressed, timeworn finish

TECHNICAL INFORMATION

- Conforms to ASTM C 1372
- Eligible for LEED v4.1 credits

| | SQUARE W / INSERT | ROUND W / INSERT |
|----------------|----------------------|---------------------|
| Bundle Type | SINGLE | SINGLE |
| Thickness (mm) | 300 MM | 300 MM |

| | | | |
|--------------------|---------|-------|-------|
| DIAMETER (inch) | Outside | 44.00 | 52.00 |
| | Inside | 28.00 | 34.00 |
| | Insert | 36.00 | 34.00 |

| | | |
|-----------------|-------|-------|
| LAYER PER UNIT | 3.00 | 3.00 |
| UNIT PER LAYER | 12.00 | 18.00 |
| UNIT PER PALLET | 36.00 | 54.00 |

| | | |
|----------------|-------|-------|
| LBS PER PALLET | 1,545 | 1,145 |
|----------------|-------|-------|

| COLORS | Reflectance | Stock | Stock |
|-----------|----------------|-------|-------|
| Limestone | SR n/a SRI n/a | ✓ | ✓ |
| River | SR n/a SRI n/a | ✓ | ✓ |
| Sandstone | SR n/a SRI n/a | ✓ | ✓ |
| Sierra | SR n/a SRI n/a | ✓ | ✓ |



LIMESTONE



RIVER



SANDSTONE



SIERRA

Single Units

SUNSET SQUARE W/INSERT
1100 x 1100 x 300mm
43 3/8 x 43 3/8 x 11 7/8"

SUNSET ROUND W/INSERT
1300 x 1300 x 300mm
51 1/4 x 51 1/4 x 11 7/8"

Notes: All measurements are nominal. Contact Unilock for more information.

Unilock Elements

TUSCANY

Large decorative accents adorn the top of the Tuscany fireplace. Brussels Fullnose™ is used to construct the ledges and mantle of the fireplace.



Tuscany Sierra with Copthorne® **



MODA SPECIAL ORDER

The Moda pre-built fireplace is constructed from Lineo™ Dimensional Stone and Series™ accent.



Moda (Lineo Dimensional Stone & Series)

TUSCANY FIREPLACE



CUSTOM ACCENTS



Copthorne®



Courtstone®



Richcliff®



Umbriano®

UNILOCK ELEMENTS ARE AVAILABLE IN TUSCANY AND BARCELONA SERIES



FIREPLACE

Two piece set (base and chimney), and it comes with stainless fire box. 5,620 lbs



HEARTH

Hearth with gentle curved front. 1,025 lbs



WOOD BOXES

Sold as a set of two and flank either side of the gas or standard fireplace. 3,750 lbs per set



GRILL ISLAND

Available with OCS Grill, protective cover, and stainless double door insert. 3,800 lbs

Guarantee: The standard Unilock guarantee applies to the units used to construct Unilock Elements. (See Unilock literature for details.) Third party grills and fireboxes carry their respective manufacturer's warranty and may change without notice.

Note: Unilock reserves the right to change model designs, accessories and colors without notice. Unilock will not be responsible for improper use or handling that results in property damage. Some models may not be exactly as shown. Fireplaces come complete with UL- approved stainless steel fireboxes. Check local building codes and regulations prior to ordering and installing Unilock Elements.

Paver Cleaners



ALLIANCE GATOR OIL & GREASE CLEANER

- Effective in removing oil and grease from the surface of concrete pavers and natural stones
- Easy to use - dissolves, dislodges and removes oil and grease



ALLIANCE GATOR EFFLORESCENCE CLEANER & SLURRY REMOVER

- Removes any efflorescence stains trapped in the concrete paver and natural stone pores
- Makes the pavers look more clean and vibrant



ALLIANCE GATOR RUST CLEANER

- Effective in removing rust from the surface of concrete pavers
- Contains no muriatic acid



ALLIANCE GATOR RUBBER, PAINT & TAR REMOVER

- Effective in removing rubber, paint and tar from the surface of concrete pavers and natural stone
- Easily washes off with water and is easy to use

Natural Stone Cleaners



UNICARE NATURAL STONE ACID CLEAN

1L and 5L

Removal of:

- Cement Staining
- Efflorescence
- Iron Oxide (Rust) Cement mortar
- Grout



UNICARE NATURAL POWER CLEAN

1L and 5L

Removal of:

- Oil & Grease
- Food Stains
- General Dirt & Mud
- Sap & certain plant stains
- Light cement contamination (on acid sensitive surfaces)



UNICARE BIOCLEAN

1L and 5L

Removal of:

- Black spot algae
- Green algae
- Plant stains from leaves, wood, trees, berries & flowers
- Organic staining from bark & compost, colored stains from food spillages, tea, coffee and wine

Natural Stone Sealers



UNICARE NATURAL STONE NATMATTE SEALER

1L and 5L

For Porous Stones

- No change of color
- No surface coating, sheen or shine at all
- Riven Sandstone & Smooth Sandstone



UNICARE NATURAL STONE NATCOLORENHANCE SEALER

1L and 5L

Color Enhancement For Porous Stones

- No surface coating, sheen or shine
- Breathable
- Lasts several years
- Easy to apply

Sealers



ALLIANCE GATOR WET LOOK SEALER

- Made from acrylic-based polymers
- Penetrates deep into concrete paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion



ALLIANCE GATOR SATIN LOOK SEALER

- Made from acrylic-based polymers
- Penetrates deep into concrete paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion
- Low-gloss matte finish, solvent-based



ALLIANCE GATOR ECO SEAL HIGH GLOSS

- 100% pure, high-grade acrylic used to seal concrete pavers, clay pavers and natural stone
- Penetrates deep into paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion



ALLIANCE GATOR ECO SEAL LOW GLOSS

- 100% pure, high-grade acrylic used to seal concrete pavers, clay pavers and natural stone
- Penetrates deep into paver and natural stone pores, reducing oil and dirt penetration
- Protects them from de-icing salt corrosion



SUREBOND 1300 JOINT SAND STABILIZING SEALER - MATTE FINISH

- Seals surface & hardens joint sand, while protecting the sealer film from mold, moss & algae
- Reduces sand washout, weeds & insect infestation
- Locks in a clean, natural look & matte finish.
- Product is breathable, designed for immediate application and is water-based; moisture or efflorescence will not get trapped
- Approximate Coverage: 80-120 sq.ft

Sealers continued



SUREBOND 7700 JOINT STABILIZING SEALER - GLOSS FINISH WITH ANTIFUNGAL PROTECTION

- Seals the surface and bonds joint sand between interlocking concrete pavers.
- Protects colored, stained and exposed aggregate concrete from staining.
- Resists acid, salt, other corrosives and weathering.
- Stabilizing sealer, water-based, single component and epoxy-modified; exceeds all VOC and EPA standards.
- Non-hazardous with the consistency of water; milky white in appearance when applied, dries crystal clear creating a semi-gloss finish.



SUREBOND 8700 WET LOOK JOINT SAND STABILIZER WITH FUNGICIDE

- An advanced premium acrylic sealer that will not yellow under exposure to sunlight.
- A 2 in 1 product; protects the substrate surface and stabilizes jointing sand at the same time.
- Specially formulated with antifungal agents designed to help inhibit the growth of mold, fungi and moss on horizontal pavement surfaces.
- Forms a tenacious bond to the concrete or masonry surface.
- Wet look, rain safe in 90 minutes, water-repellant, breathable, solvent-based.

Sands



TECHNISEAL HP NEXTGEL 50 lb/bag

- Colors: Granite & Prairie Tan
- 56 bags/skid (2860 lbs/skid)
- Dust & haze-free, fast-setting polymeric sand.
- Formulated for heavy-sloped, heavy traffic, high humidity and pool decks.
- For joints from 1/16" to 4", ideal for joints up to 1".
- Coverage: 60-120 Sq.Ft./bag for narrow joints.



TECHNISEAL NOCO STORM (40 LB)

- Colors: Tan, Granite & Black
- Multi-weather.
- For the durable jointing of pavers, natural stone, large concrete slabs, and porcelain.
- Permeable, efficient, reusable.
- Perfect for walkways, pool decks, patios, and non-vehicular areas.
- Ready-to-use, no mixing required.



POLYBIND™ HP SAND

- Colors: Nevada, Tan & Oxford Grey.
- Designed for paver joints up to a maximum of 1 inch.
- Unique mixture of polymer binders and calibrated sand.
- Installation almost identical to using regular paver joint sand, except for the application of water; once set, it becomes very firm and locks between the paver joints, maintaining pavers securely in place.
- Equally effective on both horizontal & sloped surfaces.
- Packaging: 50 lb bag 56 bags/skid.
- Coverage: 65-85 sq.ft. per bag for narrow joints/larger joints require more sand.

Sands continued



POLYBIND™ COMPLETE SAND

- Colors: Nevada, Tan & Oxford Grey
- Specifically designed for drainage and non-drainage base systems.
- Can be used with concrete pavers, wetcast and natural stones for a variety of uses including pool sides, patios, paths, driveways, parking spaces, etc.
- Sets above the freezing temperature 32°F and can be used for joints up to a maximum of 1.5 in.
- Packaging: 50 lb bag 56 bags/skid.
- Coverage: 65-85 sq.ft. per bag for narrow joints/larger joints require more sand.



POLYBIND G2 SAND - NO DUST • HAZE FREE • NO BLOWER • ONE WATERING

- Colors: Nevada & Oxford Grey
- Made with calibrated sand that is mixed with sophisticated intelligent polymers, which neutralize haze and dust; application is now dust free and haze free.
- No blower needed and the intelligent polymeric sand requires only one watering.
- Recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements, etc.
- Sets above the freezing temperature 32°F and can be used for joints up to a maximum of 2 in.
- Packaging: 50 lb bag 56 bags/skid
- Coverage: 65-85 sq.ft. per bag for narrow joints/larger joints require more sand.



POLYBIND G2 COMPLETE SAND - NO DUST • HAZE FREE • NO BLOWER • ONE WATERING

- Designed for paver joints up to maximum of 4".
- Drainage & non-drainage applications (overlays).
- The cleanest, fastest and easiest polymeric sand installed in the industry.
- Can be used with concrete pavers, wetcast & natural stones, and is recommended for use in patios, pool decks, walkways, driveways, etc.
- Packaging: 50 lb bag 56 bags/skid
- Coverage: 65-85 sq.ft./ bag for narrow joints/larger joints require more sand; 58-76 sq.ft./ bag for narrow joints/larger joints need more sand.



POLYBIND DUST

- Colors: Tan & Grey
- Designed for natural stone joints 1/2" to 4".
- A unique mixture of polymer binders and calibrated crushed stone.
- Once set, becomes very firm and locks between the stone joints, maintaining a bond that holds the stones securely in place.
- Equally effective on both horizontal and sloped surfaces.
- Packaging: 50 lb bag 56 bags/skid
- Coverage: 20-30 sq.ft. per bag for joints 1"-2" wide and stones approximately 2" thick



ALLIANCE EUROSTONE BOND

- Colors: Slate Grey.
- The first polymeric sand specifically designed for drainage and non-drainage base systems.
- Can be used with natural stones and cobblestone.
- Sets above the freezing temperature (0°C / 32°F) and can be used for joints up to a maximum of 35mm/ 1".
- Packaging: 50 lb bag 56 bags/skid.

Sands continued



ALLIANCE GATOR NITRO SAND

- Colors: Beige, Grey, Black & Silver
- Ready-to-use mixture of calibrated sand and resins which cure when exposed to air, harden from top to bottom of the joint.
- Can be installed in wet or dry weather, in joints ranging from a minimum 3/16" (5mm) to a maximum 2" (50mm) joint width; minimum jointing depth is 1" (25mm).
- Packaging: 40 lb bucket • 48 buckets/skid.
- Coverage: 10-56sf = 1 bucket depending on joint size.



SEK POLYSWEEP POLYMERIC SAND

- Colors: Tan & Grey
- Designed to keep sand in the joints by creating a semi-solid joint.
- A blend of native sands conforming to ASTM-C-144 and binders specially formulated to allow the joints to expand and contract with the elements (ie. heat, cold & freeze/thaw cycles).
- Prevents sand erosion from the pavement joints caused by rain and other water run-off, proven to produce less hazing.
- Also deters weed growth and reduces overall pavement maintenance.
- Max width: 2.5cm (1"); a larger joint width is acceptable where pavers intersect. Min depth: 3cm (1.25").
- Packaging: 50 lb bag, 56 bags / skid (2,860 lbs / skid)
- Coverage: Courtstone - 1 bag covers approx. 25sq.ft.

Note: Extra care must be exercised when using with Courtstone®, Copthorne®, Richcliff® & Town Hall®. This product is not recommended for use with Il Campo®, Series™ & Umbriano®.



SUREBOND JOINTING SAND

- Colors: Tan & Grey
- Will properly complete the interlocking of segmental pavers because it is clean, angular and meets ASTM-C144 specifications.
- More stable in the paver joints and has optimal gradation to ensure long term performance of the pavement system.
- Recommended for joints up to 3/4" • Washed, screened & dried
- Packaging: 50 lb bag

SAND RECOMMENDATIONS BY PRODUCT

| Sands | Polybind HP G2 | Polybind Complete Sand G2 | Polysweep Polymeric Sand | Unicare® Easy Pro® |
|-----------------|--|---|---|--|
| PAVERS | For joints up to 1/8" May be sealed. Tan color Non-binding sand | For joints up to 1" May be sealed. Available in Tan or Grey Binding sand | For joints up to 4" May be sealed. Available in Tan or Grey Binding sand | For joints up to 1" May be sealed. Available in Tan or Black Binding sand |
| Copthorne® | ✓ | ✓ | ✓* | ✓ |
| Courtstone® | ✓ | ✓ | ✓ | ✓ |
| Il Campo® | N/R | N/R | N/R | N/R |
| Richcliff® | ✓ | ✓ | ✓* | ✓ |
| Senzo™ | ✓ | ✓ | N/R | N/R |
| Series™ | N/R | N/R | N/R | N/R |
| Town Hall® | ✓ | ✓ | ✓ | ✓ |
| Umbriano® | ✓ | ✓ | N/R | N/R |
| Tumbled Pavers | ✓ | ✓ | ✓ | N/R |
| Standard Pavers | ✓ | ✓ | ✓ | ✓ |

N/R - Not Recommended

✓ Recommended

✓* These pavers have a very narrow or slightly angled edge (chamfer), limiting sand penetration in the joint and causing possible weak bonding areas. The life cycle performance could be affected.

IMPORTANT NOTICE

1. DO NOT USE Polymeric Jointing Sand on the following products: Series™ Il Campo®

If joint stabilization is required, use ordinary jointing sand and apply a stabilizing sealer. Contact your local Unilock office for recommended sealants and application specifics.

2. EXTRA CARE must be exercised when using Polymeric Sand on the following products:

Courtstone®

Copthorne®

Richcliff®

Town Hall®

Umbriano®

Polymeric Jointing Sand can be used on these products but the fine polymers and binders in Polymeric Jointing Sand have a natural tendency to adhere to the surface and therefore extra diligence must be taken to pre-clean the surface prior to "wetting the sand in" and squeegee off the surface post application. Failure to do so will result in a "whitish haze" on the surface that is difficult to remove.

3. IMPORTANT COMPACTION NOTICE: Always pre-compact the pavers WITHOUT SAND IN THE JOINTS. This will facilitate proper leveling. Polymeric sand can then be swept into the joints. Always use a compactor with a protective membrane attached to the bottom of the plate.

Polymeric Jointing Sand, cleaners and sealers, must always be applied by a trained and experienced professional. Contact your local Unilock office for training and the most up-to-date best practices.

NOTICE: Unilock does not accept any responsibility for damage to the surface caused by the improper application and use of polymeric sand, sealers or cleaners. Unilock will not accept responsibility for alternate suppliers of polymeric sand, jointing sand, cleaners and sealers.

Adhesives



UNILOCK SB-10 ADHESIVE

- 10 oz - ADH009-1 / 28 oz RS-ADH015-1.
- 10 oz. Tube: 20' at 1/4" bead (12/Case)(140 cs/skid) 28 oz. Tube: 52' at 1/4" bead (12/Case)(60 cs/skid).
- SPECIFICATIONS - (Conforms to UN-STD. 1804, ASTM 2339-70& FHA UM-60).



ALLIANCE XP GATOR BLOCK ADHESIVE

- RS-ADH039 10 oz; 12/case; 90 cases/skid (1080 ea).
RS-ADH040 28 oz; 12/case; 60 cases/skid (720 ea).
- Bonds permanently in 24 hours.
 - Material may be repositioned for up to 30 minutes.
 - Works in temperatures above 32°F.
 - 850 psi in 24 hrs (1000 psi in 7 days).



TECHNISEAL STRUCTURE BOND™ FOAM ADHESIVE ADH048 (24 oz)

24 oz. Canister = 600 linear feet at 3/8" bead (12/case)

An innovative super-strength foam adhesive that bonds a wide range of construction products with an application time up to 50% faster than with conventional tube adhesives. Materials are bonded in just 8 minutes and adhesive is fully cured within 24 hours. Made from high-quality modified polyurethanes with excellent long-term resistance to weathering, dilute acids and caustic solutions.



TECHNISEAL STRUCTURE BOND™ GUN II TOOL378 1 Dispenser (12/case)

The Gun II dispenser for application enables you to gain access to hard-to-reach areas and greatly limits excessive spillage or dripping, while also reducing user-fatigue, with total control on product flow. The gun allows for a precise adhesive delivery with a single pull of the trigger that stops as soon as you let go. Requires no pumping, cutting or puncturing of cartridge nozzles.



TECHNISEAL STICKY STONE

RS-ADH055 20.3 oz sausage; 15 sausages/case; 66 cases/skid

- Professional-grade vertical hardscape adhesive.
- Perfect for outdoor kitchens, fire pits & columns, etc.
- Coverage: 1/4" x 1/4" deep area, each sausage will cover 50 linft.
- Applies mess-free and easily with gun applicator.



STICKY STONE GUN

RS-TOOL557 1 dispenser gun kit; 10 kits/case

- Heavy-duty dispenser gun specially designed for Stickstone.
- Each gun kit includes: 6 nozzles, 2 extra pistons & steel hook pull.



TECHNISEAL STRUCTURE BOND™ FOAM CLEANER


CLN093 (16 oz) 1 Canister = (12/case)

Structure Bond Gun Cleaner is a powerful cleansing formula that rapidly dissolves any uncured Structure Bond adhesive residue. Specifically designed to fit Structure Bond Gun II dispensers. Simply screw a canister onto the gun and press the trigger to cleanse the tool from uncured product. The built-in sprayer nozzle will dissolve any spill, drip or adhesive residue.

X & T Slab Spacers

X & T SLAB SPACERS

- 250 per bag
- X & T bagged separately
- X spacers 2" x 2" (RS-ACC237)
- T spacers 2" x 1" (RS-ACC236)



Unilock recommends using slab spacers when installing Arcana on an open grade surface. "T" spacers are needed for running bond patterns, "X" spacers are needed for stack bond patterns. Please contact your sales manager for more information.

Edging



PERMA EDGE PAVER EDGING

- Designed to float & flex with the sub base and not work independently like standard edging & spikes.
- Quick & easy to install, typically cutting edging install time down by 80%.
- Stays under the soil/mulch grade invisible edging.
- Combats the freeze/thaw cycles in cold weather; won't deteriorate in moist/humid conditions.
- Coverage per container; yields approx. 25-30 linear feet of edging per bucket.
- Packaging: 75 lb container / 34 kg bucket 35 / skid.



ALLIANCE GATOR XTREME EDGE

- The ultimate fiber-reinforced structural edging solution for any hardscape project.
- Can be used for any traditional, open-graded, permeable, Gator Base or overlay application using concrete pavers or slabs, natural and wet cast stones.
- Offers permanent continuous lateral support.
- Packaging: 50 lb bag / 56 bags per skid.
- Coverage: 20-25 sqft coverage per bag for a 60mm paver.

Edge Restraints



PERMEDGE PERMEABLE PAVER EDGING RS-EDGE033

- Designed specifically for permeable pavement with open-graded base material.
- Holds pavement edges securely in place.
- Does straight and curved edges.

Product Information:

8' (96") length pcs.
Weight per Unit: 2.5 lbs.
Pieces per Pallet: 64 (72 ln. ft.)
Freight Class: 300
Pallet Weight: 210 lbs.
Pallet Size: 98" l x 48" w x 50" h



Spikes

- 10" Round Spikes.
- About 150 spikes per case.
- **Sold in full cases only.**

SNAPEDGE - ONE-PIECE EDGING THAT DOES IT ALL!

- Only one part required for straight runs or curved installations.
- Built-in connector fastens one piece to the next - convenient 96" size, easy to transport.
- Unique 'Snip and Flex' feature speeds installations of curves and corners without pre-planning.
- The open design allows a root system to grow through SnapEdge, further reinforcing the installation.
- Engineered to provide a strong, easy-to-install edge restraint for concrete/ clay pavers.
- Nail hole bosses are full-length cylinders. Hammer blows will not fracture or force nail heads through edging.



Product Information:

6'8" (80") length pcs.
Sidewall: 1 3/8"
Pieces per Pallet: 672 (5,376 ln. ft.)
Pieces per Bundle: 24 (192 ln. ft.)
Bundles per Pallet: 28
Pallet Weight: 1395 lbs.
Pallet Size: 98" l x 48" w x 50" h

Drainage, Separation & Reinforcement



UNILOCK DRIVEGRID™ SYSTEM

- 120' x 13' Roll,
1,572 Sq.Ft./Roll
56 lbs/Roll



GATOR GRID 30-30

Gator Grid 30-30, a biaxial geogrid, provides strength, longevity, excellent stress transfer and prevents failure to the internal structure of landing areas, retaining walls and steep slopes. It has a high molecular weight as well as high-tenacity polyester yards which are woven in tension and finished with a PVC coating.

Packaging: • 4' x 50' / 16 rolls per box
• 6' x 50' / 20 rolls per pallet



GATOR FABRIC NON-WOVEN 3.5

Gator Fabric Non-Woven 3.5 geotextile is ideal for drainage, filtration and will allow water flow in a paver or retaining wall application. It is designed for soil separation for added stability, has high strength and is dimensionally stable.

Packaging: • 3' x 100' / 4 roll package
• 6' x 100' / 12 roll package



GATOR FABRIC WOVEN 5

Gator Fabric Woven 5 is a woven geotextile made from polypropylene yarns and can achieve higher tensile strength at low elongation. It is an excellent heavy-loading geotextile, ideal for driveways, alleyways, pathways and retaining walls.

Packaging: • 4' x 100' / 4 roll package
• 6.25' x 300' / 12 roll package



GATOR FABRIC POLYSPUN 20 **SPECIAL ORDER**

Gator Fabric Polyspun 20 geotextile is specially formulated to resist deterioration in garden and landscape applications. It creates a barrier to reduce weed growth and allows water, fertilizer and air to pass through.

Packaging: • 3' x 50' / 16 rolls per case / 64 rolls per skid
• 3' x 100' / 9 rolls per case / 36 rolls per skid
• 4' x 100' / 9 rolls per case / 36 rolls per skid
• 6' x 100' / 30 rolls per case / 36 rolls per skid

Tools & Accessories



Install up to 700 sq. ft. per hour!

- Access tight or narrow areas.
- Eliminate the need for a forklift on site.
- Reduce labor costs.
- Reduce shoulder, hand & knee pain and injury.
- Improve your bottom line.

Contact your local rep for details



GATOR TILE SYSTEM

Contact Unilock for more information.



RS-ACC074-1



RS-ACC087



10oz - RS-ADH039
28oz - RS-ADH040



RS-EDGE061



MODEL
MINI P



MODEL P



MODEL L



ALL TERRAIN
PALLET MOVER



PISA XL LIFTING TONG

- The Pisa XL tong makes it easier to lift and place units, especially on the base course.
- The action of lifting the handle secures the lifter and makes for easy, balanced lifting and placement.



U-LEVEL™

- Easy to use.
- Accurate readings.
- Low maintenance.
- Works in difficult locations.
- Large working area.

A PRECISION TOOL NO HARDSCAPER SHOULD
BE WITHOUT



RS-ACC088

Calculations

AREA OF A CIRCLE

| | | | | | | | | | | | | | | |
|---|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Radius (in.) | 18 | 21 | 24 | 27 | 30 | 33 | 36 | 39 | 42 | 45 | 48 | 51 | 54 | 57 |
| Radius (ft.) | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 3.25 | 3.50 | 3.75 | 4.00 | 4.235 | 4.50 | 4.75 |
| Square Feet | 7.07 | 9.62 | 12.56 | 15.90 | 19.63 | 23.75 | 28.26 | 33.17 | 38.47 | 44.16 | 50.24 | 56.72 | 63.59 | 70.85 |
| Circumference (in.) | 113.04 | 131.88 | 150.72 | 169.56 | 188.40 | 207.24 | 226.08 | 244.92 | 263.76 | 282.60 | 301.44 | 320.28 | 339.12 | 357.96 |
| Circumference (Ft.) | 9.42 | 10.99 | 12.56 | 14.13 | 15.70 | 17.27 | 18.84 | 20.41 | 21.98 | 23.55 | 25.12 | 26.69 | 28.26 | 29.83 |
| Area of a circle = 3.14 x Radius x Radius | | | | | | | | | | | | | | |
| Circumference = 6.28 x Radius | | | | | | | | | | | | | | |

AREA CONVERSION CHART

| | | | | | | | | | | | | | | |
|-----------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|--------|--------|--------|--------|
| Square Feet | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Square Meter | 0.09 | 0.19 | 0.28 | 0.39 | 0.46 | 0.56 | 0.65 | 0.74 | 0.84 | 0.93 | 1.02 | 1.11 | 1.21 | 1.30 |
| Square Meter | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Square Feet | 10.76 | 21.53 | 32.29 | 43.06 | 53.82 | 64.58 | 75.35 | 86.11 | 96.88 | 107.64 | 118.40 | 129.17 | 139.93 | 150.69 |
| Cubic Yard | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Cubic Feet | 27 | 54 | 81 | 108 | 135 | 162 | 189 | 216 | 243 | 270 | 297 | 324 | 351 | 378 |
| Area Square = Length x Width | | | | | | | | | | | | | | |
| Area Triangle = 1/2 Base x Height | | | | | | | | | | | | | | |

LINEAR DISTANCE CONVERSION CHART

| | | | | | | | | | | | | | | |
|-------------|-------|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Inches | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Centimeters | 2.54 | 5.08 | 7.62 | 10.16 | 12.70 | 15.24 | 17.78 | 20.32 | 22.86 | 25.40 | 27.94 | 30.48 | 33.02 | 35.53 |
| Centimeters | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Inches | 0.39 | 0.79 | 1.18 | 1.57 | 1.97 | 2.36 | 2.76 | 3.5 | 3.54 | 3.94 | 4.33 | 4.72 | 5.12 | 5.51 |
| Feet | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Meters | 0.30 | 0.61 | 0.91 | 1.22 | 1.52 | 1.83 | 2.13 | 2.44 | 2.74 | 3.05 | 3.35 | 3.66 | 3.96 | 4.25 |
| Meters | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Inches | 39.37 | 78.74 | 118.11 | 157.48 | 196.85 | 236.22 | 275.59 | 314.96 | 354.33 | 393.70 | 433.07 | 472.44 | 511.81 | 551.18 |
| Feet | 3.28 | 6.56 | 9.84 | 13.12 | 16.40 | 19.69 | 22.97 | 26.25 | 29.53 | 32.81 | 36.09 | 39.37 | 42.65 | 45.93 |

WEIGHT CONVERSION CHART

| | | | | | | | | | | | | | | |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Pounds | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Kilograms | 0.45 | 0.91 | 1.36 | 1.81 | 2.27 | 2.72 | 3.18 | 3.63 | 4.08 | 4.54 | 4.99 | 5.44 | 5.90 | 6.35 |
| Kilograms | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| Pounds | 2.20 | 4.41 | 6.61 | 8.82 | 11.02 | 13.23 | 15.43 | 17.64 | 19.84 | 22.05 | 24.25 | 26.46 | 28.66 | 30.86 |

Calculation charts and formulas are provided as a service by Unilock for estimating material requirements. Unilock will not be held responsible in any way for resulting product overage or shortage.

BEDDING MATERIALS CHART (APPROXIMATE IMPERIAL TONS)

| Bedding Course | | | | | | | | | | | | |
|----------------|-----|------|-------|------|------|------|------|------|-------|------|------|------|
| Square Feet | 1" | 2" | 3" | 4" | 5" | 6" | 7" | 8" | 9" | 10" | 11" | 12" |
| 50 | 0.3 | 0.5 | 0.8 | 1.0 | 1.3 | 1.5 | 1.8 | 2.0 | 2.3 | 2.5 | 2.8 | 3.0 |
| 100 | 0.5 | 1.0 | 1.5 | 2.0 | 2.5 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 5.5 | 6.0 |
| 150 | 0.8 | 1.5 | 2.3 | 3.0 | 3.8 | 4.5 | 5.3 | 6.0 | 6.8 | 7.5 | 8.3 | 9.0 |
| 200 | 1.0 | 2.0 | 3.0 | 4.0 | 5.0 | 6.0 | 7.0 | 8.0 | 9.0 | 10.0 | 11.0 | 12.0 |
| 250 | 1.3 | 2.5 | 3.8 | 5.0 | 6.3 | 7.5 | 8.8 | 10.0 | 11.36 | 12.5 | 13.8 | 15.0 |
| 300 | 1.5 | 3.0 | 4.5 | 6.0 | 7.5 | 9.0 | 10.5 | 12.0 | 13.5 | 15.0 | 16.5 | 18.0 |
| 350 | 1.8 | 3.5 | 5.3 | 7.0 | 8.8 | 10.5 | 12.3 | 14.0 | 15.8 | 17.5 | 19.3 | 21.0 |
| 400 | 2.0 | 4.0 | 6.0 | 8.0 | 10.0 | 12.0 | 14.0 | 16.0 | 18.0 | 20.2 | 22.0 | 24.0 |
| 450 | 2.3 | 4.5 | 6.8 | 9.8 | 11.3 | 13.5 | 15.8 | 18.0 | 20.3 | 22.5 | 24.8 | 27.0 |
| 500 | 2.5 | 5.0 | 7.5 | 10.0 | 12.5 | 15.0 | 17.5 | 20.0 | 22.5 | 25.0 | 27.5 | 30.0 |
| 550 | 2.8 | 5.5 | 8.3 | 11.0 | 13.8 | 16.5 | 19.3 | 22.0 | 24.8 | 27.5 | 30.3 | 33.0 |
| 600 | 3.0 | 6.0 | 9.0 | 12.0 | 15.0 | 18.0 | 21.0 | 24.0 | 27.0 | 30.0 | 33.0 | 36.0 |
| 650 | 3.3 | 6.5 | 9.8 | 13.0 | 16.3 | 19.5 | 22.8 | 26.0 | 29.3 | 32.5 | 35.8 | 39.0 |
| 700 | 3.5 | 7.0 | 10.5 | 14.0 | 17.5 | 21.0 | 24.5 | 28.0 | 31.5 | 35.0 | 38.5 | 42.0 |
| 750 | 3.8 | 7.5 | 11.36 | 15.0 | 18.8 | 22.5 | 26.3 | 30.0 | 33.8 | 37.5 | 41.3 | 45.0 |
| 800 | 4.0 | 8.0 | 12.0 | 16.0 | 20.0 | 24.0 | 28.0 | 32.0 | 36.0 | 40.0 | 44.0 | 48.0 |
| 850 | 4.3 | 8.5 | 12.8 | 17.0 | 21.3 | 25.5 | 29.8 | 34.0 | 38.3 | 42.5 | 46.8 | 51.0 |
| 900 | 4.5 | 9.0 | 13.5 | 18.0 | 22.5 | 27.0 | 31.5 | 36.0 | 40.5 | 45.0 | 49.5 | 54.0 |
| 950 | 4.8 | 9.5 | 14.3 | 19.0 | 23.8 | 28.5 | 33.3 | 38.0 | 42.8 | 47.5 | 52.3 | 57.0 |
| 1000 | 5.0 | 10.0 | 15.0 | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | 45.0 | 50.0 | 55.0 | 60.0 |

BASE DEPTH CHARTS (CUBIC YARDS)

| Bedding Course | | | | | | | | | | | | |
|----------------|-----|-----|-----|------|------|------|------|------|------|------|------|------|
| Square Feet | 1" | 2" | 3" | 4" | 5" | 6" | 7" | 8" | 9" | 10" | 11" | 12" |
| 50 | 0.2 | 0.3 | 0.5 | 0.6 | 0.8 | 0.9 | 1.1 | 1.2 | 1.4 | 1.5 | 1.7 | 1.9 |
| 100 | 0.3 | 0.6 | 0.9 | 1.2 | 1.5 | 1.9 | 2.2 | 2.5 | 2.8 | 3.1 | 3.4 | 3.7 |
| 150 | 0.5 | 0.9 | 1.4 | 1.9 | 2.3 | 2.8 | 3.2 | 3.7 | 4.2 | 4.6 | 5.1 | 5.6 |
| 200 | 0.6 | 1.2 | 1.9 | 2.5 | 3.1 | 3.7 | 4.3 | 4.9 | 5.6 | 6.2 | 6.8 | 7.4 |
| 250 | 0.8 | 1.5 | 2.3 | 3.1 | 3.9 | 4.6 | 5.4 | 6.2 | 6.9 | 7.7 | 8.5 | 9.3 |
| 300 | 0.9 | 1.9 | 2.8 | 3.7 | 4.6 | 5.6 | 6.5 | 7.4 | 8.3 | 9.3 | 10.2 | 11.1 |
| 350 | 1.1 | 2.2 | 3.2 | 4.3 | 5.4 | 6.5 | 7.6 | 8.6 | 9.7 | 10.8 | 11.9 | 13.0 |
| 400 | 1.2 | 2.5 | 3.7 | 4.9 | 6.2 | 7.4 | 8.6 | 9.9 | 11.1 | 12.3 | 13.6 | 14.8 |
| 450 | 1.4 | 2.8 | 4.2 | 5.6 | 6.9 | 8.3 | 9.7 | 11.1 | 12.5 | 13.9 | 15.3 | 16.7 |
| 500 | 1.5 | 3.1 | 4.6 | 6.2 | 7.7 | 9.3 | 10.8 | 12.3 | 13.9 | 15.4 | 17.0 | 18.5 |
| 550 | 1.7 | 3.4 | 5.1 | 6.8 | 8.5 | 10.2 | 11.9 | 13.6 | 15.3 | 17.0 | 18.7 | 20.4 |
| 600 | 1.9 | 3.7 | 5.6 | 7.4 | 9.3 | 11.1 | 13.0 | 14.8 | 16.7 | 18.5 | 20.4 | 22.2 |
| 650 | 2.0 | 4.0 | 6.0 | 8.0 | 10.0 | 12.0 | 14.0 | 16.0 | 18.1 | 20.1 | 22.1 | 24.1 |
| 700 | 2.2 | 4.3 | 6.5 | 8.6 | 10.8 | 13.0 | 15.1 | 17.3 | 19.4 | 21.6 | 23.8 | 25.9 |
| 750 | 2.3 | 4.6 | 6.9 | 9.3 | 11.6 | 13.9 | 16.2 | 18.5 | 20.8 | 23.1 | 25.5 | 27.8 |
| 800 | 2.5 | 4.9 | 7.4 | 9.9 | 12.3 | 14.8 | 17.3 | 19.8 | 22.2 | 24.7 | 27.2 | 29.6 |
| 850 | 2.6 | 5.2 | 7.9 | 10.5 | 13.1 | 15.7 | 18.4 | 21.0 | 23.6 | 26.2 | 28.9 | 31.5 |
| 900 | 2.8 | 5.6 | 8.3 | 11.1 | 13.9 | 16.7 | 19.4 | 22.2 | 25.0 | 27.8 | 30.6 | 33.3 |
| 950 | 2.9 | 5.9 | 8.8 | 11.7 | 14.7 | 17.6 | 20.5 | 23.5 | 26.4 | 29.3 | 32.3 | 35.2 |
| 1000 | 3.1 | 6.2 | 9.3 | 12.3 | 15.4 | 18.5 | 21.6 | 24.7 | 27.8 | 30.9 | 34.0 | 37.0 |

Actual volume may vary due to type of materials, moisture content, and compaction. Calculation charts and formulas are provided as a service by Unilock for estimating material requirements. Unilock will not be held responsible in any way for resulting product overage or shortage.


FINISHES



Umbriano®
Mottled Finish with
ColorFusion™ and EasyClean



Series™
Exposed Granite Finish



Il Campo®
Brushed Finish



Smooth
Premier Finish



Flagstone
Premier Finish



Antiqued
Timeworn Finish



Classic
Thrumix Finish

COLOR BLEND DESCRIPTIONS

| COLOR NAME | DESCRIPTION |
|---------------|--|
| Avorio | Solid Beige/Tan |
| Basalt | Blueish-Black |
| Bavarian | Brown, Cream and Charcoal |
| Birch | Dark Brown, Light Brown and Cream |
| Black Granite | Black Granite and Charcoal |
| Burgundy Red | Plum with Red |
| Burnt Clay | Brown with Red |
| Cocoa Brown | Solid Dark Brown |
| Corvara | Light Grey/Beige |
| Dark Charcoal | Dark Charcoal |
| Dawn Mist | Grey and Tan |
| Desert Sand | Salmon, Buff and Charcoal |
| Fieldstone | Buff and Grey |
| Fossil | Light & Dark Grey, Chamois and White Accents |
| French Grey | Light Grey with White Flake |
| Granite | Natural and Charcoal |
| Limestone | Light Gray and Charcoal |

| COLOR NAME | DESCRIPTION |
|------------------|--|
| Midnight Sky | Charcoal and Black Flake |
| Modena | White Concrete with Black Flecks |
| Natural Blend | Light Grey and Medium Grey |
| Nevada | Chamois and Natural |
| Old Oak | Rust with Red |
| Opal Blend | Light Grey and White |
| Pebble Taupe | Tan with Light Brown |
| Rustic Red | Red and Charcoal |
| Sable Blend | Cream Tan Brown |
| Sandstone | Buff and Tan |
| Sierra | Charcoal, Russet and Buff |
| Steel Grey Blend | Dark Charcoal & Grey |
| Steel Mountain | Natural and Charcoal |
| Summer Wheat | Cream White with Pale Yellow & Beige Particles |
| Terra Cotta | Salmon and Charcoal |
| Vivanto | Dark Grey and Charcoal |
| Winter Marvel | White and Black Flake |

IMPORTANT NOTES

UNILOCK PAVER PATTERNS

This Product Data Guide contains an extensive reference to patterns and designs. The purpose of these pattern swatches is to help the designer plan unique and exceptional designs. The percentages of products shown are based on the pattern and not on bundle configurations. In fact, there may be situations in which a pattern has been created with one particular size of stone, but that stone only comes packaged with two other sizes. This means that the designer will have to plan how the other components are used in the overall plan. This is usually accomplished by adding a border or an accent. As a result, overages or shortages may occur in certain patterns. The designer and/or installer of Unilock products accepts all responsibility for design and all associated costs incurred as a result of applying any of Unilock's suggested design patterns in a project. Please plan your project and review your order carefully prior to ordering.

TRANSFERABLE LIFETIME GUARANTEE

Unilock provides a Transferable Lifetime Guarantee* on the structural integrity of our paving stones, slabs and retaining wall units to the original purchaser of the product for residential use. Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Color matching cannot be guaranteed and replacement labor is not included. Proof of purchase is required.

Excessive defective material (over the industry accepted normal of 2% for non-tumbled unit pavers) delivered to the purchaser will be replaced free of charge if a written claim is made within 5 days of delivery from the manufacturer. Such claims will not constitute reason for delaying payment. All goods shall be deemed accepted if completely installed. Inspect concrete products prior to opening bundle packaging to ensure that shape and color are as ordered. Unsatisfactory material must be available for inspection by Unilock to entitle the purchaser to any adjustment or credit. Inspect all concrete units during installation and set aside any which are chipped or cracked to use for any cut pieces required. The color of concrete products may vary significantly between production lots. Always install concrete units from several bundles simultaneously to ensure proper distribution of color. Prior to final compaction, inspect installed pavers for good color distribution. Relocate certain pavers, if necessary, to achieve desired color blend.

*Transferable Lifetime Guarantee: Register your project within 60 days of your dated proof of purchase to ensure your Unilock Guarantee is fully transferable! Simply go online at unilock.com and follow instructions. Once processed, you will receive an original Transferable Warranty Certificate for your records.

PRODUCT HANDLING WARNING

Bundle Straps Under Tension - Use extreme caution when removing or handling straps. Always wear gloves, goggles, safety footwear, and protective clothing when removing or handling straps. Failure to do so may result in serious bodily injury or loss of sight.

Cut all concrete products only in well ventilated areas. Inhalation of dust is a serious health risk. A "NIOSH" (US) or a "CSA" (CDN) approved respirator, safety goggles, hearing protectors, and gloves must be worn at all times. Always "wet-cut" or "wet grind" concrete products to minimize dust.

Do not stack bundled concrete products higher than 2 bundles high. Contents of the bundle may be unstable and subject to topple when stacked. Always use extreme caution and appropriate equipment when transporting or storing bundled concrete products. Failure to do so may result in serious bodily injury or death. Always obey gross vehicle weight (GVW) loading limitations and regulations.

Hazard Rating: Fire 0, Health 1, Reactivity 0. See MSDS Concrete Masonry (Pavers). Contact Unilock for complete sheet or view safety information at Unilock.com.

Unilock assumes no liability or responsibility for loss or damage, resulting from the improper use or handling of our products, or from failure to follow instructions, warnings, and/or advisories on the product label, and on the MSDS sheet.

TRADEMARK & LEGAL INFORMATION

Umbriano® is a trademark of Metten Stein + Design GmbH & Co KG used under license by Unilock. Unilock Ltd. and Hengestone Holdings, Inc. are the owners or authorized users of all trademarks used in this publication unless otherwise specified.

Colors shown in this brochure should be used only as a guide. Colors should always be chosen from actual samples. Contact your local Unilock representative for color availability in your area. Not all products shown are available at all Unilock locations. Log on to www.unilock.com for availability. Measurements throughout this portfolio are nominal.

©2024 Hengestone Holdings, Inc.



QUALITY COMMITMENT

Unilock was the first concrete paver manufacturer in North America to offer a Lifetime Guarantee, and since then we have continued to stand behind it to ensure customers are completely satisfied with our products. With almost 2 billion stones in the ground, that's quite the commitment!

Our products are better and stronger than other brands. In fact, our internal standards of manufacturing in the USA and Canada far exceed industry standards set by ASTM (American Society for Testing and Materials) and CSA (Canadian Standards Association) and other European organizations.



LIFETIME GUARANTEE - RESIDENTIAL

Our Transferable Lifetime Guarantee warrants the structural integrity of Unilock concrete paving stones and retaining wall units when used in residential applications. It covers any structural failure or deterioration of the concrete unit resulting from normal use or from the reasonable application of sodium chloride (common rock salt used for de-icing). StoneMark™ products have the same warranties as Unilock paving stones and retaining walls, but cannot be warranted against damage resulting from de-icing products.

Any materials installed and maintained

to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Proof of purchase is required. Customers are encouraged to submit receipts to us as soon as their project is complete, using the Unilock Warranty Registration Form on our website (Unilock.com).

Purchasers need to ensure that the product they purchase is appropriate for their intended application; for example, only certain thicknesses of products are appropriate for driveways. Color matching of the replacement product and/or lost time cannot be guaranteed and labor costs related to installing replacement product is not included. Unilock reserves the right to seek a professional diagnosis and opinion to determine the exact cause of the product failure. If the failure falls within our warranty parameters, Unilock will replace the defective product.

EXCLUSIONS – Unfortunately, some things are beyond the control of Unilock, and are therefore not covered by this warranty. These include: naturally occurring efflorescence, hazing from polymeric jointing sand, scratching and chipping resulting from snow removal or construction equipment, damage caused by natural or un-natural disasters, or negligence by anyone other than Unilock. While EasyClean helps to increase a paver's resistance to staining from various substances, it does not make our products stain-proof nor does it resist every kind of stain. The Unilock warranty also does not cover deterioration or damage as a result of poor design or poor installation practices that are contrary to specifications as laid out by ICPI (Interlocking Concrete

Pavement Institute) and the NCMA (National Concrete Masonry Association). For more information please visit www.icpi.org and www.ncma.org. Additionally, please refer to the Maintenance, Color and Installation Advisories.

MAINTENANCE ADVISORY

1. Cleaning and Sealing

As with anything that is outdoors, Unilock products are subject to harsh weather, dust, acid rain, leaf stains, water stains and general wear from foot or vehicular traffic. Therefore, periodic cleaning using environmentally safe detergents designed for cleaning concrete is recommended to maintain a bright, fresh appearance.

To make subsequent cleaning easier and more effective, a concrete sealer can be applied to new or cleaned products to help prevent the penetration of substances that can cause stains.

There are many types of concrete cleaners and sealers on the market. Always read the instructions carefully before using the product to make sure that it will function as expected. Testing first, in a small unobtrusive area, is always a good idea to ensure the results are acceptable. Consult your local hardscape dealer to find the products best suited for your paver or wall installation.



Visit Unilock.com to register for your Transferable Lifetime Guarantee.

2. Winter Maintenance

Snow removal by way of metal blades on plows or shovels will scratch and chip the surface of pavers, causing permanent damage. To mitigate this risk, metal snow clearing blades must always have a polyurethane or rubber cutting edge attached when plowing pavers.

De-icing Salts - The use of de-icing products on paver surfaces is important for safety and to help mitigate snow accumulation. Most de-icing products will have some effect on concrete, even if the product label indicates that it is safe on concrete. If you must use a de-icing product, we recommend that you use Sodium Chloride (ordinary rock salt) or Calcium Chloride (for colder climates). Always apply sparingly. The use of de-icing products on StoneMark, wet-cast pavers, slabs or coping may damage the product and therefore is not recommended. Whenever possible use a coarse sand as an anti-slip measure instead of de-icing chemicals.

COLOR ADVISORY

1. Selection

Due to the inherently variable nature of printed materials and digital monitors, Unilock cannot guarantee that products will match the color of printed or online images. Therefore, when making final product selections, decisions should be made based on actual stones which are readily available from Unilock, Authorized Contractors or Authorized Dealers. Most Unilock products are not comprised of a single color, but rather contain blended colors for a more natural appearance. This means that there will be significant color variance from stone to stone, so purchasers should view multiple units together to get a more accurate impression of the overall color.

Note: Unilock Natural Stone variations are outside the control of Unilock. Purchasers of natural stone must be willing to accept this inherent variability.

2. Pre-installation checking

Always check the label to ensure that the Unilock product delivered to your project is the product and color ordered. If there is a discrepancy, or if the product inside the packaging doesn't appear to be correct, contact your hardscape dealer before installing any pavers or wall units. If the product is installed, it indicates your acceptance of the products as delivered.

3. Blending

If the project requires more than one bundle of product it's always a good idea to draw product from several bundles when installing, as this ensures that any variation between bundles will be seamlessly integrated in the project. When bundles are from different production runs, random selection from multiple bundles is even more important.

4. Efflorescence

Efflorescence is a naturally occurring process that may appear as a white or light grey powder on the surface of concrete, clay or natural stone. It is temporary, and will disappear over time. However, if it is bothersome, an efflorescence cleaner can be used to remove it. There is no way to predict or prevent efflorescence. Because it does not compromise the structural integrity of the product, it is not covered by Unilock product warranties.

INSTALLATION ADVISORY

1. Construction Residue

While a certain amount of dirt on pavers and walls is inevitable during the construction phase, installers are strongly encouraged to clean as they go as construction residue can embed in the surface and become difficult to remove. The slurry produced during wet-saw cutting is particularly stubborn to clean if allowed to dry on the surface of pavers. Unilock warranties do not cover stains caused by a failure to remove construction residue.

2. Polymeric Haze

Surface hazing caused by polymeric jointing sand is not the responsibility of Unilock. Polymeric jointing sand should only be installed by an experienced and knowledgeable contractor. Any sand that is left on the surface prior to activation will result in a haze that is very difficult and time-consuming to remove. Only the highest quality, brand name polymeric sand that is guaranteed by the manufacturer should be used.

3. Compaction Damage

Both smooth and textured paver surfaces can be scratched by compaction equipment used to 'flatten' a new paver installation. Therefore, metal plate compactors must be fitted with a polyethylene mat to protect the paver surface from becoming scratched, or a superior option is to use a rubber-roller compactor instead. Damage to product surfaces caused by failure to follow these instructions is not covered by Unilock product warranties.

FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

OHIO PRODUCT DIRECTORY

UNIT PAVERS

| Product | Page | Finish | Pedestrian | Residential Vehicular | Commercial Vehicular | Environmental | For Borders & Accents |
|------------------------|------|--------|------------|-----------------------|----------------------|---------------|-----------------------|
| Artline™ | 4 | S | ✓ | | | | ✓ |
| Beacon Hill™ Flagstone | 5 | F | ✓ | | | | |
| Beacon Hill™ Smooth | 6 | SM | ✓ | | | | |
| Boulevard™ | 7 | F | ✓ | ✓ | | | ✓ |
| Bristol Valley® | 8 | S | ✓ | | | | |
| Brussels Block® | 9 | W | ✓ | ✓ | | | ✓ |
| Camelot™ | 10 | S | ✓ | ✓ | ✓ | | ✓ |
| Copthorne® | 11 | T | ✓ | ✓ | | | ✓ |
| Courtstone® | 12 | C | ✓ | ✓ | | | ✓ |
| Eco-Line™ | 13 | S | ✓ | ✓ | ✓ | ✓ | |
| Eco-Optiloc™ | 14 | S | ✓ | ✓ | ✓ | ✓ | |
| Eco-Priora™ | 15 | B | ✓ | ✓ | ✓ | ✓ | |
| Eco-Promenade™ | 16 | S | ✓ | ✓ | ✓ | ✓ | |
| Granito™ | 17 | SM | ✓ | ✓ | | | |
| Hex™ | 18 | S | ✓ | ✓ | | | |
| Hollandstone™ | 19 | S | ✓ | ✓ | ✓ | | ✓ |
| Holland Premier® | 20 | S | ✓ | ✓ | ✓ | | ✓ |
| Il Campo® | 21 | B | ✓ | ✓ | ✓ | | ✓ |
| Mattoni™ | 22 | T | ✓ | ✓ | | | ✓ |
| Natural Stone | 23 | | ✓ | | | | |
| Nordic Cobble™ | 27 | WS | ✓ | ✓ | ✓ | | ✓ |
| Optiloc™ | 28 | S | ✓ | ✓ | ✓ | | |
| Porcelain | 29 | | ✓ | | | | |
| Promenade™ | 31 | S | ✓ | ✓ | ✓ | | |
| Promenade EcoTerra™ | 33 | SM | ✓ | ✓ | ✓ | | |
| Richcliff® | 34 | F | ✓ | ✓ | | | ✓ |
| Series™ | 35 | WS | ✓ | ✓ | ✓ | | ✓ |
| Skyline™ | 36 | S | ✓ | | | | |
| Thornbury™ | 37 | F | ✓ | ✓ | ✓ | | |
| Town Hall® | 38 | T | ✓ | ✓ | ✓ | ✓ | ✓ |
| Treo® Premier | 39 | F | ✓ | ✓ | | | ✓ |
| Treo® Smooth | 40 | SM | ✓ | ✓ | | | ✓ |
| Tribeca Cobble | 41 | C | ✓ | ✓ | | | ✓ |
| Turfstone™ | 42 | S | | ✓ | | ✓ | |
| Umbriano® | 43 | SZ | ✓ | ✓ | ✓ | | ✓ |
| Westport™ | 46 | F | ✓ | ✓ | | | ✓ |

RETAINING WALLS

| Product | Page | Finish | Gardens | Retaining Walls | Steps | Seatwalls | Pillars |
|------------------------------|------|---------|---------|-----------------|-------|-----------|---------|
| Brussels Dimensional System™ | 47 | W | ✓ | ✓ | ✓ | ✓ | ✓ |
| Dimensional Smooth™ | 48 | SM | ✓ | ✓ | ✓ | ✓ | ✓ |
| DuraHold® | 49 | S | | ✓ | | | |
| DuraHold2® | 51 | S | | ✓ | | | |
| Estate Wall™ | 52 | SP/W | ✓ | ✓ | ✓ | ✓ | ✓ |
| Lineo™ Dimensional Stone | 53 | SZ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Pisa2® & Pisa2 XL | 54 | SP | ✓ | ✓ | ✓ | ✓ | ✓ |
| Pisa Smooth™ | 55 | SP | ✓ | ✓ | ✓ | ✓ | ✓ |
| Rivercrest® Wall | 56 | S | ✓ | ✓ | ✓ | ✓ | ✓ |
| RomanPisa™ | 57 | SP/W | ✓ | ✓ | ✓ | ✓ | ✓ |
| RomanStack™ | 58 | SP/W | ✓ | | | | |
| SienaEdge® | 59 | | | ✓ | ✓ | | |
| SienaStone® | 60 | SP | | ✓ | ✓ | | |
| Split'nStack™ | 61 | SP | ✓ | | | | |
| U-Cara® | 62 | Various | ✓ | ✓ | ✓ | ✓ | ✓ |

Finishes: B=Brushed; C=Cobblestone; D=Dimpled; DW=Dimpled and Weathered; F=Flagstone; S=Standard; SM=Smooth; SZ=Smooth Zero Bevel; SP=Split; SP/W=Split and Weathered; T=Timeworn; W=Weathered; WS=Washed. This application chart should only be used as a guide. Site conditions, base materials, pattern and frequency of use may vary the performance of various types and styles of products.

ADD 3D LANDSCAPE DESIGN TO **YOUR TOOLBOX**



UVISION ALLOWS YOU TO VISUALLY COMMUNICATE YOUR DESIGN IDEAS TO YOUR CLIENT IN BOTH 2D PLAN VIEW AND 3D PERSPECTIVE VIEW

Whether you're coming from the hand-drawn world, or a 2D AutoCAD background, the biggest impact you'll see from adopting this new 3D design software is in how well the client will understand the project you are selling. **Uvision 3D Landscape Creator** is an easy-to-use software tool that helps bring your designs ideas to life.



**SCAN THE QR CODE FOR
MORE INFORMATION OR TO
DOWNLOAD A FREE 30-DAY TRAIL
OF UVISION 3D LANDSCAPE CREATOR.**





UNILOCK.COM | 1-800-UNILOCK

Let's **BUILD YOUR BUSINESS TOGETHER.**

**CONTACT 1-800-UNILOCK OR VISIT UNILOCK.COM TO
CONNECT WITH YOUR LOCAL TERRITORY MANAGER**

BOSTON
(508) 278-4536

CHICAGO
(630) 892-9191

MILWAUKEE
(262) 742-3890

KANSAS
(913) 417-7985

MICHIGAN
(248) 437-7037

NEW YORK
(845) 278-6700

MID-ATLANTIC
(202) 798-2060

ONTARIO
(416) 646-9000

CINCINNATI/KY/TN
(513) 202-0219

**OHIO/WESTERN PA/
WNY&CNY**
(330) 927-4000

