




Courtstone[®]

1-800-UNILOCK | UNILOCK.COM

UNILOCK[®]
PAVERS & WALLS



LAYING PATTERNS



Courtstone Fixed Random A

APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Textured
 Joint Spacing - 15 mm
 Void - n/a

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

REALA™

Cast from historic street pavers

ULTIMA™

Up to 4x stronger than poured-in-place concrete

TECHNICAL INFORMATION

Conforms to ASTM C 936 Eligible for LEED v4.1 credits

Bundle Type	RANDOM
Plant Produced	AYR
Thickness (mm)	60MM

SQFT PER	Bundle	98.30
	Layer	12.29
	Section	-
	Stone	0.26

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	2.25
	Section	-
	Layer	27.69
	Bundle	221.52

UNITS PER	SqFt	3.91
	Section	-
	Bundle	384.00

LBS PER	Layer	291
	Section	-
	Bundle	2,326

COLORS	Reflectance	Stock
Basalt	SR n/a SRI n/a	✓



BASALT

5 Unit Random Bundle					
	XL RECTANGLE	LARGE RECTANGLE	RECTANGLE	SMALL RECTANGLE	SQUARE
	215 x 130 x 60mm	185 x 130 x 60mm	165 x 130 x 60mm	145 x 130 x 60mm	130 x 130 x 60mm
	8 3/8 x 5 1/8 x 2 3/8"	7 1/4 x 5 1/8 x 2 3/8"	6 1/2 x 5 1/8 x 2 3/8"	5 3/4 x 5 1/8 x 2 3/8"	5 1/8 x 5 1/8 x 2 3/8"
	128 Units/Bundle	64 Units/Bundle	64 Units/Bundle	64 Units/Bundle	64 Units/Bundle
	.30 SqFt/Stone	.28 SqFt/Stone	.23 SqFt/Stone	.20 SqFt/Stone	.18 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices in the Product Data Guide. Contact Unilock for more information.