Tribeca Cobble™

1-800-UNILOCK | UNILOCK.COM

UNILOCK®
PAVERS & WALLS

Tribeca Cobble™

ENDURACOLOR™

		SERIES EXPOSED TEXTURED
	Bundle Type	RANDOM
	Plant Produced	CHICAGO
	Thickness (mm)	70MM
SQFT PER	Bundle	97.53
	Layer	12.19
	Section	-
	Stone	0.32
PER BUNDLE	Layers	8.00
	Sections	-
SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	2.34
	Section	-
	Layer	28.49
	Bundle	227.95
UNITS PER	SqFt	3.12
	Section	-
	Bundle	304.00
LBS PER	Layer	398
	Section	-
	Bundle	3,186

COLORS	Reflectance	Stock
Cobalt Grey	SR n/a SRI n/a	SO
Peppered Granite	SR .38 SRI 42	SO

LAYING PATTERNS

Tribeca Cobble Fixed Random_A

APPLICATIONS

APPEARANCE

Edge Detail - Micro
Surface Texture - Series Exposed Textured
Joint Spacing - 10mm
Void - 5.6%

TECHNOLOGIES

PERMEABLE
Can be installed to allow water to flow through

ENDURACOLOR™
Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

COBALT GREY

PEPPERED GRANITE

Random Bundle

LARGE RECTANGLE
130 x 305 x 70mm
5 x 12 x 2 ¾"
88 units/Bundle
.43 Sq.Ft./Stone

RECTANGLE
130 x 230 x 70mm
5 x 9 x 2 ¾"
88 units/Bundle
.32 Sq.Ft./Stone

SMALL RECTANGLE
130 x 175 x 70mm
5 x 6 ⅞ x 2 ¾"
128 units/Bundle
.25 Sq.Ft./Stone

Notes: Special Order - Lead time required. Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Important: **A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices in the Product Data Guide. All measurements are nominal. Contact Unilock for more information.

TBC_MI_2022