

REGION CHICAGO

IMAGE
UNAVAILABLE

Please contact your
Unilock
Representative for
assistance.

IMAGE
UNAVAILABLE

UNILOCK® Exclusive Technologies

■ REALA™

IMAGE
UNAVAILABLE


Please contact your
Unilock
Representative for
assistance.

APPLICATIONS


Note: Not all sizes are suitable for every application. Contact Unilock Representative for assistance.




Fire Feature



Garden Wall



Outdoor Kitchen



Retaining Wall



Water Features

COLORS

COASTAL SLATE FINISH: FLAGSTONE



CORNER LEFT
380mm x 102mm x 229mm
15" x 4" x 9"

BUFF FINISH: FLAGSTONE



CORNER LEFT
380mm x 102mm x 229mm
15" x 4" x 9"

	(102) CORNER RANDOM BUNDLE
UNIT THICKNESS (MM)	102
LAYERS PER BUNDLE	5
FCFT PER BUNDLE	12.96
FCFT PER LAYER	2.59
FCFT PER UNIT	0.65
UNITS PER BUNDLE	20
UNITS PER LAYER	4
LBS PER BUNDLE	867.01
LBS PER LAYER	173.40
LBS PER UNIT	43.35

INSTALLATION NOTES

Makinaw™ Wall

Makinaw Wall is an attractive, natural stone-like landscape retaining block. This is a gravity system which relies on shear weight to retain small embankments or for use in making planters.

Applications – Design and build projects such as planters, steps, seat walls and other decorative landscape retaining walls. Recommended for straight applications only.

Capacity – walls up to 2 ft. (60 cm) in height

Recommended Base Stabilization – one layer of DriveGrid™ stabilization grid between subgrade and base material. Use under Standard Base or Permeable Base.

Standard Base – Min. 6" – 8" of ¾" Crusher Run gravel (any road base standard in accordance with ASTM-D2940) compacted to 98% Standard Proctor Density (SPD).

Alternative Permeable Base – Min. 6" – 8" of ¾" clear open-graded stone compacted to achieve full particle lock-up and consolidation. (Clear open-graded does not compact but does consolidate slightly by rattling the particles together.)

Leveling – Leveling retaining wall blocks directly on top of gravel is tedious and generally does not yield the best results. U-Grip Base units or universal base pads are recommended under all Unilock walls for improved accuracy and speedier installation. Additional benefits include long term structural integrity and an overall better appearance. Poured concrete leveling pads, reinforced with rebar, are also a great way to accomplish leveling, particularly for larger installations. You must ensure that the concrete is poured and finished perfectly in order to achieve a good visual appearance.

Connection – Just like stacked natural stone, Makinaw Wall relies on gravity to hold back gardens and embankments.

Handling – No specific handling instructions.

Coping - This wall does not require coping, but coping is sometimes used to complete the installation visually. Choose any manufactured coping such as LedgeStone Coping or any of our natural stone coping options. Cutting may be required.

The free online CSS beautifier website takes care of your dirty code and strips every unwanted

Contact Unilock Representative for actual color samples and availability. Unilock reserves the right to change product information without notice.

PDF Generated July 27, 2024, 11:36 am