# MATTONI™

THICKNESS 60MM REGION CHICAGO






**UNILOCK** TECH SHEET



EDGE ZERO EDGE DETAIL

## **UNILOCK** Exclusive Technologies

ENDURACOLOR



#### **APPLICATIONS**

Note: Not all sizes are suitable for every application. Contact Unilock Representative for assistance.



**Residential & Commercial Pedestrian** 



**Residential Driveway** 

**UNILOCK** TECH SHEET

## COLORS

DARK CHARCOAL FINISH: SMOOTH PREMIER



SABLE FINISH: SMOOTH PREMIER



COCOA BROWN FINISH: SMOOTH PREMIER



**GRANITE FUSION** SRI = 29 FINISH: SMOOTH PREMIER



STANDARD 60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"

STANDARD

STANDARD


60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"

60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"


STANDARD 60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"



## LAYING PATTERNS



LP MATTONI HB C



LP MATTONI DHB D

| <br>- 1 | <br> |  |
|---------|------|--|


LP MATTONI RB A

MATTONI™



## **TYPICAL CROSS SECTION**

Note: Base, screed bed, infill aggregates and or reinforcements may vary based on project requirements or as specified by engineer.



#### PACKAGING



|                     | STANDARD |
|---------------------|----------|
| UNIT THICKNESS (MM) | 60       |
| LAYERS PER BUNDLE   | 10       |
| LBS PER BUNDLE      | 2,965.33 |
| LBS PER LAYER       | 296.53   |

#### INSTALLATION NOTES

rates and application procedures. Always test a small area to make sure the results are as expected. Sealers

- · Product may be sealed for aesthetic or cleanliness reasons but it is not required
- Use any sealer approved for concrete pavers
- Select type for desired aesthetics
- Product must be cleaned before sealing
- Always read and follow manufacturer's application procedures
- · Always test a small area to make sure the results are as expected

The Americans with Disabilities Act Accessibility Guidelines (ADAAG) provides measurable criteria to determine compliance, not individual product evaluation. Gaps, joints or openings, greater than ½" horizontal and ¼" vertical should be avoided as they can disrupt wheelchair maneuvering (United States Access Board – Guidelines and Standards).

Contact Unilock Representative for actual color samples and availability. Unilock reserves the right to change product information without notice.

PDF Generated May 2, 2024, 11:38 am

