MATTONITM

THICKNESS

60MM

REGION

MICHIGAN









ZERO EDGE DETAIL

UNILOCK Exclusive Technologies

ENDURACOLOR



APPLICATIONS



2

Note: Not all sizes are suitable for every application. Contact Unilock Representative for assistance.



Residential & Commercial Pedestrian



Residential Driveway

COLORS

DARK CHARCOAL FINISH: SMOOTH PREMIER





STANDARD 60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"

GRANITE FUSION SRI = 29







STANDARD

60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"







STANDARD

60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"

COCOA BROWN FINISH: SMOOTH PREMIER





STANDARD


60mm x 240mm x 60mm 2 3/8" x 9 1/2" x 2 3/8"




LAYING PATTERNS







LP MATTONI DHB D




LP MATTONI RB A

TYPICAL CROSS SECTION



4

Note: Base, screed bed, infill aggregates and or reinforcements may vary based on project requirements or as specified by engineer.







	STANDARD
UNIT THICKNESS (MM)	60
LAYERS PER BUNDLE	10
LBS PER BUNDLE	3,062.89
LBS PER LAYER	306.29

UNILOCK.COM | 1-800-UNILOCK

INSTALLATION NOTES



rates and application procedures. Always test a small area to make sure the results are as expected. Sealers

- Product may be sealed for aesthetic or cleanliness reasons but it is not required
- Use any sealer approved for concrete pavers
- Select type for desired aesthetics
- · Product must be cleaned before sealing
- Always read and follow manufacturer's application procedures
- · Always test a small area to make sure the results are as expected

The Americans with Disabilities Act Accessibility Guidelines (ADAAG) provides measurable criteria to determine compliance, not individual product evaluation. Gaps, joints or openings, greater than ½" horizontal and ½" vertical should be avoided as they can disrupt wheelchair maneuvering (United States Access Board – Guidelines and Standards).

Contact Unilock Representative for actual color samples and availability. Unilock reserves the right to change product information without notice.

PDF Generated April 19, 2024, 11:44 am



UNILOCK.COM | 1-800-UNILOCK