



Mackinaw™

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS

MACKINAW™

STONEMARK™



COASTAL SLATE



GRINDSTONE

PRODUCT ATTRIBUTES

Visual Appearance	Bold, modern wall with the look of split limestone.
Finish	Stonemark™ naturally detailed surface.

PRODUCT SPECIFICATIONS



LARGE WEDGE
5½ x 28½ (25½) x 9"
140 x 720 (650) x 230mm



MEDIUM WEDGE
5½ x 20 (17) x 9"
140 x 510 (430) x 230mm




SMALL WEDGE
5½ x 11½ (8½) x 9"
140 x 290 (220) x 230mm

3 UNIT RANDOM BUNDLE



CORNER/PILLAR UNIT
5½ x 17½ x 9"
140 x 440 x 230mm



U-GRIP™ BASE PAD
14 x 19 x 2"
355 x 482 x 55mm

MACKINAW RADIUS CHART

Outside Radius (inches)	36"	59"	68"
Unit sequence	Only 11.5" units	11.5", 20", 28.5"	20", 28.5", 20", etc.

Notes: Any leftover pieces should be used on other parts of a project.

RECOMMENDED ADHESIVE



Gator Block Bond XP

- | VOC Compliant
- | Low odor- safe indoors or out
- | Fast curing- provides permanent overnight bond
- | Suitable for use in hot and cold environments
- | Non-shrinking- does not crack
- | Strong and versatile

Coverage: For 1/4" Bead (approx)

10 oz		28 oz	
m	ft.	m	ft.
-9	-31	-26	-86



UniLyft Unilyft compatible

TECHNICAL INFORMATION

ASTM C 1372 Standard Specifications for Dry-Cast Segmental Retaining Wall Units

Conforms to:

- C140 for Absorption and Compressive Strength > 3000 PSI
- C1262 for Freeze Thaw Durability <1% mass loss
- C1372 Overall dimensional variations permissible for width, height and length +/-3.2mm

Unilock standards exceed 6,000 PSI for Mackinaw™ Wall products with:

- 4% absorption avg.
- 5% absorption max.
- Dimensional Accuracy +/-2.00mm

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

TECHNICAL ADVANTAGES

REALA™

Cast from Natural Stone

PRODUCT DATA

Stones & Bundling	Face Feet Per		Linear Feet Per		Units Per		Per Bundle		Lbs Per	
	Bundle	Unit	Bundle	Unit	Bundle	Face Feet	Layers	Sections	Unit	Bundle
Georgetown Manufacturing U-Grip - Gormley										
Random Wall Bundle	17	0.71	37	-	24		3	-	-	1,990
Large Wedge	6.2	1.03	13.5	2.25	6	0.97	-	-	120.59	-
Medium Wedge	8.5	0.71	18.5	1.54	12	1.41	-	-	82.01	-
Small Wedge	2.3	0.38	5	0.83	6	2.63	-	-	47.05	-
Corner/Pillar Unit	24.21	2.0175	32.54	2.72	12	0.79	3	-	152.37	1,828
U-Grip Base Pad			85.39	1.581	54		9		46	2,500

Notes: All measurements are nominal. Contact your Unilock Territory Manager or call 1-800-UNILOCK for further information. *For custom options, please contact your Unilock Territory Manager.

APPLICATIONS



Garden Walls & Seat Walls

Coping is optional, we recommend natural stone.

***Things to know:**

Handling and Installation – Product is installed using Unilock Concrete Adhesive to secure corners and all rows. Base preparation may vary according to soil and climate conditions. Maximum height is 24” including the unit in the ground (under optimum conditions). Based on 12” deep wall coverage = 21.4 sqft per bundle. Based on an 8” deep wall coverage = 32 sqft per bundle.