



# Promenade™ Plank

1-800-UNILOCK | UNILOCK.COM

**UNILOCK**  
PAVERS & WALLS

# PROMENADE™ PLANK PAVER

ENDURACOLOR™



OPAL BLEND  
4" X 12", 4" X 16", 8" X 24"



SANDSTONE  
4" X 12"



STEEL GREY BLEND  
4" X 12", 4" X 16", 8" X 24"



LIGHT GREY **NEW**  
*IL CAMPO' FINISH*  
4" X 12", 8" X 24"



GRANITE BLEND  
*IL CAMPO' FINISH*  
4" X 12", 8" X 24"



DARK CHARCOAL **NEW**  
*IL CAMPO' FINISH*  
4" X 12", 8" X 24"



BLACK GRANITE  
*SERIES™ FINISH*  
4" X 12", 8" X 24"

## PRODUCT ATTRIBUTES

Visual Appearance	Long and narrow design facilitates a linear laying pattern resulting in a finished and sleek appearance to complement current architectural design trends, leaving no compromise on style for heavy-duty functionality.
Finish	Available in a variety of Unilock Select finishes such as Il Campo®, Series™ (Stock) and Umbriano® (Custom), to name a few.

## PRODUCT SPECIFICATIONS



8 x 24 x 4"  
200 x 600 x 100mm



4 x 16 x 4"  
100 x 400 x 100mm



4 x 12 x 4"  
100 x 300 x 100mm

## EDGE DETAILS



ROUNDED EDGE

## LAYING PATTERNS



PROMENADE PLANK PAVER A 8X24  
100% 8x24



PROMENADE PLANK PAVER C 4X16  
100% 4x16



PROMENADE PLANK PAVER G  
40% 8x24, 40% 4x16,  
20% 4x12

## RECOMMENDED SAND



Gator G2 MAXX Sand

- | Setting time - 15 mins
  - | Sets above 32° F/ 0° C
  - | Can be applied if rain is expected (min. 1 hr)
  - | Dust free and haze free
  - | Requires only one watering
  - | Four colours: Beige, Grey, Black and Ivory
- Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Grey, Ivory 50lb. bag	65-85 sqft	22-42 sqft
Black 50lb. bag	58-76 sqft	20-38 sqft

## RECOMMENDED SEALER



Gator Hybrid Low Gloss + Colour Enhancer

- | Water-based
  - | Low gloss finish
  - | Vibrant Colour Enhancer
  - | Rain safe after 24 hours
- Coverage:

Size	Area
3.78 L / 1 U.S. gal.	200 sqft
18.9 L. / 5.28 U.S. gal.	1,000 sqft

## TECHNICAL INFORMATION

### ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3mm**

Test results available upon request

### Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

## TECHNICAL ADVANTAGES

### ENDURACOLOR™

Refined surface and long-lasting colour

### DRIVE FRIENDLY

Can handle vehicular loads  
Ask about our base stabilization system

### IL CAMPO FINISH

Graphically interesting etched lines

### SERIES FINISH

Granite, Quartz and Marble surface materials

## PRODUCT DATA

Stones & Bundling	Unit	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per		Lbs Per	
	Thickness	Bundle	Layer	Section	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Bundle	Layer	Bundle
<b>Georgetown Manufacturing</b>																	
8" x 24"	4" (100mm)	51.67	10.33		1.29	5	-	0.66	-	26.2	1.97	-	78.70	0.77	40	478	2,391
4" x 16"	4" (100mm)	51.67	10.33		0.43	5	-	0.33	-	39.4	1.31	-	157.50	2.32	120	488	2,440
4" x 12"	4" (100mm)	58.13	11.63		0.32	5	-	0.33	-	59.1	0.98	-	177.20	3.10	180	532	2,659

Notes: Sold in full bundles only on a refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing.** All measurements are nominal. Contact your Unilock Territory Manager or call 1-800-UNILOCK for further information. \*For custom options, please contact your Unilock Territory Manager.

## APPLICATIONS



Pedestrian



Residential Vehicular



Commercial Vehicular (4 x 12 x 4" only)



Borders and Accents



\*Wall pairing suggestion- U-CARA™ Wall or Lineo™ Dimensional Stone

## SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI
Opal Blend	0.32	34

## LEED INFORMATION

### Materials & Resources: LEED V4:

Building Product Disclosure and Optimization

Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**

Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**

Material Ingredient Reporting - Material Ingredient Reporting • **1 point**

Material Ingredient Reporting - Material Ingredient Optimization • **1 point**

Environmental Product Declaration • **1 point**

### \*Paver Maintenance Tips:

- Equip plow scrapers and blades with shoes or high-density plastic blades to reduce the risk of damaging paver joints and the surface
- Only apply min. amount of de-icing salts necessary to melt the snow and ice. Remove excess salt after ice melts
- Regular cleaning routine should include sweeping or blowing loose debris from the pavement surface, and less frequently, deep cleaning with cleaning products and/or water
- Unilock pavers do not require sealing, however, some people choose to do so for aesthetic purposes

### \*Things to know:

Efflorescence is a naturally occurring calcium salt that can sometimes appear on the surface of concrete and clay products. Efflorescence does not affect the structural integrity of concrete, it is a purely aesthetic issue that typically disappears with no further intervention after a season of rainfall. If desired, the process can be accelerated by washing the surface with an Efflorescence Remover.