



Concord[®] Wall

1-800-UNILOCK | UNILOCK.COM

UNILOCK[®]
PAVERS & WALLS



ALMOND GROVE

GRANITE

SIERRA



UNIVERSAL BASE
19 x 14 x 2 1/4"
482 x 355 x 55mm
NATURAL ONLY
See page 71 for more
information



CORNER
8 x 12 x 6"
200 x 300 x 150mm



XL UNIT
16 x 6 x 12"
400 x 150 x 300mm



COPING
24 x 12 x 3"
600 x 300 x 75mm



WEDGE CAP
8 1/2 (7 1/4) x 12 3/4 x 3"
215 (187) x 323 x 75mm

	Corner Split	XL Wall Split	Coping 24"	Wedge Cap Split
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	150MM	150MM	75MM	86MM
Dimension mm	200mm x 150mm x 300mm	400mm x 150mm x 300mm	600mm x 75mm x 300mm	215MM X 75MM X 323MM
Dimension Imperial	7 7/8" x 5 7/8" x 11 7/8"	15 3/4" x 5 7/8" x 11 7/8"	23 5/8" X 3" X 11 7/8"	8 1/2" X 3" X 12 3/4"

FCFT PER	Bundle	15.00	21.33	16.00	64.00
	Layer	5.00000	5.33000	2.00000	8.00000
	Stone	0.83	0.67	1.00	0.67

PER BUNDLE	Layers	3.00	4.00	8.00	8.00
	Sections	-	-	2.00	-

LNFT PER	Bundle	-	-	64.00	-
	Unit	-	-	4.00	-

UNITS PER	SqFt	1.20	1.50	0.52	1.50
	Section	-	-	8.00	-
	Bundle	18.00	32.00	16.00	96.00

LBS PER	Layer	273	605	145	318
	Section	-	-	-	-
	Bundle	820	2,419	2,320	2,544

Internal Use Only. CON UX

Notes: Maximum height without setback 36" (under optimum conditions). Maximum height with setback is 42" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. Tapered units will allow for a minimum 7ft. outside radius. Wedge cap radius = 7", contains 8 Closed-end units per bundle. Closed-end not sold separately. All Concord Wall™ is layered and shipped on refundable skid. Coping is sectioned. Closed-end step tread is available. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. Contact your local Unilock Representative for details. Retaining wall engineering software is also available free of charge at www.unilock.com.