



Treo[™] Smooth

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS



FOSSIL
NEW



STEEL MOUNTAIN
NEW

Bundle Type	RANDOM
Thickness (mm)	60MM
Dimension mm	
Dimension Imperial	

SQFT PER	Bundle	116.87
	Layer	11.69000
	Section	-
	Stone	0.56

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	1.57
	Section	-
	Layer	18.35
	Bundle	183.46

UNITS PER	SqFt	1.80
	Section	-
	Bundle	210.00

LBS PER	Layer	321
	Section	-
	Bundle	3,208

3 UNIT RANDOM BUNDLE



LARGE RECTANGLE
13¼ x 8⅞ x 2⅜"
338 x 225 x 60mm



SQUARE
8⅞ x 8⅞ x 2⅜"
225 x 225 x 60mm



SMALL RECTANGLE
8⅞ x 4½ x 2⅜"
225 x 112 x 60mm

ADVANTAGES

PERMEABLE

Can be installed to allow water to flow through

DRIVE FRIENDLY

Can handle vehicular loads

Notes: **Sold in full bundles only** and is produced and sold on a required, refundable skid.

Important: A urethane rubber paver mat must be used to prevent scuffing when compacting. For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices and Important Notice on page 87. All measurements are nominal. Contact Unilock for more information.

Internal Use Only. TRE CH