



# Bristol Valley<sup>®</sup>

1-800-UNILOCK | UNILOCK.COM

**UNILOCK**  
PAVERS & WALLS



# BRISTOL VALLEY®

ENDURACOLOR™



GRANITE FUSION



SIERRA FUSION

## PRODUCT ATTRIBUTES

|                   |                                                                                                                                                                                             |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Visual Appearance | Gentle surface clefts and waved edges.                                                                                                                                                      |
| Finish            | The subtle surface texture and understated edge detail of Bristol Valley brings a new, refined elegance to projects where a more commonplace flagstone slab may have been used in the past. |

## PRODUCT SPECIFICATIONS



**LARGE RECTANGLE**  
14 x 21 x 2<sup>3</sup>/<sub>8</sub>"  
360 x 540 x 60mm



**SQUARE**  
14 x 14 x 2<sup>3</sup>/<sub>8</sub>"  
360 x 360 x 60mm



**SMALL RECTANGLE**  
7 x 14 x 2<sup>3</sup>/<sub>8</sub>"  
180 x 360 x 60mm

3 UNIT RANDOM BUNDLE


## EDGE DETAILS



WAVED EDGE


## BUNDLE CONFIGURATION

BRISTOL VALLEY  
RANDOM BUNDLE




## LAYING PATTERNS

BRISTOL VALLEY A



**BRISTOL VALLEY RANDOM A**  
40% Large Rectangle, 40%  
Square, 20% Small Rectangle

BRISTOL VALLEY B



**BRISTOL VALLEY RANDOM B**  
40% Large Rectangle, 40%  
Square, 20% Small Rectangle

## RECOMMENDED SAND



**Gator G2 MAXX Sand**

- | Setting time - 15 mins
- | Sets above 32° F/ 0° C
- | Can be applied if rain is expected (min. 1 hr)
- | Dust free and haze free
- | Requires only one watering
- | Four colours: Beige, Grey, Black and Ivory

### Coverage:

| Colour                          | Narrow Joints | Wide Joints |
|---------------------------------|---------------|-------------|
| Beige, Grey, Ivory<br>50lb. bag | 65-85 sqft    | 22-42 sqft  |
| Black<br>50lb. bag              | 58-76 sqft    | 20-38 sqft  |

## RECOMMENDED SEALER



**Gator Natural Look Sealer**

- | Water-based
- | Zero gloss finish
- | Multi purpose
- | Rain safe after 24 hours

### Coverage:

| Size                        | Area     |
|-----------------------------|----------|
| 3.78 L /<br>1 U.S. gal.     | 175 sqft |
| 18.9 L. /<br>5.28 U.S. gal. | 875 sqft |

NOTES: Bristol Valley® is not intended for vehicular applications.

## TECHNICAL INFORMATION

### ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3 mm**

*Test results available upon request*

**Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines**

## LEED INFORMATION

### Materials & Resources: LEED V4:

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

## TECHNICAL ADVANTAGES

### ENDURACOLOR™

Refined surface and long-lasting colour

### PEDESTRIAN FRIENDLY

Not recommended for vehicular

## PRODUCT DATA

| Stones & Bundling     | Unit Thickness | SqFt Per |       |         |       | Per Bundle |          | Sailor LnFt per |         |        | Units Per |       |        | Lbs Per |        |          |
|-----------------------|----------------|----------|-------|---------|-------|------------|----------|-----------------|---------|--------|-----------|-------|--------|---------|--------|----------|
|                       |                | Bundle   | Layer | Section | Stone | Layers     | Sections | SqFt            | Section | Bundle | SqFt      | Layer | Bundle | Unit    | Layer  | Bundle   |
| <b>Stocked in Ayr</b> |                |          |       |         |       |            |          |                 |         |        |           |       |        |         |        |          |
| Random Bundle         |                | 94.14    | 10.46 |         | 1.34  | 9          | -        | 0.90            |         | 85.04  | 0.76      | 8     | 72     | 35.68   | 285.43 | 2,568.90 |
| Large Rectangle       | 2 1/2" (60 mm) | -        | -     | -       | 2.09  | -          | -        |                 |         |        | 0.48      |       | 18     | -       | -      | -        |
| Square                | 2 1/2" (60 mm) | -        | -     | -       | 1.4   | -          | -        |                 |         |        | 0.72      |       | 27     | -       | -      | -        |
| Small Rectangle       | 2 1/2" (60 mm) | -        | -     | -       | 0.7   | -          | -        |                 |         |        | 1.43      |       | 27     | -       | -      | -        |

Notes: Product sold in full bundles only on a refundable skid. All measurements are nominal. **Product is not intended for vehicular applications. Important: A urethane rubber paver mat must be used to prevent scuffing.** Contact your Unilock Territory Manager or call 1-800-UNILOCK for further information.\*For custom options, please contact your Unilock Territory Manager.

## APPLICATIONS



Pedestrian



Roof Deck



\*Wall pairing suggestion- U-CARA® - matching colour and finish

### \*Paver Maintenance Tips:

- Equip plow scrapers and blades with shoes or high-density plastic blades to reduce the risk of damaging paver joints and the surface
- Only apply min. amount of de-icing salts necessary to melt the snow and ice. Remove excess salt after ice melts
- Regular cleaning routine should include sweeping or blowing loose debris from the pavement surface, and less frequently, deep cleaning with cleaning products and/or water
- Unilock pavers do not require sealing, however, some people choose to do so for aesthetic purposes

### \*Things to know:

Efflorescence is a naturally occurring calcium salt that can sometimes appear on the surface of concrete and clay products. Efflorescence does not affect the structural integrity of concrete, it is a purely aesthetic issue that typically disappears with no further intervention after a season of rainfall. If desired, the process can be accelerated by washing the surface with an Efflorescence Remover.