

DuraHold 2®



DuraHold 2[®] SPECIAL ORDER PRODUCT CLASSIC









STANDARD 72" x 12" x 14" 1830 x 300 x 360mm SPECIAL ORDER



COPING 72" x 12" x 14" 1830 x 300 x 360mm SPECIAL ORDER



CLOSED END COPING 72" x 12" x 14" 1830 x 300 x 360mm SPECIAL ORDER



TIE-BACK 72" x 12" x 14" 1830 x 300 x 360mm SPECIAL ORDER



CORNER 90° 36" x 12" x 14" 900 x 300 x 360mm SPECIAL ORDER (Right Corner Shown)

		Standard	Coping	Closed-End Coping	Tie-Back	Corner 90° Left & Right
Bundle Type		SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
	,	GORMLEY	GORMLEY	GORMLEY	GORMLEY	GORMLEY
Thickness (mm)		300MM	300MM	300MM	300MM	300MM
Dimension mm		1,830mm x 300mm x 360mm	1,830mm x 300mm x 360mm	1,830mm x 300mm x 360mm	360mm x 300mm x 1,830mm	900mm x 300mm x 360mm
Dimension Imperial		72" x 11 7/8" x 14 1/4"	72" x 11 7/8" x 14 1/4"	72" x 11 7/8" x 14 1/4"	14 1/4" X 11 7/8" X 72"	35 1/2" x 11 7/8" x 14 1/4"
FCFT PER	Bundle	24.10	24.08	24.08	4.68	16.67
	Layer	6.02000	6.02000	6.02000	1.17000	4.17000
	Stone	6.02	6.02	6.02	1.17	4.17
PER BUNDLE	Layers	4.00	4.00	4.00	4.00	4.00
	Sections	-	-	-	-	-
	Б "	04.40	04.40	04.40		
LNFT PER	Bundle	24.10	24.10	24.10	-	-
	Unit	6.02	6.02	6.02	-	-
UNITS PER	SqFt	0.17	0.17	0.17	0.85	0.24
		0.17	0.17	0.17	0.03	0.24
	Section	-	-	-	-	-
	Bundle	4.00	4.00	4.00	4.00	4.00
	Lavor	938	884	884	938	460
LBS PER	Layer	938	884	884	938	460
	Section	-	-	-	-	•
	Bundle	3,752	3,536	3,536	3,752	1,840

Notes: "Special Order - Lead time is required, minimum quantities apply. Sold in full bundles only. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone" Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.