



DuraHold[®]

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS



NATURAL



STANDARD
72 x 12 x 14"
1830 x 300 x 360mm
SPECIAL ORDER



CORNER 90°
60 X 12 X 24"
900 x 300 x 360mm
SPECIAL ORDER
(Right Corner Shown)



COPING
72 x 12 x 14"
1830 x 300 x 360mm
SPECIAL ORDER



CLOSED-END COPING
72 x 12 x 14"
1830 x 300 x 360mm
SPECIAL ORDER

	Standard	Corner 90°	Coping	Closed-End Coping
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	300MM	300MM	300MM	300MM
Dimension mm	1,830mm x 300mm x 600mm	1,520mm x 300mm x 600mm	1,830mm x 300mm x 600mm	1,830mm x 300mm x 600mm
Dimension Imperial	72" x 11 7/8" x 23 5/8"	59 7/8" x 11 7/8" x 23 5/8"	72" x 11 7/8" x 23 5/8"	72" X 11 7/8" X 23 5/8"

FCFT PER	Bundle	6.02	7.04	6.02	6.02
	Layer	6.02000	7.04000	6.02000	6.02000
	Stone	6.02	7.04	6.02	6.02

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	6.02	-	6.00	6.02
	Unit	6.02	-	6.00	6.02

UNITS PER	SqFt	0.17	0.14	0.17	0.17
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,680	1,320	1,560	1,560
	Section	-	-	-	-
	Bundle	1,680	1,320	1,560	1,560

Internal Use Only. DH1 ON

Notes: ***Special Order - Lead time is required, minimum quantities apply. Sold in full bundles only.** Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



NATURAL



TIE-BACK
72 x 12 x 14"
1830 x 300 x 360mm
SPECIAL ORDER



1/2 COPING
36" x 12" x 24"
915 x 300 x 600mm
SPECIAL ORDER



CORNER 45°
60" x 12" x 24"
1520 x 300 x 600mm
SPECIAL ORDER
(Right Corner Shown)



1/2 STANDARD
36" x 12" x 24"
915 x 300 x 600mm
SPECIAL ORDER

	Tie-Back	1/2 Coping	Corner 45°	1/2 Standard
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	300MM	300MM	300MM	300MM
Dimension mm	600mm x 300mm x 1,830mm	915mm x 300mm x 600mm	1,520mm x 300mm x 600mm	915mm x 300mm x 600mm
Dimension Imperial	23 5/8" x 11 7/8" x 72"	36" x 11 7/8" x 23 5/8"	59 7/8" x 11 7/8" x 23 5/8"	36" X 11 7/8" X 23 5/8"

FCFT PER	Bundle	2.00	2.95	7.04	3.00
	Layer	2.00000	2.95000	7.04000	3.00000
	Stone	2.00	2.95	7.04	3.00

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	-	3.00	-	3.00
	Unit	-	3.00	-	3.00

UNITS PER	SqFt	0.50	0.34	0.14	0.33
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,660	780	1,480	800
	Section	-	-	-	-
	Bundle	1,660	780	1,480	800

Internal Use Only. DHI ON

Notes: *Special Order - Lead time is required, minimum quantities apply. Sold in full bundles only. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.