









DURA HOLD[®]

RETAINING WALL SYSTEM

REF: Detail_DuraHold_System Components

DURAHOLD [®] System Units		Face Width	Back Width	Height	Depth	Weight
	Standard Unit	72"	72"	12"	24"	1740 lbs
		1830 mm	1830 mm	305 mm	610 mm	790 kg
	Tapered Half Unit	36"	34"	12"	24"	870 lbs
		915 mm	876 mm	305 mm	610 mm	395 kg
	Left Corner Unit	60"	60"	12"	24"	1450 lbs
		1525 mm	1525 mm	305 mm	610 mm	658 kg
	Right Corner Unit	60"	60"	12"	24"	1450 lbs
		1525 mm	1525 mm	305 mm	610 mm	658 kg
	45 Degree Left Corner Unit	60"	60"	12"	24"	1265 lbs
		1525 mm	1525 mm	305 mm	610 mm	575 kg
	45 Degree Right Corner Unit	60"	60"	12"	24"	1265 lbs
		1525 mm	1525 mm	305 mm	610 mm	575 kg
	Tie-Back Unit	72"	72"	12"	24"	1740 lbs
		1830 mm	1830 mm	305 mm	610 mm	790 kg
	Coping Unit	72"	72"	12"	24"	1720 lbs
		1830 mm	1830 mm	305 mm	610 mm	780 kg

DURA-HOLD [®] System Design/Construction Information		
Minimum Inside/Outside Radius	Standard Units	269'
	Tapered Half Units	82 m
Stacking Alignment	Battered/Vertical*	
Facing	Smooth Chamfered Face	
Placement Method	Machine	

* -Tapered Half Units cannot be constructed vertical when used in a curve



Engineering design by RisiStone Inc.



UNILOCK.COM | 1-800-UNILOCK