



Pisa2™ & PisaXL

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS



GRANITE

RIVER

SANDSTONE

SIERRA



STANDARD
8 x 12 x 6
200 x 300 x 150mm




TAPERED
8 x 12 x 6
200 x 300 x 150mm



CORNER
8 x 12 x 6
200 x 300 x 150mm



XL UNIT
12 x 16 x 6
300 x 400 x 150mm



COPING
12 x 12 x 3
300 x 300 x 75mm

	Standard	Tapered	Corner	XL Unit	Coping
Bundle Type	RANDOM	RANDOM	SINGLE	SINGLE	SINGLE
Thickness (mm)	150MM	150MM	150MM	150MM	75MM
Dimension mm	200mm x 150mm x 300mm	200mm x 150mm x 300mm	200mm x 150mm x 300mm	400mm x 150mm x 300mm	300mm x 75mm x 300mm
Dimension Imperial	7 7/8" x 5 7/8" x 11 7/8"	7 7/8" x 5 7/8" x 11 7/8"	7 7/8" x 5 7/8" x 11 7/8"	15 3/4" x 5 7/8" x 11 7/8"	11 7/8" x 3" x 11 7/8"

FCFT PER	Bundle	20.00	20.00	15.00	21.33	21.00
	Layer	6.67000	6.67000	5.00000	5.33000	3.00000
	Stone	0.33	0.33	0.83	0.67	0.25

PER BUNDLE	Layers	3.00	3.00	3.00	4.00	7.00
	Sections	2.00	2.00	3.00	4.00	2.00

LNFT PER	Bundle	40.00	40.00	-	42.67	84.00
	Unit	0.67	0.67	-	1.33	1.00

UNITS PER	SqFt	3.00	3.00	1.20	1.50	4.00
	Section	30.00	30.00	6.00	8.00	42.00
	Bundle	60.00	60.00	18.00	32.00	84.00

LBS PER	Layer	857	768	314	617	388
	Section	1,285	1,153	314	617	1,357
	Bundle	2,570	2,305	943	2,467	2,714

Internal Use Only, PS2 OH

Notes: **Universal Base & XL Wall units are single units and are sold in full bundles only.** When purchased by the full bundle, 12" Coping bundle has 16 units of closed-end coping (8 left and 8 right). Closed-end 12" coping not sold separately. Maximum height - 36" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. The set back on Pisa2 wall is 3/4" every course or 1 1/2" every 2 courses. Retaining wall engineering software is also available free of charge at www.unilock.com. Walls greater than 4' in height require professional engineering. Tapered Units allow for a minimum 5' Radius. All measurements are nominal. Contact Unilock for more information.