



Town Hall®



1-800-UNILOCK | UNILOCK.COM

UNILOCK®
PAVERS & WALLS



BURGUNDY RED



BURNT CLAY



OLD OAK




BASALT



HERITAGE RED



HERITAGE CLAY



BURGUNDY RED/
BURNT CLAY/OLD OAK
Sold Separately/
Blended on Site



HERITAGE
2 COLOR BLEND
Sold Separately/
Blended on Site

	STANDARD
Bundle Type	SINGLE
Thickness (mm)	70MM
Dimension mm	100MM X 250MM X 70MM
Dimension Imperial	3 7/8" X 9 7/8" X 2 3/4"

SQFT PER	Bundle	88.41
	Layer	11.05000
	Section	-
	Stone	0.28

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.19
	Section	-
	Layer	13.12
	Bundle	104.99

SAILOR LNFT PER	SqFt	2.97
	Section	-
	Layer	32.81
	Bundle	262.47

UNITS PER	SqFt	3.62
	Section	-
	Bundle	320.00

LBS PER	Layer	361
	Section	-
	Bundle	2,888



STANDARD
3 7/8" x 9 7/8" x 2 3/4"
100 x 250 x 70mm

ADVANTAGES

REALA™

Cast from historic brick

ULTIMA™

Up to 4x stronger than
poured-in-place concrete

PERMEABLE

Can be installed to allow water to
flow through

DRIVE FRIENDLY

Can handle vehicular loads

Notes: Sold in full bundles only and is produced and sold on a required, refundable skid.

Important: A urethane rubber paver mat must be used to prevent scuffing. For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices on page 86 and Important Notes on page 95. All measurements are nominal. Contact Unilock for more information.

Internal Use Only, TWN ON