

NORTHSHORE™

ENDURACOLOR™

NEW FOR 2022



FOSSIL



GRANITE MIST



MIDNIGHT CHARCOAL

6 X 12 ONLY

PRODUCT ATTRIBUTES

Visual Appearance	Gentle surface clefts and waved edges.
Finish	Soft touch finish - ultra smooth surface texture, sealed with EasyClean™ to provide integral surface protection from stains. The refined surface and long-lasting colour benefits of Enduracolor™.

PRODUCT SPECIFICATIONS



LARGE RECTANGLE
18 x 12 x 2¾"
457 x 300 x 70mm



SQUARE
12 x 12 x 2¾"
300 x 300 x 70mm



SMALL RECTANGLE
6 x 12 x 2¾"
150 x 300 x 70mm



SMALL RECTANGLE
6 x 12 x 2¾"
150 x 300 x 70mm
MIDNIGHT CHARCOAL ONLY


3 UNIT RANDOM BUNDLE

EDGE DETAILS





WAVED EDGE

LAYER CONFIGURATION



LAYING PATTERNS



*Colour selection should be chosen from actual samples.

TECHNICAL INFORMATION

ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3mm**

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

TECHNICAL ADVANTAGES

ENDURACOLOR™

Refined surface and long-lasting colour



Factory sealed to provide integral surface protection from stains

SOFT TOUCH FINISH

Ultra-smooth surface texture

DRIVE FRIENDLY

Can handle vehicular loads

Ask about our base stabilization system

PRODUCT DATA

Stones & Bundling	Unit Thickness	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per			Lbs Per	
		Bundle	Layer	Section	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Layer	Bundle	Layer	Bundle
Georgetown Manufacturing																		
Random Bundle	2 3/4" (70mm)	93.0	11.625	-	-	8	-	-	-	-	-	-	-	0.76	12	96	382.5	3,060
Large Rectangle	2 3/4" (70mm)	-	-	-	2.09	-	-	-	-	-	-	-	-	0.48	-	-	-	-
Square	2 3/4" (70mm)	-	-	-	1.40	-	-	-	-	-	-	-	-	0.72	-	-	-	-
Small Rectangle	2 3/4" (70mm)	77.52	9.69	-	0.70	8	-	-	-	-	-	-	-	1.43	20	160	368.75	2,950

Notes: Sold in full bundles only on a refundable skid. **Minimum quantities apply on custom orders.** All measurements are nominal. **Important: A urethane rubber paver mat must be used to prevent scuffing.** For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS



Pedestrian



Residential Vehicular



Commercial Vehicular
(Small Rectangle only)



Wall pairing suggestion- U-CARA

RECOMMENDED SANDS

RECOMMENDED SEALER



Romex® Fugensand
Suitable for Pedestrian, Vehicular and Heavy Duty Vehicular applications

- Manufactured from natural, raw materials
- Quick application
- Self-repairing properties
- Suitable for all load classes
- No cement haze/residue due to natural polymer binder
- Three colours: Natural, Stone Grey and Basalt

Coverage:

Colour	3mm Joints
Neutral, Stone Grey, Basalt 1 L / 5 gal	110 sqft / 55 lb bag 750 sqft / 5 gal drum



Romex® D7000 Joint Strengthener & Surface Sealer
Suitable for Pedestrian, Vehicular and Heavy Duty Vehicular applications

- All-in-one strengthener & sealer
- Eco-Friendly
- Protects against dirt, oil, corrosion from climate exposure, de-icing salts
- Protects against weed growth and wash outs

Coverage:

Colour	3mm Joints
Neutral, Stone Grey, Basalt 55 lb bag / 1 kg can	110 sqft / 55 lb bag 750 sqft / 5 gal drum



Gator G2 MAXX Sand

- Setting time - 15 mins
- Sets above 32° F / 0° C
- Can be applied if rain is expected (min. 1 hr)
- Dust free and haze free
- Requires only one watering
- Four colours: Beige, Grey, Black and Ivory

Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft
Black 50 lb bag	58-76 sqft	20-38 sqft



Gator Natural Look Sealer

- Water-based
- Zero gloss finish
- Multi purpose
- Rain safe after 24 hours

Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft
18.9 L. / 5.28 U.S. gal.	875 sqft

*Please refer to Sands & Sealers on pages 184-187 for more detailed information