

ENDURA™ COPING

UNILOCK®

TECH SHEET

THICKNESS 70MM

REGION OHIO



UNILOCK® Exclusive Technologies

ENDURACOLOR



COLORS

**DARK CHARCOAL
FINISH: SMOOTH
PREMIER**



UNIVERSAL COPING
482mm x 70mm x 355mm
19" x 2 3/4" x 14"

PACKAGING

	UNIVERSAL COPING	COPING CHAMFERED	COPING CHAMFERED	FULLNOSE COPING	COPING BULLNOSE	COPING FULLNOSE	FULLNOSE COPING
UNIT THICKNESS (MM)	70	60	60	60	60	60	60
LAYERS PER BUNDLE	6	6	10	6	6	10	6
FCFT PER BUNDLE	13.08	6.96	6.96	-	-	-	-
FCFT PER LAYER	2.18	1.16	1.16	-	-	-	-
FCFT PER UNIT	0.36	0.58	0.58	-	-	-	-
UNITS PER BUNDLE	36	12	40	24	24	40	12
UNITS PER LAYER	6	2	4	4	4	4	2
LBS PER BUNDLE	2,280	1,547.40	2,422.67	1,509.74	1,509.74	2,350	1,547.40
LBS PER LAYER	380	257.90	242.27	251.62	251.62	235	257.90
LBS PER UNIT	63.33	128.95	60.57	62.91	62.91	58.75	128.95

PACKAGING

	COPING BULLNOSE
UNIT THICKNESS (MM)	60
LAYERS PER BUNDLE	6
FCFT PER BUNDLE	6.96
FCFT PER LAYER	1.16
FCFT PER UNIT	0.58
UNITS PER BUNDLE	12
UNITS PER LAYER	2
LBS PER BUNDLE	1,547.40
LBS PER LAYER	257.90
LBS PER UNIT	128.95

INSTALLATION NOTES

IMPORTANT INFORMATION

The base units are designed to provide the installer a flat surface on the retaining wall base gravel to facilitate quick and easy installation of any retaining wall type. These units also help bridge smaller retaining wall units to prevent differential settlement between units. The multiple lines embossed into the surface provide an alignment guide when placing retaining wall units.

Handling and Installation –

The top of the unit should be located below grade in the base trench so that a minimum 6” of the first row of block sits below grade as well.

Units can be individually levelled or they can be placed on a screeded bed of stone chip for rapid installation. Although rectangular in shape, they can be installed in a “sailor” pattern or a “soldier” pattern depending on the wall type and/or the desired appearance.

Always sweep the surface clean prior to placing the first row of retaining wall units.

Contact Unilock Representative for actual color samples and availability. Unilock reserves the right to change product information without notice.

PDF Generated July 3, 2026, 10:37 am

UNILOCK