

**2022**

# PRODUCT DATA



**UNILOCK®** **50**  
PAVING IT FORWARD YEARS





“A beautiful outdoor space should stand the test of time, every time.”

---

**Ed Bryant | Unilock Founder**

November 30, 1935 - January 28, 2021





# Laying a Foundation for Inspiration

---

50 years ago, our founder had a dream. When Ed Bryant introduced the UNI-Stone paver to the North American market, he essentially established the hardscaping industry here. Since then, we have continued to innovate and grow. As a result, we are proud to have played a part in creating countless beautiful spaces, from backyard patios to landmark destinations across the continent. And we're just getting started. We know Ed would be proud.



# Quality

## FOR US, IT'S PERSONAL

**Over 50 years ago**, our founder stumbled upon a unique little European product called the UNI-Stone. Intrigued by the benefits of this revolutionary paving method, he decided to license the product and bring the concept to North America. He purchased a basic paver machine from Europe and hired a small staff to produce the stones.

In those early days, most sales of Unilock were to large-scale commercial properties and streetscapes. Any lapse in quality would be costly and would jeopardize

our owner's personal reputation, so quality was of paramount importance.

From these humble beginnings, through to the multinational company we are today, Unilock has remained a family-owned company that puts quality first. For us, it's not just a matter of dollars and cents, it's our personal reputation that's on the line.

Homeowners, Contractors, Landscape Designers and Architects across North America know they can rely on us to supply them with top quality product every time.



Today we operate 20 manufacturing plants across North America.



The first Unilock press produced a humble 817 square feet of pavers a day.

UNI-STONE™



See page 104 for more information.



# TABLE OF CONTENTS

---

## PAVERS

Ada Paver .....	24
Arcana™ .....	25
Artline™ Smooth .....	26
Artline™ Umbriano® .....	27
Beacon Hill™ Flagstone 60mm .....	28
Beacon Hill™ Flagstone 80mm .....	29
Beacon Hill™ Smooth .....	30
Bristol Valley® .....	31
Copthorne® .....	32
Courtstone® .....	33
Dura-Mat™ .....	34
Eco-Line® .....	35
Eco-Optiloc™ .....	36
Eco-Priora™ .....	37
Eco-Promenade® .....	38
Eco-Stone™ .....	39
Granito™ .....	40
Hex Paver™ .....	41
Holland Premier™ .....	42
Il Campo® .....	43
Mattoni™ .....	44
Natural Stone Sandstone .....	45
Natural Stone Limestone .....	48
Optiloc .....	50
Porcelain .....	51
Promenade™ Plank Paver .....	52
Richcliff® .....	54
Senzo™ .....	55
Series™ .....	56
Thornbury™ Smooth .....	57
Town Hall® .....	58
Transition™ .....	59
Treo® Premier .....	60
Treo® Smooth .....	61
Tribeca Cobble™ .....	62
Turfstone™ .....	63
Umbriano™ .....	64
Westport™ .....	66

## RETAINING WALLS

Brussels Dimensional System™ .....	67
Concord Wall™ .....	68
DuraHold® .....	69
DuraHold2® .....	71
Estate Wall™ .....	72
Lineo™ Dimensional Stone .....	77
SienaStone™ .....	79
U-Cara® .....	80
U-Cara® Modular System .....	84
U-Cara® Rail System .....	85

## COPING, STEPS, PILLAR CAPS

Architectural Coping .....	86
Fullnose Edger™ .....	87
Ledgestone™ .....	88
Universal Coping .....	90

## FIRE FEATURES

Sunset Firepit .....	91
RomanStack™ Firepit .....	92

## ACCESSORIES

Natural Stone Cleaners / Sealers .....	93
Paver Cleaners .....	93
Paver Sealers .....	94
Adhesive .....	94
Sands .....	95-96
Sand Charts .....	96
Edge Restraints .....	96-97
Large Equipment (Unilyft, Paver Saver) .....	98
Accessories .....	99

## PRODUCT & INSTALLATION INFORMATION

Paver Reference Guide .....	11
Wall Reference Guide .....	13
Coping Pairing Options .....	13
Finishes, Coatings & Edge Details .....	21
Application Index and Color Blends .....	23
Base Thickness Chart .....	99
Important Information .....	103
Product Directory .....	106





## PRODUCT CATEGORIES

### CLASSIC

Our budget-friendly, Unilock Classic pavers and walls are manufactured to exceed ASTM standards for quality and strength. Available in classic shapes and styles, these products utilize a traditional product mix of large and small aggregates that is consistent from top to bottom with color mixed throughout.

### ENDURACOLOR™

The refined surface of Unilock EnduraColor products is achieved with a two-step manufacturing process that combines a base of coarser aggregates for a stronger foundation with concentrated color and wear-resistant finer aggregates on top. This process protects the surface from the appearance of fading over time because the top layer prevents large, lighter color aggregates from ever showing through. Now, with U-Cara®, walls are available with EnduraColor too!



### ELEGANCE®


Deep, rich colors and a multitude of unique Reala™ textures combine to deliver the timeless beauty of Unilock Elegance. From the timeworn look of European cobblestones, to the classic luxury of riven natural stone slabs, our Elegance collection offers styles you can't get anywhere else. Thanks to Ultima™ Concrete, the look you purchase is the look that will last, with up to **4x the strength of poured-in-place concrete**.








# PERMEABLE Think Green




Developed in response to growing concerns around stormwater management, permeable pavers allow rainwater to flow between the joints and back into the subsoil. This provides a dual “green” benefit: it reduces the amount of water sent to storm sewers, and instead provides extra moisture to surrounding plant material.



The pavers used in a permeable installation look similar to traditional pavers, but are made with special spacer bars that create a wider joint.

Special materials are used in the joints and in the permeable base below, to encourage water to flow through and reach the subsoil.

Using permeable pavers will reduce puddling on the pavement when it rains, and decrease ice build-up in winter.

 Look for this permeable icon in our Unilock paver collection.





## EXCLUSIVE TECHNOLOGIES

### Reala™

Utilizing REALA technology, a multitude of natural stone surfaces, brick and historic cobblestones are cast to create a **wide variety of authentic textures** with consistent dimensions that are **more cost efficient to install**.



 ELEGANCE™

#### With Ultima

*Unilock Town Hall® pavers are built to last*



#### Without Ultima

*Deteriorating brick pavers exposed to deicing salts*

### Ultima™

Only Unilock has the technology in North America to manufacture Ultima Concrete resulting in pavers **up to four times stronger** than poured concrete. With Ultima, the look you purchase is the look that will last.

➤ Ultima Concrete is a key ingredient in the timeless elegance of our Elegance collection of premium pavers.



## ColorFusion™


The look of natural granite is achieved when color and granite particles are randomly dispersed using proprietary ColorFusion technology to achieve a unique mottled surface.



*ColorFusion also available on our U-Cara® Multi-Face Wall System.*

## EasyClean™ Integral Stain Protection

Unlike after-market sealers which merely coat the top, EasyClean goes beyond the surface and becomes integral to the product during manufacturing. The result is enhanced surface color, and protection from stains.



**AFTER**

Stains set for thirty minutes, then removed with damp paper towel, hand scrub brush and mild soap.

Nothing protects pavers from stains like EasyClean.

### EASYSKLEAN ADVANTAGES

Pavers are pre-sealed at the factory

Enhanced resistance to weathering

Reduced dirt absorption

Stains from leaves, coffee, ketchup, mustard, wine and BBQ oils are easier to remove

Pavers shown on left hand side are Thrumix pavers without EasyClean. Pavers shown on right hand side are EnduraColor pavers with EasyClean Stain Resistance Technology.



# UP YOUR GAME WITH

# UniLyft™



**/ UNILYFT MINI  
FOR COMPACT  
TRACK LOADERS**

- ❑ Reduce labor costs
- ❑ Install pavers and walls faster and more accurately
- ❑ Reduce shoulder, hand, and knee pain
- ❑ Improve your bottom line
- ❑ Retain employees and attract new ones

**SCAN THE QR CODE FOR MORE  
INFORMATION OR TO CONNECT  
WITH A UNILOCK TERRITORY  
MANAGER FOR A HANDS-ON  
DEMONSTRATION**



**// FLIP TO PAGE 98 TO LEARN MORE**


# UNILOCK PAVER REFERENCE GUIDE

UNILOCK PAVERS	Classic	EnduraColor	Elegance	EasyClean	SoftTouch	Reala	Ultima	ColorFusion	Permeable
Arcana™		•		•					
Artline™ Smooth		•							
Artline Umbriano		•		•				•	
Beacon Hill™ Flagstone 60mm		•							
Beacon Hill™ Flagstone 80mm		•							
Beacon Hill Smooth		•							
Beacon Hill Smooth XL		•							
Bristol Valley®		•		•	•				
Copthorne®		•	•			•	•		
Courtstone®		•	•			•	•		
Eco-Priora™	•								•
Holland Premier™		•							
Mattoni™		•		•					
Richcliff®		•	•			•	•		
Series 70mm		•							
Series 60mm		•							
Soreno™		•		•	•				
Town Hall®		•	•			•	•		•
Transition™		•							
Thornbury™ Smooth		•							•
Treo® Premier		•							
Treo® Smooth		•							•
Tribeca Cobble™		•							•
Umbriano® 60mm		•		•				•	
Umbriano 70mm		•		•				•	
Westport™		•		•	•				



# BUILD FASTER VERTICAL FEATURES

When the plan calls for pillars, a grill island or any vertical feature, the U-Cara Modular System lets you create customizable features **in hours - not days!** Simply build the sturdy, aluminum frame in any configuration and clad it with a wide selection of fascia panels. **SO INNOVATIVE. SO UNILOCK.**



**U-CARA®**  
**Modular System**



SCAN THE QR CODE TO  
CONNECT WITH A UNILOCK  
TERRITORY MANAGER FOR  
MORE INFORMATION



/// FLIP TO PAGE 84 TO LEARN MORE

# UNILOCK WALL REFERENCE GUIDE

UNILOCK WALLS	Classic	EnduraColor	ColorFusion	Two-Sided	Garden	Engineered
Brussels Dimensional System™	•			•	•	
Lineo™ Dimensional Stone	•			•	•	
Estate Wall™	•			•	•	
Concord Wall™	•				•	•
U-Cara®		•	•	•	•	•

STEPS & COPING	EnduraColor	Reala	Two-Sided
Architectural Pillar Cap	•		•
Ledgestone™		•	•
Universal Coping	•		•

## COPING PAIRING OPTIONS


UNILOCK COPINGS	Ledgestone	Universal Coping	Natural Stone	Fullnose	Concord Wall	Estate Wall
Brussels Dimensional System	•		•	•		•
Lineo Dimensional Stone	•		•			•
Estate Wall	•		•			•
Concord Wall	•	•	•		•	•
U-Cara	•	•	•	•		




## THE IMPORTANCE OF ASPECT RATIO

Simply defined, aspect ratio is the overall length of a paver divided by its height.  
 $\text{LENGTH/HEIGHT} = \text{ASPECT RATIO}$


If an insufficient aspect ratio is used, any flexing or rocking caused by movement on the surface such as vehicular traffic, could result in breakage of the paver units. Not only is this breakage unsightly, but it can also compromise the integrity of the segmental system.



**OVER 5 : 1**  
Pedestrian Only




**4 : 1**  
Light-Duty  
Vehicular



**3 : 1 OR LESS**  
Heavy-Duty  
Vehicular

## LAYING PATTERN CONSIDERATIONS


The laying pattern used in your application can also add a significant amount of strength to your design. A herringbone pattern provides the best 'lock-up', adding strength against rotational forces such as tires at a roadway intersection in the same way the 'L' shaped paver provides maximum performance.



## HEAVY-DUTY CONSIDERATIONS

Unilock has a variety of shapes and sizes available to fit your heavy-duty application and style preferences. For maximum performance where twisting and tipping will be factors, consider the unique "L" interlocking shape as it provides superior resistance under heavy loads. The patented locking features work in tandem with the "tri-axis" technology. The result? A stronger, more stable pavement surface.

Heavy-duty Unilock paving systems are also designed for rapid mechanized installation, making them competitive and affordable.




### H-20 & HS-20 LOAD RATING

Similar to top of deck stresses per AASHTO H-20 loading conditions (32,000 lbs/14,500 kg), Unilock pavers can support 3-4 axle vehicles. This would include delivery, fire and semi-truck and trailer traffic in light-duty roadway applications.

*SPEAK WITH YOUR UNILOCK REPRESENTATIVE FOR MORE INFORMATION.*


## NON-PERMEABLE INSTALLATIONS

Having the correct base design is essential for successful residential and commercial projects. Below are a couple of Examples of the base detail; however, every base detail must be specific to site conditions and load capacity. Contact your Unilock Representative to learn more.



### PAVER INSTALLATION ON GRANULAR

From pedestrian to heavy-duty applications this detail is tried and true. Contact your Unilock Representative to learn more. Specific installation details may vary based on site conditions.



### PAVER INSTALLATION ON SAND OVER CONCRETE

Ideal for heavy-duty applications, this detail ensures adequate base support under heavy loads. Approving the proper sand type and gradation is critical for lock up and drainage in vehicular applications. Contact your Unilock Representative to learn more. Specific installation details may vary based on site conditions.




## PERMEABLE INSTALLATIONS

Similar to the non-permeable paver systems structural component, permeable paver installations offer a secondary purpose for capturing and detaining rainwater. Common uses can range from sidewalk and plaza areas, to heavy-duty parking lots, driveways and roadways and include various base depths as shown in the two details below.


### PERMEABLE ON OPEN GRADED AGGREGATE - LIGHT DUTY

This cross-section is an example of a light-duty pedestrian sidewalk application. Contact your Unilock Representative to learn more. Specific installation details will vary based on site conditions.



### PERMEABLE ON OPEN GRADED AGGREGATE - HEAVY-DUTY


Heavy-duty permeable applications require additional base support as illustrated below. This cross section is only an example. Contact your Unilock Representative to learn more. Specific installation details will vary based on site conditions.




## TYPICAL RETAINING WALL CROSS SECTIONS

Unilock manufactured retaining wall systems are engineered to last. Individual units range from 19lbs (8.6kg) to 1,700lbs (772.7kg), and some can be used to construct walls up to 40ft (12.2m) high. Below are a couple of cross section examples, however, retaining walls must be designed and engineered to the specific loads and site conditions.

### TYPICAL GEOGRID REINFORCED APPLICATION PISA2™/CONCORD WALL™ / ROMANPISA™



### TYPICAL GRAVITY APPLICATION SIENASTONE®





# ROOF DECKS

Unilock has many options for paving products on roof decks. Various installation methods will determine the appropriate products for the application. While pedestal installation typically utilizes the square or large slabs, a granular installation will extend your product choice and design flexibility. **Ask your Unilock Representative for details.**




Product Type	Thickness	Shape	Product Weights
Arcana™ + Skyline™	50mm	606 x 606mm	24 lbs/sq.ft.
Soreno™	50mm	400 x 800mm	24 lbs/sq.ft.
Beacon Hill™ XL	60mm	900 x 540mm** 720 x 540mm**	27.5 lbs/sq.ft.




## PEDESTAL SYSTEM

Unilock offers adjustable and stackable pedestal systems for your project. Contact your Unilock Representative to learn more. Specific installation details may vary based on pedestal height, load-bearing requirements, safety standards and wind-lift.



## GRANULAR BASE SYSTEM



The cross sections shown are examples of the type of installation systems and technical features of Unilock products. Unilock shall not be deemed responsible for improper use of the product or of damage deriving from any

use different from those recommended and/or installation procedures not in line with the following instructions relevant to a raised installation. **All roof top slab/pedestal installations must be engineered by a professional engineer.**

# LEED® CREDIT OPPORTUNITIES

LEED, Leadership in Energy & Environmental Design, is a green building certification program that recognizes best-in-class building strategies and practices that have a positive impact on the health of occupants, while promoting renewable, clean energy. To receive LEED certification, building projects satisfy prerequisites and earn points to achieve different levels of certification. Unilock products can help with your certification goals.

## POTENTIAL LEED CREDITS FOR UTILIZING PERMEABLE PAVERS

### RAINWATER MANAGEMENT: LEED V4.1

Up to three points can be achieved for retaining rainwater onsite based on the percentile kept. 85% (zero lot line projects only) • 3 points, 95% – 2 points and 98% – 3 points. (all except Healthcare – subtract one point). *See LEED v4.1 for more specific project/site details.*

---

### HEAT ISLAND REDUCTION - NON-ROOF: LEED V4.1

Paving materials with a three-year aged solar reflectance (SR) value of at least 0.28. If three-year aged value information is not available, use materials with an initial SR of at least 0.33 at installation OR use an open grid pavement at least 50% pervious • 2 points (except Healthcare – 1 point). *See LEED v4.1 for more specific site calculations.*

---

### SOLAR REFLECTANCE

Solar Reflectance Index (SRI) is a criterion used by USGBC that measures values of sunlight and radiation bouncing from built surfaces. It is used to measure urban heat island effects in city centers. Dark pavement absorbs heat during the day and then releases it at night. This process creates a situation that causes urban centers to stay warmer all the time which contributes to air pollution and increased energy consumption. Careful selection of materials and colors can help reduce urban heat island effects.

*Values may change slightly by region due to variations in local aggregate and granite, please see product page for SRI values or contact your local Unilock Representative for more information.*

---

### MATERIALS AND RESOURCES: LEED V4.1

- > Building Product Disclosure and Optimization – Sourcing of Raw Materials  
– **Sourcing of Raw Materials and Extraction • 1 point**
- > Building Product Disclosure and Optimization – Material Ingredient Reporting  
– **Material Ingredient Reporting • 1 point**



# ADD 3D LANDSCAPE DESIGN TO **YOUR TOOLBOX**



## **UVISION ALLOWS YOU TO VISUALLY COMMUNICATE YOUR DESIGN IDEAS TO YOUR CLIENT IN BOTH 2D PLAN VIEW AND 3D PERSPECTIVE VIEW**

Whether you're coming from the hand-drawn world, or a 2D AutoCAD background, the biggest impact you'll see from adopting this new 3D design software is in how well the client will understand the project you are selling. **Uvision 3D Landscape Creator is an easy-to-use software tool that helps bring your designs ideas to life.**

**SCAN THE QR CODE FOR  
MORE INFORMATION OR TO  
DOWNLOAD A FREE 30-DAY TRIAL  
OF UVISION 3D LANDSCAPE CREATOR.**




# FINISHES



**Umbriano®**  
Mottled Finish with  
ColorFusion™ and EasyClean



**Series™**  
Exposed Granite Finish



**Il Campo®**  
Brushed Finish



**Smooth**  
Premier Finish




**Flagstone**  
Premier Finish



**Antiqued**  
Timeworn Finish



**Classic**  
Thrumix Finish



**Revela**  
Shot-Blast Finish

# COATINGS



Factory sealed to provide integral  
surface protection from stains

# SOFT TOUCH



Ultra-smooth surface texture

# DESCRIPTION OF EDGE DETAILS



Zero-Edge



Chamfered Edge



Rounded Bevel



Micro Bevel



# UNSIGHTLY STRUCTURES?

## U-Cara Wall Mount System has you covered.



**When unsightly buildings, exposed foundation or old steps detract from your paver plan, cover them with the U-Cara Wall Mount System.** Simply mount the galvanized steel rails to a concrete or wood substrate and clad with fascia panels for a finishing touch. Create matching vertical features with the U-Cara Modular System to complete your cohesive design. **SO INNOVATIVE. SO UNILOCK.**

// FLIP TO PAGE 85 TO LEARN MORE



# U-CARA®

**SCAN THE QR CODE TO  
CONNECT WITH A UNILOCK  
TERRITORY MANAGER FOR  
MORE INFORMATION**


# APPLICATION INDEX



PEDESTRIAN




LIGHT VEHICULAR




HEAVY-DUTY  
VEHICULAR



ROADWAYS-  
STREETS



PERMEABLE



OUTDOOR KITCHEN



FIRE FEATURE



WATER FEATURE




ROOF DECK




BORDERS &  
ACCENTS



SEAT WALLS



RETAINING WALLS  
UNDER 3'




STRUCTURAL WALL



GARDEN WALL



PILLAR



WALL COPING



POOL COPING



STEP TREADS



STEPS

## COLOR BLEND DESCRIPTIONS

COLOR NAME	DESCRIPTION
Almond Grove	Tan, Buff and Charcoal
Basalt	Blueish-Black
Black Granite	Black Granite and Charcoal
Burgundy Red	Plum with Red
Burnt Clay	Brown with Red
Corvara	Light Grey/Beige
Crystalline Basalt	Granite with Black
Dark Charcoal	Dark Charcoal
Dawn Mist	Grey and Tan
Fossil	Light & Dark Grey, Chamois and White Accents
French Grey	Light Grey with White Flake
Granite	Natural and Charcoal
Grenada White	White with Grey Speckles
Limestone	Light Gray and Charcoal
Lugano	Solid Beige/Tan
Modena	White Concrete with Black Flecks

COLOR NAME	DESCRIPTION
Natural Blend	Light Grey and Medium Grey
Midnight Sky	Charcoal and Black Flake
Notte	Mid Charcoal, White and Light Natural
Old Oak	Rust with Red
Opal Blend	Light Grey and White
Pebble Taupe	Tan with Light Brown
Sabia	Brown, Black and Light Natural
Sable Blend	Cream Tan Brown
Sierra	Charcoal, Russet and Buff
Steel Grey Blend	Dark Charcoal & Grey
Steel Blue	Pale Charcoal
Steel Mountain	Natural and Charcoal
Summer Wheat	Cream White with Pale Yellow & Beige Particles
Tuscany	Sandstone and Tan
Vivanto	Dark Grey and Charcoal
Winter Marvel	White and Black Flake

# ADA Paver Premier

**ENDURACOLOR™**



## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfer  
Surface Texture - Smooth  
Joint Spacing - 3 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

**DRIVE FRIENDLY**  
Can handle vehicular loads

## TECHNICAL INFORMATION

Conforms to ASTM C936  
Eligible for LEED v4.1 credits -  
see page 19.

	11 7/8 X 11 7/8
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	NEW YORK
Thickness (mm)	<b>70MM</b>

<b>SQFT PER</b>	Bundle	93.04
	Layer	11.63
	Section	-
	Stone	0.97

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	1.02
	Section	-
	Layer	11.81
	Bundle	94.49

<b>SAILOR LNFT PER</b>	SqFt	1.02
	Section	-
	Layer	11.81
	Bundle	94.49

<b>UNITS PER</b>	SqFt	1.03
	Section	-
	Bundle	96.00

<b>LBS PER</b>	Layer	372
	Section	-
	Bundle	2,980

<b>COLORS</b>	<b>Reflectance</b>	<b>Stock</b>
Charcoal	SR n/a SRI n/a	<b>SO</b>
Red	SR n/a SRI n/a	<b>SO</b>



CHARCOAL  
SPECIAL ORDER



RED  
SPECIAL ORDER

Single Units




**STANDARD**  
300 x 300 x 70mm  
11 7/8 x 11 7/8 x 2 3/4  
96 units/Bundle  
.97 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY.** All measurements are nominal. Contact Unilock for more information.







## LAYING PATTERNS



Arcana Random A



Arcana Random C



Arcana Random F

## APPLICATIONS



## APPEARANCE

Edge Detail - Micro  
Surface Texture - Smooth  
Joint Spacing - 0 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

## EASYSOFT™

Factory sealed to provide  
integral surface protection  
from stains

## TECHNICAL INFORMATION

Conforms to ASTM C 1782  
Eligible for LEED v4.1 credits -  
see page 19.

	12 X 24	18 X 24	24 X 24
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	50MM	50MM	50MM

SQFT PER	Bundle	36.00	54.00	72.00
	Layer	4.00	6.00	8.00
	Section	-	-	-
	Stone	2.00	3.00	4.00

PER BUNDLE	Layers	9.00	9.00	9.00
	Sections	-	-	-


SOLDIER LNFT PER	SqFt	0.49	0.50	0.50
	Section	-	-	-
	Layer	1.98	2.97	3.98
	Bundle	17.78	26.75	35.79

SAILOR LNFT PER	SqFt	0.99	0.66	0.50
	Section	-	-	-
	Layer	3.98	3.98	3.98
	Bundle	35.79	35.79	35.79

UNITS PER	SqFt	0.50	0.33	0.25
	Section	-	-	-
	Bundle	18.00	18.00	18.00

LBS PER	Layer	96	144	192
	Section	-	-	-
	Bundle	864	1,296	1,728

COLORS	Reflectance	Stock	Stock	Stock
Avorio	SR n/a SRI n/a	SO	✓	SO
Corvara	SR .30 SRI 34	SO	✓	SO
Modena	SR .46 SRI 53	SO	✓	SO
Vivanto	SR .18 SRI 16	SO	SO	SO



AVORIO **NEW**




CORVARA



MODENA



VIVANTO  
**SPECIAL ORDER**



X & T Slab Spacers  
Bagged Separately  
(see page 94)

Single Units



**12 X 24**  
301 x 606 x 50mm  
11 7/8 x 23 7/8 x 2"  
18 units/Bundle  
2 Sq.Ft./Stone  
**SPECIAL ORDER**



**18 X 24**  
453 x 606 x 50mm  
17 7/8 x 23 7/8 x 2"  
18 units/Bundle  
3 Sq.Ft./Stone




**24 X 24**  
606 x 606 x 50mm  
23 7/8 x 23 7/8 x 2"  
18 units/Bundle  
4 Sq.Ft./Stone  
**SPECIAL ORDER**

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Unilock offers adjustable and stackable pedestal systems; please contact your Territory Manager for pricing and availability. **Product is not intended for vehicular applications.** All measurements are nominal. Unilock recommends to install Arcana using T and X Slab spacers - see page 96. Please contact your sales manager for more information.



## LAYING PATTERNS



Artline Random A

## APPLICATIONS



## APPEARANCE

Edge Detail - Micro  
Surface Texture - Smooth  
Joint Spacing - 3 mm  
Void - n/a

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

SMOOTH FINISH	
Bundle Type	RANDOM
Plant Produced	NEW YORK
Thickness (mm)	70MM

SQFT PER	Bundle	93.25
	Layer	11.66
	Section	-
	Stone	0.49

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	2.06
	Section	-
	Bundle	192.00

LBS PER	Layer	388
	Section	-
	Bundle	3,100

COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	✓
Steel Mountain	SR .30 SRI 32	✓



FOSSIL



STEEL MOUNTAIN

7 Unit Random Bundle



**UNIT A**  
125 x 169 x 70mm  
4 7/8 x 6 3/4 x 2 3/4"  
32 units/Bundle  
.23 Sq.Ft./Stone



**UNIT B**  
125 x 262.5 x 70mm  
4 7/8 x 10 3/8 x 2 3/4"  
32 units/Bundle  
.35 Sq.Ft./Stone

7 Unit Random Bundle



**UNIT C**  
125 x 337.5 x 70mm  
4 7/8 x 13 3/8 x 2 3/4"  
32 units/Bundle  
.45 Sq.Ft./Stone



**UNIT D**  
125 x 450 x 70mm  
4 7/8 x 17 3/4 x 2 3/4"  
32 units/Bundle  
.61 Sq.Ft./Stone



**UNIT E**  
187.5 x 225 x 70mm  
7 1/2 x 8 7/8 x 2 3/4"  
32 units/Bundle  
.45 Sq.Ft./Stone



**UNIT F**  
187.5 x 337.5 x 70mm  
7 1/2 x 13 3/8 x 2 3/4"  
16 units/Bundle  
.58 Sq.Ft./Stone




**UNIT G**  
187.5 x 450 x 70mm  
7 1/2 x 17 3/4 x 2 3/4"  
16 units/Bundle  
.91 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Artline Random A

## APPLICATIONS



## APPEARANCE

Edge Detail - Micro  
Surface Texture - Umbriano Mottled  
Joint Spacing - 3 mm  
Void - n/a

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and  
long-lasting color

### EASYCLEAN™

Factory sealed to provide integral  
surface protection from stains

### COLORFUSION™

Subtly mottled colored finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see  
page 19.

	UMBRIANO FINISH
Bundle Type	RANDOM
Plant Produced	NEW YORK
Thickness (mm)	70MM

SQFT PER	Bundle	93.25
	Layer	11.66
	Section	-
	Stone	0.49

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	2.06
	Section	-
	Bundle	192.00

LBS PER	Layer	414
	Section	-
	Bundle	3,310

COLORS	Reflectance	Stock
French Grey	SR .35 SRI 38	✓
Winter Marvel	SR .18 SRI 17	✓



FRENCH GREY



WINTER MARVEL

7 Unit Random Bundle



### UNIT A

125 x 169 x 70mm  
4 7/8 x 6 3/4 x 2 3/4"  
32 units/Bundle  
.23 Sq.Ft./Stone



### UNIT B

125 x 262.5 x 70mm  
4 7/8 x 10 3/8 x 2 3/4"  
32 units/Bundle  
.35 Sq.Ft./Stone

7 Unit Random Bundle




### UNIT C

125 x 337.5 x 70mm  
4 7/8 x 13 3/8 x 2 3/4"  
32 units/Bundle  
.45 Sq.Ft./Stone



### UNIT D

125 x 450 x 70mm  
4 7/8 x 17 3/4 x 2 3/4"  
32 units/Bundle  
.61 Sq.Ft./Stone



### UNIT E

187.5 x 225 x 70mm  
7 1/2 x 8 7/8 x 2 3/4"  
32 units/Bundle  
.45 Sq.Ft./Stone



### UNIT F

187.5 x 337.5 x 70mm  
7 1/2 x 13 3/8 x 2 3/4"  
16 units/Bundle  
.58 Sq.Ft./Stone



### UNIT G

187.5 x 450 x 70mm  
7 1/2 x 17 3/4 x 2 3/4"  
16 units/Bundle  
.91 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.




# Beacon Hill™ Flagstone 60mm


ENDURACOLOR™




## LAYING PATTERNS



Beacon Hill Fixed Random A



Beacon Hill Fixed Random B



Beacon Hill Multi-Unit Random C

## APPLICATIONS



### APPEARANCE

Edge Detail - Rounded  
Surface Texture - Textured  
Joint Spacing - 7 mm  
Void - n/a

### TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and long-lasting color

### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

		FLAGSTONE FINISH
Bundle Type		RANDOM
Plant Produced		NEW YORK
Thickness (mm)		60MM

SQFT PER	Bundle	116.57
	Layer	11.66
	Section	-
	Stone	1.46

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.80
	Section	-
	Layer	9.35
	Bundle	93.50

UNITS PER	SqFt	0.69
	Section	-
	Bundle	80.00

LBS PER	Layer	328
	Section	-
	Bundle	3,279

COLORS	Reflectance	Stock
Almond Grove	SR .25 SRI 25	✓
Fossil	SR .22 SRI 21	✓
Steel Mountain	SR .30 SRI 32	✓
Tuscany	SR .30 SRI 32	✓



ALMOND GROVE



FOSSIL



STEEL MOUNTAIN



TUSCANY

3 Unit Random Bundle



**LARGE RECTANGLE**  
380 x 570 x 60mm  
15 x 22 ½ x 2 ¾"  
20 Units/Bundle  
2.08 SqFt./Stone



**SQUARE**  
380 x 380 x 60mm  
15 x 15 x 2 ¾"  
30 units/Bundle  
1.39 Sq.Ft./Stone



**SMALL RECTANGLE**  
380 x 190 x 60mm  
15 x 7 ½ x 2 ¾"  
30 units/Bundle  
.69 Sq.Ft./Stone


Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.

# Beacon Hill™ Flagstone 80mm


ENDURACOLOR™




## LAYING PATTERNS



BeaconHill Fixed  
Random A



BeaconHill Fixed  
Random B



BeaconHill Multi-Unit  
Random C

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Textured  
Joint Spacing - 7 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

FLAGSTONE FINISH	
Bundle Type	RANDOM
Plant Produced	NEW YORK
Thickness (mm)	80MM

SQFT PER	Bundle	73.22
	Layer	10.46
	Section	-
	Stone	1.31

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.85
	Section	-
	Layer	8.86
	Bundle	62.00

UNITS PER	SqFt	0.76
	Section	-
	Bundle	62.00

LBS PER	Layer	405
	Section	-
	Bundle	2,832

COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	SO
Steel Mountain	SR .30 SRI 32	SO



FOSSIL  
SPECIAL ORDER



STEEL MOUNTAIN  
SPECIAL ORDER

3 Unit Random Bundle



**LARGE RECTANGLE**  
360 x 540 x 80mm  
14 1/4 x 21 1/4 x 3 1/8"  
14 Units/Bundle  
2.08 SqFt/Stone



**SQUARE**  
360 x 360 x 80mm  
14 1/4 x 14 1/4 x 3 1/8"  
21 units/Bundle  
1.39 Sq.Ft./Stone




**SMALL RECTANGLE**  
360 x 180 x 80mm  
14 1/4 x 7 x 3 1/8"  
21 units/Bundle  
.69 Sq.Ft./Stone


Notes: **Special Order** - Lead time required. Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.




## LAYING PATTERNS



BeaconHill Fixed Random A



BeaconHill Fixed Random B



BeaconHill Multi-Unit Random C

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Smooth  
Joint Spacing - 7 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

		SMOOTH FINISH	
Bundle Type		RANDOM	SINGLE
Plant Produced		NEW YORK	NEW YORK
Thickness (mm)		60MM	60MM

SQFT PER	Bundle	116.57	116.57
	Layer	11.66	11.66
	Section	-	-
	Stone	1.46	5.83

PER BUNDLE	Layers	10.00	10.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	0.32
	Section	-	3.74
	Layer	-	3.74
	Bundle	-	37.40

SAILOR LNFT PER	SqFt	0.80	0.53
	Section	-	-
	Layer	9.35	6.23
	Bundle	93.50	62.30

UNITS PER	SqFt	0.69	0.17
	Section	-	-
	Bundle	80.00	20.00

LBS PER	Layer	320	320
	Section	-	-
	Bundle	3,199	3,199

COLORS	Reflectance	Stock	Stock
Almond Grove	SR .25 SRI 25	✓	✓
Fossil	SR .22 SRI 21	✓	✓
Steel Mountain	SR .30 SRI 32	✓	✓
Tuscany	SR .30 SRI 32	✓	✓
Opal	SR .24 SRI 24	SO	SO



ALMOND GROVE



FOSSIL



STEEL MOUNTAIN



TUSCANY



OPAL SPECIAL ORDER

3 Unit Random Bundle				XL Sold Separately		
	LARGE RECTANGLE	SQUARE	SMALL RECTANGLE		XL UNIT	
	380 x 570 x 60mm 15 x 22 1/2 x 2 3/8" 20 Units/Bundle 2.08 Sq.Ft./Stone	380 x 380 x 60mm 15 x 15 x 2 3/8" 30 units/Bundle 1.39 Sq.Ft./Stone	380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 30 units/Bundle .69 Sq.Ft./Stone		950 x 570 x 60mm 37 1/2 x 22 1/2 x 2 3/8" 20 units/Bundle 5.83 Sq.Ft./Stone	



Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information. Please contact Customer Service for Opal configurations.



## NEW SIZES FOR 2022



## LAYING PATTERNS

BristolValley Fixed  
Random ABristolValley Fixed  
Random B

## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Textured  
Joint Spacing - 7 mm  
Void - n/a

## TECHNOLOGIES

## ENDURACOLOR™

Refined surface and  
long-lasting color

## EASYCLEAN™

Factory sealed to provide  
integral surface protection  
from stains

## SOFT TOUCH FINISH

Ultra-smooth surface texture

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

FLAGSTONE FINISH	
Bundle Type	RANDOM
Plant Produced	UXBRIDGE
Thickness (mm)	60MM

SQFT PER	Bundle	116.57
	Layer	11.66
	Section	-
	Stone	-

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.80
	Section	-
	Layer	9.35
	Bundle	93.50

UNITS PER	SqFt	-
	Section	-
	Bundle	-

LBS PER	Layer	296
	Section	-
	Bundle	2,957

COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	✓
Steel Mountain	SR .30 SRI 32	✓



FOSSIL



STEEL MOUNTAIN

3 Unit Random Bundle



## LARGE RECTANGLE

380 x 570 x 60mm  
15 x 21 1/2 x 2 3/8"  
20 Units/Bundle  
2.08 SqFt./Stone



## SQUARE

380 x 380 x 60mm  
15 x 15 x 2 3/8"  
30 units/Bundle  
1.39 Sq.Ft./Stone




## SMALL RECTANGLE

380 x 180 x 60mm  
15 x 7 1/2 x 2 3/8"  
30 units/Bundle  
.69 Sq.Ft./Stone


Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Copthorne BW A



Copthorne RB C

## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Textured  
Joint Spacing - 3 mm  
Void - n/a

## TECHNOLOGIES

### ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

### REALA™

Cast from historic street pavers

### ULTIMA™

Up to 4x stronger than poured-in-place concrete

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

Bundle Type		SINGLE
Plant Produced		AYR
Thickness (mm)		60MM

SQFT PER	Bundle	89.20
	Layer	11.15
	Section	-
	Stone	0.15

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.43
	Section	-
	Layer	15.99
	Bundle	127.95

SAILOR LNFT PER	SqFt	4.41
	Section	-
	Layer	49.21
	Bundle	393.70

UNITS PER	SqFt	6.73
	Section	-
	Bundle	600.00

LBS PER	Layer	294
	Section	-
	Bundle	2,349

COLORS	Reflectance	Stock
Basalt	SR n/a SRI n/a	✓
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK

Single Unit




## STANDARD

65 x 200 x 60mm  
2 5/8 x 7 7/8 x 2 3/8"  
600 Units/Bundle  
.15 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices on Page 97. Contact Unilock for more information.



## LAYING PATTERNS



Courtstone Fixed  
Random A

## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Textured  
Joint Spacing - 15 mm  
Void - n/a

## TECHNOLOGIES

### ELEGANCE™

Timeless, long-lasting beauty  
with the combination of Reala  
and Ultima technologies

### REALA™

Cast from historic street pavers

### ULTIMA™

Up to 4x stronger than  
poured-in-place concrete

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

Bundle Type		RANDOM
Plant Produced		AYR
Thickness (mm)		60MM
SQFT PER	Bundle	98.30
	Layer	12.29
	Section	-
	Stone	-
PER BUNDLE	Layers	8.00
	Sections	-
SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	2.25
	Section	-
	Layer	27.69
	Bundle	221.52
UNITS PER	SqFt	3.91
	Section	-
	Bundle	384.00
LBS PER	Layer	291
	Section	-
	Bundle	2,326
COLORS	Reflectance	Stock
Basalt	SR n/a SRI n/a	✓



BASALT

5 Unit Random Bundle		<b>XL RECTANGLE</b> 215 x 130 x 60mm 8 3/8 x 5 1/8 x 2 3/8" 128 Units/Bundle .30 SqFt/Stone
		<b>LARGE RECTANGLE</b> 185 x 130 x 60mm 7 1/4 x 5 1/8 x 2 3/8" 64 Units/Bundle .28 SqFt/Stone
		<b>RECTANGLE</b> 165 x 130 x 60mm 6 1/2 x 5 1/8 x 2 3/8" 64 Units/Bundle .23 SqFt/Stone
		<b>SMALL RECTANGLE</b> 145 x 130 x 60mm 5 3/4 x 5 1/8 x 2 3/8" 64 Units/Bundle .20 SqFt/Stone
		<b>SQUARE</b> 130 x 130 x 60mm 5 1/8 x 5 1/8 x 2 3/8" 64 Units/Bundle .18 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Please refer to the Polymeric Sand Best Practices on Page 97. Contact Unilock for more information.





### APPLICATIONS



### APPEARANCE

Edge Detail - Zero  
Surface Texture - Smooth  
Joint Spacing - n/a  
Void - n/a

### TECHNOLOGIES

#### PERMEABLE

Can be installed to allow water to flow through

#### CLASSIC

Budget-friendly traditional product mix

### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

	CLASSIC FINISH
Bundle Type	SINGLE
Plant Produced	GORMLEY
Thickness (mm)	100MM

SQFT PER	Bundle	78.40
	Layer	11.20
	Section	-
	Stone	2.80

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	0.36
	Section	-
	Bundle	28.00

LBS PER	Layer	320
	Section	-
	Bundle	2,240

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	SO



Dura-Mat is typically used in applications to reduce and control erosion. Commonly used at the base of, or entrances to, retention pools.

NATURAL

Single Units



**STANDARD**  
500 x 500 x 100mm  
19 ¾ x 19 ¾ x 3 ⅞"  
28 units/Bundle  
2.80 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



### LAYING PATTERNS



Ecoline Fixed  
Random A

### APPLICATIONS



### APPEARANCE

Edge Detail - Micro  
Surface Texture - Smooth/  
Exposed/ Brushed/  
Umbriano Mottled  
Joint Spacing - 6.25 mm  
Void - 5.80%

### TECHNOLOGIES

#### PERMEABLE

Can be installed to allow water  
to flow through

#### ENDURACOLOR™

Refined surface and  
long-lasting color

#### EASYSOAK™ (Umbriano)

Factory sealed to provide integral  
surface protection from stains

#### COLOR FUSION™ (Umbriano)

Subtly mottled color finish

### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits  
- see page 19.


		MULTIPLE FINISHES
Bundle Type		RANDOM
Plant Produced		NEW YORK
Thickness (mm)		100MM
SQFT PER	Bundle	66.20
	Layer	11.03
	Section	-
	Stone	0.34
PER BUNDLE	Layers	6.00
	Sections	-
SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
UNITS PER	SqFt	2.90
	Section	-
	Bundle	192.00
LBS PER	Layer	504
	Section	-
	Bundle	3,027
COLORS	Reflectance	Stock
All Colors & Finishes	SR n/a SRI n/a	SO

8 Unit Random Bundle	UNIT A	UNIT B	UNIT C	UNIT D	UNIT E	UNIT F	UNIT G	UNIT H
	357 x 84 x 100mm	317 x 84 x 100mm	277 x 84 x 100mm	237 x 84 x 100mm	357 x 114 x 100mm	317 x 114 x 100mm	277 x 84 x 100mm	237 x 114 x 100mm
	14 x 3 5/16 x 3 7/8"	12 1/2 x 3 5/16 x 3 7/8"	12 x 3 5/16 x 3 7/8"	9 3/8 x 3 5/16 x 3 7/8"	14 x 4 1/2 x 3 7/8"	12 1/2 x 4 1/2 x 3 7/8"	11 x 4 1/2 x 3 7/8"	9 3/8 x 4 1/2 x 3 7/8"
	20 Units/Bundle	20 Units/Bundle	20 Units/Bundle	20 Units/Bundle	20 Units/Bundle	20 Units/Bundle	20 Units/Bundle	20 Units/Bundle
	.32 SqFt/Stone	.29 SqFt/Stone	.25 SqFt/Stone	.21 SqFt/Stone	.44 SqFt/Stone	.39 SqFt/Stone	.34 SqFt/Stone	.29 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



### LAYING PATTERNS



EcoOptiloc Cluster C

### APPLICATIONS



### APPEARANCE

Edge Detail - Chamfer  
Surface Texture - Smooth  
Joint Spacing - 12mm  
Void - 7.3%

### TECHNOLOGIES

#### PERMEABLE

Can be installed to allow water to flow through

#### CLASSIC

Budget-friendly traditional product mix

### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.



NATURAL

Other finishes available by Special Order. Please contact your Territory Manager for more details.

CLASSIC FINISH	
Bundle Type	<b>SINGLE</b>
Plant Produced	UXBRIDGE
Thickness (mm)	<b>80MM</b>

SQFT PER	Bundle	63.56
	Layer	9.08
	Section	-
	Stone	0.50

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	1.98
	Section	-
	Bundle	126.00

LBS PER	Layer	292
	Section	-
	Bundle	2,047

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	<b>SO</b>

Single Unit



#### STANDARD


250 x 250 x 80mm  
9 7/8 x 9 7/8 x 3 1/8"  
126 Units/Bundle  
.50 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.






### LAYING PATTERNS



EcoPriora 5x10  
RB\_A



EcoPriora 5x10  
HB\_E

### APPLICATIONS



### APPEARANCE

Edge Detail - Micro  
Surface Texture - Smooth / Umb. Mottled  
Joint Spacing - 7mm  
Void - 6.8%

### TECHNOLOGIES

#### PERMEABLE

Can be installed to allow water to flow through

#### ENDURACOLOR™

Refined surface and long-lasting color

#### CLASSIC

Budget-friendly traditional product mix

#### EASYCLEAN™ (Umbriano)

Factory sealed to provide integral surface protection from stains

#### COLOR FUSION™ (Umbriano)

Subtly mottled color finish

### TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits - see page 19.



GRANITE



MIDNIGHT SKY

SPECIAL ORDER

	5X10" SMOOTH	5X10" UMBRIANO
Bundle Type	SINGLE	SINGLE
Plant Produced	UXBRIDGE	NEW YORK
Thickness (mm)	80MM	80MM

SQFT PER	Bundle	75.95	75.95
	Layer	10.85	10.85
	Section	-	-
	Stone	0.31	0.31

PER BUNDLE	Layers	7.00	7.00
	Sections	5.00	7.00

SOLDIER LNFT PER	SqFt	1.27	1.27
	Section	-	-
	Layer	13.78	13.78
	Bundle	96.46	96.46

SAILOR LNFT PER	SqFt	2.54	2.54
	Section	-	-
	Layer	27.56	27.56
	Bundle	192.91	192.91

UNITS PER	SqFt	3.23	3.23
	Section	-	-
	Bundle	245.00	245.00

LBS PER	Layer	381	388
	Section	-	-
	Bundle	2,669	2,717

COLORS	Reflectance		
Granite (Classic)	SR .26 SRI 27	✓	
Midnight Sky (Umbriano)	SR .17 SRI 15		SO

Single Units



#### RECTANGLE

120 x 240 x 80mm  
4 ¾ x 9 ½ x 3 ⅛  
245 units/Bundle  
.31 Sq.Ft./Stone




#### RECTANGLE

120 x 240 x 80mm  
4 ¾ x 9 ½ x 3 ⅛  
245 units/Bundle  
.31 Sq.Ft./Stone  
SPECIAL ORDER


Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.




## LAYING PATTERNS



EcoPromenade 3x12  
RB\_A



EcoPromenade 3x12  
HB\_C



EcoPromenade 3x12  
DHB\_B

## APPLICATIONS



## APPEARANCE

Edge Detail - Micro  
Surface Texture - Smooth & Series  
Exposed  
Joint Spacing - 7 mm  
Void - 10.12 %

## TECHNOLOGIES

### PERMEABLE

Can be installed to allow water to flow through

### ENDURACOLOR™

Refined surface and long-lasting color

### EASYCLEAN™ (Umbriano)

Factory sealed to provide integral surface protection from stains

### COLOR FUSION™ (Umbriano)

Subtly mottled color finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

	3x12"	4x16"
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	NEW YORK	NEW YORK
Thickness (mm)	<b>100MM</b>	<b>100MM</b>

<b>SQFT PER</b>	Bundle	63.94	62.00
	Layer	10.66	10.33
	Section	-	-
	Stone	0.24	0.43

<b>PER BUNDLE</b>	Layers	6.00	6.00
	Sections	-	-

<b>SOLDIER LNFT PER</b>	SqFt	1.02	0.76
	Section	-	-
	Layer	10.83	7.87
	Bundle	64.96	47.24



<b>SAILOR LNFT PER</b>	SqFt	4.06	3.05
	Section	-	-
	Layer	43.31	31.50
	Bundle	259.84	188.98

<b>UNITS PER</b>	SqFt	4.13	2.32
	Section	-	-
	Bundle	264.00	144.00

<b>LBS PER</b>	Layer	488	455
	Section	-	-
	Bundle	2,927	2,730

COLORS	Reflectance	Stock	Stock
All Colors & Finsihes	SR n/a SRI n/a	<b>SO</b>	<b>SO</b>

Different finishes available by Special Order. Please contact your Territory Manager for more details.

Single Unit		<b>3x12"</b> 75 x 300 x 100mm 3 x 11 7/8 x 3 3/8" 220 units/Bundle .24 Sq.Ft./Stone
		<b>4x16"</b> 100 x 400 x 100mm 3 7/8 x 15 3/4 x 3 3/8" 120 units/Bundle .43 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



#### APPLICATIONS



#### APPEARANCE

Edge Detail - Chamfer  
Surface Texture - Smooth  
Joint Spacing - 6mm  
Void - 10.18%

#### TECHNOLOGIES

##### PERMEABLE

Can be installed to allow water to flow through

#### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

CLASSIC FINISH	
Bundle Type	SINGLE
Plant Produced	NEW YORK
Thickness (mm)	80MM

SQFT PER	Bundle	67.00
	Layer	9.57
	Section	-
	Stone	0.27

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	3.66
	Section	-
	Bundle	245.00

LBS PER	Layer	349
	Section	-
	Bundle	2,445

COLORS	Reflectance	Stock
Natural	SR n/a SRI n/a	SO



Different finishes available by Special Order. Please contact your Territory Manager for more details.

NATURAL

Single Unit




**STANDARD**  
115 x 230 x 80mm  
4 5/8 x 9 x 3 1/8"  
245 Units/Bundle  
.27 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.







## LAYING PATTERNS



Granito Hex\_A



Granito Fixed Random A



Granito Fixed Random B

## APPLICATIONS



### APPEARANCE

Edge Detail - Rounded  
Surface Texture - Granito/  
Granito Textured (Random)  
Joint Spacing - 7 mm  
Void - n/a

### TECHNOLOGIES

**ENDURACOLOR™ (RANDOM)**  
Refined surface and  
long-lasting color

**ARTISTA™ (RANDOM)**  
Boldly mottled color finish

### EASYSOFT™

Factory sealed to provide integral  
surface protection from stains

### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits  
see page 19

	8"X8" HEX	
<b>Bundle Type</b>	<b>SINGLE</b>	<b>RANDOM</b>
Plant Produced	ONTARIO	ONTARIO
Thickness (mm)	<b>70MM</b>	<b>60MM</b>

<b>SQFT PER</b>	Bundle	73.92	94.14
	Layer	9.24	10.46
	Section	-	-
	Stone	0.39	1.31

<b>PER BUNDLE</b>	Layers	8.00	9.00
	Sections	-	-

<b>SOLDIER LNFT PER</b>	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-

<b>SAILOR LNFT PER</b>	SqFt	-	0.85
	Section	-	-
	Layer	-	8.86
	Bundle	-	79.72

<b>UNITS PER</b>	SqFt	2.60	0.76
	Section	-	-
	Bundle	192.00	72.00

<b>LBS PER</b>	Layer	306	287
	Section	-	-
	Bundle	2,450	2,583

COLORS	Reflectance	Stock	Stock
Notte Hex	SR n/a SRI n/a	<b>SO</b>	
Sabia Hex	SR n/a SRI n/a	<b>SO</b>	
Notte Random	SR n/a SRI n/a		<b>SO</b>
Sabia Random	SR n/a SRI n/a		<b>SO</b>



NOTTE HEX  
SPECIAL ORDER



NOTTE RANDOM  
SPECIAL ORDER



SABIA HEX  
SPECIAL ORDER




SABIA RANDOM  
SPECIAL ORDER

<b>3-Unit Random Bundle</b>		<b>SMALL RECTANGLE</b> 180 x 360 x 60mm 7 x 14 1/4 x 2 3/8" 27 units/Bundle .79 Sq.Ft./Stone		<b>SQUARE</b> 360 x 360 x 60mm 14 1/4 x 14 1/4 x 2 3/8" 27 units/Bundle 1.40 Sq.Ft./Stone		<b>LARGE RECTANGLE</b> 360 x 540 x 60mm 14 1/4 x 21 1/4 x 2 3/8" 18 units/Bundle 2.09 Sq.Ft./Stone	<b>Single Unit</b>		<b>HEX</b> 200 x 200 x 70mm 7 7/8 x 7 7/8 x 3 1/8" 192 units/Bundle .39 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Hex Paver A

## TECHNOLOGIES

### PERMEABLE

Can be installed to allow water to flow through

### ENDURACOLOR™

Refined surface and long-lasting color

### COLOR FUSION™ (UMBRIANO)

Subtly mottled color finish

### EASYSOAK™ (UMBRIANO)

Factory sealed to provide integral surface protection from stains

## APPLICATIONS



## APPEARANCE

Edge Detail - Micro  
Surface Texture -  
Smooth/Exposed  
Joint Spacing - 3 mm  
Void - n/a

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits  
see page 19

		HEX	HEX PERMEABLE
Bundle Type		SINGLE	SINGLE
Plant Produced		NEW YORK	NEW YORK
Thickness (mm)		70MM	80MM
SQFT PER	Bundle	73.92	59.24
	Layer	9.24	8.46
	Section	-	-
	Stone	0.39	0.42
PER BUNDLE	Layers	8.00	7.00
	Sections	-	-
SOLDIER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-
SAILOR LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-
UNITS PER	SqFt	2.60	2.36
	Section	-	-
	Bundle	192.00	140.00
LBS PER	Layer	306	310
	Section	-	-
	Bundle	2,450	2,167
COLORS	Reflectance	Stock	Stock
Multiple Colors & Finishes	SR .n/a SRI n/a	SO	SO

Single Unit



### HEX

200 x 200 x 70mm  
7 7/8 x 7 7/8 x 2 3/4"  
192 Units/Bundle  
.39 SqFt/Stone



### HEX PERMEABLE

200 x 200 x 80mm  
7 7/8 x 7 7/8 x 3 1/8"  
140 Units/Bundle  
.42 SqFt/Stone


Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.

HEX\_NY


SPECIAL ORDER PRODUCT - NON -STOCK




## LAYING PATTERNS



HollandPremier 4x8  
RB\_B



HollandPremier 4x8  
HB\_C



HollandPremier 4x8  
BW\_D

## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfer  
Surface Texture - Smooth  
Joint Spacing - 3 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

SMOOTH FINISH	
Bundle Type	SINGLE
Plant Produced	NEW YORK
Thickness (mm)	60MM

SQFT PER	Bundle	118.00
	Layer	11.80
	Section	-
	Stone	0.22

PER BUNDLE	Layers	10.00
	Sections	-


SOLDIER LNFT PER	SqFt	1.50
	Section	-
	Layer	17.72
	Bundle	177.17

SAILOR LNFT PER	SqFt	3.00
	Section	-
	Layer	35.43
	Bundle	354.33

UNITS PER	SqFt	4.58
	Section	-
	Bundle	540.00

LBS PER	Layer	327
	Section	-
	Bundle	3,270

COLORS	Reflectance	Stock
Charcoal	SR n/a SRI n/a	✓



CHARCOAL

Single Unit




## STANDARD

100 x 200 x 60mm  
3 7/8 x 7 7/8 x 2 3/8"  
540 units/Bundle  
.22 Sq.Ft./Stone


Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.




## LAYING PATTERNS



Il Campo 4x8 RB\_F



Il Campo 4x8 SB\_G



Il Campo 8x16 HB\_E

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Il Campo  
Brushed  
Joint Spacing - 3 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

		4x8"	8x16"
<b>Bundle Type</b>		<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced		ONTARIO	ONTARIO
Thickness (mm)		<b>70MM</b>	<b>70MM</b>
<b>SQFT PER</b>	Bundle	94.40	82.67
	Layer	11.80	10.33
	Section	-	-
	Stone	0.22	0.86
<b>PER BUNDLE</b>	Layers	8.00	8.00
	Sections	-	-
<b>SOLDIER LNFT PER</b>	SqFt	1.50	0.76
	Section	-	-
	Layer	17.72	7.87
	Bundle	141.73	62.99
<b>SAILOR LNFT PER</b>	SqFt	3.00	1.52
	Section	-	-
	Layer	35.43	15.75
	Bundle	283.46	125.98
<b>UNITS PER</b>	SqFt	4.58	1.16
	Section	-	-
	Bundle	432.00	96.00
<b>LBS PER</b>	Layer	377	343
	Section	-	-
	Bundle	3,019	2,747

COLORS	Reflectance	Stock	
Dark Charcoal	SR n/a SRI n/a	<b>SO</b>	<b>SO</b>
Granite	SR n/a SRI n/a		<b>SO</b>
Light Grey	SR .22 SRI 22		<b>SO</b>



**DARK CHARCOAL**  
**SPECIAL ORDER**



**GRANITE**  
8x16 only  
**SPECIAL ORDER**



**LIGHT GREY**  
8x16 only  
**SPECIAL ORDER**

Single Unit



**4x8**  
100 x 200 x 70mm  
3 7/8 x 7 7/8 x 2 3/4"  
432 Units/Bundle  
.22 SqFt/Stone




**8x16**  
200 x 400 x 70mm  
7 7/8 x 15 3/4 x 2 3/4"  
96 Units/Bundle  
.86 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.







## LAYING PATTERNS



Mattoni RB\_A



Mattoni HB\_C



Mattoni DHB\_D

## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Smooth  
Joint Spacing - 4 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

**EASYSOAK™**  
Factory sealed to provide  
integral surface protection  
from stains

**ANTIQUED™**  
Distressed, timeworn finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

		STANDARD SMOOTH
Bundle Type		SINGLE
Plant Produced		PICKERING
Thickness (mm)		70MM

SQFT PER	Bundle	89.28
	Layer	11.16
	Section	-
	Stone	0.16

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.27
	Section	-
	Layer	14.17
	Bundle	113.39

SAILOR LNFT PER	SqFt	5.08
	Section	-
	Layer	56.69
	Bundle	453.54

UNITS PER	SqFt	6.45
	Section	-
	Bundle	576.00

LBS PER	Layer	357
	Section	-
	Bundle	2,859

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	✓
Granite Fusion	SR n/a SRI n/a	✓
Sable	SR n/a SRI n/a	✓



DARK CHARCOAL



GRANITE BLEND



SABLE BLEND

Single Unit




**STANDARD**  
60 x 240 x 70mm  
2 3/8 x 9 1/2 x 2 3/4"  
576 Units/Bundle  
.16 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.


# Natural Stone - Sandstone Slabs




## LAYING PATTERNS



NaturalStone  
12x24 RB A



NaturalStone  
24x24 RB B



NaturalStone  
Multi-Unit C

## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Brushed /  
Riven  
Joint Spacing - 0 mm  
Void - n/a

## TECHNICAL INFORMATION

More information is available  
online.

BRUSHED FINISH	12" X 24"	18" X 24"	24" X 24"	24" X 36"
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	22MM	22MM	22MM	22MM

SQFT PER	Crate	180.00	186.00	160.00	180.00
	Units	2.00	3.00	4.00	6.00

UNITS PER	Crate	90.00	62.00	40.00	30.00
	SqFt	0.50	0.33	0.25	0.17

LBS PER	Unit	24	36	48	72
	Bundle	2,149	2,221	1,910	2,149

COLORS	Reflectance	Stock	Stock	Stock	Stock
Autumn Harvest (Riven)	SR n/a SRI n/a	✓	✓	✓	✓
Golden Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓	✓
Ivory Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓	✓
Stone Cliff Grey (Riven)	SR n/a SRI n/a	✓	✓	✓	✓



AUTUMN HARVEST



GOLDEN SAND **NEW**



IVORY SAND **NEW**



STONE CLIFF GREY

Single Units



**12 X 24"**  
300 x 600 x 22mm  
11 7/8 x 23 5/8 x 7/8"  
2.0 Sq.Ft./Stone



**18 X 24"**  
450 x 600 x 22mm  
17 3/4 x 23 5/8 x 7/8"  
3.0 Sq.Ft./Stone



**24 X 24"**  
600 x 600 x 22mm  
23 5/8 x 23 5/8 x 7/8"  
4.0 Sq.Ft./Stone



**24 X 36"**  
600 x 900 x 22mm  
23 5/8 x 35 1/2 x 7/8"  
6.0 Sq.Ft./Stone

Notes: This product is not intended for vehicular applications. All measurements are nominal. Contact Unilock for more information.

# Natural Stone - Sandstone Coping



## APPLICATIONS



AUTUMN HARVEST



GOLDEN SAND **NEW**



IVORY SAND **NEW**



STONE CLIFF GREY

	48 X 12" FULLNOSE COPING	48 X 12" ROCK FACED COPING	48 X 16" ROCK FACED COPING	72 X 12" FULLNOSE COPING	72 X 12" ROCK FACED COPING	72 X 16" ROCK FACED COPING
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
<b>Thickness (mm)</b>	<b>50MM</b>	<b>50MM</b>	<b>50MM</b>	<b>50MM</b>	<b>50MM</b>	<b>50MM</b>

<b>UNITS PER</b>	Crate	20.00	20.00	20.00	12.00	12.00	10.00
	SqFt	-	-	-	-	-	-

<b>LBS PER</b>	Unit	106	101	113	159	159	209
	Bundle	2,116	2,028	2,258	1,905	1,905	2,094

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock
Autumn Harvest	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓
Golden Sand	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓
Ivory Coast	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓
Stone Cliff Grey	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓

Coping		<b>4' FULLNOSE COPING</b> 1,200 x 50 x 300mm 47 1/4 x 2 x 11 7/8"		<b>6' FULLNOSE COPING</b> 1,800 x 50 x 300mm 70 7/8 x 2 x 11 7/8"
		<b>4' ROCK FACE COPING</b> 1,200 x 50 x 300mm 47 1/4 x 2 x 11 7/8"		<b>6' ROCKFACE COPING</b> 1,800 x 50 x 300mm 70 7/8 x 2 x 11 7/8"
		<b>4' ROCK FACE COPING</b> 1,200 x 50 x 400mm 47 1/4 x 2 x 15 3/4"		<b>6' ROCKFACE COPING</b> 1,800 x 50 x 400mm 70 7/8 x 2 x 15 3/4"

# Natural Stone - Sandstone Steps & Pillar Caps



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero

Surface Texture - Brushed / Riven

Joint Spacing - 0 mm

Void - n/a

## TECHNICAL INFORMATION

More information is available online.

	24 X 24" ROCK FACED PILLAR CAP	29 X 29" ROCK FACED PILLAR CAP	48 X 16" ROCK FACED STEP	72 X 16" ROCK FACED STEP
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE
<b>Thickness (mm)</b>	64MM	64MM	150MM	150MM

<b>FCFT PER</b>	Crate	-	-	32.00	32.00
-----------------	-------	---	---	-------	-------

<b>LNFT PER</b>	Crate	-	-	24.00	24.00
	Unit	-	-	4.00	6.00

<b>UNITS PER</b>	Crate	14.00	12.00	6.00	4.00
------------------	-------	-------	-------	------	------

<b>LBS PER</b>	Unit	137	209	421	628
	Bundle	1,914	2,513	2,526	2,513

COLORS	Reflectance	Stock	Stock	Stock	Stock
Autumn Harvest	SR n/a SRI n/a	✓	✓	✓	✓
Golden Sand	SR n/a SRI n/a	✓	✓	✓	✓
Ivory Coast	SR n/a SRI n/a	✓	✓	✓	✓
Stone Cliff Grey	SR n/a SRI n/a	✓	✓	✓	✓



AUTUMN HARVEST



GOLDEN SAND **NEW**



IVORY COAST **NEW**



STONE CLIFF GREY

Steps



**48 X 16" STEP**  
1,200 x 150 x 400mm  
47 1/4 x 5 7/8 x 15 3/4"



**72 X 16" STEP**  
1,830 x 150 x 400mm  
72 x 5 7/8 x 15 3/4"

Pillar Caps



**PILLAR CAP**  
600 x 600 x 64mm  
23 5/8 x 23 5/8 x 2 5/8"



**PILLAR CAP**  
725 x 725 x 64mm  
28 5/8 x 28 5/8 x 2 5/8"


Notes: This product is not intended for vehicular applications. All measurements are nominal. Contact Unilock for more information.




# Natural Stone - Limestone Slabs




## LAYING PATTERNS



NaturalStone  
12x24 RB A



NaturalStone  
24x24 RB B



NaturalStone  
Multi-Unit C

## APPLICATIONS



### APPEARANCE

Edge Detail - Zero  
Surface Texture - Riven  
Joint Spacing - 0 mm  
Void - 0 %

### TECHNICAL INFORMATION

More information is available  
online.

	12" X 24"	18" X 24"	24" X 24"	24" X 36"
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE
<b>Thickness (mm)</b>	22MM	22MM	22MM	22MM

<b>SQFT PER</b>	Crate	180.00	186.00	160.00	180.00
	Units	2.00	3.00	4.00	6.00

<b>UNITS PER</b>	Crate	90.00	62.00	40.00	30.00
	SqFt	0.50	0.33	0.25	0.17

<b>LBS PER</b>	Unit	24	36	48	72
	Bundle	2,149	2,221	1,910	2,149

COLORS	Reflectance	Stock	Stock	Stock	Stock
Black River	SR n/a SRI n/a	✓	✓	✓	✓
Hearthstone	SR n/a SRI n/a	✓	✓	✓	✓
Winter Mist	SR n/a SRI n/a	✓	✓	✓	✓



BLACK RIVER



HEARTHSTONE



WINTER MIST

Single Units	12 X 24"	18 X 24"	24 X 24"	24 X 36"
	300 x 600 x 22mm 11 7/8 x 23 5/8 x 7/8" 2.0 Sq.Ft./Stone	450 x 600 x 22mm 17 3/4 x 23 5/8 x 7/8" 3.0 Sq.Ft./Stone	600 x 600 x 22mm 23 5/8 x 23 5/8 x 7/8" 4.0 Sq.Ft./Stone	600 x 900 x 22mm 23 5/8 x 35 1/2 x 7/8" 6.0 Sq.Ft./Stone

Notes: Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. All measurement are nominal. Product is not intended for vehicular applications.

# Natural Stone - Limestone Steps, Coping and Pillar Caps



## APPLICATIONS



BLACK RIVER



HEARTHSTONE  
Pillar Cap Only



WINTER MIST  
Pillar Cap Only

	48 X 12" ROCKFACED COPING	48 X 16" ROCK FACED COPING	72 X 12" ROCK FACED COPING	72 X 16" ROCK FACED COPING	48-X 12" FULLNOSE COPING	72 X 12" FULLNOSE COPING
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	50MM	50MM	50MM	50MM	50MM	50MM

<b>UNITS PER</b>	Crate	20.00	16.00	12.00	10.00	20.00	12.00
	SqFt	-	-	-	-	-	-

<b>LBS PER</b>	Unit	106	141	159	209	159	159
	Bundle	2,116	2,258	1,905	2,094	3,175	1,905

<b>COLORS</b>	<b>Reflectance</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>
Black River	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓

	24 X 24" ROCK FACED PILLAR CAP	28 X 28" ROCK FACED PILLAR CAP	48 X 16" ROCK FACED STEP	72 X 16" ROCK FACED STEP
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	64MM	64MM	150MM	150MM

<b>FCFT PER</b>	Crate	-	-	-	-
-----------------	-------	---	---	---	---

<b>LNFT PER</b>	Crate	-	-	24.00	24.00
	Unit	-	-	4.00	6.00

<b>UNITS PER</b>	Crate	14.00	12.00	6.00	4.00
------------------	-------	-------	-------	------	------

<b>LBS PER</b>	Unit	137	186	421	628
	Bundle	1,914	2,606	2,526	2,513


<b>COLORS</b>	<b>Reflectance</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>
Black River	SR n/a SRI n/a	✓	✓	✓	✓
Hearthstone	SR n/a SRI n/a	✓	✓		
Winter Mist	SR n/a SRI n/a	✓	✓		

48" & 72" Steps		<b>48 X 16" STEP</b> 1,200 x 150 x 400mm 47 1/4 x 5 7/8 x 15 3/4"		<b>72 X 16" STEP</b> 1,800 x 150 x 400mm 70 7/8 x 5 7/8 x 15 3/4"
		<b>24" PILLAR CAP</b> 600 x 600 x 64mm 23 5/8 x 23 5/8 x 2 5/8"		<b>28" PILLAR CAP</b> 710 x 710 x 64mm 28 x 28 x 2 5/8"
Coping		<b>48 X 12" ROCK FACE</b> 1,200 x 300 x 50mm 47 1/4 x 11 7/8 x 2"		<b>72 X 12" ROCK FACE</b> 1,800 x 300 x 50mm 70 7/8 x 11 7/8 x 2"
		<b>48 X 16" ROCK FACE</b> 400 x 1,200 x 50mm 47 1/4 x 15 3/4 x 2"		<b>72 X 16" ROCK FACE</b> 1,800 x 400 x 50mm 47 1/4 x 15 3/4 x 2"
		<b>48 X 12" FULLNOSE</b> 300 x 1,200 x 50mm 11 7/8 x 47 1/4 x 2"		<b>72 X 12" FULLNOSE</b> 1,800 x 300 x 50mm 70 7/8 x 11 7/8 x 2"


Notes: Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealers for natural stone. All measurements are nominal. Product is not intended for vehicular applications.



## LAYING PATTERNS



Optiloc A



Optiloc B

## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfer  
Surface Texture - Smooth  
Joint Spacing - 8 mm  
Void - n/a

## TECHNOLOGIES

## CLASSIC

Budget-friendly  
traditional product mix

## ENDURACOLOR™

Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

	SMOOTH CLASSIC / ENDURACOLOR
Bundle Type	SINGLE
Plant Produced	UXB/NY
Thickness (mm)	80MM

SQFT PER	Bundle	67.66
	Layer	9.67
	Section	-
	Stone	0.54

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.59
	Section	-
	Layer	15.35
	Bundle	107.48

SAILOR LNFT PER	SqFt	1.59
	Section	-
	Layer	15.35
	Bundle	107.48

UNITS PER	SqFt	1.86
	Section	-
	Bundle	126.00

LBS PER	Layer	359
	Section	-
	Bundle	2,516

COLORS	Reflectance	Stock
Natural	SR n/a SRI n/a	SO
Granite	SR n/a SRI n/a	SO

Single Unit



## STANDARD

100 x 200 x 80mm  
3 7/8 x 7 7/8 x 3 1/8"  
378 units/Bundle  
.22 Sq.Ft./Stone



GRANITE




NATURAL

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.

# Porcelain



## LAYING PATTERNS



Porcelain 24x24  
RB\_A



Porcelain 16x32  
HB\_D

## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Stone Finish  
Joint Spacing - n/a  
Void - n/a

## TECHNICAL INFORMATION

More information is available online.

		DEL CONCA 24x24" PRESSED EDGE	DEL CONCA 16x32" PRESSED EDGE	DEL CONCA COPING POOL PRESSED EDGE
Bundle Type		SINGLE	SINGLE	SINGLE
Plant Produced				
Thickness (mm)		20MM	20MM	30MM
SQFT PER	Pallet	255.75	268.71	-
	Box	7.75	6.89	-
	Unit	3.88	3.45	-
PER PALLET	Box	33.00	39.00	38.00
	SqFt	255.75	268.71	-
	Unit	66.00	78.00	38.00
UNITS PER	Pallet	66.00	78.00	38.00
	Box	2.00	2.00	1.00
LBS PER	Unit	35	32	30
	SqFt	9	9	-
	Box	70	64	30
	Pallet	2,318	2,511	1,127

COLORS	Reflectance	Stock	Stock	Stock
Arbor Bianco	SR n/a SRI n/a		✓	
Arbor Gray	SR n/a SRI n/a		✓	
Arbor Natural	SR n/a SRI n/a		✓	
Gotham Beige	SR n/a SRI n/a	✓		
Gotham Bianco	SR n/a SRI n/a	✓		
Gotham Grey	SR n/a SRI n/a	✓		
Gotham Nero	SR n/a SRI n/a	✓		
Travstone Beige	SR n/a SRI n/a	✓		
Travstone Gray	SR n/a SRI n/a			SO
Travstone Noce	SR n/a SRI n/a	✓		



ARBOR BIANCO



ARBOR GRAY



ARBOR NATURAL



GOTHAM BEIGE



GOTHAM BIANCO



GOTHAM GRAY



GOTHAM NERO



TRAVSTONE BEIGE



TRAVSTONE GRAY  
(Coping Only)



TRAVSTONE NOCE

Single Units	DEL CONCA 24x24 600 x 600 x 20mm 23 5/8 x 23 5/8 x 7/8" 3.88 Sq.Ft./Stone	DEL CONCA 16x32 400 x 800 x 20mm 15 3/4 x 31 1/2 x 7/8" 3.45 Sq.Ft./Stone	DEL CONCA COPING 330 x 600 x 30mm 13 x 23 5/8 x 1 1/4"
--------------	--	--	--

Notes: All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. Product is not intended for vehicular applications.




# Promenade™ Plank Paver 100mm 3x12" & 4x12"


**ENDURACOLOR™**




## LAYING PATTERNS



Promenade Multi-Unit Random G



Promenade 4x12 HB\_I



Promenade 4x12 RB\_H

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Smooth & Series™ Exposed  
Joint Spacing - 4 mm  
Void - n/a

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and long-lasting color

### EASYSKLEAN™ (Umbriano)

Factory sealed to provide integral surface protection from stains

### COLOR FUSION™ (Umbriano)

Subtly mottled color finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

	3 X 12	4 X 12
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	NEW YORK	NEW YORK
Thickness (mm)	<b>100MM</b>	<b>100MM</b>

<b>SQFT PER</b>	Bundle	63.94	69.76
	Layer	10.66	11.63
	Section	-	-
	Stone	0.24	0.32

<b>PER BUNDLE</b>	Layers	6.00	6.00
	Sections	-	-

<b>SOLDIER LNFT PER</b>	SqFt	1.35	1.02
	Section	-	-
	Layer	14.44	11.81
	Bundle	86.61	70.87

<b>SAILOR LNFT PER</b>	SqFt	4.06	3.05
	Section	-	-
	Layer	43.31	35.43
	Bundle	259.84	212.60

<b>UNITS PER</b>	SqFt	4.13	3.10
	Section	-	-
	Bundle	264.00	216.00

<b>LBS PER</b>	Layer	483	532
	Section	-	-
	Bundle	2,898	3,191

<b>COLORS</b>	<b>Reflectance</b>	<b>Stock</b>	<b>Stock</b>
All Colors & Finishes	SR n/a SRI n/a	<b>SO</b>	<b>SO</b>

Different finishes available by Special Order. Please contact your Territory Manager for more details.

Single Units		
	<b>3" X 12"</b> 100 x 300 x 100mm 3 7/8 x 11 1/8 x 3 7/8" 264 units/Bundle .24 Sq.Ft./Stone	<b>4" X 12"</b> 100 x 300 x 100mm 3 7/8 x 11 1/8 x 3 7/8" 216 units/Bundle .32 Sq.Ft./Stone


Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.

# Promenade™ Plank Paver 100mm 4x16" & 8x24"


**ENDURACOLOR™**




## LAYING PATTERNS



Promenade Multi-Unit  
Random G



Promenade 4x16  
HB\_C



Promenade 8x24  
RB\_D

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Smooth &  
Series™ Exposed  
Joint Spacing - 4 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

**EASYCLEAN™ (Umbriano)**  
Factory sealed to provide  
integral surface protection  
from stains

**COLOR FUSION™ (Umbriano)**  
Subtly mottled color finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

		4 X 16	8 X 24
<b>Bundle Type</b>		<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced		NEW YORK	NEW YORK
Thickness (mm)		<b>100MM</b>	<b>100MM</b>
<b>SQFT PER</b>	Bundle	62.00	62.00
	Layer	10.33	10.33
	Section	-	-
	Stone	0.43	1.29
<b>PER BUNDLE</b>	Layers	6.00	6.00
	Sections	-	-
<b>SOLDIER LNFT PER</b>	SqFt	0.76	0.51
	Section	-	-
	Layer	7.87	5.25
	Bundle	47.24	31.50
<b>SAILOR LNFT PER</b>	SqFt	3.05	1.52
	Section	-	-
	Layer	31.50	15.75
	Bundle	188.98	94.49
<b>UNITS PER</b>	SqFt	2.32	0.77
	Section	-	-
	Bundle	144.00	48.00
<b>LBS PER</b>	Layer	455	478
	Section	-	-
	Bundle	2,730	2,869
<b>COLORS</b>		<b>Reflectance</b>	<b>Stock</b>
All Colors & Finishes		SR n/a SRI n/a	<b>SO</b>


Different finishes available by Special Order. Please contact your Territory Manager for more details.

Single Units		<b>4" X 16"</b> 100 x 400 x 100mm 3 7/8 x 15 3/4 x 3 7/8" 144 units/Bundle .43 Sq.Ft./Stone
		<b>8" X 24"</b> 200 x 600 x 100mm 7 7/8 x 23 5/8 x 3 7/8" 48 units/Bundle 1.29 Sq.Ft./Stone


Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Richcliff Fixed  
Random A



Richcliff Fixed  
Random B



Richcliff LargeRec  
HB\_H

## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Textured  
Joint Spacing - 10 mm  
Void - n/a

## TECHNOLOGIES

### ELEGANCE™

Timeless, long-lasting beauty  
with the combination of RealA  
and Ultima technologies

### REALA™

Cast from historic street pavers

### ULTIMA™

Up to 4x stronger than  
poured-in-place concrete

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

		LARGE RECTANGLE	
Bundle Type	RANDOM	SINGLE	
Plant Produced	ONTARIO	ONTARIO	
Thickness (mm)	60MM	60MM	

SQFT PER	Bundle	90.30	82.39
	Layer	11.29	10.30
	Section	-	-
	Stone	0.56	1.72

PER BUNDLE	Layers	8.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	0.58
	Section	-	-
	Layer	-	5.94
	Bundle	-	47.56

SAILOR LNFT PER	SqFt	1.31	1.01
	Section	-	-
	Layer	14.78	10.39
	Bundle	118.22	83.15

UNITS PER	SqFt	1.77	0.58
	Section	-	-
	Bundle	160.00	48.00

LBS PER	Layer	309	301
	Section	-	-
	Bundle	2,472	2,411

COLORS	Reflectance	Stock	Stock
Dawn Mist	SR n/a SRI n/a	✓	✓
Pebble Taupe	SR n/a SRI n/a	✓	✓
Smoke Shale	SR n/a SRI n/a	✓	✓



DAWN MIST



PEBBLE TAUPE




SMOKE SHALE

3 Unit Random Bundle				Lg. Rect. Sold Separately		
	RECTANGLE	SQUARE	SMALL RECTANGLE			
	226 x 300 x 60mm 8 7/8 x 11 7/8 x 2 3/8"	226 x 226 x 60mm 8 7/8 x 8 7/8 x 2 3/8"	150 x 226 x 60mm 5 7/8 x 8 7/8 x 2 3/8"			
	64 Units/Bundle .75 SqFt./Stone	32 units/Bundle .58 Sq.Ft./Stone	64 units/Bundle .38 Sq.Ft./Stone			
						<b>LARGE RECTANGLE</b> 302 x 528 x 60mm 11 7/8 x 20 7/8 x 2 3/8" 48 units/Bundle 1.72 Sq.Ft./Stone


Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. The Large Rectangle unit is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Senzo 8x16\_HB\_F



Senzo 8x16\_RB\_I

## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
 Surface Texture - Senzo Matte  
 Joint Spacing - 9 mm  
 Void - n/a

## TECHNOLOGIES

## ENDURACOLOR™

Refined surface and  
 long-lasting color

## EASYSOIL™

Factory sealed to provide  
 integral surface protection  
 from stains

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits -  
 see page 19.

	<b>8 X 16</b>
<b>Bundle Type</b>	<b>SINGLE</b>
<b>Plant Produced</b>	<b>ONTARIO</b>
<b>Thickness (mm)</b>	<b>70MM</b>

<b>SQFT PER</b>	Bundle	82.67
	Layer	10.33
	Section	-
	Stone	0.86

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	0.76
	Section	-
	Layer	7.87
	Bundle	62.99

<b>SAILOR LNFT PER</b>	SqFt	1.52
	Section	-
	Layer	15.75
	Bundle	125.98

<b>UNITS PER</b>	SqFt	1.16
	Section	-
	Bundle	96.00

<b>LBS PER</b>	Layer	331
	Section	-
	Bundle	2,647

COLORS	Reflectance	Stock
Crema	SR .43 SRI 49	SO
Midnight Charcoal	SR n/a SRI n/a	SO
Mocha Brown	SR n/a SRI n/a	SO



CREMA



MIDNIGHT CHARCOAL



MOCHA BROWN

Single Unit



## RECTANGLE

200 x 400 x 70mm  
 8 7/8 x 15 3/4 x 2 3/4"  
 96 Units/Bundle  
 .86 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.




# Series™ 60mm & 70mm


ENDURACOLOR™




## LAYING PATTERNS



Series Fixed  
Random A



Series Fixed  
Random B



Series 4x8 HB\_G

## APPLICATIONS



## APPEARANCE

Edge Detail - Micro  
Surface Texture - Series Exposed  
Joint Spacing - 7mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

		4 X 8	
Bundle Type		RANDOM	SINGLE
Plant Produced		NEW YORK	NEW YORK
Thickness (mm)		60MM	70MM

SQFT PER	Bundle	104.60	104.60
	Layer	10.46	10.46
	Section	-	-
	Stone	1.31	1.31

PER BUNDLE	Layers	10.00	10.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-

SAILOR LNFT PER	SqFt	0.85	0.85
	Section	-	-
	Layer	8.86	8.86
	Bundle	88.58	88.58

UNITS PER	SqFt	0.76	0.76
	Section	-	-
	Bundle	80.00	80.00

LBS PER	Layer	296	296
	Section	-	-
	Bundle	2,960	2,960

COLORS	Reflectance	Stock	
Black Granite	SR n/a SRI n/a		✓
Peppered Granite	SR .38 SRI 42	SO	



BLACK GRANITE  
(4X8")




PEPPERED GRANITE  
(RANDOM BUNDLE)  
SPECIAL ORDER

Random Bundle				Single Unit
	LARGE RECTANGLE	SQUARE	SMALL RECTANGLE	
	360 x 540 x 60mm 14 1/4 x 21 1/4 x 2 3/8"	360 x 360 x 60mm 14 1/4 x 14 1/4 x 2 3/8"	180 x 360 x 60mm 7 x 14 1/4 x 2 3/8"	4x8"
	18 units/Bundle 2.09 Sq.Ft./Stone	27 units/Bundle 1.40 Sq.Ft./Stone	27 units/Bundle .70 Sq.Ft./Stone	100 x 200 x 70mm 3 7/8 x 7 7/8 x 2 3/4"
				432 units/Bundle .22 Sq.Ft./Stone


Notes: For Special Order items - Lead time required. Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. Please refer to the Polymeric Sand Best Practices and Important Notice on page 97. All measurements are nominal. Contact Unilock for more information.




## LAYING PATTERNS



Thornbury Fixed  
Random\_A



Thornbury Fixed  
Random\_B



Thornbury Fixed  
Random\_C

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Smooth  
Joint Spacing - 11-18 mm  
Void - 4.4%

## TECHNOLOGIES

### PERMEABLE

Can be installed to allow water  
to flow through

### ENDURACOLOR™

Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

	SMOOTH
Bundle Type	RANDOM
Plant Produced	UXBRIDGE
Thickness (mm)	70MM

SQFT PER	Bundle	88.61
	Layer	11.08
	Section	-
	Stone	0.92

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	1.08
	Section	-
	Bundle	96.00

LBS PER	Layer	355
	Section	-
	Bundle	2,838

COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	✓
Steel Mountain	SR .30 SRI 31	SO



FOSSIL **NEW**



STEEL MOUNTAIN

3 Unit Random Bundle



**LARGE RECTANGLE**  
350 x 420 x 70mm  
13 7/8 x 16 5/8 x 2 3/4"  
32 Units/Bundle



**MEDIUM RECTANGLE**  
210 x 350 x 70mm  
8 3/8 x 13 7/8 x 2 3/4"  
32 units/Bundle




**SMALL RECTANGLE**  
173 x 210 x 70mm  
6 7/8 x 8 3/8 x 2 3/4"  
32 units/Bundle


Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.




## LAYING PATTERNS



TownHall DHB\_D



TownHall HB\_B



TownHall RB\_C

## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Textured  
Joint Spacing - 10 mm  
Void - 6.5%

## TECHNOLOGIES

### ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

### REALA™

Cast from historic street pavers

### ULTIMA™

Up to 4x stronger than poured-in-place concrete

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

	STANDARD
Bundle Type	SINGLE
Plant Produced	ONTARIO
Thickness (mm)	70MM

SQFT PER	Bundle	88.41
	Layer	11.05
	Section	-
	Stone	0.28

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.19
	Section	-
	Layer	13.12
	Bundle	104.99

SAILOR LNFT PER	SqFt	2.97
	Section	-
	Layer	32.81
	Bundle	262.47

UNITS PER	SqFt	3.62
	Section	-
	Bundle	320.00

LBS PER	Layer	361
	Section	-
	Bundle	2,888

COLORS	Reflectance	Stock
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓
Basalt	SR n/a SRI n/a	✓



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK

Single Units




**STANDARD**  
250 x 100 x 70mm  
9 7/8 x 3 7/8 x 2 3/4"  
320 units/Bundle  
.28 Sq.Ft./Stone


Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Transition 6x9  
HB\_D



Transition 6x9  
RB\_C

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Textured  
Joint Spacing - 3 mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

		FLAGSTONE FINISH
<b>Bundle Type</b>		<b>SINGLE</b>
<b>Plant Produced</b>		<b>NEW YORK</b>
<b>Thickness (mm)</b>		<b>60MM</b>
<b>SQFT PER</b>	Bundle	125.00
	Layer	12.50
	Section	-
	Stone	0.42
<b>PER BUNDLE</b>	Layers	10.00
	Sections	-
<b>SOLDIER LNFT PER</b>	SqFt	1.18
	Section	-
	Layer	14.76
	Bundle	147.64
<b>SAILOR LNFT PER</b>	SqFt	1.81
	Section	-
	Layer	22.64
	Bundle	226.38
<b>UNITS PER</b>	SqFt	2.40
	Section	-
	Bundle	300.00
<b>LBS PER</b>	Layer	350
	Section	-
	Bundle	3,500
<b>COLORS</b>	<b>Reflectance</b>	<b>Stock</b>
Charcoal	SR n/a SRI n/a	✓



CHARCOAL

Single Unit




**RECTANGLE**  
150 x 230 x 60mm  
5 7/8" x 9 x 2 3/8"  
300 Units/Bundle  
.42 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.






## LAYING PATTERNS



Treo Fixed  
Random\_C



Treo Fixed  
Random\_D

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Textured  
Joint Spacing - 4mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.


		SMALL RECTANGLE	
Bundle Type		RANDOM	SINGLE
Plant Produced		NEW YORK	NEW YORK
Thickness (mm)		60MM	60MM
SQFT PER	Bundle	108.99	108.99
	Layer	10.90	10.90
	Section	-	-
	Stone	0.44	0.27
PER BUNDLE	Layers	10.00	10.00
	Sections	-	-
SOLDIER LNFT PER	SqFt	-	1.35
	Section	-	-
	Layer	-	14.76
	Bundle	-	147.64
SAILOR LNFT PER	SqFt	-	2.71
	Section	-	-
	Layer	-	29.53
	Bundle	-	295.28
UNITS PER	SqFt	2.29	3.67
	Section	-	-
	Bundle	250.00	400.00
LBS PER	Layer	302	305
	Section	-	-
	Bundle	3,015	3,050
COLORS		Reflectance	Stock
Almond Grove		SR .25 SRI 25	✓
Brown		SR n/a SRI n/a	✓
Charcoal		SR n/a SRI n/a	✓
Fossil		SR .22 SRI 21	✓
Steel Mountain		SR .30 SRI 31	✓
Tuscany		SR .30 SRI 32	✓



ALMOND GROVE



BROWN  
Small Rectangle Only



CHARCOAL  
Small Rectangle Only



FOSSIL



STEEL MOUNTAIN



TUSCANY

Random Bundle		<b>LARGE RECTANGLE</b> 225 x 337.5 x 60mm 8 7/8 x 13 3/8 x 2 3/8" 50 units/Bundle .82 Sq.Ft./Stone		<b>SQUARE</b> 225 x 225 x 60mm 8 7/8 x 8 7/8 x 2 3/8" 50 units/Bundle .55 Sq.Ft./Stone		<b>SMALL RECTANGLE</b> 112.5 x 225 x 60mm 4 1/2 x 8 7/8 x 2 3/8" 150 units/Bundle .27 Sq.Ft./Stone	Single Unit		<b>SMALL RECTANGLE</b> 112.5 x 225 x 60mm 4 1/2 x 8 7/8 x 2 3/8" 400 units/Bundle .27 Sq.Ft./Stone


Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. Please refer to the Polymeric Sand Best Practices and Important Notice on page 97. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Treo Fixed  
Random\_R



Treo Fixed  
Random\_S

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Smooth  
Joint Spacing - 7mm  
Void - 5.5%

## TECHNOLOGIES

### PERMEABLE

Can be installed to allow water to flow through

### ENDURACOLOR™

Refined surface and long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see page 19.

		SMOOTH FINISH
Bundle Type		RANDOM
Plant Produced		UXBRIGE/NEW YORK
Thickness (mm)		60MM
SQFT PER	Bundle	116.87
	Layer	11.69
	Section	-
	Stone	0.56
PER BUNDLE	Layers	10.00
	Sections	-
SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	1.57
	Section	-
	Layer	18.35
	Bundle	183.46
UNITS PER	SqFt	1.80
	Section	-
	Bundle	210.00
LBS PER	Layer	321
	Section	-
	Bundle	3,208
COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	✓
Steel Mountain	SR .30 SRI 31	✓



FOSSIL



STEEL MOUNTAIN

Random Bundle



### LARGE RECTANGLE

225 x 337.5 x 60mm  
8 7/8 x 13 3/8 x 2 3/8"  
60 units/Bundle  
.82 Sq.Ft./Stone



### SQUARE

225 x 225 x 60mm  
8 7/8 x 8 7/8 x 2 3/8"  
70 units/Bundle  
.55 Sq.Ft./Stone



### SMALL RECTANGLE

112.5 x 225 x 60mm  
4 1/2 x 8 7/8 x 2 3/8"  
80 units/Bundle  
.27 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. Please refer to the Polymeric Sand Best Practices and Important Notice on page 97. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



TribecaCobble Fixed  
Random\_A

## APPLICATIONS



## APPEARANCE

Edge Detail - Micro  
Surface Texture - Series Exposed  
Textured  
Joint Spacing - 10mm  
Void - 5.6%

## TECHNOLOGIES

### PERMEABLE

Can be installed to allow water to  
flow through

### ENDURACOLOR™

Refined surface and  
long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see  
page 19.

	CURB	
Bundle Type	SINGLE	RANDOM
Plant Produced	NEW YORK	NEW YORK
Thickness (mm)	180MM	70MM

SQFT PER	Bundle	-	97.53
	Layer	-	12.19
	Section	-	-
	Stone	-	0.32

PER BUNDLE	Layers	3.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	12.24	-
	Bundle	36.72	-

SAILOR LNFT PER	SqFt	-	2.34
	Section	-	-
	Layer	-	28.49
	Bundle	-	227.95

UNITS PER	SqFt	-	3.12
	Section	-	-
	Bundle	36.00	304.00

LBS PER	Layer	555	398
	Section	-	-
	Bundle	1,664	3,186

COLORS	Reflectance	Stock	Stock
Crystalline Basalt	SR n/a SRI n/a	✓	✓
Peppered Granite	SR .38 SRI 42	✓	✓



CRYSTALLINE BASALT




PEPPERED GRANITE

Random Bundle		<b>LARGE RECTANGLE</b> 130 x 305 x 70mm 5 x 12 x 2 3/4" 88 units/Bundle .43 Sq.Ft./Stone		<b>RECTANGLE</b> 130 x 230 x 70mm 5 x 9 x 2 3/4" 88 units/Bundle .32 Sq.Ft./Stone		<b>SMALL RECTANGLE</b> 130 x 175 x 70mm 5 x 6 7/8 x 2 3/4" 128 units/Bundle .25 Sq.Ft./Stone	Single Unit		<b>CURB</b> 230 x 290 x 180mm 9 x 11 1/2 x 7" 36 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices on page 97. All measurements are nominal. Contact Unilock for more information.



### LAYING PATTERNS



Turfstone Fixed  
Random\_R

### APPLICATIONS



### APPEARANCE

Edge Detail - Zero  
Surface Texture - Smooth  
Joint Spacing - 2mm  
Void - 40%

### TECHNOLOGIES

#### CLASSIC

Budget-friendly traditional  
product mix

### TECHNICAL INFORMATION

Conforms to ASTM C1319  
Eligible for LEED v4.1 credits -  
see page 19.

		CLASSIC FINISH
Bundle Type		RANDOM
Plant Produced		UXBRIDGE
Thickness (mm)		80MM
SQFT PER	Bundle	72.00
	Layer	10.29
	Section	-
	Stone	2.57
PER BUNDLE	Layers	7.00
	Sections	-
SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-
UNITS PER	SqFt	0.39
	Section	-
	Bundle	28.00
LBS PER	Layer	250
	Section	-
	Bundle	1,748
COLORS		Reflectance
Natural		SR .30 SRI 32
		Stock
Natural		✓



NATURAL

Single Unit



#### LARGE RECTANGLE


400 x 600 x 80mm  
15 3/4 x 23 5/8 x 3 1/8"  
28 units/Bundle  
2.57 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.






## LAYING PATTERNS



Umbriano Fixed  
Random\_A



Umbriano Fixed  
Random\_B

## APPLICATIONS



### APPEARANCE

Edge Detail - Micro  
Surface Texture - Umbriano Mottled  
Joint Spacing - 7mm  
Void - n/a

### TECHNOLOGIES

#### ENDURACOLOR™

Refined surface and  
long-lasting color

#### EASYCLEAN™

Factory sealed to provide integral  
surface protection from stains

#### COLORFUSION™

Subtly mottled colored finish

### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits - see  
page 19.

	UMBRIANO FINISH
Bundle Type	RANDOM
Plant Produced	NEW YORK
Thickness (mm)	60MM

SQFT PER	Bundle	104.60
	Layer	10.46
	Section	-
	Stone	1.31

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.82
	Section	-
	Layer	8.61
	Bundle	86.12


UNITS PER	SqFt	0.76
	Section	-
	Bundle	80.00

LBS PER	Layer	305
	Section	-
	Bundle	3,050


COLORS	Reflectance	Stock
French Grey	SR .18 SRI 17	✓
Midnight Sky	SR .17 SRI 15	SO
Summer Wheat	SR .42 SRI 48	✓
Winter Marvel	SR .35 SRI 38	✓



FRENCH GREY



MIDNIGHT SKY  
SPECIAL ORDER



SUMMER WHEAT



WINTER MARVEL

Random Bundle



#### LARGE RECTANGLE

360 x 540 x 60mm  
14 1/4 x 21 1/4 x 2 3/8"  
20 units/Bundle



#### SQUARE

360 x 360 x 60mm  
14 1/4 x 14 1/4 x 2 3/8"  
30 units/Bundle




#### SMALL RECTANGLE

180 x 360 x 60mm  
7 x 14 1/4 x 2 3/8"  
30 units/Bundle


Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. This product is not intended for vehicular use. All measurements are nominal. Contact Unilock for more information.




## LAYING PATTERNS



Umbriano 24x24  
RB\_AG



Umbriano 12x24  
HB\_O



Umbriano 16x16  
RB\_AE

## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Umbriano  
Mottled  
Joint Spacing - 7mm  
Void - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface and  
long-lasting color

**EASYCLEAN™**  
Factory sealed to provide  
integral surface protection  
from stains

**COLORFUSION™**  
Subtly mottled colored finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

	8x8"	8x16"	12x24"	16x16"	24x24"
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	NEW YORK	NEW YORK	NEW YORK	NEW YORK	NEW YORK
Thickness (mm)	<b>70MM</b>	<b>70MM</b>	<b>70MM</b>	<b>70MM</b>	<b>70MM</b>

<b>SQFT PER</b>	Bundle	82.67	82.67	93.00	82.67	62.00
	Layer	10.33	10.33	11.63	10.33	7.75
	Section	-	-	-	-	-
	Stone	0.43	0.86	1.94	1.72	3.88

<b>PER BUNDLE</b>	Layers	8.00	8.00	8.00	8.00	8.00
	Sections	-	-	-	-	-

<b>SOLDIER LNFT PER</b>	SqFt	1.52	0.76	0.51	0.76	0.51
	Section	-	-	-	-	-
	Layer	15.75	7.87	5.91	7.87	3.94
	Bundle	125.98	62.99	47.24	62.99	31.50

<b>SAILOR LNFT PER</b>	SqFt	1.52	1.52	1.02	0.76	0.51
	Section	-	-	-	-	-
	Layer	15.75	15.75	11.81	7.87	3.94
	Bundle	125.98	125.98	94.49	62.99	31.50

<b>UNITS PER</b>	SqFt	2.32	1.16	0.52	0.58	0.26
	Section	-	-	-	-	-
	Bundle	192.00	96.00	48.00	48.00	16.00

<b>LBS PER</b>	Layer	331	331	372	331	258
	Section	-	-	-	-	-
	Bundle	2,646	2,646	2,978	2,646	2,055

COLORS	Reflectance		Stock	Stock	Stock	Stock
French Grey	SR .18 SRI 17	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>
Midnight Sky	SR .17 SRI 15	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>
Summer Wheat	SR .42 SRI 48	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>
Winter Marvel	SR .35 SRI 38	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>	<b>SO</b>



FRENCH GREY  
SPECIAL ORDER



MIDNIGHT SKY  
SPECIAL ORDER



SUMMER WHEAT  
SPECIAL ORDER




WINTER MARVEL  
SPECIAL ORDER

Single Units	8 x 8	8 x 16	12 x 24	16 x 16	24 x 24
	200 x 200 x 70mm 7 7/8 x 7 7/8 x 2 3/4" 192 units/Bundle .43 Sq.Ft./Stone	200 x 400 x 70mm 7 7/8 x 15 3/4 x 2 3/4" 96 units/Bundle .86 Sq.Ft./Stone	300 x 600 x 70mm 11 7/8 x 23 5/8 x 2 3/4" 48 units/Bundle 1.94 Sq.Ft./Stone	400 x 400 x 70mm 15 3/4 x 15 3/4 x 2 3/4" 48 units/Bundle 1.72 Sq.Ft./Stone	600 x 600 x 70mm 23 5/8 x 23 5/8 x 2 3/4" 16 units/Bundle 3.88 Sq.Ft./Stone


Notes: **Special Order items, lead time is required. SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## LAYING PATTERNS



Westport Fixed  
Random\_A



Westport Fixed  
Random\_B

## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Textured  
Joint Spacing - 3-7mm  
Void - n/a

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and  
long-lasting color

### EASYSOFT™

Factory sealed to provide integral  
surface protection from stains

### SOFT TOUCH

Ultra-smooth surface texture

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits -  
see page 19.

		5X10"
Bundle Type	RANDOM	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE
Thickness (mm)	70MM	70MM

SQFT PER	Bundle	94.19	94.19
	Layer	11.77	11.77
	Section	-	-
	Stone	0.59	0.34

PER BUNDLE	Layers	8.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	0.71
	Section	-	-
	Layer	-	8.33
	Bundle	-	66.67

SAILOR LNFT PER	SqFt	1.24	1.42
	Section	-	-
	Layer	14.57	16.67
	Bundle	116.56	133.33

UNITS PER	SqFt	1.70	2.97
	Section	-	-
	Bundle	160.00	280.00

LBS PER	Layer	373	373
	Section	-	-
	Bundle	2,985	2,985

COLORS	Reflectance	Stock	Stock
Midnight Charcoal	SR.n/a SRI n/a		✓
Fossil	SR .22 SRI 21	✓	
Steel Mountain	SR .30 SRI 31	✓	✓



MIDNIGHT CHARCOAL  
(5 X 10 only)



FOSSIL  
(Random Bundle only)



STEEL MOUNTAIN  
(Random Bundle only)

Random Bundle		<b>LARGE RECTANGLE</b> 254x 380 x 70mm 10 x 15 x 2 ¾" 32 units/Bundle 1.01 Sq.Ft./Stone		<b>SQUARE</b> 254 x 254 x 70mm 10 x 10 x 2 ¾" 56 units/Bundle .67 Sq.Ft./Stone		<b>RECTANGLE</b> 127 x 254 x 70mm 5 x 10 x 2 ¾" 72 units/Bundle .34 Sq.Ft./Stone	Single 5x10 Unit		<b>5x10 Rectangle</b> 127 x 254 x 70mm 5 x 10 x 2 ¾" 280 units/Bundle .34 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



### APPLICATIONS



### CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

### APPEARANCE

Edge Detail - n/a  
Surface Texture - Standard  
Joint Spacing - 2mm  
Void - n/a

### TECHNOLOGIES

#### CLASSIC™

Budget-friendly traditional product mix

#### ANTIQUED™

Distressed, timeworn finish

### TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits – see page 19.

	STANDARD CLASSIC ANTIQUED
Bundle Type	SINGLE
Plant Produced	UXBRIDGE
Thickness (mm)	100MM

FCFT PER	Bundle	-
	Layer	6.00
	Stone	0.33

PER BUNDLE	Layers	-
	Sections	3.00

LNFT PER	Bundle	-
	Unit	1.00

UNITS PER	SqFt	3.00
	Section	36.00
	Bundle	108.00

LBS PER	Layer	-
	Section	1,091
	Bundle	3,274

COLORS		Stock
Almond Grove	SR n/a SRI n/a	✓
Limestone	SR n/a SRI n/a	✓



ALMOND GROVE

LIMESTONE

### SUNSET FIREPIT KITS



ROUND



SQUARE

Single Unit



**STANDARD**  
300 x 100 x 200mm  
11 7/8 x 3 7/8 x 7 7/8"  
108 units/Bundle  
.33 Fc.Ft./Stone

Notes: Maximum height is 24" (under optimum conditions). \*Based on 12" deep wall coverage = 21.4 sqft per bundle. Based on an 8" deep wall coverage = 32 sqft per bundle. All measurements are nominal. Contact Unilock for more information.



### APPLICATIONS



### CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

### APPEARANCE

Edge Detail - n/a  
Surface Texture - Split / Standard

### TECHNOLOGIES

#### CLASSIC™

Budget-friendly traditional product mix

### TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits - see page 19.

	CORNER SPLIT	XL WALL SPLIT	COPING 24"	WEDGE CAP
<b>Bundle Type</b>	<b>RANDOM</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE
Thickness (mm)	150MM	150MM	75MM	86MM

<b>FCFT PER</b>	Bundle	15.00	21.33	-	64.00
	Layer	5.00	5.33	3.88	8.00
	Stone	0.83	0.67	1.94	0.67

<b>PER BUNDLE</b>	Layers	3.00	4.00	-	8.00
	Sections	-	-	2.00	-

<b>LNFT PER</b>	Bundle	-	-	64.00	-
	Unit	-	-	4.00	-

<b>UNITS PER</b>	SqFt	1.20	1.50	0.52	1.50
	Section	-	-	-	-
	Bundle	18.00	32.00	-	96.00

<b>LBS PER</b>	Layer	273	605	290	318
	Section	-	-	-	-
	Bundle	820	2,419	-	2,544

COLORS		Stock	Stock	Stock	Stock
Almond Grove	SR n/a SRI n/a	✓	✓	✓	✓
Granite	SR n/a SRI n/a	✓	✓	✓	✓



ALMOND GROVE



GRANITE

Single Units



**CORNER SPLIT**  
200 x 150 x 300mm  
7 7/8 x 5 7/8 x 11 7/8"  
18 units/Bundle  
.63 Fc.Ft./Stone



**XL WALL SPLIT**  
400 x 150 x 300mm  
15 3/4 x 5 7/8 x 11 7/8"  
32 units/Bundle  
.67 Fc.Ft./Stone



**COPING 24"**  
600 x 75 x 300mm  
23 5/8 x 3 x 11 7/8"  
XX units/Bundle  
1.94 Fc.Ft./Stone



**WEDGE CAP SPLIT**  
248 x 86 x 330mm  
9 7/8 x 3 1/2 x 13"  
96 units/Bundle  
.67 Sq.Ft./Stone

Notes: Maximum height without setback 36" (under optimum conditions). Maximum height with setback is 42" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. Tapered units will allow for a minimum 7ft. outside radius. Wedge cap radius = 7", contains 8 Closed-end units per bundle. Closed-end not sold separately. All Concord Wall™ is layered and shipped on refundable skid. Coping is sectioned. Closed-end step tread is available. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. Contact your local Unilock Representative for details. Retaining wall engineering software is also available free of charge at [www.unilock.com](http://www.unilock.com).





## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a

Surface Texture - Standard

## TECHNOLOGIES

## CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C1372

Eligible for LEED v4.1 credits - see page 19.

	STANDARD	STANDARD 1/2	CORNER 45°	CORNER 90°
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	300MM	300MM	300MM	300MM

<b>FCFT PER</b>	Bundle	6.02	3.00	7.04	7.04
	Layer	6.02	3.00	7.04	7.04
	Stone	6.02	3.00	7.04	7.04

<b>PER BUNDLE</b>	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

<b>LNFT PER</b>	Bundle	6.02	3.00	-	-
	Unit	6.02	3.00	-	-





<b>UNITS PER</b>	SqFt	0.17	0.33	0.14	0.14
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

<b>LBS PER</b>	Layer	1,680	800	1,480	1,320
	Section	-	-	-	-
	Bundle	1,680	800	1,480	1,320

COLORS		Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO



NATURAL

Single Units				
	<b>STANDARD</b>	<b>STANDARD 1/2</b>	<b>CORNER 45°</b>	<b>CORNER 90°</b>
	1830 x 300 x 600mm	915 x 300 x 600mm	1520 x 300 x 600mm	1520 x 300 x 600mm
	72 x 11 7/8 x 23 5/8"	36 x 11 7/8 x 23 5/8"	59 7/8 x 11 7/8 x 23 5/8"	59 7/8 x 11 7/8 x 23 5/8"
	1 unit/Bundle 6.02 Fc.Ft./Stone	1 unit/Bundle 3.00 Fc.Ft./Stone	1 unit/Bundle 7.04 Fc.Ft./Stone	1 unit/Bundle 7.04 Fc.Ft./Stone

Notes: \*Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



### APPLICATIONS



### CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

### APPEARANCE

Edge Detail - n/a  
Surface Texture - Standard

### TECHNOLOGIES

#### CLASSIC™

Budget-friendly traditional product mix

### TECHNICAL INFORMATION

Conforms to ASTM C1372  
Eligible for LEED v4.1 credits - see page 19.

	TIE-BACK	COPING HALF	COPING STANDARD	COPING CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	300MM	300MM	300MM	300MM

FCFT PER	Bundle	2.00	2.95	6.02	6.02
	Layer	2.00	2.95	6.02	6.02
	Stone	2.00	2.95	6.02	6.02

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	-	-	-	-
	Unit	-	-	-	-





UNITS PER	SqFt	0.50	0.34	0.17	0.17
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,660	780	1,560	1,560
	Section	-	-	-	-
	Bundle	1,660	780	1,560	1,560

COLORS		Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO



NATURAL

Single Units				
	<b>TIE-BACK</b> 1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone	<b>COPING 1/2</b> 915 x 300 x 600mm 36 x 11 7/8 x 23 5/8" 1 unit/Bundle 2.95 Fc.Ft./Stone	<b>COPING STANDARD</b> 1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone	<b>COPING CLOSED-END</b> 1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone

Notes: \*Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



### APPLICATIONS



### CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

### APPEARANCE

Edge Detail - n/a  
Surface Texture - Standard

### TECHNOLOGIES

#### CLASSIC™

Budget-friendly traditional product mix

### TECHNICAL INFORMATION

Conforms to ASTM C1372  
Eligible for LEED v4.1 credits - see page 19.

	TIE-BACK	CORNER 90°	STANDARD	COPING	COPING CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	300MM	300MM	300MM	300MM	300MM

FCFT PER	Bundle	1.17	16.67	24.10	24.10	6.02
	Layer	1.17	4.17	6.02	6.02	6.02
	Stone	1.17	4.17	6.02	6.02	6.02

PER BUNDLE	Layers	2.00	2.00	2.00	2.00	2.00
	Sections	-	-	-	-	-

LNFT PER	Bundle	-	-	24.10	24.10	24.10
	Unit	-	-	6.02	6.02	6.02






UNITS PER	SqFt	0.85	0.24	0.17	0.17	0.17
	Section	-	-	-	-	-
	Bundle	1.00	-	1.00	1.00	1.00

LBS PER	Layer	940	460	884	884	884
	Section	-	-	-	-	-
	Bundle	940	-	884	884	884

COLORS		Stock	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO	SO



NATURAL

Single Units					
	<b>TIE-BACK</b> 1830 x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 1.17 Fc.Ft./Stone	<b>CORNER</b> 900 x 300 x 360mm 36 x 11 7/8 x 14 1/4" 1 unit/Bundle 4.17 Fc.Ft./Stone	<b>STANDARD</b> 1830x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 6.02 Fc.Ft./Stone	<b>COPING</b> 1830x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 6.02 Fc.Ft./Stone	<b>COPING CLOSED-END</b> 1830x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 6.02 Fc.Ft./Stone

Notes: \*Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.






The enhanced Estate Wall System with 6" high units, is ideal for all residential landscape walls and vertical element construction. The front and back of each unit is rock-faced making it perfect for seat walls and the unique tapered units can be used for both straight or curved applications.

## Estate Wall™ System


**UNILOCK**  
PAVERS & WALLS

# Units

## WALL UNITS




## CORNER UNITS




NOTE: See Product Data for packaging information.

## UNIVERSAL BASE UNIT



NOTE: Unilock Recommends using the Universal Base Units

# Cross Sections




MAXIMUM HEIGHT FOR VERTICAL APPLICATION - 21"  
MAXIMUM HEIGHT FOR SETBACK APPLICATION - 33"


## COPING



## Ledgestone™




## Brussels Fullnose™



NOTE: Different products can be used for Estate Wall coping. Ledgestone and Brussels Fullnose are two of the most popular.

## TYPICAL REINFORCED WALL




\*Higher wall up to 6' can be achieved using geogrid reinforcement. Contact your Unilock Territory Manager.



# Corners


## CONVERTIBLE LARGE WEDGE UNITS



To split a large convertible unit, use a hammer and chisel to score the top and sides, then lip the unit upside down and use the chisel to break the unit. This may require a couple of hits along the groove to achieve a clean break.

Each bundle contains approximately 9 convertible units.


## 90° SEAT WALL CORNER




## LOCKING INSERTS

Depending on the application or the wall strength required, you can construct the Estate Wall System vertically or with a setback. To assist in alignment and locking, proprietary plastic inserts are provided with each bundle. Depending on the orientation of the insert will dictate whether it goes up vertical or with a setback.



Note: It is strongly recommended that you use adhesive on all rows and for all applications to achieve maximum stability and strength.



# Seat Walls




## SEAT WALL TERMINATION



Alternate courses

# System Patterns

## RANDOM PATTERNS OPEN BACK WALL



Use Universal Base Units for base

## RANDOM PATTERNS SOLID WALL




Use Universal Base Units for base

## CURVED RADIUS

Radius achieved using only the tapered (wedge) units.

Radius in inches	35"	27"	35"	44"	31"	35"	40"
Unit sequence	9",12",14¾"	Only 9" Units	Only 12" Units	Only 14¾" Units	9",12",9",12"	9",14¾", 9"	12", 14¾", 12", 14¾"
Note:	Uses all units in bundle	These sequences will have left over units. Plan to use left overs in other parts of the project.					

Random Units



Although the three tapered unit sizes come packaged together, they can be separated to achieve various radius projects. If you construct a radius using only one size unit, the other units will be left over. Careful planning will allow you to use these units elsewhere.



### APPLICATIONS



### CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

### APPEARANCE

Edge Detail - n/a  
Surface Texture - Split

### TECHNOLOGIES

#### CLASSIC™

Budget-friendly traditional product mix

### TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits - see page 19.

	TAPERED SPLIT	CORNER SPLIT	COPING TAPERED SPLIT
Bundle Type	RANDOM	SINGLE	RANDOM
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE
Thickness (mm)	150MM	150MM	75MM

FCFT PER	Bundle	24.00	16.38	14.70
	Layer	6.00	4.10	2.10
	Stone	0.50	0.51	0.23

PER BUNDLE	Layers	4.00	4.00	7.00
	Sections	-	-	7.00

LNFT PER	Bundle	-	-	56.87
	Unit	-	-	0.90

UNITS PER	SqFt	2.00	1.95	4.29
	Section	-	-	9.00
	Bundle	48.00	32.00	63.00

LBS PER	Layer	585	444	294
	Section	-	-	294
	Bundle	2,340	1,776	2,060

COLORS		Stock	Stock	Stock
Almond Grove	SR.n/a SRI n/a	✓	✓	✓
Charcoal	SR.n/a SRI n/a	✓	✓	✓
Granite	SR.n/a SRI n/a	✓	✓	✓



ALMOND GROVE



CHARCOAL  
Coping only



GRANITE

Random Bundle				Single Unit		Coping Bundle		
	<b>LARGE TAPERED</b> 400 x 150 x 228mm 15 3/4 x 5 7/8 x 9" 16 units/Bundle .63 Fc.Ft./Stone	<b>MEDIUM TAPERED</b> 300 x 150 x 228mm 11 7/8 x 5 7/8 x 9" 16 units/Bundle .52 Fc.Ft./Stone	<b>SMALL TAPERED</b> 200 x 150 x 228mm 7 7/8 x 5 7/8 x 9" 16 units/Bundle .42 Fc.Ft./Stone		<b>CORNER SPLIT</b> 320 x 150 x 230mm 12 5/8 x 5 7/8 x 9" 32 units/Bundle .51 Sq.Ft./Stone		<b>COPING TAPERED</b> 280 x 75 x 300mm 11 x 3 x 11 7/8" 63 units/Bundle .23 Sq.Ft./Stone	<b>COPING TAPERED</b> 280 x 75 x 300mm 11 x 3 x 11 7/8" 63 units/Bundle .23 Sq.Ft./Stone

Notes: 6" random wall bundles have convertible large units that can be used for corners or ending seat walls. End caps not sold separately. All measurements are nominal. Contact Unilock for more information.



### APPLICATIONS



### CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

### APPEARANCE

Edge Detail - n/a  
Surface Texture - Standard  
Joint Spacing - n/a  
Void - n/a

### TECHNOLOGIES

#### CLASSIC™

Budget-friendly traditional product mix

### TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits - see page 19.



ALMOND GROVE



LIMESTONE

	RANDOM CLASSIC	PILLAR CLASSIC
Bundle Type	RANDOM	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE
Thickness (mm)	100MM	100MM

FCFT PER	Bundle	29.92	48.24
	Layer	9.97	16.08
	Stone	0.50	0.67

PER BUNDLE	Layers	3.00	3.00
	Sections	-	-

LNFT PER	Bundle	89.06	96.00
	Unit	1.48	1.33

UNITS PER	SqFt	2.01	1.49
	Section	-	-
	Bundle	60.00	72.00

LBS PER	Layer	881	936
	Section	-	-
	Bundle	2,643	2,808

COLORS		Stock	Stock
Almond Grove	SR.n/a SRI n/a	✓	✓
Limestone	SR.n/a SRI n/a	✓	✓

Random Bundle					Single Unit
	LARGE RECTANGLE	RECTANGLE	SMALL RECTANGLE	XL RECTANGLE	
	500 x 100 x 200mm 19 3/4 x 3 7/8 x 7 7/8 15 units/Bundle	400 x 100 x 200mm 15 3/4 x 3 7/8 x 7 7/8 15 units/Bundle	300 x 100 x 200mm 11 7/8 x 3 7/8 x 7 7/8 15 units/Bundle	600 x 100 x 200mm 23 5/8 x 3 7/8 x 7 7/8 15 units/Bundle	CORNER/PILLAR 400 x 100 x 200mm 15 3/4 x 3 7/8 x 7 7/8 72 units/Bundle .67 Sq.Ft./Stone


Notes: Solid in full bundles only and is produced and sold on a required, refundable skid. Spacing strips are shipped with random wall bundles to create even spacing between units. LedgeStone™, Unilock Natural Stone or 6"x12" Fullnose complement as possible coping options. All measurements are nominal. Contact Unilock for more information.

# Lineo™ Dimensional Stone


Shadow Box - Spacers (supplied with bundle of product)

Adhesive "mound" is placed every 4 inches apart.


Mound must be minimum 3/8" high so that the top and bottom are securely adhered.



"T" Spacers  
1" x 4 3/16" x 2"



"Strip" Spacers  
3/16" x 3/8" x 22"



## Notes:

Lineo is not a retaining wall. Lineo is a decorative landscape wall, with a typical height of 12" - 16" above grade. (Higher walls are possible when engineered by a professional engineer.)

In many cases, experienced installers are able to construct higher walls based on the actual design of the project or landscape feature. For example, designs containing 90 degree corners, box-like planters, hollow pillars and landscape features such as grill islands, can be successfully constructed to higher heights.

Disclaimer: The strength and capacity of a Lineo installation is dependent on many factors such as base material, site conditions, drainage, surcharge, design, and the quality and quantity of concrete adhesive used. Unilock cannot be responsible for installation failures. The performance of a Lineo installation rests solely on the installer or project engineer.





## APPLICATIONS



## APPEARANCE

Edge Detail - n/a

Surface Texture - Split

## CROSS SECTIONS

Cross Sections are available on  
Unilock's Contractor website under  
Products: [contractor.unilock.com](http://contractor.unilock.com)

## TECHNOLOGIES

## CLASSIC™

Budget-friendly traditional product  
mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits - see  
page 19.



GRANITE



SIERRA

	CORNER SPLIT	333 SPLIT	500 SPLIT	925 SPLIT	COPING SPLIT	CLOSED-END COPING
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE	GORMLEY
Thickness (mm)	185MM	185MM	185MM	185MM	185MM	185MM

FCFT PER	Bundle	17.19	18.00	12.00	6.00	12.00	14.43
	Layer	5.73	6.00	4.00	2.00	4.00	4.81
	Stone	2.87	2.00	2.00	2.00	2.00	2.41







PER BUNDLE	Layers	3.00	3.00	3.00	3.00	3.00	3.00
	Sections	-	-	-	-	-	-

LNFT PER	Bundle	-	-	19.50	9.75	-	23.70
	Unit	-	-	3.25	3.25	-	3.95

UNITS PER	SqFt	0.35	0.50	0.50	0.50	0.50	0.42
	Section	-	-	-	-	-	-
	Bundle		9.00	6.00	3.00	6.00	6.00

LBS PER	Layer	954	954	954	954	927	1,140
	Section	-	-	-	-	-	-
	Bundle	2,862	2,862	2,862	2,862	2,780	3,420


COLORS		Stock	Stock	Stock	Stock	Stock	Stock
Granite	SR.n/a SRI n/a	SO	SO	SO	SO	SO	✓
Sierra	SR.n/a SRI n/a	SO	SO	SO	SO	SO	

Single Units						
	<b>CORNER SPLIT</b> 925 x 185 x 500mm 36 1/2 x 7 3/8 x 19 3/4" 6 units/Bundle 2.87 Fc.Ft./Stone	<b>STANDARD 333 SPLIT</b> 1000 x 185 x 333mm 39 3/8 x 7 3/8 x 13" 9 units/Bundle 2.00 Fc.Ft./Stone	<b>STANDARD 500 SPLIT</b> 1000 x 185 x 500mm 39 3/8 x 7 3/8 x 19 3/4" 6 units/Bundle 2.00 Fc.Ft./Stone	<b>STANDARD 925 SPLIT</b> 1000 x 185 x 925mm 39 3/8 x 7 3/8 x 36 1/2" 3 units/Bundle 2.00 Fc.Ft./Stone	<b>COPING SPLIT</b> 1000 x 185 x 500mm 39 3/8 x 7 3/8 x 19 3/4" 6 units/Bundle 2.00 Fc.Ft./Stone	<b>C-E COPING</b> 1200 x 185 x 500mm 47 1/4 x 7 3/8 x 19 3/4" 6 units/Bundle 2.41 Fc.Ft./Stone


Granite Only

Notes: **Special Order - Lead time is required, minimum quantities apply.** Product is sold on a required, refundable skid. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at [www.unilock.com](http://www.unilock.com).  
All measurements are nominal. Contact Unilock for more information.

# U-Cara® Multi-Face Wall System



## APPLICATIONS



## TECHNOLOGIES










- ENDURACOLOR™**  
Refined surface and long-lasting color
- COLORFUSION™** (Umbriano)  
Subtly mottled colored finish

## APPEARANCE

- Edge Detail - n/a
- Surface Texture - Smooth, Standard, Series Exposed, Umbriano Mottled & Pitched

## TECHNICAL INFORMATION

- Conforms to ASTM C1372
- Eligible for LEED v4.1 credits - see page 19.

Pitched Finish			
	FOSSIL	STEEL MOUNTAIN	
Smooth Finish			
	OPAL SPECIAL ORDER	FOSSIL <b>NEW</b>	STEEL MOUNTAIN
Series Finish		<b>SERIES™ FINISH</b> Granite, Quartz and Marble surface materials	
	ONYX BLACK 3" panel only		
Umbriano Finish			
	FRENCH GREY SPECIAL ORDER	SUMMER WHEAT SPECIAL ORDER	WINTER MARVEL SPECIAL ORDER
	<b>UMBRIANO® FINISH</b> <b>COLORFUSION™</b> Subtly mottled color finish		

# U-Cara® Multi-Face Wall System

		Standard 6" Fascia Panel Smooth	Closed-End Fascia Panel Smooth	Standard 3" Fascia Panel Series Exposed	Standard 6" Fascia Panel Pitched	Closed-End Fascia Panel Pitched
<b>Bundle Type</b>		SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced		NEW YORK	NEW YORK	CHICAGO	NEW YORK	NEW YORK
Thickness (mm)		150MM	150MM	71MM	150MM	150MM
<b>FCFT PER</b>	Bundle	61.52	45.15	59.32	61.52	45.15
	Layer	10.25	9.03	9.89	10.25	9.03
	Stone	0.73	1.29	0.18	0.73	1.29
<b>PER BUNDLE</b>	Layers	6.00	5.00	6.00	6.00	5.00
	Sections	6.00	-	6.00	6.00	5.00
<b>LNFT PER</b>	Bundle	129.50	74.95	-	129.50	89.95
	Unit	1.54	2.14	-	1.54	2.57
<b>UNITS PER</b>	SqFt	1.37	0.78	5.66	1.37	0.78
	Section	14.00	-	56.00	14.00	7.00
	Bundle	84.00	35.00	336.00	84.00	35.00
<b>LBS PER</b>	Layer	274	207	250	291	236
	Section	274	-	250	291	236
	Bundle	1,647	1,033	1,501	1,745	1,179
<b>COLORS</b>		<b>Stock</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>	<b>Stock</b>
Fossil (P)	SR.n/a SRI n/a				✓	✓
Steel Mountain (P)	SR.n/a SRI n/a				✓	✓
Fossil (SM)	SR.n/a SRI n/a	✓	✓			
Opal (SM)	SR.n/a SRI n/a	SO	SO			
Steel Mountain (SM)	SR.n/a SRI n/a	✓	✓			
Onyx Black (SER)	SR.n/a SRI n/a			✓		


Fascia Panels		<b>6" STANDARD FASCIA PANEL</b> 5 7/8" x 18 3/8" x 2 3/8" 150 x 466 x 60mm 84 units/Bundle .73 Sq.Ft./Stone		<b>3" FASCIA PANEL</b> 2 7/8" x 9" x 2 3/8" 71 x 231 x 60mm 336 units/Bundle .18 Sq.Ft./Stone
2 Unit Corner		<b>STANDARD FASCIA HALF PANEL</b> 5 7/8" x 9 1/4" x 2 3/8" 150 x 233 x 60mm 42 units/Bundle 1.29 Sq.Ft./Stone		<b>CLOSED-END FASCIA PANEL</b> 5 7/8" x 20 7/8" x 2 3/8" 150 x 530 x 60mm 42 units/Bundle 1.29 Sq.Ft./Stone

Notes: **Special Order - Lead time is required, minimum quantities apply.** Sold in full bundles. Produced and sold on a required refundable skids. Opal Corner Bundle Only - 54.2 Face Feet/Bundle; contact Customer Service for details.

# U-Cara® Multi-Face Wall System



## APPLICATIONS



## ENDURACOLOR™

Refined surface and long-lasting color

## COLORFUSION™

Subtly mottled colored finish

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits - see page 19.


## CROSS SECTIONS

All Cross Sections are available on Unilock's Contractor web site under Products:  
[contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a  
Surface Texture - Smooth,  
Standard, Series™ Exposed,  
Umbriano® Mottled & Pitched


## U-CARA RETAINING WALL GEOGRID SECTION



## U-CARA™

### CROSS SECTION

Garden Wall - Max Height 15"




Notes:  
This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

## U-CARA™

### CROSS SECTION

Seat Wall - Max Height 21"



Notes:  
This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

# U-Cara® Multi-Face Wall System

## Components



**SURE TRACK  
CORNER BACKER**  
6 x 7 x 12"  
150 x 175 x 300mm



**SURE TRACK  
LARGE BACKER**  
6 x 7½ x 12"  
150 x 190 x 300mm



**SURE TRACK  
STANDARD BACKER**  
6 x 8 x 6"  
150 x 200 x 150mm

	LARGE/CORNER/ PILLAR BACKER	LARGE BACKER	STANDARD BACKER
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE
Plant Produced	OHIO	UXBRIDGE	OHIO
Thickness (mm)	150MM	150MM	150MM

<b>FCFT PER</b>	Bundle	15.82	20.35	33.91
	Layer	3.96	6.78	11.30
	Stone	0.28	0.32	0.32

<b>PER BUNDLE</b>	Layers	4.00	3.00	3.00
	Sections	-	3.00	-

<b>LNFT PER</b>	Bundle	-	41.34	69.99
	Unit	-	0.66	0.67

<b>UNITS PER</b>	SqFt	3.54	3.10	3.10
	Section	-	21.00	-
	Bundle	56.00	63.00	105.00

<b>LBS PER</b>	Layer	498	878	773
	Section	-	878	-
	Bundle	1,992	2,635	2,320

## Recommended Base Unit



**UNIVERSAL BASE UNIT**  
14 x 19 x 2"  
355 x 482 x 55mm

## Extra Components




**SURE TRACK  
CORNER INSERT**  
L = 2"  
50mm

Notes: Product is shipped on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.




# U-Cara® Modular System

The U-Cara Modular System offers a variety of aluminum frames that can be mixed and matched to construct vertical features like grill islands. Speak to your contractor to select a design and a U-Cara fascia panel finish to suit your project.



**With the U-Cara Modular System you can build Grill Islands, Bars, Back splashes, Fire Tables and Pillars.**



NO.	MODEL	DESCRIPTION
RS-UCARA000001	URS	UCARA 8" RAIL (10/PACK)
RS-UCARA000002	URS	ALIGNMENT BARS 39" (10/PACK)
RS-UCARA001000	UL-GC	UNIVERSAL GRILL CABINET
RS-UCARA002000	UL-BC	BASE CABINET
RS-UCARA003000	UL-CC	CORNER CABINET 27.5" x 27.5"
RS-UCARA003001	UL-CCOS	CORNER CABINET 27.5" x 36.5" OS
RS-UCARA003002	UL-CCBP	CORNER CABINET PANEL
RS-UCARA004000	UL-ECK	END CLAD KIT 27.5"
RS-UCARA004001	UL-ECKOS	END CLAD KIT 36.5" OS
RS-UCARA005000	UL-BS	BACKSPLASH-GRILL/BASE UNIT
RS-UCARA005001	UL-BSCC	BACKSPLASH CORNER CABINET
RS-UCARA005002	UL-BSCCOS	BACKSPLASH CORNER CABINET OS
RS-UCARA006000	UL-DD	STAINLESS DOUBLE ACCESS DOORS 27"
RL-UCARA007000	UL-PU	PILLAR UNIT



**LOOKING FOR MORE INFORMATION?**  
Visit [Unilock.com](http://Unilock.com) to download the U-Cara Modular System Brochure.



## U-Cara® Rail System

---



The U-Cara Wall Mount System allows you to put the finishing touches on your project by cladding existing structures like unsightly exposed foundation areas or concrete steps with U-Cara fascia panels.



U-CARA ALIGNMENT BAR:  
39" LENGTH - SOLD IN PACKS OF 10 PIECES

U-CARA RAILS:  
8' LENGTH - SOLD IN PACKS OF 10 PIECES



# Architectural Pillar Cap

ENDURACOLOR™



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth

Joint Spacing - 3mm

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits - see page 19.

	PILLAR CAP 28" SMOOTH ENDURACOLOR	
	<b>Bundle Type</b>	<b>SINGLE</b>
	Plant Produced	NEW YORK
	Thickness (mm)	<b>76MM</b>

<b>SQFT PER</b>	Bundle	3.06
	Layer	0.77
	Stone	0.77


<b>PER BUNDLE</b>	Layers	4.00
	Sections	-

<b>LNFT PER</b>	Bundle	9.36
	Unit	2.34

<b>UNITS PER</b>	SqFt	1.31
	Section	-
	Bundle	4.00

<b>LBS PER</b>	Layer	234
	Section	-
	Bundle	935

<b>COLORS</b>		<b>Stock</b>
Light Grey	SR n/a SRI n/a	✓
Midnight Charcoal	SR n/a SRI n/a	✓



LIGHT GREY



MIDNIGHT CHARCOAL

Single Unit



### PILLAR CAP

711 x 100mm x 711mm

28 x 3 7/8 x 28"

4 unit/Bundle

.77 Fc.Ft./Stone

Notes: Product is shipped on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.





### APPLICATIONS



### APPEARANCE

Edge Detail - Zero  
Surface Texture - Smooth  
Joint Spacing - 2mm

### TECHNOLOGIES

#### CLASSIC™

Budget-friendly traditional product mix

#### ANTIQUED™

Distressed, timeworn finish

### TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits – see page 19.

	FULLNOSE EDGER CLASSIC SMOOTH
Bundle Type	SINGLE
Plant Produced	UXBRIDGE
Thickness (mm)	70MM

FCFT PER	Bundle	-
	Layer	-
	Stone	-

PER BUNDLE	Layers	-
	Sections	4.00

LNFT PER	Bundle	96.00
	Unit	0.50

UNITS PER	SqFt	-
	Section	48.00
	Bundle	192.00

LBS PER	Layer	-
	Section	704
	Bundle	2,815


COLORS		Stock
Almond Grove	SR. n/a SRI n/a	✓
Charcoal	SR. n/a SRI n/a	✓
Limestone	SR. n/a SRI n/a	✓



ALMOND GROVE



CHARCOAL



LIMESTONE

Single Unit



**FULLNOSE EDGER**  
150 x 300 x 70mm  
5 7/8 x 11 7/8 x 2 3/4"  
192 unit/Bundle

Notes: Units can be adhered to pool edge using Unilock Concrete Adhesive, or with mortar. Always observe proper construction techniques when adhering pavers to a surface. Consult your local pool contractors for installation specifics.



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a

Surface Texture - Textured

## TECHNOLOGIES

### REALA™

Cast from historic street pavers

### STONEMARK™

Natural stone appearance

## TECHNICAL INFORMATION

Conforms to ASTM C 1776

Eligible for LEED v4.1 credits – see page 19.

	FULLNOSE COPING	STANDARD COPING	STANDARD CLOSED-END	LARGE COPING	LARGE CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	60MM	70MM	70MM	70MM	70MM

FCFT PER	Bundle	5.12	5.52	5.52	6.87	6.87
	Layer	-	-	-	-	-
	Stone	0.39	0.46	0.46	0.57	0.57

PER BUNDLE	Layers	-	-	-	-	-
	Sections	13.00	12.00	12.00	12.00	12.00

LNFT PER	Bundle	26.00	24.00	24.00	30.00	30.00
	Unit	2.00	2.00	2.00	2.50	2.50

UNITS PER	SqFt	2.54	2.18	2.18	1.75	1.75
	Section	1.00	1.00	1.00	1.00	1.00
	Bundle	13.00	12.00	12.00	12.00	12.00

LBS PER	Layer	-	-	-	-	-
	Section	167	64	66	94	93
	Bundle	2,169	772	796	1,128	1,116

COLORS		Stock	Stock	Stock	Stock	Stock
Buff	SR.n/a SRI n/a	✓	✓	✓	✓	✓
Grey	SR.n/a SRI n/a	✓	✓	✓	✓	✓



BUFF



GREY

Single Units					
	<b>FULLNOSE COPING</b>	<b>STANDARD COPING</b>	<b>STANDARD CLOSED-END COPING</b>	<b>LARGE COPING</b>	<b>LARGE CLOSED-END COPING</b>
	610 x 305 x 60mm	610 x 305 x 70mm	610 x 305 x 70mm	762 x 343 x 70mm	762 x 343 x 70mm
	24 x 12 x 2 3/8"	24 x 12 x 2 3/4"	24 x 12 x 2 3/8"	30 x 13 1/2 x 2 3/4"	30 x 13 1/2 x 2 3/4"
	13 unit/Bundle	12 unit/Bundle	12 unit/Bundle	12 unit/Bundle	12 unit/Bundle
	.39 Fc.Ft./Stone	.46 Fc.Ft./Stone	.46 Fc.Ft./Stone	.57 Fc.Ft./Stone	.57 Fc.Ft./Stone

Notes: This product is produced and sold on a required, refundable skid. Coping is rock faced on the front and the back; Closed-end coping and steps are rock faced on three sides. See page 85 for caulk information. All measurements are nominal. Contact Unilock for more information.



# Ledgestone™ Pillar Cap

STONEMARK™



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a

Surface Texture - Textured

## TECHNOLOGIES

### REALA™

Cast from historic street pavers

### STONEMARK™

Natural stone appearance

## TECHNICAL INFORMATION

Conforms to ASTM C 1776

Eligible for LEED v4.1 credits - see page 19.

	24" PILLAR CAP
Bundle Type	SINGLE
Plant Produced	CHICAGO
Thickness (mm)	100MM

FCFT PER	Bundle	3.28
	Layer	0.66
	Stone	0.66

PER BUNDLE	Layers	5.00
	Sections	-

LNFT PER	Bundle	10.04
	Unit	2.01

UNITS PER	SqFt	1.52
	Section	-
	Bundle	5.00

LBS PER	Layer	159
	Section	-
	Bundle	795

COLORS		Stock
Buff	SR.n/a SRI n/a	✓
Grey	SR.n/a SRI n/a	✓



BUFF



GREY

Single Units



### 24" PILLAR CAP

610 x 610 x 100mm

24 x 24 x 3 7/8"

5 unit/Bundle

.66 Fc.Ft./Stone

Notes: This product is produced and sold on a required, refundable skid. Coping is rock faced on the front and the back; Closed-end coping and steps are rock faced on three sides. All measurements are nominal. Contact Unilock for more information.

LDG\_CH

# Universal Coping & Base

**CLASSIC ENDURACOLOR™**



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a

Surface Texture - Standard / Smooth

## TECHNOLOGIES

### CLASSIC™ (Base)

Budget-friendly traditional product mix

### ENDURACOLOR™ (Coping)

Refined surface and long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits - see page 19.

	UNIVERSAL BASE CLASSIC	UNIVERSAL COPING SMOOTH ENDURACOLOR
Bundle Type	SINGLE	SINGLE
Plant Produced	UXBRIDGE	NEW YORK
Thickness (mm)	55MM	70MM

FCFT PER	Bundle	-	17.44
	Layer	-	2.18
	Stone	-	0.36


PER BUNDLE	Layers	9.00	8.00
	Sections	-	-

LNFT PER	Bundle	85.50	75.90
	Unit	1.58	1.58

UNITS PER	SqFt	-	2.75
	Section	-	-
	Bundle	54.00	48.00

LBS PER	Layer	278	358
	Section	-	-
	Bundle	2,502	2,864

COLORS		Stock	Stock
Light Grey	SR.n/a SRI n/a		✓
Midnight Charcoal	SR.n/a SRI n/a		✓
Natural	SR.n/a SRI n/a	✓	



CHARCOAL (COPING)



LIGHT GREY (COPING)



NATURAL (BASE)

Single Units



### UNIVERSAL COPING

482 x 70 x 355mm

19 x 2 ¾ x 14"

48 units/Bundle

.36 Fc.Ft./Stone



### UNIVERSAL BASE

482 x 55 x 355mm

19 x 2 ¼ x 14"

54 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is shipped on a required, refundable skid. Two (2) End Coping units per Layer (1 Left & 1 Right). All measurements are nominal. Contact Unilock for more information.

# Sunset Fire Pit Kit

CLASSIC



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Standard  
Joint Spacing - n/a  
Void % - n/a

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

### ANTIQUED™

Distressed, timeworn finish

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits - see page 19.

	SUNSET SQUARE W / INSERT	SUNSET ROUND W / INSERT
Bundle Type	SINGLE	SINGLE
Dimension Metric	1100 x 1100 x 400mm	1300 x 1300 x 400mm
Dimension Imperial	43 3/8 x 43 3/8 x 15 3/4"	51 1/4 x 51 1/4 x 15 3/4"
Thickness (mm)		300MM

DIAMETER (inch)	Outside	43	52
	Inside	29	36
	Insert	27	35

LAYER PER UNIT	4	4
UNIT PER LAYER	12	18
UNIT PER PALLET	48	72

LBS PER PALLET	1,357	1,499
----------------	-------	-------

COLORS		Stock	Stock
Almond Grove	SR. n/a SRI n/a	✓	✓
Limestone	SR. n/a SRI n/a	✓	✓



### FIRE PIT GRILL

Select fire pit kits come with a fire pit grill that fits securely into the fire pit. Sold separately. See more fire pit accessories on page 92.



ALMOND GROVE



LIMESTONE

Single Unit



### SUNSET SQUARE W/INSERT

1100 x 1100 x 300mm  
43 3/8 x 43 3/8 x 15 3/4"



### SUNSET ROUND W/INSERT

1300 x 1300 x 300mm  
51 1/4 x 51 1/4 x 15 3/4"

## FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

Notes: All measurements are nominal. Contact Unilock for more information.

# RomanStack™ Fire Pit Kit

CLASSIC



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Standard  
Joint Spacing - n/a  
Void % - n/a

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

### ANTIQUED™

Distressed, timeworn finish

## TECHNICAL INFORMATION


Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits - see page 19.



ALMOND GROVE



GRANITE



### UNILOCK REDUCED SMOKE INSERT

SELECTED FIRE PITS AVAILABLE WITH ZENTRO TECHNOLOGY FIRE PIT INSERT

There's nothing like relaxing around a firepit to bring family and friends closer together. But with ordinary firepits, smoke always blows in someone's face - usually yours. With Unilock Reduced Smoke Inserts, stinging eyes are a thing of the past. Zentro's patent-pending technology returns smoke before it gets anywhere near your eyes. Say hello to good times and good-bye to smoke.

The following accessories are available for any fire pit kit.  
Contact your local Territory Manager for details.



ROUND FIRE SCREEN  
(works with Sunset Round only)



24" SWING AWAY GRILL  
(works with Sunset Round only)



KETTLE HOOK



ACCESSORY POST  
WITH COLLAR

Single Unit



**ROMANSTACK ROUND W/INSERT**  
1525 x 1525 x 400mm  
60 x 60 x 15 3/4"

## FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

Notes: All measurements are nominal. Contact Unilock for more information.

# UniCare Natural Stone Cleaners & Sealers

For more information, visit  
[www.unicare-products.com](http://www.unicare-products.com)



## UNICARE NATURAL STONE ACID CLEAN

1L and 5L

Removal of:

- Cement Staining
- Efflorescence
- Iron Oxide (Rust)
- Cement mortar
- Grout

Note: Never use hydrochloric or sulphuric acid based products. **ONLY FOR ACID RESISTANT STONE.**

Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.



## UNICARE NATURAL POWER CLEAN

1L and 5L

Removal of:

- Oil & Grease
- Food Stains
- General Dirt & Mud
- Light cement contamination (on acid sensitive surfaces)
- Sap & certain plant stains

Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.



## UNICARE BIOCLEAN

1L and 5L

Removal of:

- Black spot algae
- Green algae
- Plant stains from leaves, wood, trees, berries & flowers
- Organic staining from bark & compost
- Colored stains from food spillages, tea, coffee and wine

Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.



## UNICARE NATURAL STONE NATCOLORENHANCE SEALER

1L and 5L

Color Enhancement For Porous Stones

- No surface coating, sheen or shine
- Breathable
- Lasts several years
- Easy to apply

Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.



## UNICARE NATURAL STONE NATMATTE SEALER

1L and 5L

For Porous Stones

- No change of color
- No surface coating, sheen or shine at all
- Riven Sandstone & Smooth Sandstone

Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.

## Cleaners



### SUREBOND EFFLO OFF

**Description:** Efflo Off is a technologically advanced concentrated blend of buffered, non-acid organic salts and additives designed for the removal of efflorescence, mineral and salt deposits from virtually any type of hardscape surface with minimal or no brushing. Efflo Off is mild but may be corrosive to certain woods, metals and plants. Covering and protecting surrounding surfaces during application may be required.

Packaging 1 gallon • Box of 4 x 1 gallon containers



### SUREBOND OIL EXTRACTOR

**Description:** Oil Extractor is a powerful solvent based oil spot cleaner with an advanced biodegradable formula that dissolves, encapsulates, and removes petroleum and food based oil and grease particles from the surface.

Packaging 1 gallon • Box of 4 x 1 gallon containers



### TECHNISEAL ORGANIC STAIN REMOVER

**Description:** Formulated to remove moss and mildew as well as tough organic stains such as dead leaves, blood, wine and non-greasy food stains on concrete pavers, slabs and walls, natural stone, etc; requires minimum scrubbing

Packaging 700g • Box of 6 x 700 g • 500 units per skid

Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.



## Cleaners (continued)



### TECHNISEAL SR SLURRY REMOVER FOR PAVERS AND SLABS

**Description:** This is the most effective product available for removing cement slurry and polymeric sand haze on concrete or clay pavers and slabs. 1 gallon of concentrated product cleans up to 600 sq.ft. Coverage will depend on surface condition and product dilution.

**Packaging** 1 gallon • Box of 4 x 1 US gallon

**Note:** Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.

## Sealers



### SUREBOND 1300 JOINT SAND STABILIZING SEALER - MATTE FINISH

Surebond Joint Stabilizing Sealer is an epoxy modified, single component VOC, EPA and OSHA compliant, solvent-free penetrating sealer that provides protection to interlocking paving stone installations against salt spray, acid rain, food and beverage stains, and other oxidizers. It binds joint sand together and ensures the integrity of the pavements by forming a homogeneous, flexible surface that stops erosion and joint sand failure in large paver installations. The sealer is also used to seal retaining walls and for concrete and aggregate and split-face stone to protect against staining salt spray and acid rain damage and discoloration for architectural, industrial, and residential installations.

**Packaging:** • 1 and 5 gallon containers available • 55 gallon drum available on special order.

**Note:** Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.



### SUREBOND 7700 JOINT SAND STABILIZING SEALER - GLOSS FINISH WITH ANTIFUNGAL PROTECTION

Seals the surface and bonds joint sand between interlocking concrete pavers. Protects colored, stained and exposed aggregate concrete from staining. Resists acid, salt, other corrosives and weathering. Stabilizing Sealer is water based, single component and epoxy-modified. It exceeds all VOC and EPA standards. The product is non-hazardous and has the consistency of water. It is milky white in appearance when applied, and dries crystal clear creating a semi-gloss finish.

**Packaging:** • 1 and 5 gallon available • 55 gallon drum available on special order

**Note:** Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.



### SUREBOND 8700 WET LOOK JOINT SAND STABILIZER WITH FUNGICIDE

SB-8700 is an advanced premium acrylic sealer that will not yellow under exposure to sunlight. It's a 2 in 1 product; it protects the substrate surface and stabilizes jointing sand at the same time. Specially formulated with antifungal agents designed to help inhibit the growth of mold, fungi and moss on horizontal pavement surfaces, it forms a tenacious bond to the concrete or masonry surface. Wet look, Rain safe within 90 minutes, water repellant, breathable, solvent based.

**Packaging:**

• 1 gallon container	• 36 cases per skid (of 1 gal)
• 5 gallon pail (36 per skid)	• 80-120 sq.ft. coverage per gallon for pavers (approx.)*
• 55 gallon container (4 per skid)	• 100-300 sq.ft. coverage per gallon for natural stone (approx.)*
• Box of 4 x 1 gallon containers (4 x 1 US gal)	

## Adhesive



### SB-10 PAVER BOND ADHESIVE

#### High Strength Structural Grade Hardscape Adhesive

10 oz. Caulk Tube: 20' at 1/4" Bead (Case of 12)      28 oz. Caulk Tube: 50' at 1/4" Bead (Case of 12)

Ideal for step veneering and retaining wall cap securement.


**SPECIFICATIONS** - (Conforms to UN-STD. 1804, ASTM 2339-70 & FHA UM-60)

**Color:** Natural Sand Color      **Viscosity:** Smooth Easy Gun Grade Mastic

**CLEANUP:** Use mineral spirits or chlorinated solvents - read solvent supplier's caution notes for use of this product.

**STORAGE:** Store in cool place, rotate stock. Keep at 70°F for 24 hours before use in cold weather. Store cartridges upright. Product does not have a flash point after it dries.

## X & T Slab Spacers



Unilock recommends using slab spacers when installing Arcana on an open grade surface. "T" spacers are needed for running bond patterns, "X" spacers are needed for stack bond patterns. Please contact your sales manager for more information.

### X & T SLAB SPACERS

- 250 per bag
- X & T bagged separately
- X spacers 2" x 2" (RS-ACC237)
- T spacers 2" x 1" (RS-ACC236)

# Sands



## POLYBIND SAND

**NO DUST • HAZE FREE • NO BLOWER • ONE WATERING**

Designed for paver joints up to a maximum of 1".

Polybind Sand is a unique mixture of polymer binders and calibrated sand available in Nevada Tan and Oxford Grey. The installation of Polybind Sand is almost identical to using regular paver joint sand except for the application of water. Once Polybind Sand sets, it becomes very firm and locks between the paver joints while still retaining flexibility and providing a long lasting, durable jointing material. Polybind Sand is recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements etc. Colors: Oxford Grey & Nevada Tan.

Packaging: 50lb Bag 56 bags per skid • 65-85 sq. ft. coverage per bag for narrow joints, larger joints will require more sand.



## POLYBIND G2 SAND

**NO DUST • HAZE FREE • NO BLOWER • ONE WATERING**

Designed for paver joints up to a maximum of 2 inches.

Polybind G2 Sand is a unique mixture of polymer binders and calibrated sand available in Nevada Tan & Oxford Grey. The installation of Polybind Sand is almost identical to using regular paver joint sand, except for the application of water. Once it sets, it becomes very firm and locks between the paver joints. This firm bond maintains pavers securely in place, being equally effective on both horizontal and sloped surfaces. Colors: Oxford Grey and Nevada Tan

Packaging: 50 lb bag / 56 bags per skid • 65-85 sq.ft. coverage per bag for narrow joints, larger joints will require more sand



## POLYBIND COMPLETE G2 SAND

**NO DUST • HAZE FREE • NO BLOWER • ONE WATERING**

Designed for paver joints up to a maximum of 4 inches.

Polybind G2 Sand is a unique mixture of polymer binders and calibrated sand available in Nevada Tan & Oxford Grey. The installation of Polybind Sand is almost identical to using regular paver joint sand, except for the application of water. Once it sets, it becomes very firm and locks between the paver joints. This firm bond maintains pavers securely in place, being equally effective on both horizontal and sloped surfaces. It sets above the freezing temperature 32°F and can be used for joints up to a maximum of 4 in. Colors: Nevada Tan & Oxford Grey

Packaging: 50 lb/bag / 56 bags per skid • 65-85 sq.ft./bag for narrow joints, larger joints will require more sand



## SABLE MARCO EV EVOLUTION

EV EVOLUTION polymeric sand is a specially formulated high performance mix of graded sand and binding agent to fill pavers joints. Its superior performance and durability is ideal for the installation of pavers or slabs as well as replacing existing joints on sidewalks, patios, sloped driveways or walkways. It will remain stable and flexible and maintain its flexibility and durability in the most extreme weather conditions. Three natural Colors: grey, beige & black (contains no pigment or dyes).

Packaging: 50 lb bags / 63 bags per skid (3150 lbs/skid) • Approximately 120 sq. ft./container. Coverage will vary depending on the type/size of stone used.

**Note:** Extra care must be exercised when using on Courtstone, Copthorne, Richcliff and Town Hall. This product is not recommended for Il Campo, Series or Umbriano.



## TECHNISEAL® HP NEXTGEL POLYMERIC SAND **NEW**

Designed for paver joints up to a maximum of 1 inch.

This paver sand is a high-performance polymer sand - it is the ideal product for heavy traffic and wet areas. Weeds and insects in paver joints is part of the past with this high-end product. This polymer sand is a mixture of graded sand (ASTM C144) and binder. It penetrates easily into joints, ensuring a fast and efficient jointing solution. This easy to use jointing sand will start to harden in minutes after water activation, and it quickly becomes resistant to erosion caused by water (rain, sprinklers and spray). Colors: Urban Grey, Granite Grey and Tan

Packaging: 50 lb bag / 56 bags per skid • 65-85 sq.ft. coverage per bag for narrow joints, larger joints will require more sand



## GATOR NITRO SAND **NEW**

40 lb (18.1kg) , 48 units/pallet

A ready-to-use mixture of calibrated sand and resins which cure when exposed to air, hardening from top to bottom of the joint. Can be installed in wet or dry weather, in joints ranging from a minimum 3/16" (5mm) to a maximum 2" (50mm) joint width. The minimum joint depth is 1" (25mm). Color: Beige, Grey and Black

Packaging: 40 lb / 48 units per pallet • Coverage per 40 lb: yields approximately 10-56 square feet depending on joint size

## Sands (continued)

		SAND RECOMMENDATIONS BY PRODUCT
Sands		Polymeric Sand
PAVERS \ FEATURES	For joints up to 1" May be sealed. Available in Tan, Black or Grey Binding Sand	
Artline™		✓+
Beacon Hill Flagstone™		✓
Beacon Hill Smooth		✓
Bristol Valley™		✓+
Copthorne®		✓+
Courtstone®		✓+
Il Campo®		N/R
Richcliff®		✓+
Series™		N/R
Senzo™		✓
Town Hall®		✓+
Thornbury™		✓
Transition™		✓
Treo™		✓
Tribeca Cobble		✓+
Umbriano®		✓+
Westport™		✓
Tumbled Pavers		✓
Classic Pavers		✓

N/R - Not Recommended

✓ - Recommended

✓+ - Recommended with Extra Care  
(contact your Territory Manager for more information)

### IMPORTANT NOTICE

**1. DO NOT USE** Polymeric Jointing Sand on the following products: Series™ Il Campo®

If joint stabilization is required, use ordinary jointing sand and apply a stabilizing sealer. **Contact your local Unilock office for recommended sealants and application specifics.**

**2. EXTRA CARE** must be exercised when using Polymeric Sand on the following products:

Courtstone® Copthorne® Richcliff® Senzo™ Town Hall® Tribeca Cobble™ Umbriano®

Unilock's Polymeric Jointing Sand can be used on these products but the fine polymers and binders in Unilock Polymeric Jointing Sand have a natural tendency to adhere to the surface and therefore extra diligence must be taken to pre-clean the surface prior to "wetting the sand in" and squeegee off the surface post application. Failure to do so will result in a "whitish haze" on the surface that is difficult to remove.

**3. IMPORTANT COMPACTION NOTICE:** Always pre-compact the pavers WITHOUT SAND IN THE JOINTS. This will facilitate proper leveling. Polymeric sand can then be swept into the joints. Always use a compactor with a protective membrane attached to the bottom of the plate.

Unilock Polymeric Jointing Sand, cleaners and sealers, must always be applied by a trained and experienced professional. Contact your local Unilock office for training and the most up-to-date best practices.

NOTICE: Unilock does not accept any responsibility for damage to the surface caused by the improper application and use of Unilock polymeric sand, sealers or cleaners.

## Edge Restraints



### PERMA PAVER EDGING

5 Gallon, 75 lb container

Designed to be mixed with water to use - 1 gallon water to 1 container product and is ideal for patios, pool decks and walkways. Better suited to open-graded aggregates, Perma Edge will outlast and out-perform traditional paver edging. It is quicker and easier to use, cutting installation time by 75%. Projects can be compacted and fine-graded immediately after installation.

- Coverage per container: yields approximately 25-30 lineal feet of edging per bucket



### SEK EDGECRETE

50 lb bag

Designed For Open Graded Base & Permeable Applications



Introducing EdgeCrete, SEK-Surebond's Paver Restraint In a Bag. EdgeCrete is a fiber-reinforced, polymer-modified concrete edge restraint designed for paver and natural stone applications on an open-graded or permeable base. Can be used with paver and natural stone applications on a standard base. Just mix 1/2 gallon of water with each 50 lb. bag of EdgeCrete and install using instructions.

- Fiber Reinforced to Resist Cracking
- Polymer Modified for Superior Strength
- Simple to Install - No Spikes Required

# Edge Restraints

## SnapEdge – One-Piece Edging That Does It All!


- Only one part required for straight runs or curved installations
- Built-in connector fastens one piece to the next – convenient 96" size, makes them easy to transport
- Unique 'Snip and Flex' feature speeds installations of curves and corners without pre-planning
- The open design allows a root system to grow through SnapEdge, further reinforcing the installation
- Engineered to provide a strong, easy-to-install edge restraint for concrete/clay pavers
- Nail hole bosses are full-length cylinders. Hammer blows will not fracture or force nail heads through edging



- |                   |                       |                        |
|-------------------|-----------------------|------------------------|
| 1. SnapEdge       | 2. 10" Spiral Spike   | 3. Soil                |
| 4. Turf           | 5. Sand Jointed Paver | 6. Sand Jetting Course |
| 7. Aggregate Base | 8. Compacted Subgrade |                        |

## PermEdge – Permeable Paver Edge Restraint

- Comes fully assembled - no field assembly required
- Installs on top of the stone chip setting bed
- One-piece design for straight and curved applications
- Integral section-to-section connector
- 100% recycled material



## GATOR EDGE RIGID

Gator Edge Rigid is made with 100% Polypropylene Co-Polymer. This will give it great strength as well as providing greater flexibility. Rigid can be locked together with the "Twist & Lock" connection system.

## Strong Lateral Support

A triangular angle at all key points has been engineered to provide a strong lateral support, essential for the load transfer on the paving units. The Rigid model can be modified into a Flex by simply cutting the connector between each triangular angle.

- 1 piece = 8 linear feet
- 1 mini-pack = 6 pieces = 48 linear feet

- 1 master-pack = 4 mini-packs = 192 linear feet
- 1 pallet = 28 master packs = 5,376 linear feet



- 1 piece = 8 linear feet
- 1 bundle = 24 pieces

- 1 bundle = 24 pieces = 192 linear feet
- 1 pallet = 16 bundles = 3,072 linear feet

# PaverSaver Uni Mat



## PAVERSAVER UNI MAT

Universal Design - for use on most compactors

The PaverSaver Uni Mat is made out of a specially formulated urethane rubber. This material is soft enough to protect the paver surface and hard enough to minimally affect travel speed. The universal sizing fits most compactor plates and easily attaches and detaches from the compactor.

# UniLyft™



- Install up to 700 sq. ft. per hour!
- Access tight or narrow areas
- Eliminate the need for a forklift on site
- Reduce labor costs
- Reduce shoulder, hand and knee pain and injury
- Improve your bottom line
- Financing available

Contact your local rep for details



# Silcasystem



16" x 18-1/8" x 1-1/2"

## SILCASYSTEM

This system is ideal for applications where decking materials like wood lumber or composite lumber would have otherwise been the only choice. When connected to wood floor joists, Silca Grate™ grids provide a substructure (sub-floor) for a wide variety of decking materials: stone, brick pavers, slate, travertine pavers, marble or granite. Because it is engineered for strength and easy installation, this durable outdoor flooring makes it possible for residential do it yourself, as well as commercial architects, designers and builders, to create a new, exciting outdoor living space!

# Landscape Fabric and Grid System




## GEOGRID AND FABRICS

Strata 150 - 22.22 sq. yds/roll  
Strata 200 - 200 sq. yds/roll  
Filter Fabric - 6.25' x 360'; 250 sq yds/roll



## LANDSCAPE SPIKES

50lb case



## WHY DRIVEGRID SYSTEM™?

- ✓ Easy to install
- ✓ Inexpensive
- ✓ Reduces overall project cost
- ✓ Proven Tensar® TriAx® Technology



## UNILOCK DRIVEGRID™ SYSTEM

- 120' x 13' Roll, 1,572 Square Feet/Roll, 56 lb/Roll



# Tools and Accessories

	UNITS PER PACKAGE		UNITS PER PACKAGE
<b>ADHESIVES</b>		<b>CLEANERS &amp; SEALERS</b>	
Unilock Adhesive - 10 oz. (by the case)	12 per case	Surebond Efflo Off	1 gallon
Unilock Adhesive - 28 oz. (by the case)	12 per case	Surebond Oil Extractor	1 gallon
<b>EDGE RESTRAINTS</b>		Techniseal Organic Stain Remover	70 oz.
8" Snap Edge	24 pcs/bundle	Techniseal Slurry Remover	1 gallon
10" Spikes (50lb case) by the case only.	250 per case	Unicare NatMatt Sealer	1L
Perma Edge	36 per skid	Unicare NatMatt Sealer	5L
SEK Edgecrete	56 bags per skid	Unicare NatColorEnhance Sealer	1L
<b>GEOGRID AND FABRICS</b>		Unicare NatColorEnhance Sealer	5L
Strata 150 - 22.22 sq. yds/roll	1 roll	Unicare PowerClean	1L
Strata 200 - 200 sq. yds/roll	1 roll	Unicare PowerClean	5L
Filter Fabric - 6.25' x 360' roll	1 roll	Unicare AcidClean	1L
<b>TENSAR TRIAX GEOGRID</b>		Unicare Acid Clean	5L
TX130S - 120' x 13.1' Roll	1 roll	Unicare BioClean	1L
<b>SANDS</b>		Unicare Bio Clean	5L
Sable Marco EV Sand - Beige, Black & Grey	63 bags/skid		
Polybind G2 Sand - Oxford Grey & Nevada Tan	56 bags/skid		
Polybind Complete G2 Sand - Oxford Grey & Nevada Tan	56 bags/skid		
Polybind Sand - Oxford Grey & Nevada Tan	56 bags/skid		
Techniseal HP NextGel Polymeric Sand - Urban Grey, Granite Grey & Tan	56 bags/skid		
Gator Nitro Sand - Grey, Beige & Black	48 units/skid		

## Base Thickness Chart (General)

APPLICATION	GRAVEL BASE	BEDDING COURSE	BACKFILL WIDTH (WALLS ONLY)
PATIOS, WALKWAYS, POOL DECKS	4" - 6" (10cm-15cm)	1" (2.5cm)	
DRIVEWAYS	8" - 12" (20cm - 30cm)	1" (2.5cm)	
STEPS, PLANTERS, RAISED PATIO	6" (15cm)	0 - 1/8" (0cm - 0.3cm)	8" - 12" (20cm - 30cm)
RETAINING WALLS UNDER 18" (45cm)	6" (15cm)	0 - 1/8" (0cm - 0.3cm)	12" (30cm)
RETAINING WALLS OVER 18" (45cm)	6" (15cm)	0 - 1/8" (0cm - 0.3cm)	16" (50cm)
Soil condition - In areas with poor soil conditions, (eg., heavy clay, disturbed soils) increase the depth of the base to provide more stability. Where poor soil conditions exist it may be advisable to contact an engineer when constructing a retaining wall in excess of 24" in height.			

AREA = (LENGTH) X (WIDTH)	METRIC EQUIVALENTS
Area of a Circle = 3.14 x (Radius) x (Radius)	1 inch = 2.5400 centimeters 1 centimeter = 0.3937 inch
Area of a Half Circle = 1.57 x (Radius) x (Radius)	1 foot = 0.3048 meter 1 meter = 39.3701 inches
Area of a Quarter Circle = .78 x (Radius) x (Radius)	1 yard = 0.9144 meter
Area of a Triangle = (1/2 Base) x (Height)	1 sq. foot = 929.030 sq. centimeters
Perimeter of a Circle = 6.28 x (Radius)	1 sq. meter = 1.196 sq. yards
Perimeter of a Half Circle = 3.14 x (Radius)	27 cu feet = 1 cu. yard
Perimeter of a Quarter Circle = 1.57 x (Radius)	

## BEDDING MATERIALS CHART (APPROXIMATE IMPERIAL TONS)

Square Feet	Bedding Course											
	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.3	0.5	0.8	1.0	1.3	1.5	1.8	2.0	2.3	2.5	2.8	3.0
100	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0
150	0.8	1.5	2.3	3.0	3.8	4.5	5.3	6.0	6.8	7.5	8.3	9.0
200	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0
250	1.3	2.5	3.8	5.0	6.3	7.5	8.8	10.0	11.36	12.5	13.8	15.0
300	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0	13.5	15.0	16.5	18.0
350	1.8	3.5	5.3	7.0	8.8	10.5	12.3	14.0	15.8	17.5	19.3	21.0
400	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.2	22.0	24.0
450	2.3	4.5	6.8	9.8	11.3	13.5	15.8	18.0	20.3	22.5	24.8	27.0
500	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	22.5	25.0	27.5	30.0
550	2.8	5.5	8.3	11.0	13.8	16.5	19.3	22.0	24.8	27.5	30.3	33.0
600	3.0	6.0	9.0	12.0	15.0	18.0	21.0	24.0	27.0	30.0	33.0	36.0
650	3.3	6.5	9.8	13.0	16.3	19.5	22.8	26.0	29.3	32.5	35.8	39.0
700	3.5	7.0	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
750	3.8	7.5	11.36	15.0	18.8	22.5	26.3	30.0	33.8	37.5	41.3	45.0
800	4.0	8.0	12.0	16.0	20.0	24.0	28.0	32.0	36.0	40.0	44.0	48.0
850	4.3	8.5	12.8	17.0	21.3	25.5	29.8	34.0	38.3	42.5	46.8	51.0
900	4.5	9.0	13.5	18.0	22.5	27.0	31.5	36.0	40.5	45.0	49.5	54.0
950	4.8	9.5	14.3	19.0	23.8	28.5	33.3	38.0	42.8	47.5	52.3	57.0
1000	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0

## BASE DEPTH CHARTS (CUBIC YARDS)

Square Feet	Bedding Course											
	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.2	0.3	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.5	1.7	1.9
100	0.3	0.6	0.9	1.2	1.5	1.9	2.2	2.5	2.8	3.1	3.4	3.7
150	0.5	0.9	1.4	1.9	2.3	2.8	3.2	3.7	4.2	4.6	5.1	5.6
200	0.6	1.2	1.9	2.5	3.1	3.7	4.3	4.9	5.6	6.2	6.8	7.4
250	0.8	1.5	2.3	3.1	3.9	4.6	5.4	6.2	6.9	7.7	8.5	9.3
300	0.9	1.9	2.8	3.7	4.6	5.6	6.5	7.4	8.3	9.3	10.2	11.1
350	1.1	2.2	3.2	4.3	5.4	6.5	7.6	8.6	9.7	10.8	11.9	13.0
400	1.2	2.5	3.7	4.9	6.2	7.4	8.6	9.9	11.1	12.3	13.6	14.8
450	1.4	2.8	4.2	5.6	6.9	8.3	9.7	11.1	12.5	13.9	15.3	16.7
500	1.5	3.1	4.6	6.2	7.7	9.3	10.8	12.3	13.9	15.4	17.0	18.5
550	1.7	3.4	5.1	6.8	8.5	10.2	11.9	13.6	15.3	17.0	18.7	20.4
600	1.9	3.7	5.6	7.4	9.3	11.1	13.0	14.8	16.7	18.5	20.4	22.2
650	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.1	20.1	22.1	24.1
700	2.2	4.3	6.5	8.6	10.8	13.0	15.1	17.3	19.4	21.6	23.8	25.9
750	2.3	4.6	6.9	9.3	11.6	13.9	16.2	18.5	20.8	23.1	25.5	27.8
800	2.5	4.9	7.4	9.9	12.3	14.8	17.3	19.8	22.2	24.7	27.2	29.6
850	2.6	5.2	7.9	10.5	13.1	15.7	18.4	21.0	23.6	26.2	28.9	31.5
900	2.8	5.6	8.3	11.1	13.9	16.7	19.4	22.2	25.0	27.8	30.6	33.3
950	2.9	5.9	8.8	11.7	14.7	17.6	20.5	23.5	26.4	29.3	32.3	35.2
1000	3.1	6.2	9.3	12.3	15.4	18.5	21.6	24.7	27.8	30.9	34.0	37.0

Actual volume may vary due to type of materials, moisture content, and compaction. Calculation charts and formulas are provided as a service by Unilock for estimating material requirements. Unilock will not be held responsible in any way for resulting product overage or shortage.

## Notes



# INCREASE SALES BY OFFERING A PAYMENT OPTIONS PLAN... ON EVERY PROJECT!

Ultimately, offering payment options inspires more homeowners to complete the project they truly want without delay. When homeowners learn upfront about their payment options, they are less anxious about the potential for a large price tag during the process. **The positive customer experience due to payment arrangement flexibility often results in more and better referrals, creating a cycle of success that's a win-win for everyone.**

**SCAN THE QR CODE FOR MORE  
INFORMATION OR TO CONNECT  
WITH A UNILOCK TERRITORY  
MANAGER FOR MORE INFORMATION.**



# IMPORTANT NOTES

---

## UNILOCK PAVER PATTERNS

This Product Data Guide contains an extensive reference to patterns and designs. The purpose of these pattern swatches is to help the designer plan unique and exceptional designs. The percentages of products shown are based on the pattern and not on bundle configurations. In fact, there may be situations in which a pattern has been created with one particular size of stone, but that stone only comes packaged with two other sizes. This means that the designer will have to plan how the other components are used in the overall plan. This is usually accomplished by adding a border or an accent. As a result, overages or shortages may occur in certain patterns. The designer and/or installer of Unilock products accepts all responsibility for design and all associated costs incurred as a result of applying any of Unilock's suggested design patterns in a project. Please plan your project and review your order carefully prior to ordering.

## TRANSFERABLE LIFETIME GUARANTEE

Unilock provides a Transferable Lifetime Guarantee\* on the structural integrity of our paving stones, slabs and retaining wall units to the original purchaser of the product for residential use. Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Color matching cannot be guaranteed and replacement labor is not included. Proof of purchase is required.

Excessive defective material (over the industry accepted normal of 2% for non-tumbled unit pavers) delivered to the purchaser will be replaced free of charge if a written claim is made within 5 days of delivery from the manufacturer. Such claims will not constitute reason for delaying payment. All goods shall be deemed accepted if completely installed. Inspect concrete products prior to opening bundle packaging to ensure that shape and color are as ordered. Unsatisfactory material must be available for inspection by Unilock to entitle the purchaser to any adjustment or credit. Inspect all concrete units during installation and set aside any which are chipped or cracked to use for any cut pieces required. The color of concrete products may vary significantly between production lots. Always install concrete units from several bundles simultaneously to ensure proper distribution of color. Prior to final compaction, inspect installed pavers for good color distribution. Relocate certain pavers, if necessary, to achieve desired color blend.

\*Transferable Lifetime Guarantee: Register your project within 60 days of your dated proof of purchase to ensure your Unilock Guarantee is fully transferable! Simply go online at [unilock.com](http://unilock.com) and follow instructions. Once processed, you will receive an original Transferable Warranty Certificate for your records.

## PRODUCT HANDLING WARNING

**Bundle Straps Under Tension - Use extreme caution when removing or handling straps.** Always wear gloves, goggles, safety footwear, and protective clothing when removing or handling straps. Failure to do so may result in serious bodily injury or loss of sight.

Cut all concrete products only in well ventilated areas. Inhalation of dust is a serious health risk. A "NIOSH" (US) or a "CSA" (CDN) approved respirator, safety goggles, hearing protectors, and gloves must be worn at all times. Always "wet-cut" or "wet grind" concrete products to minimize dust.

Do not stack bundled concrete products higher than 2 bundles high. Contents of the bundle may be unstable and subject to topple when stacked. Always use extreme caution and appropriate equipment when transporting or storing bundled concrete products. Failure to do so may result in serious bodily injury or death. Always obey gross vehicle weight (GVW) loading limitations and regulations.

Hazard Rating: Fire 0, Health 1, Reactivity 0. See MSDS Concrete Masonry (Pavers). Contact Unilock for complete sheet or view safety information at [Unilock.com](http://Unilock.com).

Unilock assumes no liability or responsibility for loss or damage, resulting from the improper use or handling of our products, or from failure to follow instructions, warnings, and/or advisories on the product label, and on the MSDS sheet.

## TRADEMARK & LEGAL INFORMATION

Umbriano® is a trademark of Metten Stein + Design GmbH & Co KG used under license by Unilock. Unilock Ltd. and Hengestone Holdings, Inc. are the owners or authorized users of all trademarks used in this publication unless otherwise specified.

Colors shown in this brochure should be used only as a guide. Colors should always be chosen from actual samples. Contact your local Unilock representative for color availability in your area. Not all products shown are available at all Unilock locations. Log on to [www.unilock.com](http://www.unilock.com) for availability. Measurements throughout this portfolio are nominal.

©2022 Hengestone Holdings, Inc.





## QUALITY COMMITMENT

Unilock was the first concrete paver manufacturer in North America to offer a Lifetime Guarantee, and since then we have continued to stand behind it to ensure customers are completely satisfied with our products. With almost 2 billion stones in the ground, that's quite the commitment!

Our products are better and stronger than other brands. In fact, our internal standards of manufacturing in the USA and Canada far exceed industry standards set by ASTM (American Society for Testing and Materials) and CSA (Canadian Standards Association) and other European organizations.



### LIFETIME GUARANTEE - RESIDENTIAL

Our Transferable Lifetime Guarantee warrants the structural integrity of Unilock concrete paving stones and retaining wall units when used in residential applications. It covers any structural failure or deterioration of the concrete unit resulting from normal use or from the reasonable application of sodium chloride (common rock salt used for de-icing). StoneMark™ products have the same warranties as Unilock paving stones and retaining walls, but cannot be warranted against damage resulting from de-icing products.

Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Proof of purchase is required. Customers are encouraged to submit receipts to us as soon as their project is complete, using the Unilock Warranty Registration Form on our website (Unilock.com).

Purchasers need to ensure that the product they purchase is appropriate for their intended application; for example, only certain thicknesses of products are appropriate for driveways. Color matching of the replacement product and/or lost time cannot be guaranteed and labor costs related to installing replacement product is not included. Unilock reserves the right to seek a professional diagnosis and opinion to determine the exact cause of the product failure. If the failure falls within our warranty parameters, Unilock will replace the defective product.

**EXCLUSIONS** – Unfortunately, some things are beyond the control of Unilock, and are therefore not covered by this warranty. These include: naturally occurring efflorescence, hazing from polymeric jointing sand, scratching and chipping resulting from snow removal or construction equipment, damage caused by natural or un-natural disasters, or negligence by anyone other than Unilock. The Unilock warranty also does not cover deterioration or damage as a result of poor design or poor installation practices that are contrary to specifications as laid out by ICPI

(Interlocking Concrete Pavement Institute) and the NCMA (National Concrete Masonry Association). For more information please visit [www.icpi.org](http://www.icpi.org) and [www.ncma.org](http://www.ncma.org). Additionally, please refer to the Maintenance, Color and Installation Advisories.

### MAINTENANCE ADVISORY

#### 1. Cleaning and Sealing

As with anything that is outdoors, Unilock products are subject to harsh weather, dust, acid rain, leaf stains, water stains and general wear from foot or vehicular traffic. Therefore, periodic cleaning using environmentally safe detergents designed for cleaning concrete is recommended to maintain a bright, fresh appearance.

To make subsequent cleaning easier and more effective, a concrete sealer can be applied to new or cleaned products to help prevent the penetration of substances that can cause stains.

There are many types of concrete cleaners and sealers on the market. Always read the instructions carefully before using the product to make sure that it will function as expected. Testing first, in a small unobtrusive area, is always a good idea to ensure the results are acceptable. Consult your local hardscape dealer to find the products best suited for your paver or wall installation.



*Visit [Unilock.com](http://Unilock.com) to register for your Transferable Lifetime Guarantee.*

## 2. Winter Maintenance

Snow removal by way of metal blades on plows or shovels will scratch and chip the surface of pavers, causing permanent damage. To mitigate this risk, metal snow clearing blades must always have a polyurethane or rubber cutting edge attached when plowing pavers.

**De-icing Salts** – The use of de-icing products on paver surfaces is important for safety and to help mitigate snow accumulation. Most de-icing products will have some effect on concrete, even if the product label indicates that it is safe on concrete. If you must use a de-icing product, we recommend that you use Sodium Chloride (ordinary rock salt) or Calcium Chloride (for colder climates). Always apply sparingly. The use of de-icing products on StoneMark, wet-cast pavers, slabs or coping may damage the product and therefore is not recommended. Whenever possible use a coarse sand as an anti-slip measure instead of de-icing chemicals.

## COLOR ADVISORY

### 1. Selection

Due to the inherently variable nature of printed materials and digital monitors, Unilock cannot guarantee that products will match the color of printed or online images. Therefore, when making final product selections, decisions should be made based on actual stones which are readily available from Unilock, Authorized Contractors or Authorized Dealers. Most Unilock products are not comprised of a single color, but rather contain blended colors for a more natural appearance. This means that there will be significant color variance from stone to stone, so purchasers should view multiple units together to get a more accurate impression of the overall color.

*Note:* Unilock Natural Stone variations

are outside the control of Unilock. Purchasers of natural stone must be willing to accept this inherent variability.

### 2. Pre-installation checking

Always check the label to ensure that the Unilock product delivered to your project is the product and color ordered. If there is a discrepancy, or if the product inside the packaging doesn't appear to be correct, contact your hardscape dealer before installing any pavers or wall units. If the product is installed, it indicates your acceptance of the products as delivered.

### 3. Blending

If the project requires more than one bundle of product it's always a good idea to draw product from several bundles when installing, as this ensures that any variation between bundles will be seamlessly integrated in the project. When bundles are from different production runs, random selection from multiple bundles is even more important.

### 4. Efflorescence

Efflorescence is a naturally occurring process that may appear as a white or light grey powder on the surface of concrete, clay or natural stone. It is temporary, and will disappear over time. However, if it is bothersome, an efflorescence cleaner can be used to remove it. There is no way to predict or prevent efflorescence. Because it does not compromise the structural integrity of the product, it is not covered by Unilock product warranties.

## INSTALLATION ADVISORY

### 1. Construction Residue

While a certain amount of dirt on pavers and walls is inevitable during the construction phase, installers are strongly encouraged to clean as they go as construction residue can embed in the surface and become difficult

to remove. The slurry produced during wet-saw cutting is particularly stubborn to clean if allowed to dry on the surface of pavers. Unilock warranties do not cover stains caused by a failure to remove construction residue.

### 2. Polymeric Haze

Surface hazing caused by polymeric jointing sand is not the responsibility of Unilock. Polymeric jointing sand should only be installed by an experienced and knowledgeable contractor. Any sand that is left on the surface prior to activation will result in a haze that is very difficult and time-consuming to remove. Only the highest quality, brand name polymeric sand that is guaranteed by the manufacturer should be used.

### 3. Compaction Damage

Both smooth and textured paver surfaces can be scratched by compaction equipment used to 'flatten' a new paver installation. Therefore, metal plate compactors must be fitted with a polyethylene mat to protect the paver surface from becoming scratched, or a superior option is to use a rubber-roller compactor instead. Damage to product surfaces caused by failure to follow these instructions is not covered by Unilock product warranties.

## FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

# PRODUCT DIRECTORY

## UNIT PAVERS

Product	Page	Finish	Pedestrian	Residential Vehicular	Commercial Vehicular	Environmental	For Borders & Accents
ADA Paver	24	S	✓	✓	✓		
Arcana™ EASYCLEAN	25	S	✓				
Artline™ Smooth	26	SM/S	✓	✓			
Artline™ Umbriano EASYCLEAN	27	SM/S	✓	✓			
Beacon Hill™ Flagstone	28-29	F	✓	80mm			
Beacon Hill™ Smooth	30	SM	✓	80mm			
Bristol Valley® EASYCLEAN	31	S	✓				
Cophorne®	32	T	✓	✓			✓
Courtstone®	33	C	✓	✓			✓
Dura-Mat™	34	S			✓	✓	
Eco-Line®	35	CU	✓	✓	✓	✓	
Eco-Optiloc™	36	S	✓	✓	✓	✓	
Eco-Priora™	37	B	✓	✓	✓	✓	
Eco-Promenade™	38	S	✓	✓	✓	✓	
Eco-Stone™	39	CU	✓	✓	✓	✓	✓
Granito™ EASYCLEAN	40	S	✓	✓			
Granito™ Hex	40	S	✓	✓			
Hex Paver	41	S	✓	✓	80mm		
Holland Premier®	42	S	✓	✓			✓
Il Campo®	43	B	✓	✓	✓		✓
Mattoni™ EASYCLEAN	44	T	✓	✓			✓
Natural Stone	45-49	SM	✓				
Optiloc™	50	S	✓	✓	✓		
Porcelain	51	SM	✓				
Promenade® Paver	52	CU	✓	✓	✓		✓
Richcliff®	54	F	✓	✓			✓
Senzo™ EASYCLEAN	55	SM	✓	✓	✓		
Series™	56	WS	✓	✓	✓		✓
Thornbury™ Smooth	57	SM	✓	✓	✓	✓	
Town Hall®	58	T	✓	✓	✓	✓	✓
Transition™	59	F	✓	✓			
Treo® Premier	60	F	✓	✓			
Treo® Smooth	61	S	✓	✓	✓	✓	
Tribeca Cobble	62	W/C	✓	✓		✓	✓
Turfstone™	63	S		✓	✓	✓	
Umbriano™	64-65	SZ	✓	70mm	80mm		✓
Westport™ EASYCLEAN	66	F	✓	✓			✓

## RETAINING WALLS

Product	Page	Finish	Gardens	Retaining Walls	Steps	Seatwalls	Pillars
Brussels Dimensional System™	67	W	✓	✓	✓	✓	✓
Concord Wall™	68	SP	✓	✓	✓		
DuraHold®	69-70	S		✓			
DuraHold2®	71	S		✓			
Estate Wall™	72-76	SP/W	✓		✓	✓	✓
Lineo™ Dimensional Stone	77-78	SZ	✓		✓	✓	✓
SienaStone®	79	SP		✓	✓		
U-Cara®	80-85	Various	✓	✓		✓	✓

Finishes: B=Brushed; C=Cobblestone; CU=Custom; D=Dimpled; DW=Dimpled and Weathered; F=Flagstone; S=Standard; SM=Smooth; SZ=Smooth Zero Bevel; SP=Split; SP/W=Split and Weathered; T=Timeworn; W=Weathered; WS=Washed

This application chart should only be used as a guide. Site conditions, base materials, pattern and frequency of use may vary the performance of various types and styles of products.

**New for 2022**

# UNILOCK HOW-TO GUIDES

Be sure to check out our instructional manuals complete with not only step-by-step instructions but equipment and supply lists, detailed cross sections and diagrams, as well as full color 3D renderings.

**TOPICS INCLUDED:**

- ❑ Patio on Grade
- ❑ Paver Driveway
- ❑ Pool Coping
- ❑ Retaining Wall
- ❑ Outdoor Kitchen
- ❑ Many more coming soon!

**BE SURE TO CHECK BACK REGULARLY  
FOR ADDITIONAL GUIDES.**



PAVER  
INSTALLATION



VERTICAL  
FEATURES



WALL  
INSTALLATION



**SCAN THE QR CODES TO  
VIEW OR DOWNLOAD OUR  
NEW HOW-TO GUIDES**



# Let's **BUILD YOUR BUSINESS** **together.**

Being a hardscape contractor is tough work. No one gets that better than Unilock. We've been supporting hardscaping professionals since 1973, longer than any other company in the industry. Getting our boots dirty is part of our promise to support our Unilock contractors in any way we can. You're never alone - not even on the project site.

**CONTACT 1-800-UNILOCK OR VISIT UNILOCK.COM TO CONNECT  
WITH YOUR LOCAL TERRITORY MANAGER**



**BOSTON**  
(508) 278-4536

**CHICAGO**  
(630) 892-9191

**MILWAUKEE**  
(262) 742-3890

**KANSAS**  
(913) 417-7985

**MICHIGAN**  
(248) 437-7037

**NEW YORK**  
(845) 278-6700

**MID-ATLANTIC**  
(202) 798-2060

**ONTARIO**  
(416) 646-9000

**CINCINNATI/KY/TN**  
(513) 202-0219

**OHIO/WESTERN PA/  
WNY&CNY**  
(330) 927-4000

**UNILOCK.COM | 1-800-UNILOCK**

©2022 Hengestone Holdings, Inc.