


2024

**PRODUCT  
DATA**



TRANSFORMING  
HARDSCAPES

# UNILOCK<sup>®</sup>

## THE **ONE** INNOVATOR WITH GAME-CHANGING PRODUCTS

### **BUILD VERTICALS FASTER**

When the plan calls for pillars, a grill island or any vertical feature, the U-Cara Modular System lets you create customizable features in hours - not days!

Simply build the sturdy, aluminum frame in any configuration and choose from a wide selection of fascia panels to clad it with.



Learn more

**UNI-CARA<sup>®</sup>**  
MODULAR SYSTEM

# TABLE OF CONTENTS - MICHIGAN

## PAVERS

Anchorlock™	4
Artline™	5
Beacon Hill™ Flagstone	6
Beacon Hill™ Smooth	7
Boulevard™	9
Bristol Valley®	10
Brussels Block®	11
Copthorne®	12
Courtstone®	13
Eco-Optiloc™	14
Eco-Priora™	15
Eco-Promenade®	16
Granito™	17
Hex™	18
Hollandstone™	19
Holland Premier™	20
Il Campo®	21
Mattoni™	22
Natural Stone	23
Nordic Cobble™	25
Porcelain	26
Promenade™	28
Promenade EcoTerra™	31
Richcliff®	32
Series™	33
Skyline™	34
Thornbury™	35
Town Hall®	36
Treo® Smooth	37
Tribeca Cobble™	38
Turfstone™	39
Umbriano®	40
Urban™	43
Westport™	44

## RETAINING WALLS

Brussels Dimensional System™	45
DuraHold®	46
DuraHold2®	48
Estate Wall™	49
Lineo™ Dimensional Stone	50
Pisa™	51

Pisa™ Smooth XL	52
Rivercrest® Wall	53
SienaEdge™	54
SienaStone™	55
SienaStone™ Smooth	56
U-Cara® Multi-Face Wall System	58
U-Cara® Modular System	63
U-Cara® Wall Mount System	64

## COPING, STEPS, PILLAR CAPS

Architectural Cap & Coping	67
Brussels Fullnose™	68
Universal Coping & Base Pad	69
Ledgestone™	70
Umbriano® Coping	72

## FIRE FEATURES

Sunset Fire Pit	73
Unilock Elements	74


## ACCESSORIES

Paver Cleaners	76
Natural Stone Cleaners	76
Natural Stone Sealers	76
Paver Sealers	76
Adhesives	77
Sands	78
Edge Restraints	80
DriveGrid, Gator Grid & Gator Base	81
Large Equipment (Unilyft)	82


## PRODUCT & INSTALLATION INFORMATION

Base Thickness Chart	82
Bedding Chart / Basic Depth	83
Finishes	84
Important Notes	86
Unilock's Quality Commitment	88
Product Directory	90

## APPLICATION INDEX



## DESCRIPTION OF EDGE DETAILS





## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfer  
 Surface Texture - Smooth  
 Joint Spacing - 3 mm  
 Void - n/a

## TECHNOLOGIES

### CLASSIC

Budget-friendly traditional product mix

### DRIVE FRIENDLY

Can handle vehicular loads

## TECHNICAL INFORMATION

Conforms to ASTM C936  
 Eligible for LEED v4.1 credits

	<b>8 7/8 x 8 7/8</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN
Thickness (mm)	80 MM

<b>SQFT PER</b>	Bundle	78.80
	Layer	11.26
	Section	-
	Stone	0.42

<b>PER BUNDLE</b>	Layers	7.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-


<b>SAILOR LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>UNITS PER</b>	SqFt	2.37
	Section	-
	Bundle	186.69

<b>LBS PER</b>	Layer	411
	Section	-
	Bundle	2,937

COLORS	Reflectance	Stock
Natural	SR .43 SRI 32	SO

## LAYING PATTERN



Anchorlock A



NATURAL

Single Unit

**STANDARD**  
 225 x 225 x 80mm  
 8 7/8 x 8 7/8 x 3 1/8  
 186.69 units/Bundle  
 .42 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY.** All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Micro  
 Surface Texture - Smooth &  
 Il Campo® Brushed (Granite)  
 Joint Spacing - 3 mm

**TECHNOLOGIES**

**ENDURACOLOR™**  
 Refined surface and long-lasting color

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	SMOOTH FINISH	BRUSHED FINISH
<b>Bundle Type</b>	<b>RANDOM</b>	<b>RANDOM</b>
Plant Produced	MICHIGAN	CHICAGO
Thickness (mm)	70 MM	70 MM

SQFT PER	Bundle	93.25	93.25
	Layer	11.66	11.66
	Section	-	-
	Stone	0.49	0.49

PER BUNDLE	Layers	8.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-


SAILOR LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-

UNITS PER	SqFt	2.06	2.06
	Section	-	-
	Bundle	192.00	192.00

LBS PER	Layer	373	370
	Section	-	-
	Bundle	2,986	2,963

COLORS	Reflectance	Stock	Stock
Birch	SR .28 SRI 30	✓	
Granite (Il Campo)	SR .28 SRI 29		SO
Granite	SR .28 SRI 29	✓	

**LAYING PATTERN**




Artline Fixed  
Random A



BIRCH



GRANITE (IL CAMPO)



GRANITE

7 Unit Random Bundle

**UNIT A**  
 125 x 169 x 70mm  
 4 7/8 x 6 3/4 x 2 3/4"  
 32 units/Bundle  
 .23 Sq.Ft./Stone

**UNIT B**  
 125 x 262.5 x 70mm  
 4 7/8 x 10 3/8 x 2 3/4"  
 32 units/Bundle  
 .35 Sq.Ft./Stone

7 Unit Random Bundle

**UNIT C**  
 125 x 337.5 x 70mm  
 4 7/8 x 13 3/8 x 2 3/4"  
 32 units/Bundle  
 .45 Sq.Ft./Stone

**UNIT D**  
 125 x 450 x 70mm  
 4 7/8 x 17 3/4 x 2 3/4"  
 32 units/Bundle  
 .61 Sq.Ft./Stone

**UNIT E**  
 187.5 x 225 x 70mm  
 7 1/2 x 8 7/8 x 2 3/4"  
 32 units/Bundle  
 .45 Sq.Ft./Stone

**UNIT F**  
 187.5 x 337.5 x 70mm  
 7 1/2 x 13 3/8 x 2 3/4"  
 16 units/Bundle  
 .58 Sq.Ft./Stone

**UNIT G**  
 187.5 x 450 x 70mm  
 7 1/2 x 17 3/4 x 2 3/4"  
 16 units/Bundle  
 .91 Sq.Ft./Stone

Notes: **Il Campo finish is a Special Order Item - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
 Surface Texture - Textured  
 Joint Spacing - 7 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits


## LAYING PATTERNS



Beacon Hill Fixed Random A



Beacon Hill Fixed Random B



Beacon Hill Multi-Unit Random C



BIRCH



FOSSIL



SIERRA

<b>Bundle Type</b>	<b>RANDOM</b>
Plant Produced	MICHIGAN
Thickness (mm)	60 MM

<b>SQFT PER</b>	Bundle	104.91
	Layer	11.66
	Section	-
	Stone	1.46

<b>PER BUNDLE</b>	Layers	9.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>SAILOR LNFT PER</b>	SqFt	0.80
	Section	-
	Layer	9.35
	Bundle	84.15

<b>UNITS PER</b>	SqFt	0.69
	Section	-
	Bundle	72.00

<b>LBS PER</b>	Layer	320
	Section	-
	Bundle	2,879

COLORS	Reflectance	Stock
Birch	SR n/a SRI n/a	✓
Fossil	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

3 Unit Random Bundle



**LARGE RECTANGLE**  
 380 x 570 x 60mm  
 15 x 22 1/2 x 2 3/8"  
 18 Units/Bundle  
 2.08 SqFt/Stone



**SQUARE**  
 380 x 380 x 60mm  
 15 x 15 x 2 3/8"  
 27 units/Bundle  
 1.39 Sq.Ft./Stone



**SMALL RECTANGLE**  
 380 x 190 x 60mm  
 15 x 7 1/2 x 2 3/8"  
 27 units/Bundle  
 .69 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY.** This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
 Surface Texture - Smooth  
 Joint Spacing - 7 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Beacon Hill Fixed Random A

Beacon Hill Fixed Random B

Beacon Hill Multi-Unit Random C

\*Note: 9 layer Beacon Hill XL bundle available while supplies last.



BIRCH

DARK CHARCOAL

FOSSIL

GRANITE

GRINDSTONE

IVORY

OPAL BLEND

			XL	SMALL RECTANGLE
<b>Bundle Type</b>	<b>RANDOM</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN	MICHIGAN	MICHIGAN	MICHIGAN
Thickness (mm)	60 MM	60 MM	60 MM	60 MM

<b>SQFT PER</b>	Bundle	104.91	81.60	104.91
	Layer	11.66	11.66	11.66
	Section	-	-	-
	Stone	1.46	5.83	0.78

<b>PER BUNDLE</b>	Layers	9.00	7.00	9.00
	Sections	-	-	-

<b>SOLDIER LNFT PER</b>	SqFt	-	0.32	0.80
	Section	-	-	-
	Layer	-	3.74	9.35
	Bundle	-	26.18	84.15

<b>SAILOR LNFT PER</b>	SqFt	0.80	0.53	1.60
	Section	-	-	-
	Layer	9.35	6.23	18.70
	Bundle	84.15	43.61	168.31

<b>UNITS PER</b>	SqFt	0.69	0.17	1.29
	Section	-	-	-
	Bundle	72.00	14.00	135.00

<b>LBS PER</b>	Layer	320	320	320
	Section	-	-	-
	Bundle	2,879	2,239	2,879

COLORS	Reflectance	Stock	Stock	Stock
Birch	SR n/a SRI 30	✓	-	-
Dark Charcoal	SR n/a SRI n/a	-	-	✓
Fossil	SR n/a SRI 21	✓	✓	✓
Granite	SR .28 SRI 29	✓	✓	✓
Grindstone	SR n/a SRI n/a	✓	-	-
Ivory	SR n/a SRI n/a	-	-	✓
Opal Blend	SR .24 SRI 24	✓	✓	-

<b>3 Unit Random Bundle</b>				<b>Single Units</b>		
	<b>LARGE RECTANGLE</b> 380 x 570 x 60mm 15 x 22 1/2 x 2 3/8" 18 Units/Bundle	<b>SQUARE</b> 380 x 380 x 60mm 15 x 15 x 2 3/8" 27 units/Bundle	<b>SMALL RECTANGLE</b> 380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 27 units/Bundle		<b>XL UNIT</b> 950 x 570 x 60mm 37 1/2 x 22 1/2 x 2 3/8" 14 units/Bundle 5.83 Sq.Ft./Stone	<b>SMALL RECTANGLE</b> 380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 135 units/Bundle .78 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY.** XL unit is produced and sold on a required refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
 Surface Texture - Smooth  
 Joint Spacing - 7 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Beacon Hill Fixed  
Random A



Beacon Hill Fixed  
Random B



FOSSIL



GRANITE

Bundle Type		RANDOM
Plant Produced		MICHIGAN
Thickness (mm)		80 MM

SQFT PER	Bundle	73.22
	Layer	10.46
	Section	-
	Stone	1.31

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.85
	Section	-
	Layer	8.86
	Bundle	62.01

UNITS PER	SqFt	0.76
	Section	-
	Bundle	56.00

LBS PER	Layer	383
	Section	-
	Bundle	2,679

COLORS	Reflectance	Stock
Fossil	SR n/a SRI 21	✓
Granite	SR .28 SRI 29	✓

3 Unit Random Bundle



**LARGE RECTANGLE**  
 360 x 540 x 80mm  
 14 1/8 x 21 1/4 x 3 1/8"  
 14 Units/Bundle



**SQUARE**  
 360 x 360 x 80mm  
 14 1/8 x 14 1/8 x 3 1/8"  
 21 units/Bundle



**SMALL RECTANGLE**  
 360 x 180 x 80mm  
 14 1/8 x 7 1/8 x 3 1/8"  
 21 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY.** Important: A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Smooth  
 Joint Spacing - 3 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERN



Boulevard Fixed  
 Random B



RIVER

Bundle Type		RANDOM
Plant Produced		MICHIGAN
Thickness (mm)		70 MM

SQFT PER	Bundle	93.00
	Layer	11.63
	Section	-
	Stone	1.45

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	1.03
	Section	-
	Layer	12.00
	Bundle	96.04

UNITS PER	SqFt	0.69
	Section	-
	Bundle	64.00

LBS PER	Layer	372
	Section	-
	Bundle	2,978

COLORS	Reflectance	Stock
River	SR n/a SRI n/a	*

*\*While Supplies Last*

3 Unit Random Bundle



**LARGE RECTANGLE**  
 610 x 305 x 70mm  
 24 x 12 x 2 ¾"  
 24 Units/Bundle  
 2.00 SqFt/Stone



**MEDIUM RECTANGLE**  
 457 x 305 x 70mm  
 18 x 12 x 2 ¾"  
 16 units/Bundle  
 1.50 Sq.Ft./Stone



**SQUARE**  
 305 x 305 x 70mm  
 12 x 12 x 2 ¾"  
 24 units/Bundle  
 1.00 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY.** This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Textured  
 Joint Spacing - 7 mm

## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color

## EASYSOFT™

Factory Sealed to provide integral stain resistance


## COMFORT STEP™

Ultra-smooth surface texture


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Bristol Valley Fixed  
 Random A



Bristol Valley Fixed  
 Random B

<b>Bundle Type</b>	<b>RANDOM</b>
Plant Produced	MARENGO
Thickness (mm)	60 MM

<b>SQFT PER</b>	Bundle	116.57
	Layer	11.66
	Section	-
	Stone	1.46

<b>PER BUNDLE</b>	Layers	10.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>SAILOR LNFT PER</b>	SqFt	0.80
	Section	-
	Layer	9.35
	Bundle	93.50

<b>UNITS PER</b>	SqFt	0.69
	Section	-
	Bundle	80.00

<b>LBS PER</b>	Layer	324
	Section	-
	Bundle	3,241

COLORS	Reflectance	Stock
Bavarian	SR n/a SRI n/a	✓
Fossil	SR n/a SRI n/a	✓
Steel Mountain	SR n/a SRI n/a	✓



BAVARIAN



FOSSIL



STEEL MOUNTAIN

3 Unit Random Bundle



**LARGE RECTANGLE**  
 380 x 570 x 60mm  
 15 x 22 1/2 x 2 3/8"  
 20 Units/Bundle  
 2.08 SqFt./Stone



**SQUARE**  
 380 x 380 x 60mm  
 15 x 15 x 2 3/8"  
 30 units/Bundle  
 1.39 Sq.Ft./Stone



**SMALL RECTANGLE**  
 380 x 190 x 60mm  
 15 x 7 1/2 x 2 3/8"  
 30 units/Bundle  
 .69 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Weathered  
 Joint Spacing - 2 mm

## TECHNOLOGIES

**CLASSIC**  
 Budget-friendly traditional product mix


## ANTIQUED™

Distressed, timeworn finish


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Brussels Multi-Unit  
 Random Y



Brussels Multi-Unit  
 Random X



COFFEE CREEK



CHARCOAL



LIMESTONE



MAHOGANY ASH



SANDSTONE

	HALF	STANDARD	XL
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN	MICHIGAN	MICHIGAN
Thickness (mm)	70 MM	70 MM	70 MM

SQFT PER	Bundle	99.79	95.94	95.94
	Layer	12.47	11.99	9.59
	Section	14.26	15.99	-
	Stone	0.20	0.40	0.80

PER BUNDLE	Layers	8.00	8.00	10.00
	Sections	7.00	6.00	-

SOLDIER LNFT PER	SqFt	1.72	1.42	0.85
	Section	24.57	22.70	-
	Layer	21.50	17.03	8.19
	Bundle	172.00	136.22	81.90

SAILOR LNFT PER	SqFt	2.95	1.71	1.43
	Section	42.04	27.30	-
	Layer	36.79	20.47	13.70
	Bundle	294.30	163.78	137.00

UNITS PER	SqFt	5.05	2.50	1.25
	Section	72.00	40.00	-
	Bundle	504.00	240.00	120.00

LBS PER	Layer	399	384	307
	Section	457	512	-
	Bundle	3,195	3,072	3,072

COLORS	Reflectance	Stock	Stock	Stock
Coffee Creek	SR n/a SRI n/a	✓	✓	✓
Charcoal	SR n/a SRI n/a	✓	-	-
Limestone	SR .28 SRI 29	✓	✓	✓
Mahogany Ash	SR n/a SRI n/a	✓	✓	✓
Sandstone	SR .41 SRI 46	✓	✓	✓

Single Units



**HALF**  
 104 x 173 x 70mm  
 4 1/8 x 6 7/8 x 2 3/4"  
 504 units/Bundle  
 .20 Sq.Ft./Stone



**STANDARD**  
 173 x 208 x 70mm  
 6 7/8 x 8 1/4 x 2 3/4"  
 240 units/Bundle  
 .40 Sq.Ft./Stone



**XL**  
 208 x 348 x 70mm  
 8 1/4 x 13 3/4 x 2 3/4"  
 120 units/Bundle  
 .80 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY. Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
 Surface Texture - Textured  
 Joint Spacing - 3 mm

## TECHNOLOGIES

### EASYCLEAN™

Factory Sealed to provide integral stain resistance

### ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

### REALA™

Cast from historical brick


### ULTIMA™

Up to 4x stronger than poured-in-place concrete


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Copthorne BW A



Copthorne RB C



ARCTIC GREY



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK



STEEL BLUE

<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	AYR
Thickness (mm)	60 MM

<b>SQFT PER</b>	Bundle	89.20
	Layer	11.15
	Section	-
	Stone	0.15

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	1.43
	Section	-
	Layer	15.99
	Bundle	127.95

<b>SAILOR LNFT PER</b>	SqFt	4.41
	Section	-
	Layer	49.21
	Bundle	393.70

<b>UNITS PER</b>	SqFt	6.73
	Section	-
	Bundle	600.00

<b>LBS PER</b>	Layer	294
	Section	-
	Bundle	2,349

COLORS	Reflectance	Stock
Arctic Grey	SR n/a SRI n/a	✓
Basalt	SR n/a SRI n/a	✓
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓
Steel Blue	SR n/a SRI n/a	✓

Single Unit



### STANDARD

65 x 200 x 60mm  
 2 5/8 x 7 7/8 x 2 3/8"  
 600 Units/Bundle  
 .15 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Textured  
 Joint Spacing - 15 mm

## TECHNOLOGIES

### EASYSOFT™

Factory Sealed to provide integral stain resistance

### ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

### REALA™

Cast from European cobblestones

### ULTIMA™

Up to 4x stronger than poured-in-place concrete

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Courtstone Fixed  
 Random A

Bundle Type		RANDOM
Plant Produced		AYR
Thickness (mm)		60 MM

SQFT PER	Bundle	98.30
	Layer	12.29
	Section	-
	Stone	0.26

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	2.25
	Section	-
	Layer	27.69
	Bundle	221.52

UNITS PER	SqFt	3.91
	Section	-
	Bundle	384.00

LBS PER	Layer	291
	Section	-
	Bundle	2,326

COLORS	Reflectance	Stock
Basalt	SR n/a SRI n/a	✓



BASALT

Random Bundle					
	<b>XL RECTANGLE</b>	<b>LARGE RECTANGLE</b>	<b>RECTANGLE</b>	<b>SMALL RECTANGLE</b>	<b>SQUARE</b>
	215 X 130 X 60MM	185 X 130 X 60MM	165 X 130 X 60MM	145 X 130 X 60MM	130 X 130 X 60MM
	8 3/8 X 5 1/8 X 2 3/8"	7 1/4 X 5 1/8 X 2 3/8"	6 1/2 X 5 1/8 X 2 3/8"	5 3/4 X 5 1/8 X 2 3/8"	5 1/8 X 5 1/8 X 2 3/8"
	128 Units/Bundle	64 Units/Bundle	64 Units/Bundle	64 Units/Bundle	64 Units/Bundle
	.30 SqFt/Stone	.28 SqFt/Stone	.23 SqFt/Stone	.20 SqFt/Stone	.18 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Chamfer  
 Surface Texture - Smooth  
 Joint Spacing - 7 mm  
 Void - 7.30%

**TECHNOLOGIES**

**CLASSIC**  
 Budget-friendly traditional product mix

**PERMEABLE**

Can be installed to allow water to flow through

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	STANDARD SMOOTH
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN
Thickness (mm)	80 MM

<b>SQFT PER</b>	Bundle	63.56
	Layer	9.08
	Section	-
	Stone	0.50

<b>PER BUNDLE</b>	Layers	7.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>SAILOR LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>UNITS PER</b>	SqFt	1.98
	Section	-
	Bundle	126.00

<b>LBS PER</b>	Layer	332
	Section	-
	Bundle	2,325

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	SO

**LAYING PATTERN**



Eco-Optiloc Cluster A



NATURAL

Single Unit



**STANDARD**  
 250 x 250 x 80mm  
 9 7/8 x 9 7/8 x 3 1/8"  
 126 units/Bundle  
 .50 Sq.Ft./Stone

Notes: **Special Order Item - Lead time required.** Most standard colors are available by special order and are subject to minimum quantities. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on an optional skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Micro  
 Surface Texture - Smooth  
 Joint Spacing - 7mm  
 Void - 4.6-7.08%

**TECHNOLOGIES**

**CLASSIC**

Budget-friendly traditional product mix

**ENDURACOLOR™**

Refined surface and long-lasting color


**PERMEABLE**

Can be installed to allow water to flow through


**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

**LAYING PATTERNS**



Eco-Priora 5x10  
RB\_A



Eco-Priora 5x10  
HB\_E

	SMOOTH CLASSIC	SMOOTH ENDURACOLOR
Bundle Type	SINGLE	SINGLE
Plant Produced	MICHIGAN	MICHIGAN
Thickness (mm)	80 MM	80 MM

SQFT PER	Bundle	75.95	75.95
	Layer	10.85	10.85
	Section	-	-
	Stone	0.31	0.31

PER BUNDLE	Layers	7.00	7.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	1.27	1.27
	Section	-	-
	Layer	13.78	13.78
	Bundle	96.46	96.46

SAILOR LNFT PER	SqFt	2.54	2.54
	Section	-	-
	Layer	27.56	27.56
	Bundle	192.91	192.91

UNITS PER	SqFt	3.23	3.23
	Section	-	-
	Bundle	245.00	245.00

LBS PER	Layer	397	397
	Section	-	-
	Bundle	2,778	2,778


COLORS	Reflectance	Stock	Stock
Beechwood	SR .n/a SRI n/a	✓	-
Fossil	SR .n/a SRI n/a	-	✓
Granite	SR .26 SRI 27	-	✓



BEECHWOOD



FOSSIL



GRANITE

Single Unit



**RECTANGLE**  
 120 x 240 x 80mm  
 4 ¾ x 9 ½ x 3 ⅛  
 245 units/Bundle  
 .31 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on an optional, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Rounded  
 Surface Texture - Smooth  
 Joint Spacing - 7 mm  
 Void - 10.12%

**TECHNOLOGIES**

**ENDURACOLOR™**  
 Refined surface and long-lasting color


**PERMEABLE**

Can be installed to allow water to flow through


**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits


**LAYING PATTERNS**



Eco-Promenade  
3x12\_RB\_A



Eco-Promenade  
3x12\_DHB\_B



Eco-Promenade  
3x12\_HB\_C

	<b>3 x 12 PERMEABLE SMOOTH</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN
Thickness (mm)	100 MM

<b>SQFT PER</b>	Bundle	63.94
	Layer	10.66
	Section	-
	Stone	0.24

<b>PER BUNDLE</b>	Layers	6.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	1.02
	Section	-
	Layer	10.83
	Bundle	64.96

<b>SAILOR LNFT PER</b>	SqFt	4.06
	Section	-
	Layer	43.31
	Bundle	259.84

<b>UNITS PER</b>	SqFt	4.13
	Section	-
	Bundle	264.00

<b>LBS PER</b>	Layer	482
	Section	-
	Bundle	2,893

COLORS	Reflectance	Stock
Opal Blend	SR .24 SRI 24	SO
Steel Gray	SR .n/a SRI n/a	SO



OPAL BLEND



STEEL GREY

Single Unit



**3 x 12**  
 75 x 300 x 100mm  
 3 x 11<sup>7</sup>/<sub>8</sub> x 3<sup>7</sup>/<sub>8</sub>"  
 264 units/Bundle  
 .24 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on an optional, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



(Note: Hex only is drive friendly)

## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded

Surface Texture - Textured(Random)/ Hex(Smooth)

Joint Spacing - 7 mm

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and long-lasting color

### ARTISTA™

Boldly mottled color finish

### EASYSOAK™

Factory Sealed to provide integral stain resistance

## TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

		<b>8 x 8 HEX</b>	
	<b>Bundle Type</b>	<b>SINGLE</b>	<b>RANDOM</b>
	Plant Produced	PICKERING	PICKERING
	Thickness (mm)	70 MM	60 MM

<b>SQFT PER</b>	Bundle	73.92	94.14
	Layer	9.24	10.46
	Section	-	-
	Stone	0.39	1.31

<b>PER BUNDLE</b>	Layers	8.00	9.00
	Sections	-	-

<b>SOLDIER LNFT PER</b>	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-


<b>SAILOR LNFT PER</b>	SqFt	-	0.85
	Section	-	-
	Layer	-	8.86
	Bundle	-	79.72

<b>UNITS PER</b>	SqFt	2.60	0.76
	Section	-	-
	Bundle	192.00	72.00


<b>LBS PER</b>	Layer	306	287
	Section	-	-
	Bundle	2,450	2,583

COLORS	Reflectance	Stock	Stock
Notte Hex	SR n/a SRI n/a	<b>SO</b>	-
Sabia Hex	SR n/a SRI n/a	<b>SO</b>	-
Notte Random	SR n/a SRI n/a	-	<b>SO</b>
Sabia Random	SR n/a SRI n/a	-	<b>SO</b>


## LAYING PATTERNS



Granito Hex\_A



Granito Fixed  
Random\_A



Granito Fixed  
Random\_B



NOTTE HEX



SABIA HEX



NOTTE RANDOM



SABIA RANDOM

<b>3-Unit Random Bundle</b>		<b>SMALL RECTANGLE</b> 180 x 360 x 60mm 7 x 14 1/4 x 2 3/8" 27 units/Bundle		<b>SQUARE</b> 360 x 360 x 60mm 14 1/4 x 14 1/4 x 2 3/8" 27 units/Bundle		<b>LARGE RECTANGLE</b> 360 x 540 x 60mm 14 1/4 x 21 1/4 x 2 3/8" 18 units/Bundle	<b>Single Unit</b>		<b>HEX</b> 200 x 200 x 70mm 7 7/8 x 7 7/8 x 2 3/4" 192 units/Bundle .39 Sq.Ft./Stone (Note: Hex only is drive friendly)
-----------------------------	---	--	---	--	---	---	--------------------	---	--

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Micro  
 Surface Texture - Smooth  
 Joint Spacing - 3 mm


**TECHNOLOGIES**

**ENDURACOLOR™**  
 Refined surface and long-lasting color

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits


**LAYING PATTERN**



Hex Paver\_A



DARK CHARCOAL



GRANITE

		<b>8 x 8</b>
<b>Bundle Type</b>		<b>SINGLE</b>
Plant Produced		MICHIGAN
Thickness (mm)		70 MM

<b>SQFT PER</b>	Bundle	73.92
	Layer	9.24
	Section	-
	Stone	0.39

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>SAILOR LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>UNITS PER</b>	SqFt	2.60
	Section	-
	Bundle	192.00

<b>LBS PER</b>	Layer	306
	Section	-
	Bundle	2,450

<b>COLORS</b>	<b>Reflectance</b>	<b>Stock</b>
Dark Charcoal	SR .n/a SRI n/a	✓
Granite	SR .n/a SRI n/a	✓

Single Unit



**HEX**  
 200 x 200 x 70mm  
 7 7/8 x 7 7/8 x 2 3/4"  
 192 Units/Bundle  
 .39 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfer  
 Surface Texture - Smooth  
 Joint Spacing - 3 mm

## TECHNOLOGIES

**CLASSIC**  
 Budget-friendly traditional product mix


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Hollandstone 4x8  
 RB\_B



Hollandstone 4x8  
 HB\_C



BEECHWOOD



RUSTIC RED



TERRA COTTA

	4 x 8	4 x 8
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN	MICHIGAN
Thickness (mm)	60 MM	80 MM

SQFT PER	Bundle	106.20	82.60
	Layer	11.80	11.80
	Section	17.70	13.77
	Stone	0.22	0.22

PER BUNDLE	Layers	9.00	7.00
	Sections	6.00	6.00

SOLDIER LNFT PER	SqFt	1.50	1.50
	Section	26.57	20.67
	Layer	17.72	17.71
	Bundle	159.45	124.00

SAILOR LNFT PER	SqFt	3.00	-
	Section	53.15	-
	Layer	35.43	-
	Bundle	318.90	-

UNITS PER	SqFt	4.58	4.58
	Section	81.00	63.00
	Bundle	486.00	378.00

LBS PER	Layer	324	426
	Section	486	497
	Bundle	2,914	2,985

COLORS	Reflectance	Stock	Stock
Beechwood	SR n/a SRI n/a	✓	SO
Rustic Red	SR n/a SRI n/a	✓	SO
Terra Cotta	SR n/a SRI n/a	✓	SO

Single Unit		<b>4 x 8</b> 100 x 200 x 60mm 3 7/8 x 7 7/8 x 2 3/8" 486 units/Bundle .22 Sq.Ft./Stone		<b>4 x 8</b> 100 x 200 x 80mm 3 7/8 x 7 7/8 x 3 1/8" 378 units/Bundle .22 Sq.Ft./Stone
-------------	---	--	---	--

Notes: Minimum quantities apply for 80mm (special order). SOLD IN FULL BUNDLES ONLY and is produced and sold on an optional, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfer  
 Surface Texture - Smooth  
 Joint Spacing - 3 mm

## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits


## LAYING PATTERNS



Holland Prem 4x8  
 RB\_B



Holland Prem 4x8  
 HB\_C



Holland Prem 4x8  
 BW\_D

	<b>4 x 8</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN
Thickness (mm)	60 MM

<b>SQFT PER</b>	Bundle	106.20
	Layer	11.80
	Section	17.70
	Stone	0.22

<b>PER BUNDLE</b>	Layers	9.00
	Sections	6.00

<b>SOLDIER LNFT PER</b>	SqFt	1.50
	Section	26.57
	Layer	17.72
	Bundle	159.45

<b>SAILOR LNFT PER</b>	SqFt	3.00
	Section	53.15
	Layer	35.43
	Bundle	318.90

<b>UNITS PER</b>	SqFt	4.58
	Section	81.00
	Bundle	486.00

<b>LBS PER</b>	Layer	324
	Section	486
	Bundle	2,914

COLORS	Reflectance	Stock
Charleston	SR n/a SRI n/a	✓
Dark Charcoal	SR n/a SRI n/a	✓
Fossil	SR .22 SRI 21	✓
Granite	SR n/a SRI n/a	✓
Ivory	SR n/a SRI n/a	✓



CHARLESTON



DARK CHARCOAL



FOSSIL



GRANITE



IVORY

Single Unit



**4 x 8**  
 100 x 200 x 60mm  
 3 7/8 x 7 7/8 x 2 3/8"  
 486 units/Bundle  
 .22 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY. Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
 Surface Texture - Il Campo® Brushed  
 Joint Spacing - 3 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits


## LAYING PATTERNS




Il Campo 4x8\_RB\_F



Il Campo 4x8\_SB\_G



Il Campo 4x8\_HB-H



DARK CHARCOAL

	<b>4 x 8 BRUSHED</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	PICKERING
Thickness (mm)	70 MM

<b>SQFT PER</b>	Bundle	94.40
	Layer	11.80
	Section	15.73
	Stone	0.22

<b>PER BUNDLE</b>	Layers	8.00
	Sections	6.00

<b>SOLDIER LNFT PER</b>	SqFt	1.50
	Section	23.62
	Layer	17.72
	Bundle	141.73

<b>SAILOR LNFT PER</b>	SqFt	3.00
	Section	47.24
	Layer	35.43
	Bundle	283.46

<b>UNITS PER</b>	SqFt	4.58
	Section	72.00
	Bundle	432.00

<b>LBS PER</b>	Layer	377
	Section	502
	Bundle	3,014

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	✓

Single Unit



**4 x 8**  
 100 x 200 x 70mm  
 3 7/8 x 7 7/8 x 2 3/4"  
 432 Units/Bundle  
 .22 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Zero  
 Surface Texture - Timeworn  
 Joint Spacing - 4 mm


**TECHNOLOGIES**

**ENDURACOLOR™**  
 Refined surface and long-lasting color


**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits


**LAYING PATTERNS**



RB\_A



HB\_C



DHB\_D




COCOA BROWN



DARK CHARCOAL



SABLE BLEND



GRANITE FUSION

		STANDARD SMOOTH
	Bundle Type	SINGLE
	Plant Produced	AURORA
	Thickness (mm)	60 MM

SQFT PER	Bundle	111.60
	Layer	11.16
	Section	-
	Stone	0.16

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.27
	Section	-
	Layer	14.17
	Bundle	141.73

SAILOR LNFT PER	SqFt	5.08
	Section	-
	Layer	56.69
	Bundle	566.93

UNITS PER	SqFt	6.45
	Section	-
	Bundle	720.00

LBS PER	Layer	306
	Section	-
	Bundle	3,063

COLORS	Reflectance	Stock
Cocoa Brown	SR n/a SRI n/a	✓
Dark Charcoal	SR n/a SRI n/a	✓
Sable Blend	SR n/a SRI n/a	✓
Granite Fusion	SR n/a SRI n/a	✓

Single Unit



**STANDARD**  
 60 x 240 x 60mm  
 2 3/8 x 9 1/2 x 2 3/8"  
 720 Units/Bundle  
 .16 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.

# Natural Stone Slabs



	12 x 24	18 x 24	24 x 24	24 x 36
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Thickness (mm)	22 MM	22 MM	22 MM	22 MM

<b>SQFT PER</b>	Crate	180.00	186.00	160.00	180.00
	Units	2.00	3.00	4.00	6.00

<b>UNITS PER</b>	Crate	90.00	62.00	40.00	30.00
	SqFt	0.50	0.33	0.25	0.17

<b>LBS PER</b>	Unit	24	36	48	72
	Crate	2,149	2,221	1,910	2,149

<b>COLORS</b>	Reflectance	Stock	Stock	Stock	Stock
Ivory Sand	SR n/a SRI n/a	✓	✓	✓	✓
Golden Sand	SR n/a SRI n/a	✓	✓	✓	✓
Stone Cliff Gray	SR n/a SRI n/a	✓	✓	✓	✓
Black River	SR n/a SRI n/a	✓	✓	✓	✓

## APPLICATIONS




## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Brushed / Riven  
 Joint Spacing - 0 mm


## TECHNICAL INFORMATION

Visit [Unilock.com](http://Unilock.com) for more information.


## LAYING PATTERNS



Natural Stone  
12x24 RB A



Natural Stone  
24x24 RB B



Natural Stone  
Multi-Unit C



IVORY SAND



GOLDEN SAND



STONE CLIFF GREY



BLACK RIVER

<b>Single Units</b>	<b>12 x 24</b>	<b>18 x 24</b>	<b>24 x 24</b>	<b>24 x 36</b>
		300 x 600 x 22mm 11 7/8" x 23 5/8" x 7/8" 2.0 Sq.Ft./Unit	450 x 600 x 22mm 17 3/4" x 23 5/8" x 7/8" 3.0 Sq.Ft./Unit	600 x 600 x 22mm 23 5/8" x 23 5/8" x 7/8" 4.0 Sq.Ft./Unit

Notes: **SOLD IN FULL CRATES ONLY** and all units except the 24x24" require a refundable skid. This product is not intended for vehicular applications. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.

# Natural Stone Steps, Coping and Pillar Caps



## APPLICATIONS



	<b>48 x 16 STEP</b>
<b>Bundle Type</b>	SINGLE
<b>Thickness (mm)</b>	150 MM

<b>FCFT PER</b>	Crate	32.00
-----------------	-------	-------

<b>LNFT PER</b>	Crate	24.00
-----------------	-------	-------

<b>UNITS PER</b>	Crate	6.00
------------------	-------	------

<b>LBS PER</b>	Crate	2,526
----------------	-------	-------

COLORS		Stock
Ivory Sand		✓
Golden Sand		✓
Stone Cliff Gray		✓
Black River (Limestone)		✓

Natural Limestone Pillar Caps



**NATURAL LIMESTONE PILLAR CAP**  
737 x 737 x 75mm  
29 x 29 x 3"

**NATURAL LIMESTONE PILLAR CAP**  
813 x 813 x 75mm  
32 x 32 x 3"

Chart is not displayed; Cap sold by the piece.

	48 x 14 BULLNOSE COPING	48 x 12 BULLNOSE COPING	48 x 12 NATURAL EDGE COPING	48 x 14 NATURAL EDGE COPING	24 x 24 SANDSTONE PILLAR CAP	28 x 28 SANDSTONE PILLAR CAP	24 x 24 LIMESTONE PILLAR CAP	28 x 28 LIMESTONE PILLAR CAP
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
<b>Thickness (mm)</b>	50 MM	50 MM	50 MM	50 MM	65 MM	65 MM	65 MM	65 MM

UNITS PER	Crate	20.00	20.00	20.00	20.00	14.00	12.00	14.00	12.00
	SqFt	-	-	-	-	-	-	-	-

LBS PER	Unit	-	-	-	-	137	210	137	210
	Crate	2,557	2,116	2,116	2,557	1,914	2,514	1,914	2,514

COLORS	Reflectance	Stock							
Ivory Sand	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓		
Golden Sand	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓		
Stone Cliff Gray	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓		
Black River	SR n/a SRI n/a	✓	✓	✓	✓			✓	✓

48" Step



**NATURAL EDGE STEP 48 x 16**  
1,200 x 150 x 400mm  
47 1/4 x 5 7/8 x 15 3/4"

Pillar Caps



**SANDSTONE PILLAR CAP 600 x 600 x 65mm**  
23 5/8 x 23 5/8 x 2 5/8"

**SANDSTONE PILLAR CAP 711 x 711 x 65mm**  
28 x 28 x 2 5/8"



**LIMESTONE PILLAR CAP 600 x 600 x 65mm**  
23 5/8 x 23 5/8 x 2 5/8"

**LIMESTONE PILLAR CAP 711 x 711 x 65mm**  
28 x 28 x 2 5/8"

Coping



**48 x 12 BULLNOSE COPING**  
1,200 x 50 x 300mm  
47 1/4 x 2 x 11 7/8"



**48 x 14 BULLNOSE COPING**  
1,200 x 50 x 356mm  
47 1/4 x 2 x 13 7/8"



**48 x 12 NATURAL EDGE COPING**  
1,200 x 50 x 300mm  
47 1/4 x 2 x 11 7/8"



**48 x 14 NATURAL EDGE COPING**  
1,200 x 50 x 356mm  
47 1/4 x 2 x 13 7/8"

Notes: Steps, Coping & Pillar Caps require a refundable skid. This product is not intended for vehicular applications. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Cobble

## TECHNOLOGIES

### PERMEABLE

Can be installed to allow water to flow through


### ENDURACOLOR™

Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
Eligible for LEED v4.1 credits


## LAYING PATTERNS




NordicCobble\_A



NordicCobble\_Fan




NordicCobble\_Circle



DARK CHARCOAL



GRANITE FUSION



OPAL

	<b>PREMIER</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	CHICAGO
Thickness (mm)	60 MM

<b>SQFT PER</b>	Bundle	98.25
	Layer	9.82
	Section	-
	Stone	0.09

<b>PER BUNDLE</b>	Layers	10.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	3.39
	Section	-
	Layer	33.30
	Bundle	333.07

<b>SAILOR LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>UNITS PER</b>	SqFt	10.99
	Section	-
	Bundle	1,080

<b>LBS PER</b>	Layer	230.10
	Section	-
	Bundle	2,301

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	SO
Granite Fusion	SR n/a SRI n/a	SO
Opal Blend	SR n/a SRI n/a	SO

Single Unit



**STANDARD**  
89.9 x 94 x 60mm  
3 5/8 x 3 3/4 x 2 3/8"  
1,080 units/Bundle  
.09 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.

# Porcelain




## APPLICATIONS




## TECHNICAL INFORMATION

Visit [Unilock.com](http://Unilock.com) for more information.

## LAYING PATTERNS



Porcelain 24x24 RB\_A



Porcelain 24x24 SB\_LB




CHAMONIX BEIGE




CHAMONIX BIANCO



CHAMONIX DARK GREY



CHAMONIX GREY



GOTHAM BIANCO



GOTHAM GREY



GOTHAM NERO



TRAVSTONE BEIGE



TRAVSTONE GRAY



WEST 57TH BIANCO



WEST 57TH GRAY



ESSENTIAL WHITE



ESSENTIAL GRAY



ESSENTIAL GRAPHITE



ESSENTIAL BEIGE



NATURE DOLOMITE



NATURE CARRARA



NEW ENGLAND WHITE



NEW ENGLAND IVORY



NEW ENGLAND COLD GRAY

		DEL CONCA SQUARE PRESSED EDGE
Bundle Type		SINGLE
Thickness (mm)		20 MM
SQFT PER	Pallet	248.00
	Box	7.75
	Unit	3.88
PER PALLET	Box	32.00
	SqFt	248.00
	Unit	64.00
UNITS PER	Pallet	64.00
	Box	2.00
LBS PER	Unit	36
	SqFt	9
	Box	72
	Pallet	2,289

COLORS	Reflectance	Stock
Chamonix Beige	n/a	SO
Chamonix Bianco	n/a	SO
Chamonix Dark Gray	n/a	SO
Chamonix Gray	n/a	SO
Gotham Bianco	n/a	SO
Gotham Gray	n/a	SO
Gotham Nero	n/a	SO
Travstone Beige	n/a	SO
Travstone Gray	n/a	SO
West 57th Bianco	n/a	SO
West 57th Gray	n/a	SO
Essential White	n/a	SO
Essential Gray	n/a	SO
Essential Graphite	n/a	SO
Essential Beige	n/a	SO
Nature Dolomite	n/a	SO
Nature Carrara	n/a	SO
New England White	n/a	SO
New England Ivory	n/a	SO
New England Cold Gray	n/a	SO



Notes: **SOLD IN FULL PALLETES ONLY.** **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. **Product is not intended for vehicular applications.**

# Porcelain



## APPLICATIONS




## TECHNICAL INFORMATION

Visit [Unilock.com](http://Unilock.com) for more information.

## LAYING PATTERNS



Porcelain 16x32  
RB\_C




Porcelain 16x32  
HB\_D



ARBOR BIANCO



TRAVSTONE BEIGE



TRAVSTONE GRAY



NEW ENGLAND WHITE



NEW ENGLAND IVORY



NEW ENGLAND COLD GRAY



QUARTZITE BIANCO



QUARTZITE DARK GRAY



QUARTZITE GRAY



QUARTZITE SAND

		DEL CONCA RECTANGLE PRESSED EDGE
<b>Bundle Type</b>		<b>SINGLE</b>
Thickness (mm)		20 MM

<b>SQFT PER</b>	Pallet	165.36
	Box	6.89
	Unit	3.45

<b>PER PALLET</b>	Box	24.00
	SqFt	165.36
	Unit	48.00

<b>UNITS PER</b>	Pallet	48.00
	Box	2.00

<b>LBS PER</b>	Unit	32
	SqFt	9
	Box	64
	Pallet	1,538

COLORS	Reflectance	Stock
Arbor Bianco	n/a	SO
Travstone Beige	n/a	SO
Travstone Gray	n/a	SO
New England White	n/a	SO
New England Ivory	n/a	SO
New England Cold Gray	n/a	SO
Quartzite Bianco	n/a	SO
Quartzite Dark Gray	n/a	SO
Quartzite Gray	n/a	SO
Quartzite Sand	n/a	SO

Single Unit



### DEL CONCA RECTANGLE

400 x 800 x 20mm  
15 ¾ x 31 ½ x ¾"  
3.45 Sq.Ft./Stone

Notes: **SOLD IN FULL PALLETS ONLY.** **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. **Product is not intended for vehicular applications.**



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
 Surface Texture - Smooth, Series™ Exposed  
 & Il Campo® Brushed  
 Joint Spacing - 4 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Promenade 4x12  
RB\_H



Promenade 4x12  
HB\_I



BLACK GRANITE



DARK CHARCOAL



GRANITE BLEND



LIGHT GREY



OPAL BLEND



SANDSTONE



STEEL GREY BLEND

		SMOOTH	SERIES	IL CAMPO
	<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE
	Plant Produced	PICKERING	GEORGETOWN	PICKERING
	Thickness (mm)	100 MM	100 MM	100 MM
<b>SQFT PER</b>	Bundle	58.13	58.13	58.13
	Layer	11.63	11.63	11.63
	Section	-	-	-
	Stone	0.32	0.32	0.32
<b>PER BUNDLE</b>	Layers	5.00	5.00	5.00
	Sections	-	-	-
<b>SOLDIER LNFT PER</b>	SqFt	1.02	1.02	1.02
	Section	-	-	-
	Layer	11.81	11.81	11.81
	Bundle	59.06	59.06	59.06
<b>SAILOR LNFT PER</b>	SqFt	3.05	3.05	3.05
	Section	-	-	-
	Layer	35.43	35.43	35.43
	Bundle	177.17	177.17	177.17
<b>UNITS PER</b>	SqFt	3.10	3.10	3.10
	Section	-	-	-
	Bundle	180.00	180.00	180.00
<b>LBS PER</b>	Layer	532	532	526
	Section	-	-	-
	Bundle	2,659	2,659	2,629

COLORS	Reflectance	Stock	Stock	Stock
Black Granite (Series)	SR n/a SRI n/a		SO	
Dark Charcoal (Il Campo)	SR n/a SRI n/a			SO
Granite Blend (Il Campo)	SR n/a SRI n/a			SO
Light Gray (Il Campo)	SR n/a SRI n/a			SO
Opal Blend (Smooth)	SR .24 SRI 24	SO		
Sandstone (Smooth)	SR n/a SRI n/a	SO		
Steel Gray Blend (Smooth)	SR n/a SRI n/a	SO		

Single Unit

**4 x 12 SMOOTH**  
 100 x 300 x 100mm  
 3 7/8 x 11 7/8 x 3 1/8"  
 180 units/Bundle  
 .32 Sq.Ft./Stone

Single Unit

**4 x 12 SERIES**  
 100 x 300 x 100mm  
 3 7/8 x 11 7/8 x 3 1/8"  
 180 units/Bundle  
 .32 Sq.Ft./Stone

Single Unit

**4 x 12 IL CAMPO BRUSHED**  
 100 x 300 x 100mm  
 3 7/8 x 11 7/8 x 3 1/8"  
 180 units/Bundle  
 .32 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
 Surface Texture - Smooth  
 Joint Spacing - 4 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Promenade 4x16  
 HB\_C



Promenade 4x16  
 RB\_A



OPAL BLEND



STEEL GREY BLEND

		<b>4 x 16 SMOOTH</b>
<b>Bundle Type</b>		<b>SINGLE</b>
Plant Produced		PICKERING / MI
Thickness (mm)		100 MM

<b>SQFT PER</b>	Bundle	51.67
	Layer	10.33
	Section	-
	Stone	0.43

<b>PER BUNDLE</b>	Layers	5.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	0.76
	Section	-
	Layer	7.87
	Bundle	39.37

<b>SAILOR LNFT PER</b>	SqFt	3.05
	Section	-
	Layer	31.50
	Bundle	157.48

<b>UNITS PER</b>	SqFt	2.32
	Section	-
	Bundle	120.00

<b>LBS PER</b>	Layer	488
	Section	-
	Bundle	2,440

COLORS	Reflectance	Stock
Opal Blend (Smooth)	SR .24 SRI 24	<b>SO</b>
Steel Gray Blend (Smooth)	SR n/a SRI n/a	<b>SO</b>

Single Unit



**4 x 16 SMOOTH**  
 100 x 400 x 100mm  
 3 7/8 x 15 3/4 x 3 7/8"  
 120 units/Bundle  
 .43 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
 Surface Texture - Smooth, Series™ Exposed & Il Campo®  
 Brushed  
 Joint Spacing - 4 mm


## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Promenade 8x24  
HB\_F



Promenade 8x24  
RB\_D

	8 x 24 SMOOTH	8 x 24 SERIES	8 x 24 IL CAMPO
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE
Plant Produced	PICKERING	GEORGETOWN	PICKERING
Thickness (mm)	100 MM	100 MM	100 MM

SQFT PER	Bundle	51.67	51.67	51.67
	Layer	10.33	10.33	10.33
	Section	-	-	-
	Stone	1.29	1.29	1.29

PER BUNDLE	Layers	5.00	5.00	5.00
	Sections	-	-	-

SOLDIER LNFT PER	SqFt	0.51	0.51	0.51
	Section	-	-	-
	Layer	5.25	5.25	5.25
	Bundle	26.25	26.25	26.25

SAILOR LNFT PER	SqFt	1.52	1.52	1.52
	Section	-	-	-
	Layer	15.75	15.75	15.75
	Bundle	78.74	78.74	78.74

UNITS PER	SqFt	0.77	0.77	0.77
	Section	-	-	-
	Bundle	40.00	40.00	40.00

LBS PER	Layer	478	478	478
	Section	-	-	-
	Bundle	2,391	2,391	2,391

COLORS	Reflectance	Stock	Stock	Stock
Black Granite (Series)	SR n/a SRI n/a		SO	
Dark Charcoal (Il Campo)	SR n/a SRI n/a			SO
Granite Blend (Il Campo)	SR n/a SRI n/a			SO
Light Gray (Il Campo)	SR n/a SRI n/a			SO
Opal Blend (Smooth)	SR .24 SRI 24	SO		
Steel Gray Blend (Smooth)	SR n/a SRI n/a	SO		



BLACK GRANITE



DARK CHARCOAL



GRANITE BLEND



LIGHT GREY



OPAL BLEND



STEEL GREY BLEND

Single Unit

**8 x 24 SMOOTH**  
 200 x 600 x 100mm  
 7 7/8 x 23 5/8 x 3 7/8"  
 40 units/Bundle  
 1.29 Sq.Ft./Stone

Single Unit

**8 x 24 SERIES EXPOSED**  
 200 x 600 x 100mm  
 7 7/8 x 23 5/8 x 3 7/8"  
 40 units/Bundle  
 1.29 Sq.Ft./Stone

Single Unit

**8 x 24 IL CAMPO BRUSHED**  
 200 x 600 x 100mm  
 7 7/8 x 23 5/8 x 3 7/8"  
 40 units/Bundle  
 1.29 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

- Edge Detail - Rounded
- Surface Texture - Smooth
- Joint Spacing - n/a

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and long-lasting color

### ECOTERRA®

Reduced carbon emissions and refined surface protection

## TECHNICAL INFORMATION

- Conforms to ASTM C 936
- Eligible for LEED v4.1 credits

	<b>4 x 12</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	ONTARIO
Thickness (mm)	70 MM

<b>SQFT PER</b>	Bundle	93.04
	Layer	11.63
	Section	23.26
	Stone	0.32

<b>PER BUNDLE</b>	Layers	8.00
	Sections	4.00

<b>SOLDIER LNFT PER</b>	SqFt	1.02
	Section	23.62
	Layer	11.81
	Bundle	94.49


<b>SAILOR LNFT PER</b>	SqFt	3.05
	Section	70.87
	Layer	35.43
	Bundle	283.46

<b>UNITS PER</b>	SqFt	3.10
	Section	72.00
	Bundle	288.00


<b>LBS PER</b>	Layer	393
	Section	785
	Bundle	3,140

COLORS	Reflectance	Stock
Light Opal Blend	SR n/a SRI n/a	<b>SO</b>
Light Steel Gray	SR n/a SRI n/a	<b>SO</b>

## LAYING PATTERNS



4x12 RB\_A



4x12 HB\_C



LIGHT OPAL BLEND



LIGHT STEEL GRAY

Single Unit



**4 x 12**  
 100 x 300 x 70 mm  
 3<sup>7</sup>/<sub>8</sub> x 11<sup>7</sup>/<sub>8</sub> x 2<sup>3</sup>/<sub>4</sub>  
 288 units/Bundle  
 .32 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - n/a  
 Surface Texture - Textured  
 Joint Spacing - 10 mm

**TECHNOLOGIES**

**EASYSOAK™**

Factory Sealed to provide integral stain resistance

**ELEGANCE™**

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

**REALA™**

Cast from natural stone.


**ULTIMA™**

Up to 4x stronger than poured-in-place concrete


**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

**LAYING PATTERNS**



Richcliff Fixed Random A



Richcliff Fixed Random B



Richcliff Large Rec HB\_H



DAWN MIST



PEBBLE TAUPE



SMOKE SHALE

		LARGE RECTANGLE	
Bundle Type		RANDOM	SINGLE
Plant Produced		AYR	AYR
Thickness (mm)		60 MM	60 MM

SQFT PER	Bundle	90.30	82.39
	Layer	11.29	10.30
	Section	-	-
	Stone	0.56	1.72

PER BUNDLE	Layers	8.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	0.58
	Section	-	-
	Layer	-	5.94
	Bundle	-	47.56

SAILOR LNFT PER	SqFt	1.31	1.01
	Section	-	-
	Layer	14.78	10.39
	Bundle	118.22	83.15

UNITS PER	SqFt	1.77	0.58
	Section	-	-
	Bundle	160.00	48.00

LBS PER	Layer	309	301
	Section	-	-
	Bundle	2,472	2,411

COLORS	Reflectance	Stock	Stock
Dawn Mist	SR n/a SRI n/a	✓	SO
Pebble Taupe	SR n/a SRI n/a	✓	SO
Smoke Shale	SR n/a SRI n/a	✓	SO

3 Unit Random Bundle



**RECTANGLE**  
 226 x 300 x 60mm  
 8 7/8 x 11 7/8 x 2 3/8"  
 64 Units/Bundle  
 .75 SqFt./Stone



**SQUARE**  
 226 x 226 x 60mm  
 8 7/8 x 8 7/8 x 2 3/8"  
 32 units/Bundle  
 .58 Sq.Ft./Stone



**SMALL RECTANGLE**  
 150 x 226 x 60mm  
 5 7/8 x 8 7/8 x 2 3/8"  
 64 units/Bundle  
 .38 Sq.Ft./Stone

Single Unit



**LARGE RECTANGLE**  
 302 x 528 x 60mm  
 11 7/8 x 20 7/8 x 2 3/8"  
 48 units/Bundle  
 1.72 Sq.Ft./Stone  
 (Not drive friendly)

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. The Large Rectangle unit is not intended for vehicular applications. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfer  
 Surface Texture - Series Exposed  
 Joint Spacing - 3mm

## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


## PERMEABLE (for 4x12 only)

Can be installed to allow water to flow through


## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

## LAYING PATTERNS



Series 4x8\_HB\_F



Series 4x8\_HB\_G



GOLDEN TAN



ONYX BLACK



ARCTIC GRAY



NORDIC STAR

	4 x 8 SERIES EXPOSED	4 x 12 SERIES EXPOSED
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	CHICAGO	CHICAGO
Thickness (mm)	60 MM	80 MM

SQFT PER	Bundle	117.90	93.04
	Layer	11.80	11.63
	Section	19.67	-
	Stone	0.22	0.32

PER BUNDLE	Layers	10.00	8.00
	Sections	6.00	-

SOLDIER LNFT PER	SqFt	1.50	1.02
	Section	29.53	-
	Layer	17.72	11.81
	Bundle	177.17	94.49

SAILOR LNFT PER	SqFt	3.00	3.05
	Section	59.06	-
	Layer	35.43	35.43
	Bundle	354.33	283.46

UNITS PER	SqFt	4.58	3.10
	Section	90.00	-
	Bundle	540.00	288.00

LBS PER	Layer	306	426
	Section	511	-
	Bundle	3,065	3,404

COLORS	Reflectance	Stock	Stock
Golden Tan	SR .40 SRI 45	SO	
Onyx Black	SR n/a SRI n/a	✓	
Arctic Gray	SR n/a SRI n/a		SO
Nordic Star	SR n/a SRI n/a		SO

Single Unit



**4 x 8**  
 100 x 200 x 60mm  
 3 7/8 x 7 7/8 x 2 3/8"  
 540 units/Bundle  
 .22 Sq.Ft./Stone



**4 x 12**  
 100 x 300 x 80mm  
 3 7/8 x 11 7/8 x 3 1/8"  
 288 units/Bundle  
 .32 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Rounded  
Surface Texture - Smooth  
Joint Spacing - 2mm

## TECHNOLOGIES

### COLORFUSION™ (UMBRIANO)

Subtly mottled colored finish

### EASYCLEAN™ (UMBRIANO)

Factory Sealed to provide integral stain resistance


### ENDURACOLOR™

Refined surface and long-lasting color


## TECHNICAL INFORMATION

Conforms to ASTM C 1782  
Eligible for LEED v4.1 credits

## LAYING PATTERNS



Skyline 24x24 SB\_A



Skyline 24x24 RB\_B

	24 x 24"	23 7/8 x 23 7/8 UMBRIANO FINISH	23 7/8 x 23 7/8
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	MARENGO	GEORGETOWN	GEORGETOWN
Thickness (mm)	50 MM	50 MM	50 MM

<b>SQFT PER</b>	Bundle	80.00	38.75	38.75
	Layer	8.00	7.75	7.75
	Section	-	-	-
	Stone	4.00	3.88	3.88

<b>PER BUNDLE</b>	Layers	10.00	5.00	5.00
	Sections	-	-	-

<b>SOLDIER LNFT PER</b>	SqFt	0.50	0.52	0.51
	Section	-	-	-
	Layer	4.00	4.00	3.94
	Bundle	40.00	20.00	19.70

<b>SAILOR LNFT PER</b>	SqFt	0.50	0.52	0.51
	Section	-	-	-
	Layer	4.00	4.00	3.94
	Bundle	40.00	20.00	19.70


<b>UNITS PER</b>	SqFt	0.25	0.26	0.26
	Section	-	-	-
	Bundle	20.00	10.00	10.00

<b>LBS PER</b>	Layer	183	175	175
	Section	-	-	-
	Bundle	1,833	874	874

COLORS	Reflectance	Stock		
Chamois	SR .41 SRI 46	✓		
Silver Gray	SR n/a SRI 37	✓		
Grenada White	SR n/a SRI 52		✓	
Opal Blend	SR n/a SRI n/a			SO



CHAMOIS



SILVER GREY



GRANADA WHITE



OPAL BLEND

Single Unit



606 x 606 x 50mm  
24 x 24 x 2"  
20 units/Bundle  
4.00 Sq.Ft./Stone

(Silver Grey and Chamois only)



600 x 600 x 50mm  
23 7/8 x 23 7/8 x 2"  
10 units/Bundle  
3.88 Sq.Ft./Stone

(Grenada White and Opal Blend Only)



**PEDESTAL SYSTEM**  
Contact your local  
Unilock Rep for more  
information.

Notes: Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Product is not intended vehicular applications.** Unilock offers adjustable and stackable pedestal systems; please contact your Territory Manager for pricing and availability. All measurements are nominal.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Zero  
 Surface Texture - Textured  
 Joint Spacing - 11-18 mm  
 Void - 4.4%

**TECHNOLOGIES**

**PERMEABLE**

Can be installed to allow water to flow through

**ENDURACOLOR™**

Refined surface and long-lasting color

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

Bundle Type	RANDOM
Plant Produced	MICHIGAN
Thickness (mm)	70 MM

SQFT PER	Bundle	88.61
	Layer	11.08
	Section	-
	Stone	0.92

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	1.08
	Section	-
	Bundle	96.00


LBS PER	Layer	355
	Section	-
	Bundle	2,837

COLORS	Reflectance	Stock
Birch	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓


**LAYING PATTERNS**




Thornbury Fixed Random A



Thornbury Fixed Random B



Thornbury Fixed Random C



BIRCH



SIERRA

Random Bundle		<b>LARGE RECTANGLE</b> 350 x 420 x 70mm 13 7/8 x 16 5/8 x 2 3/4" 32 Units/Bundle		<b>MEDIUM RECTANGLE</b> 210 x 350 x 70mm 8 3/8 x 13 7/8 x 2 3/4" 32 units/Bundle		<b>SMALL RECTANGLE</b> 173 x 210 x 70mm 6 7/8 x 8 3/8 x 2 3/4" 32 units/Bundle
---------------	---	---	---	---	---	---

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced on an optional, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - n/a  
 Surface Texture - Textured  
 Joint Spacing - 10 mm  
 Void - 6.50%

**TECHNOLOGIES**

**PERMEABLE**

Can be installed to allow water to flow through

**EASYCLEAN™**

Factory Sealed to provide integral stain resistance

**ELEGANCE™**

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

**REALA™**

Cast from historical brick

**ULTIMA™**

Up to 4x stronger than poured-in-place concrete

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	<b>4 x 10</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	AYR
Thickness (mm)	70 MM

<b>SQFT PER</b>	Bundle	88.41
	Layer	11.05
	Section	-
	Stone	.28

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	1.19
	Section	-
	Layer	13.12
	Bundle	104.99


<b>SAILOR LNFT PER</b>	SqFt	2.97
	Section	-
	Layer	32.81
	Bundle	262.47

<b>UNITS PER</b>	SqFt	3.62
	Section	-
	Bundle	320.00


<b>LBS PER</b>	Layer	361
	Section	-
	Bundle	2,888

COLORS	Reflectance	Stock
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓
Basalt	SR n/a SRI n/a	✓

**LAYING PATTERNS**



Town Hall 4x10 HB\_B



Town Hall 4x10 RB\_C



BURGUNDY RED



BURNT CLAY



OLD OAK



BASALT

Single Unit



**4 x 10**  
 100 x 250 x 70mm  
 3 7/8 x 9 7/8 x 2 3/4"  
 320 units/Bundle  
 .28 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Rounded  
 Surface Texture - Smooth  
 Joint Spacing - 7mm  
 Void - 5.5%

**TECHNOLOGIES**

**PERMEABLE**

Can be installed to allow water to flow through

**ENDURACOLOR™**

Refined surface and long-lasting color

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	<b>SMOOTH</b>
<b>Bundle Type</b>	<b>RANDOM</b>
Plant Produced	MICHIGAN
Thickness (mm)	60 MM

<b>SQFT PER</b>	Bundle	105.18
	Layer	11.69
	Section	-
	Stone	0.56

<b>PER BUNDLE</b>	Layers	9.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-


<b>SAILOR LNFT PER</b>	SqFt	1.57
	Section	-
	Layer	18.35
	Bundle	165.11

<b>UNITS PER</b>	SqFt	1.80
	Section	-
	Bundle	189.00

<b>LBS PER</b>	Layer	321
	Section	-
	Bundle	2,886

COLORS	Reflectance	Stock
Fossil	SR n/a SRI n/a	✓
Granite	SR n/a SRI n/a	✓
Tuscany	SR n/a SRI n/a	✓

**LAYING PATTERNS**



Treo Fixed Random\_R Treo Fixed Random\_S



FOSSIL GRANITE TUSCANY

<b>Random Bundle</b>		<b>LARGE RECTANGLE</b> 225 x 337.5 x 60mm 8 7/8 x 13 3/8 x 2 3/8" 54 units/Bundle .82 Sq.Ft./Stone		<b>SQUARE</b> 225 x 225 x 60mm 8 7/8 x 8 7/8 x 2 3/8" 63 units/Bundle .55 Sq.Ft./Stone		<b>SMALL RECTANGLE</b> 112.5 x 225 x 60mm 4 1/2 x 8 7/8 x 2 3/8" 72 units/Bundle .27 Sq.Ft./Stone
----------------------	---	--	---	--	---	---

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Micro  
 Surface Texture - Series Exposed Textured  
 Joint Spacing - 10mm  
 Void - 5.6%

**TECHNOLOGIES**

**PERMEABLE**

Can be installed to allow water to flow through

**ENDURACOLOR™**

Refined surface and long-lasting color

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	<b>SERIES EXPOSED TEXTURED</b>
<b>Bundle Type</b>	<b>RANDOM</b>
Plant Produced	CHICAGO
Thickness (mm)	70 MM

<b>SQFT PER</b>	Bundle	97.53
	Layer	12.19
	Section	-
	Stone	0.32

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>SAILOR LNFT PER</b>	SqFt	2.34
	Section	-
	Layer	28.49
	Bundle	227.95

<b>UNITS PER</b>	SqFt	3.12
	Section	-
	Bundle	304.00


<b>LBS PER</b>	Layer	378
	Section	-
	Bundle	3,021

COLORS	Reflectance	Stock
Cobalt Gray	SR n/a SRI n/a	SO
Peppered Granite	SR .38 SRI 42	SO

**LAYING PATTERNS**



Tribeca Cobble Fixed Random\_A



COBALT GREY



PEPPERED GRANITE

Random Bundle		<p><b>LARGE RECTANGLE</b>                  130 x 305 x 70mm                  5 x 12 x 2 ¾"                  88 units/Bundle                  .43 Sq.Ft./Stone</p>		<p><b>RECTANGLE</b>                  130 x 230 x 70mm                  5 x 9 x 2 ¾"                  88 units/Bundle                  .32 Sq.Ft./Stone</p>		<p><b>SMALL RECTANGLE</b>                  130 x 175 x 70mm                  5 x 6 7/8 x 2 ¾"                  128 units/Bundle                  .25 Sq.Ft./Stone</p>
---------------	---	---	---	--	---	---

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices on page 79. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Zero  
 Surface Texture - Standard  
 Joint Spacing - 2mm  
 Void - 40%

**TECHNOLOGIES**

**PERMEABLE**

Can be installed to allow water to flow through

**CLASSIC**

Budget-friendly traditional product mix

**TECHNICAL INFORMATION**

Conforms to ASTM C1319  
 Eligible for LEED v4.1 credits

	<b>SMOOTH</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN
Thickness (mm)	80 MM

<b>SQFT PER</b>	Bundle	80.00
	Layer	10.00
	Section	-
	Stone	2.50

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-


<b>SAILOR LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-

<b>UNITS PER</b>	SqFt	0.40
	Section	-
	Bundle	32.00

<b>LBS PER</b>	Layer	247
	Section	-
	Bundle	1,975

<b>COLORS</b>	<b>Reflectance</b>	<b>Stock</b>
Natural	SR .30 SRI 32	✓

**LAYING PATTERNS**



Turfstone A



NATURAL

Single Unit



**STANDARD**  
 400 x 600 x 80mm  
 15 3/4 x 23 5/8 x 3 1/8"  
 32 units/Bundle  
 2.50 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on an optional, refundable skid. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero

Surface Texture - Umbriano Mottled

Joint Spacing - 3mm

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and long-lasting color

### EASYCLEAN™

Factory Sealed to provide integral stain resistance

### COLORFUSION™

Subtly mottled colored finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

Bundle Type	RANDOM
Plant Produced	GEORGETOWN
Thickness (mm)	60 MM

SQFT PER	Bundle	94.14
	Layer	10.46
	Section	-
	Stone	1.31

PER BUNDLE	Layers	9.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	0.85
	Section	-
	Layer	8.86
	Bundle	79.72

UNITS PER	SqFt	0.76
	Section	-
	Bundle	72.00


LBS PER	Layer	287
	Section	-
	Bundle	2,583

COLORS	Reflectance	Stock
French Gray	SR .18 SRI 17	✓
Summer Wheat	SR .42 SRI 48	✓
Winter Marvel	SR .35 SRI 38	✓
Grenada White	SR n/a SRI n/a	SO

## LAYING PATTERNS



Umbriano Fixed  
Random\_A



Umbriano Fixed  
Random\_B




FRENCH GREY



SUMMER WHEAT



WINTER MARVEL



GRENADA WHITE

Random Bundle



**LARGE RECTANGLE**  
350 x 546 x 60mm  
13 7/8 x 21 1/2 x 2 3/8"  
18 units/Bundle



**SQUARE**  
360 x 360 x 60mm  
14 1/4 x 14 1/4 x 2 3/8"  
27 units/Bundle



**SMALL RECTANGLE**  
180 x 360 x 60mm  
7 x 14 1/4 x 2 3/8"  
27 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Umbriano Mottled  
Joint Spacing - 3mm

## TECHNOLOGIES

**ENDURACOLOR<sup>™</sup>**  
Refined surface and long-lasting color

## EASYSOAK<sup>™</sup>

Factory Sealed to provide integral stain resistance

## COLORFUSION<sup>™</sup>


Subtly mottled colored finish

## TECHNICAL INFORMATION


Conforms to ASTM C 936  
Eligible for LEED v4.1 credits

(Note: 8x16" only is drive friendly)

## LAYING PATTERNS



Umbriano 24x24  
RB\_AG



Umbriano 12x24  
HB\_0



FRENCH GREY



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

	8 x 16	12 x 24	16 x 16
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	GEORGETOWN	GEORGETOWN	GEORGETOWN
Thickness (mm)	70 MM	70 MM	70 MM

SQFT PER	Bundle	82.67	93.00	82.67
	Layer	10.33	11.63	10.33
	Section	27.56	-	-
	Stone	0.86	1.94	1.72

PER BUNDLE	Layers	8.00	8.00	8.00
	Sections	3.00	-	-

SOLDIER LNFT PER	SqFt	0.76	0.51	0.76
	Section	21.00	-	-
	Layer	7.87	5.91	7.87
	Bundle	62.99	47.24	62.99

SAILOR LNFT PER	SqFt	1.52	1.02	0.76
	Section	41.99	-	-
	Layer	15.75	11.81	7.87
	Bundle	125.98	94.49	62.99

UNITS PER	SqFt	1.16	0.52	0.58
	Section	32.00	-	-
	Bundle	96.00	48.00	48.00

LBS PER	Layer	343	393	350
	Section	915	-	-
	Bundle	2,746	3,142	2,797

COLORS	Reflectance	Stock	Stock	Stock
French Gray	SR .18 SRI 17	SO	SO	SO
Midnight Sky	SR .17 SRI 15	SO		
Summer Wheat	SR .42 SRI 48	SO	SO	SO
Winter Marvel	SR .35 SRI 38	SO	SO	SO

Single Units



**8 x 16**  
200 x 400 x 70mm  
7 7/8 x 15 3/4 x 2 3/4"  
96 units/Bundle  
.86 Sq.Ft./Stone



**12 x 24**  
300 x 600 x 70mm  
11 7/8 x 23 5/8 x 2 3/4"  
48 units/Bundle  
1.94 Sq.Ft./Stone



**16 x 16**  
400 x 400 x 70mm  
15 3/4 x 15 3/4 x 2 3/4"  
48 units/Bundle  
1.72 Sq.Ft./Stone

Notes: **Special Order items, lead time is required. SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Rounded  
 Surface Texture - Umbriano Mottled  
 Joint Spacing - 3 mm

**TECHNOLOGIES**

**PERMEABLE**

Can be installed to allow water to flow through

**ENDURACOLOR<sup>™</sup>**

Refined surface and long-lasting color

**EASYCLEAN<sup>™</sup>**

Factory sealed to provide integral stain resistance


**COLORFUSION<sup>™</sup>**

Subtly mottled colored finish


**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

**LAYING PATTERNS**



Umbriano 4x12 HB\_1



Umbriano 4x12 RB\_H

	4 x 12
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MARENGO
Thickness (mm)	80 MM

<b>SQFT PER</b>	Bundle	93.04
	Layer	11.63
	Section	-
	Stone	0.32

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	1.02
	Section	-
	Layer	11.81
	Bundle	94.49

<b>SAILOR LNFT PER</b>	SqFt	3.05
	Section	-
	Layer	35.43
	Bundle	283.46

<b>UNITS PER</b>	SqFt	3.10
	Section	-
	Bundle	288.00

<b>LBS PER</b>	Layer	426
	Section	-
	Bundle	3,404

COLORS	Reflectance	Stock
French Gray	SR .18 SRI 17	SO
Midnight Sky	SR .17 SRI 15	SO
Winter Marvel	SR .35 SRI 38	SO



FRENCH GREY



MIDNIGHT SKY



WINTER MARVEL

Single Unit



**4 x 12**  
 100 x 300 x 80mm  
 3 7/8 x 11 7/8 x 3 1/8"  
 288 units/Bundle  
 .32 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**APPEARANCE**

Edge Detail - Rounded  
 Surface Texture - Smooth  
 Joint Spacing - n/a

**TECHNOLOGIES**

**ENDURACOLOR™**  
 Refined surface and long-lasting color

**TECHNICAL INFORMATION**

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

**LAYING PATTERNS**

	<b>18 x 24</b>	<b>18 x 36</b>	<b>COPING CHAMFERED</b>	<b>COPING BULLNOSE</b>
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	AYR	AYR	PICKERING	PICKERING
Thickness (mm)	60 MM	60 MM	60 MM	60 MM

<b>SQFT PER</b>	Bundle	93	52.31	-	-
	Layer	11.62	8.71	-	-
	Section	-	-	-	-
	Stone	2.91	4.36	-	-

<b>PER BUNDLE</b>	Layers	8.00	6.00	6.00	6.00
	Sections	-	-	-	-


<b>SOLDIER LNFT PER</b>	SqFt	0.51	0.68	-	-
	Section	-	-	-	-
	Layer	5.91	5.91	-	-
	Bundle	47.25	35.44	-	-

<b>SAILOR LNFT PER</b>	SqFt	0.68	1.35	-	-
	Section	-	-	-	-
	Layer	7.87	11.81	5.91	5.91
	Bundle	62.99	70.87	35.46	35.46


<b>UNITS PER</b>	SqFt	-	-	-	-
	Section	-	-	-	-
	Bundle	32.00	12.00	12.00	12.00

<b>LBS PER</b>	Layer	319	239	258	258
	Section	-	-	-	-
	Bundle	2,552	1,435	1,547	1,547

COLORS	Reflectance	Stock	Stock	Stock	Stock
Indiana Buff	SR .n/a SRI 61	✓	✓	SO	SO
Sterling	SR .n/a SRI 17	✓	✓	SO	SO



Urban 18x36 HB\_C



Urban 18x36 RB\_D



INDIANA BUFF



STERLING

<b>Single Units</b>		<b>18 x 24</b> 450x 600 x 60mm 17 3/4 x 23 5/8 x 2 3/8" 32 units/Bundle 2.91 Sq.Ft./Stone		<b>18 x 36</b> 450 x 900 x 60mm 17 3/4 x 35 1/2 x 2 3/8" 12 units/Bundle 4.36 Sq.Ft./Stone		<b>COPING CHAMFERED</b> 485 x 900 x 60 mm 19 x 36 x 2 3/8" 12 units/Bundle		<b>COPING BULLNOSE</b> 485 x 900 x 60 mm 19 x 36 x 2 3/8" 12 units/Bundle
---------------------	---	---	---	--	---	---	---	--

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Textured  
 Joint Spacing - 3-7mm

## TECHNOLOGIES

**CLASSIC™**  
 Budget-friendly traditional product mix

## CLASSIC COAT

Factory-sealed to protect surface texture and color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

<b>Bundle Type</b>	<b>RANDOM</b>
Plant Produced	MICHIGAN
Thickness (mm)	70 MM

<b>SQFT PER</b>	Bundle	94.19
	Layer	11.77
	Section	-
	Stone	0.59

<b>PER BUNDLE</b>	Layers	8.00
	Sections	-

<b>SOLDIER LNFT PER</b>	SqFt	-
	Section	-
	Layer	-
	Bundle	-


<b>SAILOR LNFT PER</b>	SqFt	1.24
	Section	-
	Layer	14.57
	Bundle	116.56

<b>UNITS PER</b>	SqFt	1.70
	Section	-
	Bundle	160.00


<b>LBS PER</b>	Layer	367
	Section	-
	Bundle	2,937

COLORS	Reflectance	Stock
Beechwood	SR n/a SRI n/a	✓
Granite	SR n/a SRI n/a	✓

## LAYING PATTERNS



Westport Fixed  
Random\_A



Westport Fixed  
Random\_B



BEECHWOOD



GRANITE

Random Bundle



**LARGE RECTANGLE**  
 254 x 380 x 70mm  
 10 x 15 x 2 ¾"  
 32 units/Bundle



**SQUARE**  
 254 x 254 x 70mm  
 10 x 10 x 2 ¾"  
 56 units/Bundle



**SMALL RECTANGLE**  
 127 x 254 x 70mm  
 5 x 10 x 2 ¾"  
 72 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on an optional, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products:  
[contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a  
 Surface Texture - Tumbled

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

### ANTIQUED™

Distressed, timeworn finish

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
 Eligible for LEED v4.1 credits

## SUNSET FIREPIT KITS

Located on page 73



ROUND



SQUARE

	<b>STANDARD</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN
Thickness (mm)	100 MM

<b>FCFT PER</b>	Bundle	32.00
	Layer	5.33
	Stone	0.33

<b>PER BUNDLE</b>	Layers	6.00
	Sections	4.00

<b>LNFT PER</b>	Bundle	96.00
	Unit	1.00

<b>UNITS PER</b>	SqFt	3.00
	Section	24.00
	Bundle	96.00

<b>LBS PER</b>	Layer	473
	Section	709
	Bundle	2,836

COLORS	Reflectance	Stock
Coffee Creek	SR n/a SRI n/a	✓
Charcoal	SR n/a SRI n/a	✓
Limestone	SR n/a SRI n/a	✓
Mahogany Ash	SR n/a SRI n/a	✓
Sandstone	SR n/a SRI n/a	✓



COFFEE CREEK



CHARCOAL



LIMESTONE



MAHOGANY ASH



SANDSTONE

Single Unit



**STANDARD**  
 300 x 100 x 200mm  
 11 7/8 x 3 7/8 x 7 7/8"  
 96 units/Bundle  
 .33 Fc.Ft./Stone

Notes: **Sold in full bundles only on an optional skid.** Maximum height is 24" (under optimum conditions). \*Based on 12" deep wall coverage = 21.4 sqft per bundle. Based on an 8" deep wall coverage = 32 sqft per bundle. LedgeStone, Brussels XL complement as a possible coping unit. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products:

[contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a

Surface Texture - Standard

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	STANDARD	STANDARD HALF	CORNER 45° (Left & Right)	CORNER 90° (Left & Right)
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	GORMLEY	GORMLEY	GORMLEY	GORMLEY
Thickness (mm)	300 MM	300 MM	300 MM	300 MM

FCFT PER	Bundle	6.02	3.00	7.04	7.04
	Layer	6.02	3.00	7.04	7.04
	Stone	6.02	3.00	7.04	7.04

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	6.02	3.00	-	-
	Unit	6.02	3.00	-	-

UNITS PER	SqFt	0.17	0.33	0.14	0.14
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,680	800	1,480	1,320
	Section	-	-	-	-
	Bundle	1,680	800	1,480	1,320

COLORS	Reflectance	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO



NATURAL

Single Units				
	<b>STANDARD</b>	<b>STANDARD HALF</b>	<b>CORNER 45°</b>	<b>CORNER 90°</b>
	1830 x 300 x 600mm	915 x 300 x 600mm	1520 x 300 x 600mm	1520 x 300 x 600mm
	72 x 11 7/8 x 23 5/8"	36 x 11 7/8 x 23 5/8"	59 7/8 x 11 7/8 x 23 5/8"	59 7/8 x 11 7/8 x 23 5/8"
	1 unit/Bundle 6.02 Fc.Ft./Stone	1 unit/Bundle 3.00 Fc.Ft./Stone	1 unit/Bundle 7.04 Fc.Ft./Stone	1 unit/Bundle 7.04 Fc.Ft./Stone

Notes: \*Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY and is produced and sold on an required, refundable skid. **PALLETIZED 2 PIECES PER PALLET.** Closed-end coping units are closed on both ends so that they may be used as left or right units. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soil information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a  
Surface Texture - Standard

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	COPING HALF	COPING STANDARD	COPING CLOSED-END
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE
Plant Produced	GORMLEY	GORMLEY	GORMLEY
Thickness (mm)	300 MM	300 MM	300 MM

FCFT PER	Bundle	2.95	6.02	6.02
	Layer	2.95	6.02	6.02
	Stone	2.95	6.02	6.02

PER BUNDLE	Layers	1.00	1.00	1.00
	Sections	-	-	-

LNFT PER	Bundle	-	-	-
	Unit	-	-	-

UNITS PER	SqFt	0.34	0.17	0.17
	Section	-	-	-
	Bundle	1.00	1.00	1.00

LBS PER	Layer	780	1,560	1,560
	Section	-	-	-
	Bundle	780	1,560	1,560

COLORS	Reflectance	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO



NATURAL

Single Units			
	<b>COPING HALF</b>	<b>COPING</b>	<b>CLOSED-END COPING</b>
	915 x 300 x 600mm 36 x 11 7/8 x 23 5/8" 1 unit/Bundle 2.95 Fc.Ft./Stone	1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone	1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8" 1 unit/Bundle 6.02 Fc.Ft./Stone

Notes: \*Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY and is produced and sold on an required, refundable skid. **PALLETIZED, 2 PIECES PER PALLET.** Closed-end coping units are closed on both ends so that they may be used as left or right units. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soil information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a  
Surface Texture - Standard

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	STANDARD	CORNER 90° (Left & Right)	COPING	COPING CLOSED-END
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	GORMLEY	GORMLEY	GORMLEY	GORMLEY
Thickness (mm)	300 MM	300 MM	300 MM	300 MM

FCFT PER	Bundle	24.10	16.67	24.08	24.08
	Layer	6.02	4.17	6.02	6.02
	Stone	6.02	4.17	6.02	6.02

PER BUNDLE	Layers	4.00	4.00	4.00	4.00
	Sections	-	-	-	-

LNFT PER	Bundle	24.10	-	24.10	24.10
	Unit	6.02	-	6.02	6.02

UNITS PER	SqFt	0.17	0.24	0.17	0.17
	Section	-	-	-	-
	Bundle	4.00	4.00	4.00	4.00

LBS PER	Layer	938	460	884	884
	Section	-	-	-	-
	Bundle	3,752	1,840	3,536	3,536

COLORS	Reflectance	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	S0	S0	S0	S0



NATURAL

Single Units				
	<b>Corner 90°</b>	<b>STANDARD</b>	<b>COPING</b>	<b>CLOSED-END COPING</b>
	900 x 300 x 360mm 35 1/2 x 11 7/8 x 14 1/4"	1830 x 300 x 360mm 72 x 11 7/8 x 14 1/4"	1830 x 300 x 360mm 72 x 11 7/8 x 14 1/4"	1830 x 300 x 360mm 72 x 11 7/8 x 14 1/4"
	4 unit/Bundle	4 unit/Bundle	4 unit/Bundle	4 unit/Bundle
	4.17 Fc.Ft./Stone	6.02 Fc.Ft./Stone	6.02 Fc.Ft./Stone	6.02 Fc.Ft./Stone

Notes: **\*Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY** and is produced and sold on an required, refundable skid. Closed-end coping units are closed on both ends so that they may be used as left or right units. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soil information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products:

[contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a

Surface Texture - Split

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	TAPERED SPLIT CLASSIC ANTIQUED	CORNER SPLIT CLASSIC ANTIQUED	COPING TAPERED CLASSIC ANTIQUED
<b>Bundle Type</b>	<b>RANDOM</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	150 MM	150 MM	75 MM

FCFT PER	Bundle	31.25	20.83	18.74
	Layer	6.25	4.17	2.34
	Stone	0.52	0.52	0.26

PER BUNDLE	Layers	5.00	5.00	8.00
	Sections	4.00	4.00	3.00

LNFT PER	Bundle	62.30	41.60	66.00
	Unit	1.04	1.04	.92

UNITS PER	SqFt	1.92	1.92	3.84
	Section	15.00	10.00	24.00
	Bundle	60.00	40.00	72.00

LBS PER	Layer	608	452.8	299
	Section	760	566	797
	Bundle	3,040	2,264	2,392

COLORS	Reflectance	Stock	Stock	Stock
Granite	SR n/a SRI n/a	✓	✓	✓
Sandstone	SR n/a SRI n/a	✓	✓	✓
Sierra	SR n/a SRI n/a	✓	✓	✓



GRANITE



SANDSTONE



SIERRA

Random Bundle				Single Units		
	<b>LARGE TAPERED</b> 380 x 150 x 230mm 15 x 5 7/8 x 9" 20 units/Bundle .63 Fc.Ft./Stone	<b>MEDIUM TAPERED</b> 320 x 150 x 230mm 12 5/8 x 5 7/8 x 9" 20 units/Bundle .52 Fc.Ft./Stone	<b>SMALL TAPERED</b> 250 x 150 x 230mm 9 7/8 x 5 7/8 x 9" 20 units/Bundle .42 Fc.Ft./Stone		<b>CORNER SPLIT</b> 320 x 150 x 230mm 12 5/8 x 5 7/8 x 9" 40 units/Bundle .52 Sq.Ft./Stone	<b>COPING TAPERED</b> 320 x 75 x 300mm 12 5/8 x 3 x 11 7/8" 72 units/Bundle .26 Sq.Ft./Stone

Notes: 6" random wall bundles have convertible large units that can be used for corners or ending seat walls. End caps not sold separately. Ledgestone™ coping, Brussels Block® XL or Brussels Fullnose™ complement as a possible coping. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a  
Surface Texture - Smooth

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	RANDOM CLASSIC	PILLAR CLASSIC
<b>Bundle Type</b>	RANDOM	SINGLE
<b>Plant Produced</b>	MICHIGAN	MICHIGAN
<b>Thickness (mm)</b>	100 MM	100 MM

FCFT PER	Bundle	29.92	29.97
	Layer	9.97	9.99
	Stone	0.50	0.33

PER BUNDLE	Layers	3.00	3.00
	Sections	3.00	-

LNFT PER	Bundle	89.06	-
	Unit	1.48	-

UNITS PER	SqFt	2.01	3.00
	Section	20.00	-
	Bundle	60.00	90.00

LBS PER	Layer	881	893
	Section	881	-
	Bundle	2,643	2,679

COLORS	Reflectance	Stock	Stock
Limestone	SR.n/a SRI n/a	✓	✓
Charcoal	SR.n/a SRI n/a	✓	✓
Sandstone	SR.n/a SRI n/a	✓	✓



LIMESTONE



CHARCOAL



SANDSTONE

Random Bundle	XL RECTANGLE	LARGE RECTANGLE	RECTANGLE	SMALL RECTANGLE	Single Unit
					
	600 x 100 x 200mm 23 5/8 x 3 7/8 x 7 7/8 15 units/Bundle	500 x 100 x 200mm 19 3/4 x 3 7/8 x 7 7/8 15 units/Bundle	400 x 100 x 200mm 15 3/4 x 3 7/8 x 7 7/8 15 units/Bundle	300 x 100 x 200mm 11 7/8 x 3 7/8 x 7 7/8 15 units/Bundle	CORNER/PILLAR 300 x 100 x 200mm 11 7/8 x 3 7/8 x 7 7/8" 90 units/Bundle .33 Fc.Ft./Stone

Notes: Sold in full bundles only and is produced and sold on an optional, refundable skid. Spacing strips are shipped with random wall and pillar bundles to create even spacing between units. LedgeStone™ or Unilock Natural Stone complement as possible coping options. All measurements are nominal. Contact Unilock for more information.



	CORNER DOUBLE SPLIT	TAPERED SPLIT	COPING
<b>Bundle Type</b>	DOUBLE UNIT	DOUBLE UNIT	DOUBLE UNIT
Plant Produced	MICHIGAN	MICHIGAN	MICHIGAN
Thickness (mm)	150 MM	150 MM	75 MM

FCFT PER	Bundle	20.17	20.00	20.34
	Layer	6.72	6.67	2.91
	Stone	1.68	0.67	0.48

PER BUNDLE	Layers	3.00	3.00	7.00
	Sections	4.00	2.00	2.00

LNFT PER	Bundle	-	40.00	82.95
	Unit	-	1.33	1.97

UNITS PER	SqFt	0.59	1.50	2.06
	Section	3.00	15.00	21.00
	Bundle	12.00	30.00	42.00

LBS PER	Layer	440	860	393
	Section	330	1,290	1,375
	Bundle	1,320	2,580	2,750

COLORS	Reflectance	Stock	Stock	Stock
Beechwood	SR.n/a SRI n/a	✓	✓	✓
Charcoal	SR.n/a SRI n/a	✓	✓	✓
Granite	SR.n/a SRI n/a	✓	✓	✓
Sandstone	SR.n/a SRI n/a	✓	✓	✓

**APPLICATIONS**



**CROSS SECTIONS**

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

**APPEARANCE**

Edge Detail - n/a  
Surface Texture - Split  
Joint Spacing - n/a

**TECHNOLOGIES**

**CLASSIC™**  
Budget-friendly traditional product mix

**TECHNICAL INFORMATION**

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits



BEECHWOOD CHARCOAL GRANITE SANDSTONE

Single Units		<b>CORNER</b> 300 x 150 x 200mm 11 7/8 x 5 7/8 x 7 7/8" 12 units/Bundle 1.68 Fc.Ft./Stone		<b>TAPERED SPLIT</b> 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 30 units/Bundle .67 Fc.Ft./Stone		<b>COPING</b> 300 x 75 x 300mm 11 7/8 x 3 x 11 7/8" 42 units/Bundle .48 Fc.Ft./Stone
--------------	--	---	--	---	--	--

Notes: \* **TAPERED WALL UNITS ARE DOUBLE UNITS AND ARE SOLD IN FULL BUNDLES ONLY.** 12" Coping bundle has 16 units of closed-end coping (8 left and 8 right). Closed-end 12" coping is not sold separately. Maximum height - 36" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. The set back on Pisa wall is 3/4" every course or 1 1/2" every 2 courses. Min radius is 5 ft. Retaining wall engineering software is also available free of charge at [www.unilock.com](http://www.unilock.com). Walls greater than 4' in height require professional engineering. All measurements are nominal. Contact Unilock for more information.



	CORNER	XL TAPERED	COPING
<b>Bundle Type</b>	SINGLE	SINGLE	MULTI-COMPONENT
Plant Produced	MICHIGAN	MICHIGAN	MICHIGAN
Thickness (mm)	150 MM	150 MM	75 MM

FCFT PER	Bundle	46.52	20.67	15.50
	Layer	11.63	5.17	1.94
	Stone	0.97	0.65	0.32

PER BUNDLE	Layers	4.00	4.00	8.00
	Sections	-	-	-

LNFT PER	Bundle	-	42.00	62.99
	Unit	-	1.31	1.31

UNITS PER	SqFt	1.03	1.55	3.10
	Section	-	-	-
	Bundle	48.00	32.00	48.00

LBS PER	Layer	695	627	282
	Section	-	-	-
	Bundle	2,780	2,508	2,256

COLORS	Reflectance	Stock	Stock	Stock
Fieldstone	SR.n/a SRI n/a	✓	✓	✓
Granite	SR.n/a SRI n/a	✓	✓	✓
Charcoal	SR.n/a SRI n/a	✓	✓	✓

## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products:  
[contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a  
 Surface Texture - Smooth  
 Joint Spacing - n/a

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
 Eligible for LEED v4.1 credits



FIELDSTONE




GRANITE




CHARCOAL

Single Units




### CORNER

400 x 150 x 200mm  
 15 3/4 x 5 7/8 x 7 7/8"  
 48 units/Bundle  
 .97 Fc.Ft./Stone



### XL TAPERED

400 x 150 x 300mm  
 15 3/4 x 5 7/8 x 11 7/8"  
 32 units/Bundle  
 .65 Fc.Ft./Stone



### COPING - MULTI-COMPONENT

400 x 75 x 325mm  
 15 3/4 x 3 x 12 3/4"  
 48 units/Bundle  
 .32 Fc.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY.** 12" Coping bundle has 48 units of coping (32 regular coping and 16 closed-end units). Closed-end 12" coping is not sold separately. Maximum height - 36" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. Min radius is 7.3' outside, with an 8mm (3 degree). Retaining wall engineering software is also available free of charge at [www.unilock.com](http://www.unilock.com). Walls greater than 4' in height require professional engineering. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
Surface Texture - Textured

## TECHNOLOGIES

### REALA™

Cast from natural stone

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	WALL	CORNER
<b>Bundle Type</b>	<b>RANDOM</b>	<b>RANDOM</b>
Plant Produced	AYR	AYR
Thickness (mm)	57 MM	57 MM

FCFT PER	Bundle	24.30	16.21
	Layer	3.0	4.0
	Stone	0.19	0.41

PER BUNDLE	Layers	8.00	4.00
	Sections	-	-

LNFT PER	Bundle	130.69	-
	Unit	-	-

UNITS PER	SqFt	5.27	2.47
	Section	-	-
	Bundle	128.00	40.00

LBS PER	Layer	251.87	293
	Section	-	-
	Bundle	2,015	1,173

COLORS	Reflectance	Stock	Stock
Buff	SR n/a SRI n/a	✓	✓
Coastal Slate	SR n/a SRI n/a	✓	✓



BUFF



COASTAL SLATE

Corner Bundle		<b>LONG CORNER UNIT</b> 17½ x 9-10 x 2¼" 450 x 230-250 x 57mm		<b>SHORT CORNER UNIT</b> 14½ x 9-10 x 2¼" 375 x 230-250 x 57mm
	Random Bundle		<b>STANDARD UNIT 1</b> 8 x 9-10 x 2¼" 200 x 230-250 x 57mm	
		<b>STANDARD UNIT 3</b> 12 x 9-10 x 2¼" 300 x 230-250 x 57mm		<b>STANDARD UNIT 4</b> 17 x 9-10 x 2¼" 425 x 230-250 x 57mm

Notes: All measurements are nominal. Rivercrest™ is recommended for walls under 2ft. Ideal for straight or curved walls, seat walls, pillars, tree rings, planters, firepits and grill islands. Integrated connectors require no pins or clips. Minimum radius using equal amounts of each unit is 1.25m / 4.1ft. Using only units 1 & 3, a 1.055m / 3.5ft radius can be achieved. Unilock, through Risi Stone Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. Contact your local Unilock representative for details. Retaining wall engineering software is also available free of charge at [www.unilock.com](http://www.unilock.com).



## APPLICATIONS



## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE

Edge Detail - n/a  
Surface Texture - Smooth

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	STANDARD	COPING
Bundle Type	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO
Thickness (mm)	180 MM	180 MM

FCFT PER	Bundle	20.88	20.88
	Layer	6.96	6.96
	Stone	1.74	1.74

PER BUNDLE	Layers	3.00	3.00
	Sections	-	-

LNFT PER	Bundle	35.43	35.43
	Unit	2.95	2.95

UNITS PER	FcFt	0.57	0.57
	Section	-	-
	Bundle	12.00	12.00

LBS PER	Layer	932.4	932.4
	Section	-	-
	Bundle	2,797	2,797

COLORS	Reflectance	Stock	Stock
Granite	SR.n/a SRI n/a	✓	✓
Fieldstone	SR.n/a SRI n/a	✓	✓
Charcoal	SR.n/a SRI n/a	✓	✓



GRANITE



FIELDSTONE



CHARCOAL

Single Units



**STANDARD WALL**  
290 x 900 x 180 mm  
11 1/2 x 35 7/16 x 7"  
12 units/Bundle  
1.74 Fc.Ft./Stone



**COPING**  
290 x 900 x 180mm  
11 1/2 x 35 7/16 x 7"  
12 units/Bundle  
1.74 Fc.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at [www.unilock.com](http://www.unilock.com). All measurements are nominal. Contact Unilock for more information.



**APPLICATIONS**



**CROSS SECTIONS**

Cross Sections are available on Unilock's Contractor website under Products: [contractor.unilock.com](http://contractor.unilock.com)

**APPEARANCE**

Edge Detail - n/a  
Surface Texture - Split

**TECHNOLOGIES**

**CLASSIC™**

Budget-friendly traditional product mix

**TECHNICAL INFORMATION**

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	CORNER 90° SPLIT	CORNER 45° SPLIT	STANDARD 500 SPLIT	STANDARD 925 SPLIT	COPING SPLIT	COPING SPLIT C-E
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	GORMLEY	GORMLEY	GORMLEY	GORMLEY	GORMLEY	GORMLEY
Thickness (mm)	185 MM	185 MM	185 MM	185 MM	185 MM	185 MM

FCFT PER	Bundle	19.11	-	14.43	7.21	14.43	14.43
	Layer	6.37	-	4.81	2.40	4.81	4.81
	Stone	3.19	-	2.41	2.40	2.41	2.41

PER BUNDLE	Layers	3.00	3.00	3.00	3.00	3.00	3.00
	Sections	-	-	3.00	-	3.00	3.00

LNFT PER	Bundle	-	-	24.00	12.00	23.70	23.70
	Unit	-	-	4.00	4.00	3.95	3.95

UNITS PER	SqFt	0.31	-	0.42	0.42	0.42	0.42
	Section	-	-	2.00	-	2.00	2.00
	Bundle	6.00	6.00	6.00	3.00	6.00	6.00

LBS PER	Layer	1,140	1,050	1,140	1,140	1,140	1,140
	Section	-	-	1,140	-	1,140	1,140
	Bundle	3,420	3,150	3,420	3,420	3,420	3,420

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock
Natural	n/a	SO	SO	SO	SO	SO	✓



NATURAL

Single Units	CORNER 90° SPLIT	CORNER 45° SPLIT	STANDARD 500 SPLIT	STANDARD 925 SPLIT	COPING SPLIT	COPING C-E SPLIT
	1100 x 185 x 500mm 43 3/8 x 7 3/8 x 19 3/4"	1100 x 185 x 500mm 43 3/8 x 7 3/8 x 19 3/4"	1200 x 185 x 500mm 47 1/4 x 7 3/8 x 19 3/4"	1200 x 185 x 925mm 47 1/4 x 7 3/8 x 36 1/2"	1200 x 185 x 500mm 47 1/4 x 7 3/8 x 19 3/4"	1200 x 185 x 500mm 47 1/4 x 7 3/8 x 19 3/4"
	6 units/Bundle	6 units/Bundle	6 units/Bundle	3 units/Bundle	6 units/Bundle	6 units/Bundle
	3.19 Fc.Ft./Stone		2.41 Fc.Ft./Stone	2.40 Fc.Ft./Stone	2.41 Fc.Ft./Stone	2.41 Fc.Ft./Stone

Notes: **Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY** and is sold on a required, refundable skid. Stocked CE is sold by the piece. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at [www.unilock.com](http://www.unilock.com). All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth

## CROSS SECTIONS

Cross Sections are available on Unilock's

Contractor website under Products:

[contractor.unilock.com](http://contractor.unilock.com)

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	SIENASTONE 38½" DOUBLE CORNER	SIENASTONE 48" SMOOTH WALL	SIENASTONE 48" SMOOTH COPING	SIENASTONE 48" SMOOTH COPING CLOSED-END R & L
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	GORMLEY	GORMLEY	GORMLEY	GORMLEY
Thickness (mm)	180 MM	180 MM	180 MM	180 MM

FCFT PER	Bundle	15.71	20.93	20.93	20.93
	Layer	5.24	6.98	6.98	6.98
	Stone	5.24	2.33	2.33	2.33

PER BUNDLE	Layers	3.00	3.00	3.00	3.00
	Sections	-	-	-	-

LNFT PER	Bundle	-	36.00	36.00	36.00
	Unit	-	4.00	4.00	4.00

UNITS PER	SqFt	0.19	0.43	0.43	0.43
	Section	-	-	-	-
	Bundle	3.00	9.00	9.00	9.00

LBS PER	Layer	648	1,182	1,185	1,185
	Section	-	-	-	-
	Bundle	1,944	3,546	3,555	3,555

COLORS	Reflectance	Stock	Stock	Stock	Stock
Granite	SR.n/a SRI n/a	✓	✓	✓	✓
Safari	SR.n/a SRI n/a	SO	SO	SO	SO



GRANITE



SAFARI

Single Units	CORNER UNIT 375	STANDARD 375	48" COPING	48" COPING CLOSED-END R OR L
	975 x 180 x 375mm 38 ½ x 7 x 14 ⅞" 3 units/Bundle 5.24 Fc.Ft./Stone	1200 x 180 x 375mm 47 ¼ x 7 x 14 ⅞" 9 units/Bundle 2.33 Fc.Ft./Stone	1200 x 180 x 383mm 47 ¼ x 7 x 15" 9 units/Bundle 2.33 Fc.Ft./Stone	1200 x 180 x 383mm 47 ¼ x 7 x 15" 9 units/Bundle 2.33 Fc.Ft./Stone

Notes: Sold on a required, refundable skid. CLOSE-END COPING LEFT AND RIGHT ARE SOLD SEPARATELY. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Smooth

## CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products:  
[contractor.unilock.com](http://contractor.unilock.com)

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	SIENASTONE 48" SMOOTH STEP	SIENASTONE 72" SMOOTH STEP
<b>Bundle Type</b>	SINGLE	SINGLE
Plant Produced	GORMLEY	GORMLEY
Thickness (mm)	180 MM	180 MM

FCFT PER	Bundle	13.95	6.97
	Layer	4.65	3.49
	Stone	2.33	3.49

PER BUNDLE	Layers	3.00	2.00
	Sections	-	-

LNFT PER	Bundle	24.00	11.81
	Unit	4.00	5.91

UNITS PER	SqFt	0.43	0.29
	Section	-	-
	Bundle	6.00	2.00

LBS PER	Layer	1,081	798
	Section	-	-
	Bundle	3,242	1,596

COLORS	Reflectance	Stock	Stock
Dusk	SR.n/a SRI n/a	✓	SO
Granite Blend	SR.n/a SRI n/a	✓	SO
Light Grey	SR.n/a SRI n/a	*	-
Charcoal	SR.n/a SRI n/a	✓	SO
Safari	SR.n/a SRI n/a	✓	SO

\*While Supplies Last



DUSK



GRANITE BLEND



LIGHT GREY



CHARCOAL



SAFARI

Single Units



**48" STEP**  
1200 x 180 x 500mm  
47 1/4 x 7 x 19 3/4"  
6 units/Bundle  
2.33 Fc.Ft./Stone




**72" STEP**  
1800 x 180 x 500mm  
70 7/8 x 7 x 19 3/4"  
2 units/Bundle  
3.49 Fc.Ft./Stone

Notes: Product is sold on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
 Surface Texture - Smooth, Series Exposed,  
 Umbriano® Mottled & Pitched

## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color


**COLORFUSION™**  
 Subtly mottled colored finish

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
 Eligible for LEED v4.1 credits



Download the U-Cara Multi-Face Wall Installation Guide.



Pitched Finish		Smooth Finish		Umbriano Finish		Series Finish		3" PANEL		Subway		Lavano		COMING SOON
----------------	--	---------------	--	-----------------	--	---------------	--	----------	--	--------	--	--------	--	-------------

	STANDARD 6" FASCIA SMOOTH	CLOSED-END 6" FASCIA SMOOTH	STANDARD 3" FASCIA SMOOTH	STANDARD 3" FASCIA SERIES EXPOSED	STANDARD 6" FASCIA UMBRIANO	CLOSED-END 6" FASCIA UMBRIANO	STANDARD 6" FASCIA PITCHED	CLOSED-END 6" FASCIA PITCHED
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	MICHIGAN	MICHIGAN	MICHIGAN	CHICAGO	GEORGETOWN	GEORGETOWN	MICHIGAN	MICHIGAN
Thickness (mm)	150 MM	150 MM	71 MM	71 MM	150 MM	150 MM	150 MM	150 MM

FCFT PER	Bundle	61.52	54.18	63.20	59.32	61.52	54.18	61.52	54.18
	Layer	10.25	9.03	10.53	9.89	10.25	9.03	10.25	9.03
	Stone	0.73	1.29	0.19	0.18	0.73	1.29	0.73	1.29

PER BUNDLE	Layers	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00
	Sections	-	-	-	-	-	-	-	-

LNFT PER	Bundle	129.50	104.86	-	-	-	104.86	129.50	104.86
	Unit	1.54	2.50	-	-	-	2.50	1.54	2.50

UNITS PER	SqFt	1.37	0.78	5.32	5.66	1.37	0.78	1.37	0.78
	Section	-	-	-	-	-	-	-	-
	Bundle	84.00	42.00	336.00	336.00	84.00	42.00	84.00	42.00

LBS PER	Layer	252	207	242	250	252	213	291	236
	Section	-	-	-	-	-	-	-	-
	Bundle	1,513	1,240	1,453	1,501	1,513	1,240	1,745	1,415

COLORS	Reflectance	Stock								
Dark Charcoal	SR.n/a SRI n/a	✓	✓	-	-	-	-	-	-	-
Fossil	SR.n/a SRI n/a	✓	✓	*	-	-	-	✓	✓	
French Gray	SR.n/a SRI n/a	-	-	-	-	SO	SO	-	-	
Granite	SR.n/a SRI n/a	✓	✓	-	-	-	-	✓	✓	
Midnight Sky	SR.n/a SRI n/a	-	-	-	-	SO	SO	-	-	
Natural	SR.n/a SRI n/a	✓	✓	-	-	-	-	-	-	
Onyx Black	SR.n/a SRI n/a	-	-	-	✓	-	-	-	-	
Summer Wheat	SR.n/a SRI n/a	-	-	-	-	SO	SO	-	-	
Sierra	SR.n/a SRI n/a	*	*	-	-	-	-	*	*	
Winter Marvel	SR.n/a SRI n/a	-	-	-	-	SO	SO	-	-	
Indiana Buff	SR.n/a SRI n/a	✓	✓	-	-	-	-	-	-	

\*While Supplies Last

Single Unit		<b>6" STANDARD FASCIA PANEL</b> 5 7/8 x 18 3/8 x 2 3/8" 150 x 466 x 60mm 84 units/Bundle .73 Sq.Ft./Stone	Single Unit		<b>3" FASCIA PANEL</b> 2 7/8 x 9 x 2 3/8" 71 x 231 x 60mm 336 units/Bundle .18 Sq.Ft./Stone
2 Unit Corner		<b>STANDARD FASCIA HALF PANEL</b> 5 7/8 x 9 1/4 x 2 3/8" 150 x 233 x 60mm			<b>CLOSED-END FASCIA PANEL</b> 5 7/8 x 20 7/8 x 2 3/8" 150 x 530 x 60mm  <i>Close-End panels: 24 rights/18 lefts per pallet</i>

# U-Cara® Multi-Face Wall System



	LAVANO STANDARD	SUBWAY STANDARD	CLOSED END/HALF PANEL
<b>Bundle Type</b>	SINGLE	SINGLE	BUNDLE
Plant Produced	MICHIGAN	MICHIGAN	MICHIGAN
Thickness (mm)	150 MM	150 MM	150 MM

FCFT PER	Bundle	61.52	61.52	54.18
	Layer	10.25	10.25	9.03
	Stone	0.73	0.73	1.29

PER BUNDLE	Layers	6.00	6.00	6.00
	Sections	-	-	-


LNFT PER	Bundle	129.50	129.50	104.86
	Unit	1.54	1.54	2.50

UNITS PER	SqFt	1.37	1.37	0.78
	Section	-	-	-
	Bundle	84.00	84.00	42.00

LBS PER	Layer	252.00	252.00	207.00
	Section	-	-	-
	Bundle	1,513	1,513	1,240

COLORS	Reflectance	Stock	Stock	Stock
Granite Fusion	SR n/a SRI n/a	COMING SOON	-	COMING SOON
Fossil	SR n/a SRI n/a	COMING SOON	-	COMING SOON
Dark Charcoal	SR n/a SRI n/a	-	✓	✓
Opal	SR n/a SRI n/a	-	✓	✓
Ivory	SR n/a SRI n/a	-	✓	✓

## APPLICATIONS



## CROSS SECTIONS

All Cross Sections are available on Unilock's Contractor web site under Products:

[contractor.unilock.com](http://contractor.unilock.com)

## APPEARANCE



Edge Detail - n/a

Surface Texture - Smooth

## TECHNICAL INFORMATION

Conforms to ASTM C 1372


Eligible for LEED v4.1 credits



Notes: Sold in full bundles. Produced and sold on a required refundable skids. Sure Track Large Backer Units when used as corners in a pillar application, can achieve 42 FFT/bundle or .757 FFT/unit.



## APPLICATIONS



## TECHNOLOGIES

**ENDURACOLOR™**  
Refined surface  
and long-lasting color

**COLORFUSION™**  
Subtly mottled colored finish

## CROSS SECTIONS

All Cross Sections are available on Unilock's Contractor website under Products:

[contractor.unilock.com](http://contractor.unilock.com)


## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

## APPEARANCE

Edge Detail - n/a  
Surface Texture - Smooth, Series  
Exposed, Umbriano® Mottled & Pitched


## U-CARA RETAINING WALL GEOGRID SECTION



## U-CARA®

### CROSS SECTION

Garden Wall - Max Height 15"




Notes:  
This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

## U-CARA®

### CROSS SECTION

Seat Wall - Max Height 21"



Notes:  
This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

# U-Cara® Wall Mount System

	LARGE BACKER	STANDARD BACKER
<b>Bundle Type</b>	SINGLE	SINGLE
<b>Plant Produced</b>	MICHIGAN	MICHIGAN
<b>Thickness (mm)</b>	150 MM	150 MM

FCFT PER	Bundle	15.82	33.91
	Layer	3.96	11.30
	Stone	0.28	0.32

PER BUNDLE	Layers	4.00	3.00
	Sections	-	-

LNFT PER	Bundle	-	69.99
	Unit	-	0.67

UNITS PER	SqFt	3.54	3.10
	Section	-	-
	Bundle	56.00	105.00

LBS PER	Layer	503	812
	Section	-	-
	Bundle	2,012	2,437

COMPONENTS	Reflectance	Stock	Stock
Large Backer	n/a	✓	-
Standard Backer	n/a	-	✓

**Components**



**SURE TRACK  
LARGE BACKER**  
5 7/8" x 6 7/8" x 11 5/8"  
150 x 175 x 294mm



**SURE TRACK  
STANDARD BACKER**  
5 7/8" x 5 7/8" x 7 7/8"  
150 x 150 x 195mm

*Notes: Sold in full pallets only on a refundable skid. All measurements are nominal. Contact Unilock for more information.*

**Umbiano Panels**



FRENCH GREY



SUMMER WHEAT



WINTER MARVEL



MIDNIGHT SKY

**Smooth Panel**

Smooth Panel



GRANITE



FOSSIL



NATURAL



SIERRA



DARK CHARCOAL



INDIANA BUFF

**Pitched Panel**

Pitched Panel



FOSSIL



GRANITE



SIERRA

**Series 3" Panel**



ONYX BLACK

**Recommended Base Unit**



**UNIVERSAL BASE**  
482 x 355 x 55mm  
19 x 14 x 2 1/4"  
54 units/Bundle

*Please go to page 69 for more Universal product information.*

**Extra Components**


**SURE TRACK CORNER INSERT**  
L = 2"  
50mm  
40pcs/bag




# U-Cara® Modular System

The U-Cara Modular System offers a variety of aluminum frames that can be mixed and matched to construct vertical features like grill islands. Speak to your contractor to select a design and a U-Cara fascia panel finish to suit your project.

**With the U-Cara Modular System you can build Grill Islands, Bars, Back splashes, Fire Places and Pillars.**



NO.	MODEL	DESCRIPTION
UCARA000001	URS	UCARA 8' RAIL (10/PACK)
UCARA000003	URS	ALIGNMENT BARS 39" (10/PACK)
UCARA000007	UL-OSK	CABINET DEPTH CHANGE KIT
UCARA000009	UL-FIR	U-CARA FIREPLACE
UCARA000010	UL-FIR-M	U-CARA FIREPLACE MANTLE
UCARA000016	UL-FIR-MW	U-CARA FIREPLACE MANTLE WIDE UNIT
UCARA000017	UL-FIR-CH	U-CARA U-CARA FIREPLACE CHIMNEY UNIT
UCARA000018	UL-FIR-CH-MW	U-CARA FIREPLACE CHIMNEY WIDE UNIT
UCARA000019	UL-FIR-RTN	U-CARA FIREPLACE RETURN
UCARA000020	UL-FIR-RTN-OS	U-CARA FIREPLACE RETURN OVERSIZED
UCARA001000	UL-GC	UNIVERSAL GRILL CABINET (fits 36-42" grill)
UCARA002000	UL-BC	BASE CABINET (fits fire table or fridge)
UCARA003000	UL-CC	CORNER CABINET 27.5" x 27.5"
UCARA003001	UL-CC-OS	CORNER CABINET 27.5" x 36.5" OS
UCARA003002	UL-CC-BP	CORNER CABINET BACK PANEL
UCARA004000	UL-ECK	END CLAD KIT 27.5"
UCARA004001	UL-ECK-OS	END CLAD KIT 36.5" OS
UCARA005000	UL-BS	BACKSPLASH-GRILL/BASE UNIT 64½"
UCARA005001	UL-BS-CC	BACKSPLASH CORNER CABINET
UCARA005002	UL-BS-CC-OS	BACKSPLASH CORNER CABINET OS
UCARA006000	UL-DD	STAINLESS DOUBLE ACCESS DOORS 27"
UCARA007000	UL-PU	PILLAR UNIT (18¾" x 18¾")
UCARA001002	UL-GC-36	UNIVERSAL GRILL CABINET (FITS 36"-42" GRILL)
UCARA002001	UL-BC-36	BASE CABINET (FITS FIRE TABLE OR FRIDGE)
UCARA003004	UL-CC-OS-36	CRNR CABINET 27.5X36.5 OS
UCARA003005	UL-CC-36	CORNER CABINET 27.5X27.5
UCARA004002	UL-ECK-36	END CLAD KIT 27.5"
UCARA004003	UL-ECK-OS-36	END CLAD KIT 36.5" OS



Download the U-Cara Modular Fireplace Installation Guide.

# U-Cara® Wall Mount System

---



The U-Cara Wall Mount System allows you to put the finishing touches on your project by cladding existing structures like unsightly exposed foundation areas or concrete steps with U-Cara fascia panels.



U-CARA ALIGNMENT BAR:  
39" LENGTH - SOLD IN PACKS OF 10 PIECES

U-CARA RAILS:  
8' LENGTH - SOLD IN PACKS OF 10 PIECES

# U-Cara® Wall Mount System INSTALLATION

## Alignment Bar

- | 38-5/8" tall (up to 7 courses of 6" fascia panels)
- | Pre-punched to accommodate both 3" & 6" panels
- | Eliminates the need to measure for rail spacing
- | Speeds up installation
- | 10 per bundle



## Horizontal Rail

- | 8' long with pre-punched holes every 8"
- | Heavy duty galvanized steel
- | 10 per bundle




## U-Cara Fascia Panels

- | EnduraColor Technology
- | Available in 4 different finishes and several colors
- | Apply adhesive and hang on wall mount system



### Wood Substrate Application




- Barrithane VP**
- | Damp surface tolerant
  - | Immediately rain resistant
  - | Single coat application
  - | Apply as low as 15° F




- Sharp Point Roofing Screw #12 x 1-1/2"**
- | Hex head
  - | Rubber washer
  - | Corrosion resistant coating

### Concrete Substrate Application




- Titen 2 Hex Head 3/16" x 1-3/4"**
- | Improved thread design
  - | Increased load capacity
  - | Reduced snapping
  - | 450+ pound tension load
  - | 275+ pound shear load

# U-Cara® Wall Mount System INSTALLATION




**Step 1:** Determine finished top height, mark with chalk line. Align orange painted end of alignment bar with chalk line.

Alignment bars should be placed 16" in from end of horizontal rail, and every 32".




**Step 2:** Fasten both horizontal rail and alignment bars to substrate at points 1, 2, and 3; ensuring the rail is level.

The first four screws are the most important, as they will establish your grid pattern for all your horizontal rails in this section.




**Step 3:** Fasten the bottom horizontal rail and alignment bar at point 4; use a level or a square to ensure alignment bar is plumb

You have now established your grid pattern for the rest of your horizontal rails in this section.



**Step 4:** Fasten the bottom horizontal rail and alignment bars at points 5 and 6.



**Step 5:** Fasten remaining horizontal rails.

All horizontal rail should be fastened to substrate every 16" and on both ends.

# Architectural Cap & Coping



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
 Surface Texture - Exposed  
 Joint Spacing - n/a

## TECHNOLOGIES

**ENDURACOLOR™**  
 Refined surface and long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	COPING ENDURACOLOR	PILLAR CAP 28" ENDURACOLOR
Bundle Type	SINGLE	SINGLE
Thickness (mm)	60 MM	76 MM

SQFT PER	Bundle	-	-
	Unit	-	-

FCFT PER	Bundle	-	-
	Layer	-	-
	Unit	-	-

LNFT PER	Bundle	42.00	-
	Unit	2.00	-

UNITS PER	Bundle	21.00	6.00
	SqFt	-	-

LBS PER	Unit	68	183
	Bundle	1,428	1,098

COLORS	Reflectance	Stock	Stock
Buff	SR n/a SRI n/a	✓	✓
Charcoal	SR n/a SRI n/a	✓	✓



BUFF



CHARCOAL

Single Units		<b>COPING</b> 609 x 60mm x 355mm 24 x 2 3/8 x 14" 21 units/Bundle		<b>PILLAR CAP</b> 711 x 711mm x 76mm 28 x 28 x 3" 6 units/Bundle
--------------	---	--	---	---

Notes: COPING SOLD IN FULL PALLETS ONLY and is shipped on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Textured  
 Joint Spacing - 2mm

## TECHNOLOGIES

### CLASSIC™

Budget-friendly traditional product mix

### ANTIQUED™

Distressed, timeworn finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	<b>FULLNOSE CLASSIC ANTIQUED</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Plant Produced	MICHIGAN
Thickness (mm)	70 MM

<b>FCFT PER</b>	Bundle	-
	Layer	-
	Stone	-

<b>PER BUNDLE</b>	Layers	8.00
	Sections	4.00

<b>LNFT PER</b>	Bundle	96.00
	Unit	0.50

<b>UNITS PER</b>	SqFt	-
	Section	48.00
	Bundle	192.00

<b>LBS PER</b>	Layer	384
	Section	769
	Bundle	3,074

COLORS	Reflectance	Stock
Charcoal	SR. n/a SRI n/a	✓
Coffee Creek	SR. n/a SRI n/a	✓
Limestone	SR. n/a SRI n/a	✓
Mahogany Ash	SR. n/a SRI n/a	✓
Sandstone	SR. .41 SRI 46	✓



DARK CHARCOAL



COFFEE CREEK



LIMESTONE



MAHOGANY ASH



SANDSTONE

Single Unit

**BRUSSELS FULLNOSE**  
 150 x 300 x 70mm  
 5 7/8 x 11 7/8 x 2 3/4"  
 192 units/Bundle

Notes: **SOLD IN FULL PALLETS ONLY.** Units can be adhered to pool edge using Unilock Concrete Adhesive, or with mortar. Always observe proper construction techniques when adhering pavers to a surface. Consult your local pool contractors for installation specifics.

# Universal Coping & Base

**CLASSIC / ENDURACOLOR™**



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Standard / Smooth

## TECHNOLOGIES

**CLASSIC™ (Base)**  
Budget-friendly traditional product mix

**ENDURACOLOR™ (Coping)**  
Refined surface and long-lasting color

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
Eligible for LEED v4.1 credits

	UNIVERSAL BASE CLASSIC	UNIVERSAL COPING SMOOTH ENDURACOLOR
Bundle Type	SINGLE	SINGLE
Plant Produced	MICHIGAN	MICHIGAN
Thickness (mm)	55 MM	70 MM

FCFT PER	Bundle	-	17.44
	Layer	-	2.18
	Stone	-	0.36

PER BUNDLE	Layers	9.00	8.00
	Sections	-	-

LNFT PER	Bundle	85.50	75.90
	Unit	1.58	1.58

UNITS PER	SqFt	-	2.75
	Section	-	-
	Bundle	54.00	48.00

LBS PER	Layer	278	343
	Section	-	-
	Bundle	2,502	2,747

COLORS	Reflectance	Stock	Stock
Charcoal (EC)	SR.n/a SRI n/a	-	✓
Natural (Classic & EC)	SR.n/a SRI n/a	✓	✓
Sandstone (EC)	SR.n/a SRI n/a	-	✓



CHARCOAL



NATURAL



SANDSTONE

Single Units



**UNIVERSAL COPING**  
482 x 70 x 355mm  
19 x 2 ¾ x 14"  
48 units/Bundle  
.36 Fc.Ft./Stone



**UNIVERSAL BASE**  
482 x 355 x 55mm  
19 x 14 x 2 ¼"  
54 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is shipped on an optional, refundable skid. Two (2) End Coping units per Layer (1 Left & 1 Right). All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Textured

## TECHNOLOGIES

### REALA™

Cast from natural stone

## TECHNICAL INFORMATION

Conforms to ASTM C 1776  
Eligible for LEED v4.1 credits

	FULLNOSE COPING	STANDARD COPING	STANDARD CLOSED-END	LARGE COPING	LARGE CLOSED-END
<b>Bundle Type</b>	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	60 MM	70 MM	70 MM	70 MM	70 MM

FCFT PER	Bundle	5.12	5.52	5.52	6.87	6.87
	Layer	0.39	1.38	1.38	1.72	1.72
	Stone	0.39	0.46	0.46	0.57	0.57

PER BUNDLE	Layers	13.00	4.00	4.00	4.00	4.00
	Sections	-	-	-	-	-

LNFT PER	Bundle	26.00	24.00	24.00	30.00	30.00
	Unit	2.00	2.00	2.00	2.50	2.50

UNITS PER	SqFt	2.54	2.18	2.18	1.75	1.75
	Section	-	-	-	-	-
	Bundle	13.00	12.00	12.00	12.00	12.00

LBS PER	Layer	56	193	199	282	279
	Section	-	-	-	-	-
	Bundle	723	772	796	1,128	1,116

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock
Buff	SR.n/a SRI n/a	✓	✓	✓	✓	✓
Gray	SR.n/a SRI n/a	✓	✓	✓	✓	✓



BUFF

GREY

Single Units	FULLNOSE COPING	STANDARD COPING	STANDARD CLOSED-END COPING	LARGE COPING	LARGE CLOSED-END COPING
	610 x 305 x 60mm 24 x 12 x 2 3/8" 13 unit/Bundle .39 Fc.Ft./Stone	610 x 305 x 70mm 24 x 12 x 2 3/4" 12 unit/Bundle .46 Fc.Ft./Stone	610 x 305 x 70mm 24 x 12 x 2 3/4" 12 unit/Bundle .46 Fc.Ft./Stone	762 x 343 x 70mm 30 x 13 1/2 x 2 3/4" 12 unit/Bundle .57 Fc.Ft./Stone	762 x 343 x 70mm 30 x 13 1/2 x 2 3/4" 12 unit/Bundle .57 Fc.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Coping is rock faced on the front and the back; Closed-end coping are rock faced on three sides. Fullnose is rounded only on one side, no Closed-end available. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - n/a  
Surface Texture - Textured

## TECHNOLOGIES

### REALA™

Cast from natural stone

## TECHNICAL INFORMATION

Conforms to ASTM C 1776  
Eligible for LEED v4.1 credits

	48" STEP	24" PILLAR CAP
<b>Bundle Type</b>	<b>SINGLE</b>	<b>SINGLE</b>
Plant Produced	GEORGETOWN	CHICAGO
Thickness (mm)	150 MM	100 MM

FCFT PER	Bundle	5.91	3.28
	Layer	1.97	0.66
	Stone	1.97	0.66

PER BUNDLE	Layers	3.00	5.00
	Sections	-	-

LNFT PER	Bundle	12.00	10.04
	Unit	4.00	2.01

UNITS PER	SqFt	0.51	1.52
	Section	-	-
	Bundle	3.00	5.00

LBS PER	Layer	574	159
	Section	-	-
	Bundle	1,721	795

COLORS	Reflectance	Stock	Stock
Buff	SR.n/a SRI n/a	*	✓
Gray	SR.n/a SRI n/a	*	✓

\*While Supplies Last



BUFF



GREY

Single Units	 <p><b>48" STEP</b> 1220 x 610 x 150mm 48 x 24 x 5 7/8" 3 unit/Bundle 1.97 Fc.Ft./Stone</p>	 <p><b>24" PILLAR CAP</b> 610 x 610 x 100mm 24 x 24 x 3 7/8" 5 unit/Bundle .66 Fc.Ft./Stone</p>
--------------	--	--

Notes: **SOLD BY BUNDLE OR PIECE.** Produced and sold on a required, refundable skid. Step is rock-faced on 3 sides, while the Pillar Caps are rock-faced on all 4 sides. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Chamfered, Rounded  
 Surface Texture - Umbriano Mottled  
 Joint Spacing - 7mm

## TECHNOLOGIES

### ENDURACOLOR™

Refined surface and long-lasting color

### EASYSOAK™

Factory Sealed to provide integral stain resistance

### COLORFUSION™

Subtly mottled colored finish

## TECHNICAL INFORMATION

Conforms to ASTM C 936  
 Eligible for LEED v4.1 credits

	CHAMFERED	BULLNOSE
<b>Bundle Type</b>	SINGLE	SINGLE
<b>Plant Produced</b>	ONTARIO	ONTARIO
<b>Thickness (mm)</b>	60 MM	60 MM

FCFT PER	Bundle	9.30	9.30
	Layer	-	-
	Stone	0.39	0.39

PER BUNDLE	Layers	6.00	6.00
	Sections	2.00	2.00

LNFT PER	Bundle	47.24	47.24
	Unit	1.97	1.97

UNITS PER	SqFt	-	-
	Section	12.00	12.00
	Bundle	24.00	24.00

LBS PER	Layer	252	252
	Section	755	755
	Bundle	1,510	1,510

COLORS	Reflectance	Stock	Stock
French Grey	SR n/a SRI n/a	SO	SO
Grenada White	SR n/a SRI 52	SO	SO
Midnight Sky	SR n/a SRI n/a	SO	SO
Summer Wheat	SR n/a SRI 48	SO	SO
Winter Marvel	SR n/a SRI 38	SO	SO



FRENCH GREY



GRENADA WHITE



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

Single Units



**CHAMFERED**  
 360 x 600 x 60 mm  
 14 x 24 x 2 3/8"  
 24 units/Bundle



**BULLNOSE**  
 360 x 600 x 60 mm  
 14 x 24 x 2 3/8"  
 24 units/Bundle

Notes: **Special Order items, lead time is required. SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



## APPLICATIONS



## APPEARANCE

Edge Detail - Zero  
 Surface Texture - Standard / Tumbled  
 Joint Spacing - n/a

## TECHNOLOGIES

**CLASSIC™**  
 Budget-friendly traditional product mix

## ANTIQUED™

Distressed, timeworn finish

## TECHNICAL INFORMATION

Conforms to ASTM C 1372  
 Eligible for LEED v4.1 credits

	<b>ROUND</b>
<b>Bundle Type</b>	<b>SINGLE</b>
Dimension Metric	1300 x 1300 x 300mm
Dimension Imperial	51 1/4 x 51 1/4 x 11 7/8"
Thickness (mm)	300 MM

<b>DIAMETER (inch)</b>	Outside	52.00
	Inside	36.00
	Insert	34.00

<b>LAYER PER UNIT</b>	3.00
<b>UNIT PER LAYER</b>	20.00
<b>UNIT PER PALLET</b>	60.00

<b>LBS PER PALLET</b>	1,125
-----------------------	-------

COLORS	Reflectance	Stock
Coffee Creek	SR. n/a SRI n/a	✓
Limestone	SR. n/a SRI n/a	✓
Mahogany Ash	SR. n/a SRI n/a	✓
Sandstone	SR n/a SRI n/a	✓



COFFEE CREEK



LIMESTONE




MAHOGANY ASH




SANDSTONE

## FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.



**INSERT DIAMETER**  
34"



**INSERT DIAMETER**  
38"

Single Unit



**SUNSET ROUND W/INSERT**  
 1300 x 1300 x 300mm  
 51 1/4 x 51 1/4 x 11 7/8"

**FIRE PIT INSERTS SOLD SEPARATELY**

# Unilock Elements

## TUSCANY COLLECTION



**TUSCANY FIREPLACE**  
Sandstone with Copthorne® (3 Color Blend)  
**SPECIAL ORDER**



**TUSCANY FIREPLACE**  
Sierra with Copthorne® (3 Color Blend)

**WEIGHTS**  
**Tuscany Collection**  
Fireplace Top – 2,925 lbs  
Fireplace Bottom – 4,225 lbs  
Wood Boxes – 4,005 lbs  
Arched Hearth – 1,170 lbs

## BARCELONA COLLECTION

**SPECIAL ORDER**



**BARCELONA FIREPLACE**  
Sierra with Umbriano® (Summer Wheat)

**WEIGHTS:**  
**Barcelona Collection**  
Fireplace Top – 2,725 lbs  
Fireplace Bottom – 4,170 lbs  
Wood Boxes – 4,200 lbs  
Arched Hearth – 1,200 lbs



**TUSCANY / BARCELONA GRILL ISLAND**  
**SPECIAL ORDER**  
Available with OCS Grill, protective cover and stainless steel double door insert.



**MODA**  
**SPECIAL ORDER**

**WEIGHTS**  
Moda Base – 3,550 lbs  
Moda Top – 1,915 lbs


The Moda pre-built fireplace is constructed from Lineo Dimensional Stone and Series™ accent.




Note: Items shown are Tuscany units. Please contact Unilock for more information on special order items. Units and measurements may not be exactly as shown.

# Unilock Elements

## TYPICAL CROSS SECTION FOR CONCRETE PAD INSTALLATION



## TUSCANY & BARCELONA FIREPLACE



### GUARANTEE

The standard Unilock guarantee applies to the units used to construct Unilock Elements. (See Unilock literature for details.) Third party grills and fireboxes carry their respective manufacturer's warranty, and may change without notice.

**Note:** Unilock reserves the right to change model designs, accessories and colors without notice. Unilock will not be responsible for improper use or handling that results in property damage. Some models may not be exactly as shown. Fireplaces come complete with UL- approved stainless steel fireboxes. Check local building codes and regulations prior to ordering and installing Unilock Elements.

## Paver Cleaners



### POLYBIND™ SHAMPOO

CLN047 (1 Gallon) 1 & 5 Gallon available 1 US Gal/Box  
Polybind Shampoo removes ground-in dirt from the surface of concrete pavers and natural stones. This shampoo will make your patio, walkway, driveway, etc. look clean and vibrant. Use it before sealer application to assure you of a deeper penetration into the cleaned surface. No muriatic acid in product - washes off with water.  
Note: 5 Gallon is SPECIAL ORDER



### POLYBIND OIL & GREASE REMOVER

CLN050 (1 Quart) 1 Quart Container (6/Box)  
Polybind Oil & Grease Remover is effective in removing oil and grease from the surface of concrete pavers and natural stones. Easy to use - dissolves, dislodges and removes oil and grease. No hydrochloric acid in product - washes off with water.



### POLYBIND EFFLORESCENCE CLEANER

CLN045 (1 Gallon) & CLN046 (5 Gallon)  
Polybind Efflorescence Cleaner will remove any efflorescence stains trapped in the concrete paver and natural stone pores. It will make the pavers look more clean and vibrant. This efflorescence cleaning is a necessary step before a sealer is applied. The sealer will be able to get a deeper penetration into the now-clean pores.



### POLYBIND RUST REMOVER

CLN051 (1 Quart) (6/Box)  
Polybind Rust Remover is effective in removing rust from the surface of concrete pavers. Contains no muriatic acid.



### POLYBIND RUBBER, PAINT & TAR REMOVER

CLN049 (1 Quart) (6/Box)  
Polybind Rubber, Paint & Tar Remover is effective in removing rubber, paint and tar from the surface of concrete pavers and natural stone. Easily washes off with water and is easy to use.

\* While Supplies Last



### POLYBIND SEALER STRIPPER

CLN068 (1 Gallon) & CLN069 (5 Gallon)  
(Box of 4 x 1 US Gallon)  
Polybind Sealer Stripper is extremely effective for removing either water-based or solvent-based sealers from concrete pavers or stone. It is environmentally responsible (water-based), yet it removes multiple layers in a single application. It is a paste which is easily applied with a brush or roller.

## Natural Stone Cleaners



### UNICARE NATURAL STONE ACID CLEAN

CLN095 (1L), CLN098-(5L)

#### Removal of:

- Cement Staining • Efflorescence
- Iron Oxide (Rust) Cement mortar • Grout

Note: Never use hydrochloric or sulphuric acid based products.

ONLY FOR ACID-RESISTANT STONE.

## Natural Stone Cleaners



### UNICARE BIOCLEAN\*

CLN097 (1L), CLN100 (5L),

#### Removal of:

- Black spot algae • Green algae • Plant stains from leaves, wood, trees, berries & flowers
- Organic staining from bark & compost • Colored stains from food spillages, tea, coffee and wine



### UNICARE POWER CLEAN\*

CLN096 (1L) & CLN099 (5L)

- Oil & Grease • Food Stains • General Dirt & Mud
- Light cement contamination
- Sap & certain plant stains sensitive surfaces

\*Possible While Supplies Last

## Natural Stone Sealers



### UNICARE NATURAL MATTE SEALER

SEAL229 (1L) & SEAL231 (5L)

#### For Porous Stones

- No change of color • No surface coating, sheen or shine at all • Riven Sandstone & Smooth Sandstone
- Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see SDS.



### UNICARE NATURAL COLOR ENHANCER SEALER

SEAL230 (1L) & SEAL232 (5L)

#### For Porous Stones

- No surface coating, sheen or shine at all • Soaks into the stone surface which remains completely natural and enhances the natural colour. • Stain protection

Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see SDS.

\* Possible While Supplies Last

## Sealers



### POLYBIND™ HIGH GLOSS SEALER (BLUE)

SEAL145 (1 Gallon) & SEAL146 (5 Gallon)

1 & 5 Gallon Available Box of 4 x 1 US Gallon

This water based sealer offers a high-gloss finish for all concrete pavers that have never been sealed or pre-sealed in the manufacturing process.



### POLYBIND ECO SEAL HIGH GLOSS SEALER + COLOR ENHANCER WB

SEAL185 (1 Gallon) & SEAL186 (5 Gallon)

1 & 5 Gallon Available Box of 4 x 1 US Gallon

This high gloss sealer is 100% pure, high-grade acrylic used to seal concrete, clay pavers and natural stone, by penetrating deep into their pores, thus reducing oil and dirt penetration as well as protecting them from the corrosion of de-icing salt. It provides a high-gloss finish as well as vibrant color enhancement.

## Sealers (continued)



### POLYBIND ECO SEAL LOW GLOSS SEALER + COLOR ENHANCER WB

SEAL178 (1 Gallon) & SEAL179 (5 Gallon)  
1 & 5 Gallon Available Box of 4 x 1 Us Gallon  
Polybind Eco Low Gloss Sealer + Color Enhancer is 100% pure high-grade acrylic for concrete pavers. It penetrates deep into the concrete paver pores, reducing oil and dirt penetration as well as corrosion from de-icing salt.



### POLYBIND™ ECO SEAL LOW GLOSS

SEAL147 (1 Gallon) & SEAL148 (5 Gallon)  
Box of 4 x 1 US Gallon  
Polybind Eco Seal Low Gloss is 100% pure, high-grade acrylic used to seal concrete pavers, clay pavers and natural stone. It penetrates deep into the pavers and natural stone pores, thus reducing the oil and dirt penetration, as well as protecting them from the corrosion of de-icing salt.



### POLYBIND RESEALER SB

SEAL155 (1 Gallon) & SEAL156 (5 Gallon)  
1 & 5 Gallon Available Box of 4 x 1 Us Gallon  
Polybind Resealer penetrates the existing sealer and reactivates it to create rejuvenated protection of the paver surface, thus reducing oil and dirt penetration as well as protecting it from the corrosion of de-icing salt.



### POLYBIND™ WET LOOK SEALER SB

SEAL143 (1 Gallon) & SEAL144 (5 Gallon)  
1 & 5 Gallon Available Box of 4 x 1 US Gallon  
This wet look sealer is made from acrylic-based polymers that penetrate deep into the concrete paver and natural stone pores, This results in reduced oil and dirt penetration, as well as protecting them from the corrosion of de-icing salt.



### POLYBIND™ SEAL SATIN LOOK

SEAL141 for 1 Gallon & SEAL142 for 5 Gallon  
Sealer is made from acrylic-based polymers. Polybind Satin Look Sealer penetrates deep into the concrete pavers, thus reducing the oil and dirt penetration, as well as protecting them from the corrosion of de-icing salt. Specifically formulated to be used on unsealed surfaces only.



### GATOR SEAL SLIT FOAM ROLLER FOR SOLUTION BASED SEALERS 9.5"

CLN070  
For Semi-Rough and Rough Surfaces

- Applies Sealers Evenly
- Works Great on Textured Surfaces
- Remains Spongy and will not Compress



### BACK TO BLACK SEALER FOR NATURAL STONE

SEAL 238

- Quickly revives and enhances faded dark limestone
- Provides a strong and uniform color enhancement
- Excellent water resistance
- Single coat provides a rich enhanced color
- 1 liter covers up to 40m2 based on one coat, depending on surface porosity

## Adhesives



### SUREBOND SB-10 ADHESIVE

ADH002 28oz tube; 12/Case; 60 Cases/skid  
(Conforms to UN-STD. 1804, ASTM 2339-70 & FHA UM-60)  
Surebond SB-10 adhesive is a fast set-up, quick curing, superior strength, structural grade hardscape adhesive. Adheres well in extreme conditions such as temperatures ranging from 0° to 100° F, frozen and/or damp substrates.  
Light Tan • Low odor • VOC compliant • 900 psi



### POLYBIND XTRA PERFORMANCE (XP) POLYURETHANE ADHESIVE

ADH035 (10 oz) & ADH038 (28 oz)  
10 oz. Tube = 20' at 1/4" bead & 28 oz. Tube = 52' at 1/4" bead  
Formulated for fast cure time, extra bond strength and durability. Applications include concrete pavers and walls, overlays, pool copings, steps & wall caps, wetcast and natural stones. It can be applied above 32° & on either dry or damp surfaces. Drying times vary depending on factors such as humidity, porosity, temperature and materials bonded together.



### TECHNISEAL STRUCTURE BOND™ FOAM ADHESIVE

ADH048 (24 oz)  
Canister = 600 linear feet at 3/8" bead (12/Case)  
An innovative super-strength foam adhesive that bonds a wide range of construction products with an application time up to 50% faster than with conventional tube adhesives. Materials are bonded in just 8 minutes and adhesive is fully cured within 24 hours. Made from high-quality modified polyurethanes with excellent long-term resistance to weathering, dilute acids and caustic solutions.



### TECHNISEAL STRUCTURE BOND™ GUN II TOOL378 1 Dispenser (12/Case)

The Gun II dispenser for application enables you to gain access to hard-to-reach areas and greatly limits excessive spillage or dripping, while also reducing user-fatigue, with total control on product flow. The gun allows for a precise adhesive delivery with a single pull of the trigger that stops as soon as you let go. Requires no pumping, cutting or puncturing of cartridge nozzles.



### TECHNISEAL STRUCTURE BOND™ FOAM CLEANER

CLN093 (16 oz) 1 Canister = (12/Case)  
Structure Bond Gun Cleaner is a powerful cleansing formula that rapidly dissolves any uncured Structure Bond adhesive residue. Specifically designed to fit Structure Bond Gun II dispensers. Simply screw a canister onto the gun and press the trigger to cleanse the tool from uncured product. The built-in sprayer nozzle will dissolve any spill, drip or adhesive residue.

# Sands



## ALLIANCE GATOR NITRO SAND

SAND196 - Beige, SAND197 - Gray, SAND198 - Black  
SAND236-Silver  
Packaging: 50 lb/bucket 48 buckets/skid  
Coverage: 10-56sf = 50lb bucket.  
Ready-to-use mixture of calibrated sand and resins which cure when exposed to air.  
This product hardens from top to bottom of the joint. This can be installed in wet or dry weather, in joints ranging from a minimum 3/16" (5mm) to a maximum 2" (50mm) joint width. The minimum jointing depth is 1" (25mm).



## EUROSTONE BOND

SAND097 - SLATE GRAY 50lb. bag (56 bags/skid)  
For Driveway Aprons Application & Cobblestone Joints up to 3.5cm / 1"  
Eurostone Bond is the first polymeric sand specifically designed for drainage and non-drainage base systems and can be used with natural stones and cobblestone. Recommended for many uses, including streets, plazas (pedestrian and vehicular traffic) paths, sloping areas, around pools, etc. Sets above freezing (0°C / 32°F) and can be used for joints up to a maximum of 3.5 cm / 1".



## POLYBIND G2 COMPLETE SAND

SAND152 (Nevada Tan), SAND153 (Oxford Gray), SAND154 (Jet Black), SAND155 (Ivory White - **SPECIAL ORDER** - Full Skid Quantities Only)  
Packaging: 50lb/bag 56 bags/skid  
65-85 sq.ft./bag for narrow joints  
Designed for paver joints up to a maximum of 4 inches. Drainage & Non-Drainage Applications  
No Dust - No Haze - No Blower - One Watering.  
This is the cleanest, fastest and easiest polymeric sand installed in the industry. It can be used with concrete pavers, wetcast & natural stones.  
This is recommended for use in patios, pool decks, walkways, driveways, etc.



## PS-1500 RJS REACTIVE RESIN JOINT SAND SYSTEM

SAND233 (Pebble), SAND234 (Slate), SAND235 (Driftwood)  
Made with a new generation synthetic resin that hardens when it reacts with the air. It can be used in new or existing installations to create beautiful yet extremely durable hardened sand joints that will withstand the rigors of residential vehicle traffic and harsh freeze/thaw conditions.



## POLYBIND DUST

SAND072 (Dust Tan), SAND073 (Dust Gray)  
A unique mixture of polymer binders and calibrated stone available in Beige and Gray. Once Polybind Dust sets, it becomes very firm and locks between the wet cast or natural stone joints while still retaining flexibility and providing a long lasting, durable jointing material. Polybind Dust is recommended for a variety of uses including pool decks, patios, footpaths, and any other pedestrian applications.



## SEK JOINTING SAND

SAND001-1 - Tan  
SAND140 - Gray  
SAND148 - Platinum (**SPECIAL ORDER** - Full Skid Quantities Only)  
Kiln dried and angular shaped in order to flow easily and stay in place.  
Packaging: 50 lb/bag 56 bags/skid



## SEK POLYSWEEP SAND

SAND045 (Tan), SAND046 (Gray), SAND147 (Platinum)  
Packaging: 50 lb/bag 56 bags/skid  
For concrete paver, cast stone pavements, slabs and natural stone joints up to 3/4". PolySweep polymeric sand is a blend of native sands and high quality synthetic polymers specially formulated to allow the joints to expand and contract with elements such as extreme heat, extreme cold and freeze/thaw cycles.

# Sands continued

## SUGGESTED POLYMERIC SAND COVERAGE BY PRODUCT

PRODUCT	COVERAGE PER BAG
Anchorlock™	60-65 sf
Artline™	60-65 sf
Beacon Hill™	50-60 sf
Boulevard™	50-60 sf
Bristol Valley™	55-60 sf
Brussels Block®	80-85 sf
Copthorne®	50-60 sf
Courtstone®	30-40 sf
Eco-Optiloc™	40-50 sf
Eco-Priora™	50-60 sf
Eco-Promenade®	40-50 sf
Granito™	50-60 sf
Hex Paver™	50-60 sf
Hollandstone™	70-75 sf
Holland Premier™	70-75 sf
Il Campo®	70-75 sf
Mattoni™	45-50 sf
Natural Stone	N/A
Nordic Cobble™	20-25 sf
Porcelain	N/A
Promenade™	20 sf
Promenade Ecoterra®	50-60 sf
Richcliff®	45-50 sf
Series™	50-60 sf
Skyline™	60-65 sf
Thornbury™ (Permeable)	40-45 sf
Town Hall®	40-45 sf
Tribeca Cobble™	40-45 sf
Treo®	50-60 sf
Umbriano® 6cm Random	55-60 sf
Umbriano® 7cm	60-65 sf
Urban™	55-60 sf
Westport™	55-60 sf

Approximate Coverage: Jointing material type, paver thickness, joint width, and bedding course type may affect quantities required. Installation practices may affect the amount of sand used per product.

## IMPORTANT NOTICE

**1. EXTRA CARE** Extra Care must be exercised when using polymeric sand on all Unilock products.

Polymeric Jointing Sand can be used on these products but the fine polymers and binders in Polymeric Jointing Sand have a natural tendency to adhere to the surface. Therefore extra diligence must be taken to pre-clean the surface prior to “wetting the sand in” and squeegee off the surface post application. Failure to do so will result in a “whitish haze” on the surface that is difficult to remove.

**2. DO NOT USE** Polymeric Jointing Sand on the following products:

Series™ Il Campo® Tribeca Cobble™

If joint stabilization is required, use ordinary jointing sand and apply a stabilizing sealer. **Contact your local Unilock office for recommended sealants and application specifics.**

**3. IMPORTANT COMPACTION NOTICE:** Always pre-compact the pavers WITHOUT SAND IN THE JOINTS. This will facilitate proper leveling. Polymeric Sand can then be swept into the joints. Always use a compactor with a protective membrane attached to the bottom of the plate.

**Polymeric Jointing Sand, cleaners and sealers, must always be applied by a trained and experienced professional. Contact your local Unilock office for training and the most up-to-date best practices.**

**NOTICE:** Unilock does not accept any responsibility for damage to the surface caused by the improper application and use of polymeric sand, sealers or cleaners. Unilock will not accept responsibility for alternate suppliers of polymeric sand, jointing sand, cleaners and sealers.

# Edge Restraints


## SNAPEDGE - One-Piece Edging That Does It All!

### EDGE001


- Only one part required for straight runs or curved installations
- Built-in connector fastens one piece to the next
- Convenient 96" size, makes them easy to transport
- Unique 'Snip and Flex' feature speeds installations of curves and corners without pre-planning
- The open design allows a root system to grow through SnapEdge, further reinforcing the installation
- Engineered to provide a strong, easy-to-install edge restraint for concrete/clay pavers
- Nail hole bosses are full-length cylinders. Hammer blows will not fracture or force nail heads through edging

### PRODUCT INFORMATION:


8' (96") length pcs.  
 Sidewall: 1 7/8"  
 Pieces per Pallet: 672 (5,376 In. ft.)  
 Pieces per Bundle: 24 (192 In. ft.)  
 Bundles per Pallet: 28  
 Pallet Weight: 1395 lbs.  
 Pallet Size: 98" l x 48" w x 50" h




## TIPS FOR QUICK AND EASY INSTALLATION WITHOUT PRE-PLANNING




Sharp Inside Corner




Sharp Outside Corner




Proper Wall Installation



Gentle Outside Curves



Gentle Inside Curves



Pieces Snap Together

## POLYBIND EDGE EDGING

### EDGE056 - Rigid / EDGE061 - Tile Edge

- Rigid has Twist & Lock connection system
- Rigid can be changed to a partial flex by cutting the bridge support
- Tile Edge provides stability and strong lateral support for all porcelain tile installations



### RIGID EDGE

Product Information:  
 8' (96") length pcs.  
 Sidewall: 1 3/4"  
 Pieces per Bundle: 24 (192 In. ft.)  
 Pieces per Pallet: 672 (5376 In. ft.)



### TILE EDGE:

Product Information:  
 8' (96") length pcs.  
 Sidewall: 5/8"  
 Pieces per Bundle: 24 (192 In. ft.)  
 Pieces per Pallet: 384 (3072 In. ft.)

## SNAPEDGE PERMEABLE PAVER EDGING

### EDGE033

- Designed specifically for permeable pavement with open-graded base material.
- Holds pavement edges securely in place.
- Does straight and curved edges.



### PRODUCT INFORMATION:

8' (96") length pcs.  
 Weight per Unit: 2.5 lbs.  
 Pieces per Pallet: 64 (72 In. ft.)  
 Pallet Weight: 320 lbs.

## ALLIANCE GATOR XTREME EDGE

### EDGE076

- The ultimate fiber-reinforced structural edging solution for any hardscape project.
- Can be used for any traditional, open-graded, permeable, Gator Base or overlay application using concrete pavers or slabs, natural and wet cast stones.
- Offers permanent continuous lateral support.
- Packaging: 50 lb bag / 56 bags per skid.
- Coverage: 20-25 sqft coverage per bag for a 60mm paver.



## Edge Restraints continued

### PERMA EDGE PAVER EDGING

EDGE074 5 Gallon, 75 lb container



- Designed to float and flex with the sub base and not work independently like standard edging and spikes
- Quick & easy to install, typically cutting edging install time down by 80%
- Stays under the soil/mulch grade invisible edging
- Combats the freeze/thaw cycles in cold weather; won't deteriorate in moist/humid conditions
- Coverage per container; yields approx. 25-30 linear feet of edging per bucket

## Gator Base



**FEATURES:** For Pedestrian use only. Replaces concrete foundations and is used to replace 6" of crushed stone. The interlocking panels distribute all dynamic and static loads to a very wide area, practically eliminating any pressure on the ground. Gator Base is a unique evolution in base technology. Manufactured using lightweight high-density polypropylene. Environmentally friendly and 100% recyclable. Extremely durable, will not degrade in the ground. Designed with LOCK-N-GO tongue and groove system. Packaging: 10 units per pack, 12 packs per Box, 120 units per pallet SAND109

## Gator Base Screws

### GATOR BASE SCREWS

FAB033 - 1 Box of 50

- Fastens Gator Edge to Gator Base
- Reinforces the outside perimeter, creating strong lateral support



## Drainage, Separation and Reinforcement



### GATOR GRID 30-30

Gator Grid 30-30, a biaxial geogrid, provides strength, longevity, excellent stress transfer and prevents failure to the internal structure of landing areas, retaining walls and steep slopes. It has a high molecular weight as well as high-tenacity polyester yards which are woven in tension and finished with a PVC coating.

Packaging & Unilock SKU

4' x 50' - FAB070 / 6' x 50' - FAB071 / 6' x 150' - FAB072



### GATOR FABRIC NON-WOVEN 3.5

Gator Fabric Non-Woven 3.5 geotextile is ideal for drainage, filtration and will allow water flow in a paver or retaining wall application. It is designed for soil separation for added stability, has high strength and is dimensionally stable.

Packaging & Unilock SKU

4' x 100' - FAB038 / 6' x 100' - FAB040



### GATOR FABRIC NON-WOVEN 4.4

Gator Fabric Non-Woven 4.4 geotextile is ideal for drainage, filtration and will allow water flow in a paver or retaining wall application. It is designed for soil separation for added stability, has high strength and is dimensionally stable.

Packaging & Unilock SKU

4' x 100' - FAB044 / 3' x 100' - FAB043 / 6' x 100' - FAB046



### GATOR FABRIC WOVEN 5

Gator Fabric Woven 5 is a woven geotextile made from polypropylene yarns and can achieve higher tensile strength at low elongation. It is an excellent heavy-loading geotextile, ideal for driveways, alleyways, pathways and retaining walls.

Packaging & Unilock SKU

4' x 100' FAB049 / 6.25' x 300' - FAB052



### DRIVEGRID™ TENSAR GRID 12.5x120

FAB104

- 12.5' x 120' Roll - 1,572 sq. ft./54 lbs per roll

# Base Thickness Chart (General)

APPLICATION	GRAVEL BASE	BEDDING COURSE	BACKFILL WIDTH (WALLS ONLY)
PATIOS, WALKWAYS, POOL DECKS	4" - 6" (10cm - 15cm)	1" (2.5cm)	
DRIVEWAYS	8" - 12" (20cm - 30cm)	1" (2.5cm)	
STEPS, PLANTERS, RAISED PATIOS	6" (15cm)	0 - 1/8" (0cm-.3cm)	8" - 12" (20cm - 30cm)
RETAINING WALLS UNDER 18" (45cm)	6" (15cm)	0 - 1/8" (0cm-.3cm)	12" (30cm)
RETAINING WALLS OVER 18" (45cm)	6" (15cm)	0 - 1/8" (0cm-.3cm)	16" (50cm)

Soil condition - In areas with poor soil conditions, (e.g., heavy clay, disturbed soils) increase the depth of the base to provide more stability. Where poor soil conditions exist, it may be advisable to contract an engineer when constructing a retaining wall in excess of 24" in height.

Area = (Length) x (Width)

Area of a Circle = 3.14 x (Radius) x (Radius)

Area of a Half Circle = 1.57 x (Radius) x (Radius)

Area of a Quarter Circle = .78 x (Radius) x (Radius)

Area of a Triangle = (1/2 Base) x (Height)

Perimeter of a Circle = 6.28 x (Radius)

Perimeter of a Half Circle = 3.14 x (Radius)

Perimeter of a Quarter Circle = 1.57 x (Radius)

Metric Equivalents

1 inch = 2.5400 centimeters

1 foot = 0.3048 meter

1 yard = 0.9144 meter

1 sq. foot = 929.030 sq. centimeters

1 sq. meter = 1.196 sq. yards

27 cu. feet = 1 cu. yard

1 centimeter = 0.3937 inch

1 meter = 39.3701 inches

## Large Equipment



Model L



Model Mini P



Model PM

- Install up to 700 sq. ft. per hour!
- Access tight or narrow areas
- Eliminate the need for a forklift on site
- Reduce labor costs
- Reduce shoulder, hand & knee pain and injury
- Improve your bottom line

**SPECIAL ORDER**

Contact your local rep for details.

### VPR 700 PAVER ROLLER

- Centrifugal Force: 3,147 lbs
- Machine Weight: 386 lbs
- Base Plate Width: 26"
- Engine: Honda GX160 Four-Stroke



**SPECIAL ORDER**

### VPR 450 PAVER ROLLER

- Centrifugal Force: 1,798 lbs
- Machine Weight: 238 lbs
- Base Plate Width: 17"
- Engine: Honda GX160 Four-Stroke



**SPECIAL ORDER**

### U-LEVEL™

- Easy to use
- Accurate readings
- Low maintenance
- Works in difficult locations
- Large working area



A PRECISION TOOL NO  
HARDSCAPER SHOULD BE WITHOUT

**SPECIAL ORDER**

# BEDDING MATERIALS CHART (Approximate Imperial Tons)

Bedding Course												
Square Feet	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.3	0.5	0.8	1.0	1.3	1.5	1.8	2.0	2.3	2.5	2.8	3.0
100	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0
150	0.8	1.5	2.3	3.0	3.8	4.5	5.3	6.0	6.8	7.5	8.3	9.0
200	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0
250	1.3	2.5	3.8	5.0	6.3	7.5	8.8	10.0	11.36	12.5	13.8	15.0
300	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0	13.5	15.0	16.5	18.0
350	1.8	3.5	5.3	7.0	8.8	10.5	12.3	14.0	15.8	17.5	19.3	21.0
400	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.2	22.0	24.0
450	2.3	4.5	6.8	9.8	11.3	13.5	15.8	18.0	20.3	22.5	24.8	27.0
500	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	22.5	25.0	27.5	30.0
550	2.8	5.5	8.3	11.0	13.8	16.5	19.3	22.0	24.8	27.5	30.3	33.0
600	3.0	6.0	9.0	12.0	15.0	18.0	21.0	24.0	27.0	30.0	33.0	36.0
650	3.3	6.5	9.8	13.0	16.3	19.5	22.8	26.0	29.3	32.5	35.8	39.0
700	3.5	7.0	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
750	3.8	7.5	11.36	15.0	18.8	22.5	26.3	30.0	33.8	37.5	41.3	45.0
800	4.0	8.0	12.0	16.0	20.0	24.0	28.0	32.0	36.0	40.0	44.0	48.0
850	4.3	8.5	12.8	17.0	21.3	25.5	29.8	34.0	38.3	42.5	46.8	51.0
900	4.5	9.0	13.5	18.0	22.5	27.0	31.5	36.0	40.5	45.0	49.5	54.0
950	4.8	9.5	14.3	19.0	23.8	28.5	33.3	38.0	42.8	47.5	52.3	57.0
1000	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0

# BASE DEPTH CHARTS (Cubic Yards)

Bedding Course												
Square Feet	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.2	0.3	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.5	1.7	1.9
100	0.3	0.6	0.9	1.2	1.5	1.9	2.2	2.5	2.8	3.1	3.4	3.7
150	0.5	0.9	1.4	1.9	2.3	2.8	3.2	3.7	4.2	4.6	5.1	5.6
200	0.6	1.2	1.9	2.5	3.1	3.7	4.3	4.9	5.6	6.2	6.8	7.4
250	0.8	1.5	2.3	3.1	3.9	4.6	5.4	6.2	6.9	7.7	8.5	9.3
300	0.9	1.9	2.8	3.7	4.6	5.6	6.5	7.4	8.3	9.3	10.2	11.1
350	1.1	2.2	3.2	4.3	5.4	6.5	7.6	8.6	9.7	10.8	11.9	13.0
400	1.2	2.5	3.7	4.9	6.2	7.4	8.6	9.9	11.1	12.3	13.6	14.8
450	1.4	2.8	4.2	5.6	6.9	8.3	9.7	11.1	12.5	13.9	15.3	16.7
500	1.5	3.1	4.6	6.2	7.7	9.3	10.8	12.3	13.9	15.4	17.0	18.5
550	1.7	3.4	5.1	6.8	8.5	10.2	11.9	13.6	15.3	17.0	18.7	20.4
600	1.9	3.7	5.6	7.4	9.3	11.1	13.0	14.8	16.7	18.5	20.4	22.2
650	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.1	20.1	22.1	24.1
700	2.2	4.3	6.5	8.6	10.8	13.0	15.1	17.3	19.4	21.6	23.8	25.9
750	2.3	4.6	6.9	9.3	11.6	13.9	16.2	18.5	20.8	23.1	25.5	27.8
800	2.5	4.9	7.4	9.9	12.3	14.8	17.3	19.8	22.2	24.7	27.2	29.6
850	2.6	5.2	7.9	10.5	13.1	15.7	18.4	21.0	23.6	26.2	28.9	31.5
900	2.8	5.6	8.3	11.1	13.9	16.7	19.4	22.2	25.0	27.8	30.6	33.3
950	2.9	5.9	8.8	11.7	14.7	17.6	20.5	23.5	26.4	29.3	32.3	35.2
1000	3.1	6.2	9.3	12.3	15.4	18.5	21.6	24.7	27.8	30.9	34.0	37.0

Actual volume may vary due to type of materials, moisture content, and compaction. Calculation charts and formulas are provided as a service by Unilock for estimating material requirements. Unilock will not be held responsible in any way for resulting product overage or shortage.


# FINISHES



**Umbriano®**  
Mottled Finish with  
ColorFusion™ and EasyClean



**Series™**  
Exposed Granite Finish



**Il Campo®**  
Brushed Finish



**Smooth**  
Premier Finish



**Flagstone**  
Premier Finish



**Antiqued**  
Timeworn Finish



**Classic**  
Thrumix Finish

## COLOR BLEND DESCRIPTIONS

COLOR NAME	DESCRIPTION
Arctic Gray	Dark Brown, Light Brown with White Granite
Basalt	Blueish-Black
Bavarian	Brown, Cream and Charcoal
Beechwood	Tan and Charcoal
Birch	Dark Brown, Light Brown and Cream
Black Granite	Black Granite and Charcoal
Black River	Dark Gray and Black
Buff	Tan
Burgundy Red	Plum with Red
Burnt Clay	Brown with Red
Chamois	Medium Buff
Charcoal	Mid Brown and Light Charcoal
Charleston	Plum, Charcoal and Sand
Coastal Slate	Charcoal and Black Flake
Cocoa Brown	Solid Dark Brown
Cobalt Gray	White, Gray and Blue hues
Coffee Creek	Sandstone, Brown and Charcoal
Dark Charcoal	Dark Charcoal
Dawn Mist	Gray and Tan
Dusk	Grey, Tan and White
Fieldstone	Buff and Gray
Fossil	Light & Dark Gray, Chamois and White

COLOR NAME	DESCRIPTION
French Gray	Light Gray with White Flake
Golden Sand	Tan with Light Brown lines
Golden Tan	Dark Brown, Light Brown with White Granite
Granite	Natural and Charcoal
Gray	Gray
Grenada White	White and Gray
Indiana Buff	Gray and Tan
Ivory Sand	White and Cream with Gray lines
Light Gray	Light Gray
Light Opal Blend	Light Grey and White
Light Steel Gray	Light Grey and Dark Charcoal
Limestone	Light Gray and Charcoal
Mahogany Ash	Mid Brown and Light Charcoal
Midnight Charcoal	Charcoal and Black
Midnight Sky	Charcoal and Black Flake
Natural	Light Gray and Medium Gray
Nordic Star	Black and White accents
Notte	Mid Charcoal, White and Light Natural
Old Oak	Rust with Red
Onyx Black	Dark Charcoal with Black Granite
Opal	Light Gray and White
Pebble Taupe	Tan with Light Brown

COLOR NAME	DESCRIPTION
Peppered Granite	White aggregates with black flecks
River	Buff, Natural and Charcoal
Rustic Red	Red and Charcoal
Sabia	Brown, Black and Light Natural
Sable Blend	Cream Tan Brown
Safari	Cream and White
Sandstone	Buff and Tan
Sierra	Charcoal, Russet and Buff
Silver Gray	Light Gray with Black, White and Tan flecks
Smoke Shale	Charcoal and Dark Charcoal
Steel Blue	Mid Gray
Sterling	White, Tan and Gray
Stone Cliff Gray	Light Gray
Steel Gray	Dark Charcoal & Gray
Steel Mountain	Natural and Charcoal
Summer Wheat	Cream White with Pale Yellow & Beige Particles
Terra Cotta	Salmon and Charcoal
Tuscany	Sandstone and Tan
Winter Marvel	White and Black Flake

## THE IMPORTANCE OF ASPECT RATIO


Simply defined, aspect ratio is the overall length of a paver divided by its height.

LENGTH/HEIGHT = ASPECT RATIO


If an insufficient aspect ratio is used, any flexing or rocking caused by movement on the surface such as vehicular traffic, could result in breakage of the paver units. Not only is this breakage unsightly, but it can also compromise the integrity of the segmental system.



**OVER 5 : 1**  
Pedestrian Only




**4 : 1**  
Light-Duty Vehicular



**3 : 1 OR LESS**  
Heavy-Duty Vehicular

## LAYING PATTERN CONSIDERATIONS

The laying pattern used in your application can also add a significant amount of strength to your design. A herringbone pattern provides the best 'lock-up', adding strength against rotational forces such as tires at a roadway intersection in the same way the 'L' shaped paver provides maximum performance.



## HEAVY-DUTY CONSIDERATIONS


Unilock has a variety of shapes and sizes available to fit your heavy-duty application and style preferences. For maximum performance where twisting and tipping will be factors, consider the unique "L" interlocking shape as it provides superior resistance under heavy loads. The patented locking features work in tandem with the "tri-axis" technology. The result? A stronger, more stable pavement surface.

Heavy-duty Unilock paving systems are also designed for rapid mechanized installation, making them competitive and affordable.



### H-20 & HS-20 LOAD RATING

Similar to top of deck stresses per AASHTO H-20 loading conditions (32,000 lbs/14,500 kg), Unilock pavers can support 3-4 axle vehicles. This would include delivery, fire and semi-truck and trailer traffic in light-duty roadway applications.



Speak with your Unilock Representative for more information.

# IMPORTANT NOTES

---

## UNILOCK PAVER PATTERNS

This Product Data Guide contains an extensive reference to patterns and designs. The purpose of these pattern swatches is to help the designer plan unique and exceptional designs. The percentages of products shown are based on the pattern and not on bundle configurations. In fact, there may be situations in which a pattern has been created with one particular size of stone, but that stone only comes packaged with two other sizes. This means that the designer will have to plan how the other components are used in the overall plan. This is usually accomplished by adding a border or an accent. As a result, overages or shortages may occur in certain patterns. The designer and/or installer of Unilock products accepts all responsibility for design and all associated costs incurred as a result of applying any of Unilock's suggested design patterns in a project. Please plan your project and review your order carefully prior to ordering.

## TRANSFERABLE LIFETIME GUARANTEE

Unilock provides a Transferable Lifetime Guarantee\* on the structural integrity of our paving stones, slabs and retaining wall units to the original purchaser of the product for residential use. Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Color matching cannot be guaranteed and replacement labor is not included. Proof of purchase is required.

Excessive defective material (over the industry accepted normal of 2% for non-tumbled unit pavers) delivered to the purchaser will be replaced free of charge if a written claim is made within 5 days of delivery from the manufacturer. Such claims will not constitute reason for delaying payment. All goods shall be deemed accepted if completely installed. Inspect concrete products prior to opening bundle packaging to ensure that shape and color are as ordered. Unsatisfactory material must be available for inspection by Unilock to entitle the purchaser to any adjustment or credit. Inspect all concrete units during installation and set aside any which are chipped or cracked to use for any cut pieces required. The color of concrete products may vary significantly between production lots. Always install concrete units from several bundles simultaneously to ensure proper distribution of color. Prior to final compaction, inspect installed pavers for good color distribution. Relocate certain pavers, if necessary, to achieve desired color blend.

\*Transferable Lifetime Guarantee: Register your project within 60 days of your dated proof of purchase to ensure your Unilock Guarantee is fully transferable! Simply go online at [unilock.com](http://unilock.com) and follow instructions. Once processed, you will receive an original Transferable Warranty Certificate for your records.

## PRODUCT HANDLING WARNING

**Bundle Straps Under Tension - Use extreme caution when removing or handling straps.** Always wear gloves, goggles, safety footwear, and protective clothing when removing or handling straps. Failure to do so may result in serious bodily injury or loss of sight.

Cut all concrete products only in well ventilated areas. Inhalation of dust is a serious health risk. A "NIOSH" (US) or a "CSA" (CDN) approved respirator, safety goggles, hearing protectors, and gloves must be worn at all times. Always "wet-cut" or "wet grind" concrete products to minimize dust.

Do not stack bundled concrete products higher than 2 bundles high. Contents of the bundle may be unstable and subject to topple when stacked. Always use extreme caution and appropriate equipment when transporting or storing bundled concrete products. Failure to do so may result in serious bodily injury or death. Always obey gross vehicle weight (GVW) loading limitations and regulations.

Hazard Rating: Fire 0, Health 1, Reactivity 0. See MSDS Concrete Masonry (Pavers). Contact Unilock for complete sheet or view safety information at [Unilock.com](http://Unilock.com).

Unilock assumes no liability or responsibility for loss or damage, resulting from the improper use or handling of our products, or from failure to follow instructions, warnings, and/or advisories on the product label, and on the MSDS sheet.

## TRADEMARK & LEGAL INFORMATION

Umbriano® is a trademark of Metten Stein + Design GmbH & Co KG used under license by Unilock. Unilock Ltd. and Hengestone Holdings, Inc. are the owners or authorized users of all trademarks used in this publication unless otherwise specified.

Colors shown in this brochure should be used only as a guide. Colors should always be chosen from actual samples. Contact your local Unilock representative for color availability in your area. Not all products shown are available at all Unilock locations. Log on to [www.unilock.com](http://www.unilock.com) for availability. Measurements throughout this portfolio are nominal.

©2024 Hengestone Holdings, Inc.





# QUALITY COMMITMENT

Unilock was the first concrete paver manufacturer in North America to offer a Lifetime Guarantee, and since then we have continued to stand behind it to ensure customers are completely satisfied with our products. With almost 2 billion stones in the ground, that's quite the commitment!

Our products are better and stronger than other brands. In fact, our internal standards of manufacturing in the USA and Canada far exceed industry standards set by ASTM (American Society for Testing and Materials) and CSA (Canadian Standards Association) and other European organizations.



## LIFETIME GUARANTEE - RESIDENTIAL

Our Transferable Lifetime Guarantee warranties the structural integrity of Unilock concrete paving stones and retaining wall units when used in residential applications. It covers any structural failure or deterioration of the concrete unit resulting from normal use or from the reasonable application of sodium chloride (common rock salt used for de-icing). StoneMark™ products have the same warranties as Unilock paving stones and retaining walls, but cannot be warranted against damage resulting from de-icing products.

Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Proof of purchase is required. Customers are encouraged to submit receipts to us as soon as their project is complete, using the Unilock Warranty Registration Form on our website (Unilock.com).

Purchasers need to ensure that the product they purchase is appropriate for their intended application; for example, only certain thicknesses of products are appropriate for driveways. Color matching of the replacement product and/or lost time cannot be guaranteed and labor costs related to installing replacement product is not included. Unilock reserves the right to seek a professional diagnosis and opinion to determine the exact cause of the product failure. If the failure falls within our warranty parameters, Unilock will replace the defective product.

**EXCLUSIONS** - Unfortunately, some things are beyond the control of Unilock, and are therefore not covered by this warranty. These include: naturally occurring efflorescence, hazing from polymeric jointing sand, scratching and chipping resulting from snow removal or construction equipment, damage caused by natural or un-natural disasters, or negligence by anyone other than Unilock. While EasyClean helps to increase a paver's resistance to staining from various substances, it does not make our products stain-proof nor does it resist every kind of stain. The Unilock warranty also does

not cover deterioration or damage as a result of poor design or poor installation practices that are contrary to specifications as laid out by ICPI (Interlocking Concrete Pavement Institute) and the NCMA (National Concrete Masonry Association). For more information please visit [www.icpi.org](http://www.icpi.org) and [www.ncma.org](http://www.ncma.org). Additionally, please refer to the Maintenance, Color and Installation Advisories.

## MAINTENANCE ADVISORY

### 1. Cleaning and Sealing

As with anything that is outdoors, Unilock products are subject to harsh weather, dust, acid rain, leaf stains, water stains and general wear from foot or vehicular traffic. Therefore, periodic cleaning using environmentally safe detergents designed for cleaning concrete is recommended to maintain a bright, fresh appearance.

To make subsequent cleaning easier and more effective, a concrete sealer can be applied to new or cleaned products to help prevent the penetration of substances that can cause stains.

There are many types of concrete cleaners and sealers on the market. Always read the instructions carefully before using the product to make sure that it will function as expected. Testing first, in a small unobtrusive area, is always a good idea to ensure the results are acceptable. Consult your local hardscape dealer to find the products best suited for your paver or wall installation.



*Visit [Unilock.com](http://Unilock.com) to register for your Transferable Lifetime Guarantee.*

## 2. Winter Maintenance

Snow removal by way of metal blades on plows or shovels will scratch and chip the surface of pavers, causing permanent damage. To mitigate this risk, metal snow clearing blades must always have a polyurethane or rubber cutting edge attached when plowing pavers.

De-icing Salts – The use of de-icing products on paver surfaces is important for safety and to help mitigate snow accumulation. Most de-icing products will have some effect on concrete, even if the product label indicates that it is safe on concrete. If you must use a de-icing product, we recommend that you use Sodium Chloride (ordinary rock salt) or Calcium Chloride (for colder climates). Always apply sparingly. The use of de-icing products on StoneMark, wet-cast pavers, slabs or coping may damage the product and therefore is not recommended. Whenever possible use a coarse sand as an anti-slip measure instead of de-icing chemicals.

## COLOR ADVISORY

### 1. Selection

Due to the inherently variable nature of printed materials and digital monitors, Unilock cannot guarantee that products will match the color of printed or online images. Therefore, when making final product selections, decisions should be made based on actual stones which are readily available from Unilock, Authorized Contractors or Authorized Dealers. Most Unilock products are not comprised of a single color, but rather contain blended colors for a more natural appearance. This means that there will be significant color variance from stone to stone, so purchasers should view multiple units together to get a more accurate impression of the overall color.

Note: Unilock Natural Stone variations are outside the control of Unilock.

Purchasers of natural stone must be willing to accept this inherent variability.

### 2. Pre-installation checking

Always check the label to ensure that the Unilock product delivered to your project is the product and color ordered. If there is a discrepancy, or if the product inside the packaging doesn't appear to be correct, contact your hardscape dealer before installing any pavers or wall units. If the product is installed, it indicates your acceptance of the products as delivered.

### 3. Blending

If the project requires more than one bundle of product it's always a good idea to draw product from several bundles when installing, as this ensures that any variation between bundles will be seamlessly integrated in the project. When bundles are from different production runs, random selection from multiple bundles is even more important.

### 4. Efflorescence

Efflorescence is a naturally occurring process that may appear as a white or light gray powder on the surface of concrete, clay or natural stone. It is temporary, and will disappear over time. However, if it is bothersome, an efflorescence cleaner can be used to remove it. There is no way to predict or prevent efflorescence. Because it does not compromise the structural integrity of the product, it is not covered by Unilock product warranties.

## INSTALLATION ADVISORY

### 1. Construction Residue

While a certain amount of dirt on pavers and walls is inevitable during the construction phase, installers are strongly encouraged to clean as they go as construction residue can embed in the surface and become difficult to remove. The slurry produced

during wet-saw cutting is particularly stubborn to clean if allowed to dry on the surface of pavers. Unilock warranties do not cover stains caused by a failure to remove construction residue.

### 2. Polymeric Haze

Surface hazing caused by polymeric jointing sand is not the responsibility of Unilock. Polymeric jointing sand should only be installed by an experienced and knowledgeable contractor. Any sand that is left on the surface prior to activation will result in a haze that is very difficult and time-consuming to remove. Only the highest quality, brand name polymeric sand that is guaranteed by the manufacturer should be used.

### 3. Compaction Damage

Both smooth and textured paver surfaces can be scratched by compaction equipment used to 'flatten' a new paver installation. Therefore, metal plate compactors must be fitted with a polyethylene mat to protect the paver surface from becoming scratched, or a superior option is to use a rubber-roller compactor instead. Damage to product surfaces caused by failure to follow these instructions is not covered by Unilock product warranties.

## FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

# MICHIGAN PRODUCT DIRECTORY

## UNIT PAVERS

Product	Page	Finish	Pedestrian	Residential Vehicular	Commercial Vehicular	Environmental	For Borders & Accents
Anchorlock™	4	S	✓	✓	✓		
Artline™	5	SM	✓				
Beacon Hill™ Flagstone	6	F	✓				
Beacon Hill™ Smooth	7-8	SM	✓	80 mm	80 mm		
Boulevard™	9	SM	✓				
Bristol Valley°	10	F	✓				
Brussels Block°	11	W	✓	✓			✓
Copthorne°	12	T	✓	✓			✓
Courtstone°	13	C	✓	✓			✓
Eco-Optiloc™	14	S	✓	✓	✓	✓	
Eco-Priora™	15	S/SM	✓	✓	✓	✓	
Eco-Promenade°	16	SM	✓	✓	✓	✓	
Granito™	17	F	✓				
Granito Hex	17	SM	✓	✓	✓		
Hex™	18	SM	✓	✓	✓		
Hollandstone™	19	S	✓	✓	✓		✓
Holland Premier°	20	SM	✓	✓	✓		✓
Il Campo°	21	B	✓	✓	✓		✓
Mattoni™	22	T	✓	✓	✓		✓
Natural Stone	23-24	F/SM	✓				
Nordic Cobble™	25	C	✓	✓	✓		
Porcelain	26-27		✓				
Promenade™	28-30	SM/B/WS	✓	✓	✓		✓
PromenadeEcoTerra™	31	SM	✓	✓		✓	
Richcliff°	32	F	✓	Random			✓
Series™	33	WS	✓	✓	✓		✓
Skyline™	34	SM	✓				
Thornbury™	35	F	✓	✓		✓	
Town Hall°	36	T	✓	✓	✓	✓	✓
Treo™ Smooth	37	SM	✓	✓		✓	
Tribeca Cobble™	38	C/WS	✓	✓	✓		✓
Turfstone™	39	S	✓	✓	✓	✓	
Umbriano° - 60 mm	40	SZ	✓				
Umbriano° - 70 mm	41	SZ	✓	✓			✓
Umbriano° - 80 mm	42	SZ	✓	✓	✓		
Urban™ Smooth	43	SM	✓				✓
Westport™	44	F	✓	✓			

## RETAINING WALLS

Product	Page	Finish	Gardens	Retaining Walls	Steps	Seatwalls	Pillars
Brussels Dimensional System™	45	W	✓		✓	✓	✓
DuraHold°	46-47	S		✓			
DuraHold2°	48	S		✓			
Estate Wall™	49	SP/W	✓		✓	✓	✓
Lineo™ Dimensional Stone	50	SZ	✓			✓	✓
Pisa™	51	SP	✓	✓	✓		✓
Pisa™ Smooth XL	52	SM	✓	✓	✓		✓
Rivercrest° Wall	53	F	✓		✓	✓	✓
SienaEdge°	54	SM	✓	✓	✓	✓	
SienaStone°	55	SP		✓	✓		
SienaStone° Smooth	56-57	SM		✓	✓	✓	
U-Cara°	58-66		✓	✓	✓	✓	✓

Finishes: B=Brushed; C=Cobblestone; D=Dimpled; DW=Dimpled and Weathered; F=Flagstone; S=Standard; SM=Smooth; SZ=Smooth Zero Bevel; SP=Split; SP/W=Split and Weathered; T=Timeworn; W=Weathered; WS=Washed. This application chart should only be used as a guide. Site conditions, base materials, pattern and frequency of use may vary the performance of various types and styles of products.

# ADD 3D LANDSCAPE DESIGN TO YOUR TOOLBOX



## **U**VISION ALLOWS YOU TO VISUALLY COMMUNICATE YOUR DESIGN IDEAS TO YOUR CLIENT IN BOTH 2D PLAN VIEW AND 3D PERSPECTIVE VIEW

Whether you're coming from the hand-drawn world, or a 2D AutoCAD background, the biggest impact you'll see from adopting this new 3D design software is in how well the client will understand the project you are selling. **Uvision 3D Landscape Creator is an easy-to-use software tool that helps bring your designs ideas to life.**



**SCAN THE QR CODE FOR MORE INFORMATION OR TO DOWNLOAD A FREE 30-DAY TRIAL OF UVISION 3D LANDSCAPE CREATOR.**





TRANSFORMING HARDSCAPES

UNILOCK.COM | 1-800-UNILOCK

# Let's **BUILD YOUR BUSINESS TOGETHER.**

**CONTACT 1-800-UNILOCK OR VISIT UNILOCK.COM TO  
CONNECT WITH YOUR LOCAL TERRITORY MANAGER**

**BOSTON**  
(508) 278-4536

**CHICAGO**  
(630) 892-9191

**MILWAUKEE**  
(262) 742-3890

**KANSAS**  
(913) 417-7985

**MICHIGAN**  
(248) 437-7037

**NEW YORK**  
(845) 278-6700

**MID-ATLANTIC**  
(202) 798-2060

**ONTARIO**  
(416) 646-9000

**CINCINNATI/KY/TN**  
(513) 202-0219

**OHIO/WESTERN PA/  
WNY&CNY**  
(330) 927-4000

